



ENGINEERING CHANGE BULLETIN # 10009

CUSTOMERS' NOTIFICATION OF PART NUMBER CHANGE

Date Change Effective: 4/5/2012

Explanation of change from existing to new update:

Recommended processing temp/time for Nylon 9T material (.100 CC male headers) are changed to 260 C for 10 sec max.

CUSTOMERS' NOTIFICATION OF PART NUMBER CONFIGURATION REVISIONS

Date Change Effective: 4/5/2012

Explanation of configuration change:

Recommended processing temp/time for part number listed below (Nylon 9T) is changed from 260 C 120 sec max to 260 C for 10 sec max.

- G_C_S_N-M30, 10058-H
- G_C_D_N-M30, 10059-F
- G_C_S_N-M89, 10060-E
- G_C_D_N, (ST), 10419-F
- G_C_S_N, (ST), 10436-D
- G_C_S_N, (RA), 10909-D
- G_C_D_N, (RA), 10912-C
- G_C_D_N-M71, 11028-C
- G_C_S_N-M71, 11432-B

Configuration impacts for fit, form, and function are:

None

Existing parts will remain active for purchase? Yes No

New or revised parts are interchangeable to the previous part applications?

Yes No

Engineering Approval:

Truong Tran

(Signature)

Date: 4/5/12

Distribution: Sales/Purchasing/Manufacturing Operations/Quality Assurance/Document Control/Technical Support