

STREET STREET





T-FORCE GRMING DDR4 XTREEM

With unique trench design and $\frac{1}{0}$ mprove radiating performance

The Team Group design team had built a heat spreader with an all new exterior design concept. The overclocking memory module


with highest specification is built by top notch aluminum extrusion process and CNC machining. The unique trench design can increase the radiating area to improve radiating efficiency. XTREEM combines simple and magnificent design with its top specification overclocking memory module. The clean, sleek lines are able to magnify its high speed specification.



1 layers of circuit board largely improves stability

The number of PCB layers is 25% more than normal memories. This provides better efficiency and performance since the power layer and the signal layer has a farther distance between each other. Without the interference between the power and the signal, it can offer players the overclocking pleasure and a high stability overclocking memory module.





Selected high quality SAMSUNG original IC chips

Team Group insists on using high quality SAMSUNG original IC chips and passed through various rigorous internal tests. Its high reliability makes players feel at ease.



Ultra low working voltage 400/0

With low working voltage $1.2{\sim}1.4V$ from DDR4 XTREEM , it is not only energy saving but it can also reduce the temperature and the heat generated to offer the high speed running memory a stable and long time operation.



XMP2.0 step overclocking technology

All XTREEM series support Intel XMP 2.0. It is only one step away to experience the high speed sensation of overclocking.





QV approved by motherboard manufacturers

Multiple compatibility verifications with mainstream DDR4 motherboards to make sure its stability with all motherboards on the QVL(Qualified Vendor List). Therefore, you wouldn't' have to worry about compatibility issues when purchasing high speed memory.

Main Feature

- The finest crafted heat spreader with unique trench design
- High-efficiency aluminum heat spreader
- 10 layers of circuit board
- Selected high quality SAMSUNG original IC chips
- 1.2V~1.4V ultra low working voltage
- Support Intel XMP 2.0 smart overclocking technology
- QVL approved by motherboard manufactures in the market





Specification

Item	Specification						
Module Type	288 Pin Unbuffered DIMM Non ECC						
Capacity	4GBx2 / 8GBx2	8GBx2					
Frequency	3466	3600	3733	3866	4000		
Data transfer bandwidth	27,728 MB/s (PC4 27700)	28,800 MB/s (PC4 28800)	29,864 MB/s (PC4 29800)	30,928 MB/s (PC4 30900)	32,000 MB/s (PC4 32000)		
CL-Value	CL17-19-19-39	CL17-19-19-39 CL18-20-20-39	CL17-19-19-39 CL18-20-20-39	CL18-20-20-39 CL18-20-20-44	CL18-20-20-44		
Voltage	1.2V						
Heat Sink	Aluminum heat-sink						
Operation System	Desktop or notebook computer with DDR4 Memory Slots Required OS: Windows 10 / 8.1 / 8 / 7 / Vista / XP						
Warranty	Lifetime Warrant	у					



Ordering Information

Description	Color	Timings/Voltage	Capacity	Team P/N
TEAM Xtreem UD-D4 3466		CL17-19-19-39 1.35V	4GBx2	TXD48G3466HC17ADC01
TLAM ATTECHN OD-D4 3400		CL17-19-19-39 1.35V	8GBx2	TXD416G3466HC17ADC01
TEAM Xtreem UD-D4 3600	Silver	CL17-19-19-39 1.35V	4GBx2	TXD48G3600HC17ADC01
		CL18-20-20-39 1.35V	8GBx2	TXD416G3600HC18ADC01
TEAM Xtreem UD-D4 3733		CL17-19-19-39 1.35V	4GBx2	TXD48G3733HC17ADC01
		CL18-20-20-39 1.35V	8GBx2	TXD416G3733HC18ADC01
TEAM Xtreem UD-D4 3866		CL18-20-20-39 1.35V	4GBx2	TXD48G3866HC18ADC01
		CL18-20-20-44 1.35V	8GBX2	TXD416G3866HC18EDC01
TEAM Xtreem UD-D4 4000		CL18-20-20-44 1.35V	8GBX2	TXD416G4000HC18EDC01
TEAM Xtreem UD-D4 3466	Gold	CL17-19-19-39 1.35V	4GBx2	TXGD48G3466HC17ADC01
		CL17-19-19-39 1.35V	8GBx2	TXGD416G3466HC17ADC01
TEAM Xtreem UD-D4 3600		CL17-19-19-39 1.35V	4GBx2	TXGD48G3600HC17ADC01
		CL18-20-20-39 1.35V	8GBx2	TXGD416G3600HC18ADC01
TEAM Xtreem UD-D4 3733		CL17-19-19-39 1.35V	4GBx2	TXGD48G3733HC17ADC01
		CL18-20-20-39 1.35V	8GBx2	TXGD416G3733HC18ADC01
TEAM Vivosm LID D4 2066		CL18-20-20-39 1.35V	4GBx2	TXGD48G3866HC18ADC01
TEAM Xtreem UD-D4 3866		CL18-20-20-44 1.35V	8GBX2	TXGD416G3866HC18EDC01
TEAM Xtreem UD-D4 4000		CL18-20-20-44 1.35V	8GBX2	TXGD416G4000HC18EDC01

Above technical information is based on industry standard data and tested to be reliable. However, Team makes no warranty, either expressed or implied, as to its accuracy and assumes no liability in connection with the use of this product.

