



Standard Micapacitors

Data Sheet

7.5 kVDC Rated



(Dimensions shown as in/mm)

Part Number	Voltage kVDC)	Cap. (nF)	Length	Width	Thickness
M252A752A000	7.5	2.5	1.56/39.6	0.84/21.3	0.19/4.8
M502A752A000	7.5	5	1.81/46.0	1.08/27.4	0.20/5.1
M103A752A000	7.5	10	2.19/55.6	1.32/33.5	0.22/5.6
M253A752A000	7.5	25	2.69/68.3	1.75/44.5	0.28/7.1
M503A752A002	7.5	50	3.19/81.0	2.16/54.9	0.33/8.4

1. Capacitance Tolerance: +/- 10%
2. Dissipation Factor: .005 Max. @ 25°C, 1 kHz
3. Insulation Resistance:
 - 4000 MΩ*μF @25°C, need not exceed 100GΩ
 - 25 MΩ*μF @125°C, need not exceed 1GΩ
4. Dielectric withstanding voltage:
 - 7.5 kV rated
 - 11.2 kV burn-in for 2 hours @ 100°C
 - 15.0 kV proof for 5 seconds
5. Mylar wrapped, epoxy endcapped
6. Black dot indicates outer foil
7. Wire leads are AWG 18 solder coated copper
8. Safety: Capacitors are shipped with leads shorted

We also manufacture military quality standard and custom designed Spark Gaps and Voltage Multipliers. If you have a corona test requirement but lack the necessary test equipment, we offer AC and DC corona testing services including a test report. Call for information concerning these services.

Teledyne Reynolds, Incorporated
 5005 McConnell Avenue Los Angeles, CA 90066
 Tel: (310) 823-5491 • Fax: (310) 822-8046
 www.TeledyneReynolds.com • ReynoldsInc@Teledyne.com

