

Tempilaq® Temperature Indicating Liquid 800 °F (427 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 31/08/2015

Revision date:

Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Tempilaq® Temperature Indicating Liquid 800 °F (427 °C)

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Temperature indicator

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

LA-CO Industries Europe S.A.S.
Parc Industriel de la Plaine de
l'Ain - Allée des Combes.
01150.BLYES.France.
Phone: +33 (0)4 74 46 23 23
Fax: +33 (0)4 74 46 23 29
E-mail: info@eu.laco.com
Web: http://www.markal.com



1.4. Emergency telephone number

Emergency number : 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887

EU Member State	Officieel adviesorgaan	Adres	Noodnummer
AUSTRIA	Vergiftungsinformationszentrale (Poisons Information Centre)	Allgemeines Krankenhaus Waehringer Geurtel 18-20 1090 Wien	+43 1 406 43 43
BELARUS	The Belarus Republican Poisons Centre	Kizhevatova str. 58 Minsk 220115	+375 (0)17 201 9158
BELGIUM	Centre Anti-Poisons/Antigifocentrum c/o Hôpital Central de la Base - Reine Astrid	Rue Bruyn 1 B -1120 Bruxelles/Brussel	+32 70 245 245
BULGARIA	Национален токсикологичен информационен център National Clinical Toxicology Centre, Emergency Medical Institute "Pirogov"	21 Tottleben Boulevard 1606 SOFIA	+359 2 9154 409
CROATIA	Poisons Control Centre Institute of Medical Research & Occupational Health	Ksaverska Cesta 2 P.O. Box 291 HR-10000 Zagreb	+385 1 234 8342
CZECH REPUBLIC	Toxikologické informační středisko Clinic For Occupational Medicine, 1st Medical Faculty, Charles University	Na Bojišti 1 120 00 Praha 2	+42 2 2491 9293 +42 2 2491 5402
DENMARK	Gifflinjen Bispebjerg Hospital	Bispebjerg Bakke 23, 60, 1 DK-2400 København NV	+45 82 12 12 12 +45 35 31 55 55
ESTONIA	Mürgistusteabekeskus	Gonsiori 29 15027 Tallinn	+372 626 93 90
FINLAND	Myrkytystietokeskus	P.O.B 340 (Haartmaninkatu 4) HUS SF - 00029 Helsinki	+358 9 471 977
FRANCE	ORFILA		+33 1 45 42 59 59
GERMANY	Berliner Betrieb für Zentrale Gesundheitliche Aufgaben	Oranienburger Strasse 285 13437 Berlin	+49 30 19240
GERMANY	Informations und Beratungszentrum für Vergiftungsfälle	Kirrberger Straße, Gebäude 9 D-66421 Homburg/Saar	+49 6841 19240
GERMANY	Beratungstelle bei Vergiftungen, Klinische Toxikologie und Beratungsstelle bei Vergiftungen	Langenbeckstrasse 1 55131 Mainz	+49 6131 19240
GREECE	Poisons Information Centre	11527 Athens	+30 10 779 3777
HUNGARY	Országos Kémiai Biztonsági Intézet (National Institute of Chemical Safety) Egészségügyi Toxikológiai Tájékoztató Szolgálat (Health Toxicological Information Service)	1437 Budapest PO Box 839 1097 Budapest, Nagyvárad tér 2	+36 80 20 11 99
ICELAND	Eitrunarmiðstöðin	Eitrunarmiðstöðin 108 Reykjavik	+354 543 22 22
IRELAND	National Poisons Information Centre	Beaumont Hospital PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2166

Tempilaq® Temperature Indicating Liquid 800 °F (427 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

LATVIA	Valsts Toksikoloģijas centra Saindēšanās un zāļu informācijas centrs	2 Hipocrate Street LV 1038 Riga	+371 67 04 24 73
LITHUANIA	Apsinuodijimų kontrolės ir informacijos biuras	Siltnamiu 29 2043 Vilnius	+370 5 236 20 52/+370 687 53 378
MALTA	Medicines & Poisons Info Office	Mater Dei Hospital, Msida MSD 2090 Malta	25450000
NETHERLANDS	Nationaal Vergiftigingen Informatie Centrum National Institute for Public Health and the Environment, NB this service is only available to health professionals	Huispostnummer B.00.118, PO Box 85500 3508 GA Utrecht	+31 30 274 88 88
PORTUGAL	Centro de Informação Antivenenos Instituto Nacional de Emergência Médica (INEM)	Rua Almirante Barroso, 36 1000-013 Lisboa	808 250 143 (for use only in Portugal), +351 21 330 3284
ROMANIA	Biroul pentru Regulamentul Sanitar International si Informare Toxicologica	Str. Dr. Leonte Anastasievici Nr.1-3, Sector 5 50463 Bucuresti	+40 21 318 36 06
SLOVAKIA	Národné toxikologické informačné centrum University Hospital Bratislava	Limbová 5 833 05 Bratislava	+421 2 54 77 4 166
SPAIN	Servicio de Información Toxicológica Instituto Nacional de Toxicología, Departamento de Madrid	Calle Luis Cabrera 9 E-28002 Madrid	+34 91 562 04 20
SWEDEN	Giftinformationscentralen Swedish Poisons Information Centre, Karolinska Hospital	Box 60 500 SE-171 76 Stockholm	+46 8 33 12 31 (International) 112 (National)
SWITZERLAND	Centre Suisse d'Information Toxicologique	Freiestrasse 16 Postfach CH-8028 Zurich	+41 44 251 51 51 (International) 145 (National)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin Irrit. 2 H315
Eye Dam. 1 H318
Skin Sens. 1 H317
Carc. 1B H350
Repr. 1B H360
STOT SE 3 H335
STOT RE 2 H373

Full text of classification categories and H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) : Danger

Hazardous ingredients : 1,2-epoxybutane, 1-bromopropane, 1-Butanol, formaldehyde, potassium molybdate, Molybdenum trioxide

Hazard statements (CLP) : H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H335 - May cause respiratory irritation
H350 - May cause cancer
H360 - May damage fertility or the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (CLP) : P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P260 - Do not breathe mist, spray, vapours
P264 - Wash hands thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P272 - Contaminated work clothing should not be allowed out of the workplace
P280 - Wear eye protection, protective gloves, protective clothing
P302+P352 - IF ON SKIN: Wash with plenty of water

Tempilaq® Temperature Indicating Liquid 800 °F (427 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308+P313 - IF exposed or concerned: Get medical advice/attention
P310 - Immediately call a POISON CENTER/doctor
P312 - Call a poison center or doctor if you feel unwell
P321 - Specific treatment (see First aid measures on this label)
P332+P313 - If skin irritation occurs: Get medical advice/attention
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
P362+P364 - Take off contaminated clothing and wash it before reuse
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P405 - Store locked up
P501 - Dispose of contents/container to an authorised waste collection point

Unknown acute toxicity (CLP: Classification, Labelling, Packaging.) - SDS

: 1.77% of the mixture consists of ingredient(s) of unknown acute oral toxicity
1.77% of the mixture consists of ingredient(s) of unknown acute dermal toxicity
1.77% percent of the mixture consists of ingredient(s) of unknown acute inhalation (dust/mist) toxicity

2.3. Other hazards

PBT: not yet assessed

vPvB: not yet assessed

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
potassium molybdate	(CAS No) 13446-49-6 (EC no) 236-599-2	30 – 40	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
Molybdenum trioxide	(CAS No) 1313-27-5 (EC no) 215-204-7 (EC index no) 042-001-00-9	10 – 20	Eye Irrit. 2, H319 Carc. 2, H351 STOT SE 3, H335
1,3,5-Triazine-2,4,6-triamine, polymer with formaldehyde, butylated	(CAS No) 68002-25-5 (EC no) *614-205-3	5 – 10	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312
1-bromopropane substance listed as REACH Candidate (1-bromopropane (n-propyl bromide))	(CAS No) 106-94-5 (EC no) 203-445-0 (EC index no) 602-019-00-5	5 – 10	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Repr. 1B, H360FD STOT SE 3, H335 STOT SE 3, H336 STOT RE 2, H373
1-Butanol	(CAS No) 71-36-3 (EC no) 200-751-6 (EC index no) 603-004-00-6	1 – 5	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 STOT SE 3, H335 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336
formaldehyde	(CAS No) 50-00-0 (EC no) 200-001-8 (EC index no) 605-001-00-5	0.1 – 1	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:dust,mist), H331 Skin Corr. 1B, H314 Skin Sens. 1, H317 Muta. 2, H341 Carc. 1B, H350 STOT SE 3, H335
Toluene	(CAS No) 108-88-3 (EC no) 203-625-9 (EC index no) 601-021-00-3	< 0.1	Flam. Liq. 2, H225 Repr. 2, H361d Asp. Tox. 1, H304 STOT RE 2, H373 Skin Irrit. 2, H315 STOT SE 3, H336
1,2-epoxybutane	(CAS No) 106-88-7 (EC no) 203-438-2 (EC index no) 603-102-00-9	< 0.1	Flam. Liq. 2, H225 Carc. 2, H351 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Aquatic Chronic 3, H412
nitromethane	(CAS No) 75-52-5 (EC no) 200-876-6 (EC index no) 609-036-00-7	< 0.1	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302
Polyethylene Glycol	(CAS No) 25322-68-3 (EC no) 500-038-2	< 0.1	Not classified

Tempilaq® Temperature Indicating Liquid 800 °F (427 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

Name	Product identifier	Specific concentration limits
formaldehyde	(CAS No) 50-00-0 (EC no) 200-001-8 (EC index no) 605-001-00-5	(C >= 0.2) Skin Sens. 1, H317 (C >= 5) STOT SE 3, H335 (5 =< C < 25) Eye Irrit. 2, H319 (5 =< C < 25) Skin Irrit. 2, H315 (C >= 25) Skin Corr. 1B, H314

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.
- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
- First-aid measures after skin contact : Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.
- First-aid measures after ingestion : Drink plenty of water. Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.
- Symptoms/injuries after inhalation : May cause an allergic skin reaction. May cause cancer by inhalation. May cause respiratory irritation.
- Symptoms/injuries after skin contact : Causes skin irritation.
- Symptoms/injuries after eye contact : Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

All treatments should be based on observed signs and symptoms of distress in the patient.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Carbon dioxide. Dry powder. Foam. Sand. Water fog.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Burning produces irritating, toxic and noxious fumes.
- Explosion hazard : Product is not explosive.

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not allow run-off from fire fighting to enter drains or water courses.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Wear fire/flame resistant/retardant clothing. Wear a self contained breathing apparatus. EN469.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid all eye and skin contact and do not breathe vapour and mist.

6.1.1. For non-emergency personnel

- Protective equipment : Chemical goggles or safety glasses. Wear suitable protective clothing and gloves.
- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Chemical goggles or safety glasses. Wear suitable protective clothing and gloves.
- Emergency procedures : Stop leak if safe to do so. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Do not allow minor leaks or spills to accumulate on walking surfaces.
- Methods for cleaning up : Absorb and/or contain spill with inert material, then place in suitable container.

6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

Tempilaq® Temperature Indicating Liquid 800 °F (427 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapour and mist. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tightly closed. Keep only in the original container.

Incompatible products : Strong acids. Strong bases.

Incompatible materials : Heat sources. Direct sunlight.

Prohibitions on mixed storage : Incompatible materials.

Storage area : Store in dry, cool, well-ventilated area.

7.3. Specific end use(s)

Temperature indicator.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

1-bromopropane (106-94-5)		
Spain	VLA-ED (ppm)	10 ppm
Spain	Notes	TR1B
nitromethane (75-52-5)		
Denmark	Grænseværdie (kortvarig) (mg/m ³)	100 mg/m ³
Denmark	Grænseværdie (kortvarig) (ppm)	40 ppm
Polyethylene Glycol (25322-68-3)		
Austria	MAK (mg/m ³)	1000 mg/m ³ (einatembare Fraktion)
Austria	MAK Short time value (mg/m ³)	4000 mg/m ³ max. 4x15 min./Schicht (einatembare Fraktion)
Denmark	Grænseværdie (langvarig) (mg/m ³)	1000 mg/m ³
Denmark	Grænseværdie (kortvarig) (mg/m ³)	2000 mg/m ³
Denmark	Anmærkninger (DK)	(Polyethylenglycol (PEG) med middelmolvægt på 200-600)
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	1000 mg/m ³
Germany	TRGS 900 Limitation of exposure peaks (mg/m ³)	8000 mg/m ³
Germany	Remark (TRGS 900)	(einatembare Fraktion)
Slovakia	NPHV (priemerná) (mg/m ³)	1000 mg/m ³
Slovakia	Upozornenie (SK)	krátkodobý: kategória II.
Switzerland	VME (ppm)	1000 ppm
Switzerland	Remark (CH)	(mittlere Molmasse 200–600)
Toluene (108-88-3)		
EU	IOELV TWA (mg/m ³)	192 mg/m ³
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m ³)	384 mg/m ³
EU	IOELV STEL (ppm)	100 ppm
EU	Notes	Skin
Denmark	Grænseværdie (kortvarig) (mg/m ³)	188 mg/m ³
Denmark	Grænseværdie (kortvarig) (ppm)	50 ppm
France	Note (FR)	Peau
Germany	TRGS 903 (BGW)	3 mg/l o-Kresol (Urin; bei Langzeitexposition/Expositionsende bzw. Schichtende) 1 mg/l Toluol (Blut; Expositionsende bzw. Schichtende)
Slovakia	NPHV (priemerná) (mg/m ³)	192 mg/m ³ (K)

Tempilaq® Temperature Indicating Liquid 800 °F (427 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

Toluene (108-88-3)		
Slovakia	NPHV (priemerná) (ppm)	50 ppm (K) 600 ppm (Toluén) 1.5 ppm (O-krezol) 2401 ppm (Kyselina hippurová)
Sweden	Anmärkning (SE)	(B,H)
1-Butanol (71-36-3)		
Finland	Huomautus (FI)	iho
Germany	TRGS 903 (BGW)	2 mg/g Kreatinin 1-Butanol (Urin; vor nachfolgender Schicht) 10 mg/g Kreatinin 1-Butanol (Urin; Expositionsende bzw. Schichtende)
Slovakia	NPHV (priemerná) (mg/m ³)	310 mg/m ³ krátkodobý: kategória I.
Slovakia	NPHV (priemerná) (ppm)	100 ppm krátkodobý: kategória I. 2 ppm (M,d) 10 ppm (M,b)
Spain	VLA-EC (mg/m ³)	154 mg/m ³
Spain	VLA-EC (ppm)	50 ppm
Spain	Notes	vía dérmica,
Sweden	Anmärkning (SE)	H
Norway	Grenseverdier (Takverdi) (mg/m ³)	75 mg/m ³
Norway	Grenseverdier (Takverdi) (ppm)	25 ppm
formaldehyde (50-00-0)		
Slovakia	NPHV (priemerná) (mg/m ³)	0.37 mg/m ³
Slovakia	NPHV (priemerná) (ppm)	0.3 ppm
Slovakia	Upozornenie (SK)	(S)
Spain	VLA-EC (mg/m ³)	0.37 mg/m ³
Spain	VLA-EC (ppm)	0.3 ppm
Spain	Notes	vía dérmica,TR1B
Sweden	Anmärkning (SE)	(C,H,S,M)
Norway	Grenseverdier (AN) (mg/m ³)	0.6 mg/m ³
Norway	Grenseverdier (AN) (ppm)	0.5 ppm
Norway	Grenseverdier (Takverdi) (mg/m ³)	1.2 mg/m ³
Norway	Grenseverdier (Takverdi) (ppm)	1 ppm
Norway	Merknader (NO)	A, K
Molybdenum trioxide (1313-27-5)		
Finland	Huomautus (FI)	Mo

8.2. Exposure controls

Appropriate engineering controls	: Avoid splashing. Ensure good ventilation of the work station.
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Use rubber gloves. EN 374.
Eye protection	: Chemical goggles or safety glasses. EN166.
Skin and body protection	: Wear suitable protective clothing. Long sleeved protective clothing.
Respiratory protection	: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Use an approved respirator equipped with oil/mist cartridges. EN 12083.
Environmental exposure controls	: Prevent leakage or spillage.
Consumer exposure controls	: Keep out of reach of children. Avoid contact during pregnancy/while nursing.
Other information	: Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Opaque liquid.
Colour	: Green.
Odour	: No data available

Tempilaq® Temperature Indicating Liquid 800 °F (427 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 93 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content : 18.4 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Direct sunlight. Heat.

10.5. Incompatible materials

Strong bases. Strong acids.

10.6. Hazardous decomposition products

Burning produces irritating, toxic and noxious fumes. Carbon dioxide. Carbon monoxide. Hydrogen halide. Bromides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

1,2-epoxybutane (106-88-7)	
LD50 oral rat	1100 µl/kg
LC50 inhalation rat (Vapours - mg/l/4h)	30 minute exposure- 5/5 died, All unconscious when removed. Died by end of day. 12 minute exposure- 5/5 died, All unsteady when removed and died two hours after exposure. 6 minute exposure- 0/3 died.
ATE CLP (oral)	500.000 mg/kg bodyweight
ATE CLP (dermal)	1100.000 mg/kg bodyweight
ATE CLP (gases)	4500.000 ppmv/4h
ATE CLP (vapours)	11.000 mg/l/4h
ATE CLP (dust,mist)	1.500 mg/l/4h
1-bromopropane (106-94-5)	
LD50 oral rat	> 2000
LD50 dermal rat	> 2000 mg/kg
LC50 inhalation rat (ppm)	14374 ppm/4h
ATE CLP (gases)	14374.000 ppmv/4h

Tempilaq® Temperature Indicating Liquid 800 °F (427 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

nitromethane (75-52-5)	
LD50 oral rat	1506 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 12.75 mg/l 1 h
ATE CLP (oral)	1506.000 mg/kg bodyweight
Polyethylene Glycol (25322-68-3)	
LD50 oral rat	47000 mg/kg
LD50 dermal rat	> 20000 mg/kg
ATE CLP (oral)	47000.000 mg/kg bodyweight
Toluene (108-88-3)	
LD50 oral rat	5580 mg/kg EU Method B.1 (Acute Toxicity (Oral))
LC50 inhalation rat (mg/l)	> 20 mg/l/4h OECD Guideline 403 (Acute Inhalation Toxicity)
ATE CLP (oral)	5580.000 mg/kg bodyweight
1-Butanol (71-36-3)	
ATE CLP (oral)	500.000 mg/kg bodyweight
formaldehyde (50-00-0)	
LC50 inhalation rat (ppm)	31.7 ppm
ATE CLP (oral)	100.000 mg/kg bodyweight
ATE CLP (dermal)	300.000 mg/kg bodyweight
ATE CLP (dust,mist)	0.500 mg/l/4h
1,3,5-Triazine-2,4,6-triamine, polymer with formaldehyde, butylated (68002-25-5)	
LD50 oral rat	> 1100 mg/kg
LD50 dermal rabbit	1800 mg/kg
LC50 inhalation rat (mg/l)	> 6 mg/l/4h
ATE CLP (dermal)	1800.000 mg/kg bodyweight
Molybdenum trioxide (1313-27-5)	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight
LC50 inhalation rat (mg/l)	> 3.92 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation. Causes skin irritation
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer.
Reproductive toxicity	: May damage fertility or the unborn child.
Specific target organ toxicity (single exposure)	: May cause respiratory irritation. May cause respiratory irritation
Specific target organ toxicity (repeated exposure)	: May cause damage to organs through prolonged or repeated exposure. May cause damage to organs through prolonged or repeated exposure

1-bromopropane (106-94-5)	
NOAEL (inhalation, rat, dust/mist/fume, 90 days)	1 mg/l/6h/day

Toluene (108-88-3)	
LOAEL (inhalation, rat, gas, 90 days)	1250 ppmv/6h/day
NOAEL (oral, rat, 90 days)	625 mg/kg bodyweight/day EU Method B.26. Increased relative weights of liver and kidney are interpreted as toxicologically insignificant differences in the absence of histological findings.
NOAEL (inhalation, rat, gas, 90 days)	300 ppmv/6h/day OECD Guideline 453

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

1,2-epoxybutane (106-88-7)	
LC50 fish 1	> 100 mg/l 96 h
EC50 Daphnia 1	70 mg/l 48 h
ErC50 (algae)	> 500 mg/l 72 h

Tempilaq® Temperature Indicating Liquid 800 °F (427 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

1-bromopropane (106-94-5)	
EC50 Daphnia 1	203 mg/l 24 h
ErC50 (algae)	52.4 mg/l
nitromethane (75-52-5)	
LC50 fish 1	659.2 mg/l 96 h
EC50 Daphnia 1	> 103 mg/l 48 h
Polyethylene Glycol (25322-68-3)	
LC50 fish 1	> 100 mg/l
LC50 other aquatic organisms 1	1000 mg/l
Toluene (108-88-3)	
LC50 fish 1	5.5 mg/l
EC50 Daphnia 2	3.78 mg/l
ErC50 (algae)	134 mg/l
LOEC (chronic)	2.77 mg/l
NOEC chronic fish	1.39 mg/l
NOEC chronic crustacea	0.74 mg/l
formaldehyde (50-00-0)	
LC50 fish 1	31.8 (21.1 - 47.7) mg/l 96 h
EC50 Daphnia 1	1.9 mg/l 48 h
Molybdenum trioxide (1313-27-5)	
LC50 fish 1	>= 43.3 (≤ 58) mg/l
NOEC (chronic)	> 87.8 mg/l

12.2. Persistence and degradability

1,2-epoxybutane (106-88-7)	
Persistence and degradability	Readily biodegradable.
1-bromopropane (106-94-5)	
Persistence and degradability	Readily biodegradable.
nitromethane (75-52-5)	
Persistence and degradability	Not readily biodegradable.
Biodegradation	9.9 % 28 d
Toluene (108-88-3)	
Persistence and degradability	Readily biodegradable.
formaldehyde (50-00-0)	
Persistence and degradability	Readily biodegradable.

12.3. Bioaccumulative potential

1,2-epoxybutane (106-88-7)	
Log Pow	0.86
1-bromopropane (106-94-5)	
BCF fish 1	11.29 L/kg ww
Log Pow	2.16
nitromethane (75-52-5)	
Log Pow	-0.241
Toluene (108-88-3)	
Bioconcentration factor (BCF REACH)	90
Log Kow	2.73
formaldehyde (50-00-0)	
BCF fish 1	< 1
Log Pow	0.35

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Tempilaq® Temperature Indicating Liquid 800 °F (427 °C)	
PBT: not yet assessed	
vPvB: not yet assessed	

Tempilaq® Temperature Indicating Liquid 800 °F (427 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

Component	
1-bromopropane (106-94-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations	: Do not dispose of waste into sewer.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
European List of Waste (LoW) code	: For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used.
H code	: H10 - 'Toxic for reproduction': substances and preparations which, if they are inhaled or ingested or if they penetrate the skin, may induce non-hereditary congenital malformations or increase their incidence. H13 - 'Sensitizing': substances and preparations which, if they are inhaled or if they penetrate the skin, are capable of eliciting a reaction of hypersensitization such that on further exposure to the substance or preparation, characteristic adverse effects are produced. H5 - 'Harmful': substances and preparations which, if they are inhaled or ingested or if they penetrate the skin, may involve limited health risks. H8 - 'Corrosive': substances and preparations which may destroy living tissue on contact. H7 - 'Carcinogenic': substances and preparations which, if they are inhaled or ingested or if they penetrate the skin, may induce cancer or increase its incidence.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

Not considered a dangerous good for transport regulations

14.2. UN proper shipping name

Proper Shipping Name (ADR) :

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

14.6.1. Overland transport

No additional information available

14.6.2. Transport by sea

No additional information available

14.6.3. Inland waterway transport

Carriage prohibited (ADN) : No

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains substance on the REACH candidate list in concentration $\geq 0.1\%$ or with a lower specific limit: 1-bromopropane (n-propyl bromide) (EC 203-445-0, CAS 106-94-5)

Contains no REACH Annex XIV substances

VOC content : 18.4 %

15.1.2. National regulations

Germany

Tempilaq® Temperature Indicating Liquid 800 °F (427 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

Water hazard class (WGK)	: 3 - severe hazard to waters
WGK remark	: Classification based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

according to Regulation (EU) 2015/830

Indication of changes:
Original Document.

Abbreviations and acronyms:

	ACGIH (American Conference of Government Industrial Hygienists)
	ATE: Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	CLP: Classification, Labelling, Packaging.
	EC50: Environmental Concentration associated with a response by 50% of the test population.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
	LD50: Lethal Dose for 50% of the test population
	OSHA: Occupational Safety & Health Administration
	PBT: Persistent, Bioaccumulative, Toxic
	PNEC: Predicted No Effect Level
	STEL: Short Term Exposure Limits
	TSCA: Toxic Substances Control Act
	TWA: Time Weighted Average

Data sources	: Canadian Centre for Occupational Health and Safety. Accessed at: http://www.ccohs.ca/oshanswers/legisl/whmis_classifi.html .
	ESIS (European chemical Substances Information System; accessed at: http://esis.jrc.ec.europa.eu/index.php?PGM=cla).
	European Chemicals Agency (ECHA) Registered Substances list. Accessed at http://echa.europa.eu/ . Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition.
	National Fire Protection Association; Fire Protection Guide to Hazardous Materials; 10th edition.
	OSHA 29CFR 1910.1200 Hazard Communication Standard.
	REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.
	TSCA Chemical Substance Inventory. Accessed at http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html .

Other information : None.

Full text of R-, H- and EUH-statements:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1B	Carcinogenicity, Category 1B
Carc. 2	Carcinogenicity, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Muta. 2	Germ cell mutagenicity, Category 2
Repr. 1B	Reproductive toxicity, Category 1B
Repr. 1B	Reproductive toxicity, Category 1B
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1B

Tempilaq® Temperature Indicating Liquid 800 °F (427 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H301	Toxic if swallowed
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H341	Suspected of causing genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H360	May damage fertility or the unborn child
H360FD	May damage fertility. May damage the unborn child
H361d	Suspected of damaging the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H412	Harmful to aquatic life with long lasting effects

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Skin Irrit. 2	H315	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 1B	H350	Calculation method
Repr. 1B	H360	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Expert judgment

LA-CO EU CLP SDS

SDS Prepared by: The Redstone Group, LLC
6077 Frantz Rd.
Suite 206
Dublin, OH USA 43016
T 614-923-7472
www.redstonegrp.com

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product