

TITANIUM DIOXIDE

T e c h n i c a l D a t a

CR-826

TRONOX® CR-826 rutile titanium dioxide pigment is a universal product which combines very high durability, gloss retention and chalk resistance in exterior applications with excellent optical performance. The combination of high tint strength and outstanding durability makes this product an excellent choice for both coatings and plastic applications.

Applications

Interior and exterior industrial coatings ■ Interior and exterior architectural coatings ■ Powder coatings ■ Coil finishes ■ Marine finishes ■ Solvent and water based coatings ■ Vinyl siding ■ Vinyl window profiles ■ Vinyl fencing ■ Composite decking ■ Vinyl pipe

Typical Properties¹

TiO ₂ content %	93
Density	
Specific gravity	4.0
Bulk	0.8 kg/l or 50 lbs/cu.ft.
Oil absorption	18
pH	8.5
Specific Resistance, kohms-cm.	.8
Average particle size ² (µm).	0.20
Durability	Very High
Specification	
ASTM D476- 00(2005)	Type II, III, IV, V, VI, VII
ISO 591-1:2000	.R2
NSF/ANSI standard.	14/61
FDA	.Food Contact Substance ³

¹Typical properties not to be construed as specifications

²By electron microscope

³Limitations apply. Contact Tronox representative for more information.

The information herein is believed to be reliable. However, no warranty, expressed or implied, is made as to its accuracy or completeness and none is made as to the merchantability of the material or its fitness for any purpose. The manufacturer shall not be liable for consequential damages or for damages to persons or property resulting from its use. Nothing herein shall be construed as a recommendation for use in violation of any patent.

Plant Locations:

Botlek, The Netherlands
Mississippi, U.S
Kwinana, Australia

Sales Offices:

Oklahoma City 1-800-654-3911
Singapore +65-6255-0098
Shanghai, China +86-21-63912658
Perth, Australia +61-8-9361-4700
Botlek, The Netherlands +31-181-246600

TRONOX