# AC-PRO-MP-IITM TRIP UNIT MICRO-CONTROLLER BASED

Fully Programmable
Direct Plug-In Replacement Trip Unit
for Masterpact STR Trip Units

NOTE: The AC-PRO-MP-II will be available for purchase in 2015.

#### **MASTERPACT MP**

### **Direct Replacement Trip Unit**

The AC-PRO-MP-II is a plug-in, direct replacement trip unit for Merlin Gerin & Square D Masterpact MP, IEC or UL rated breakers.

The AC-PRO-MP-II is user programmed to replace any of the versions of STR-18M, 28D, 38S or 58U trip units. The AC-PRO-MP-II has the same protective functions, settings and time-current-curves as the original STR.

### **Standard Trip Unit Functions**

Based on the STR type entered:

- ☐ Long-Time
- ☐ Short-Time
- □Instantaneous
- ☐ Residual Ground Fault
- ☐ Ground Return Ground Fault
- ☐ Instantaneous on Closing (DINF)
- **□** Over Temperature Trip
- ☐ Patented Sluggish Breaker Detection

## Advanced Trip Unit Functions ☐ No Rating Plugs

No physical rating plug is required. The required rating plug value is a programmed setting.

□ QUICK-TRIP® Arc Flash Reduction
QUICK-TRIP instantaneous & ground
fault settings are standard for arc
flash reduction. A QUICK-TRIP switch
is easily accessible on the face of the
AC-PRO-MP-II. Connections for an
optional remote QUICK-TRIP switch
and indicating light are available.

### ☐ Security Code

A security code system protects against unauthorized changes to the settings.

### Information & Alarm Functions are Standard

- □ 2 Load monitoring settings with output contacts.
- ☐ Pre-trip alarm contact & LED indicator. ☐ Breaker tripped alarm output contact
- is programmable by type of trip.

  Trip events are time stamped
- ☐ Wave form capture



### Display, LEDs & Push Buttons

- ☐ The OLED display is easy to read in either low or high ambient light conditions.
- ☐ The "Smart" push buttons have actions that are configured based on the displayed information.
- ☐ A "SELF-TEST OK" LED indicates a properly operating trip unit.
- ☐ A pre-trip LED indicates a pending trip.

### Test Port

- ☐ The front mounted test port allows for easy connection to a secondary injection test set that performs actual phase & ground fault tests not simulated tests.
- ☐ Front mounted electrically isolated USB port for data upload/download

### Communication

The AC-PRO-MP-II has wireless communication capability.

### **Power Monitoring**

The AC-PRO-MP-II reads the 3 phase voltage to display KW, KWH and power factor.

### Warranty

All AC-PRO-MP-II's come with a 2-year limited warranty.

