A Interface module selection

◆ 16-channel digital direct input - R System — 1 module

Wiring	Compact version	Connection: Screw	Connection: Tension c.	1 LED per ch.	Discon-nectable	Fuse	Order No.	Type
1-wire (signal)		✓					• **9441500000**	RS16ES RSV1,6/V
		✓			✓		• *9441860000*	RS16ES-I RSV1,6/V
2-wire (signal, + or –)		✓					• **9441700000**	RS16ES-DP RSV1,6/V
		✓				✓	• *9441560000*	RS16ES-DP/F RSV1,6/V
3-wire (signal, + and –)		✓			✓		• *9441600000*	RS16E-3E/I RSV1,6/V

B Cable selection

◆ Compatible cable

Type	Qty	Order No.
Standard	1	• *7789016xxx*

Note:
The Order No. suffix **xxx** indicates the length of the cable in **dm (= 10 cm)**.

Standard lengths:

Length **L**	Suffix **(xxx)**
• 1,00 m	(010)
• 1,50 m	(015)
• 2,00 m	(020)
• 3,00 m	(030)
• 4,00 m	(040)
• 5,00 m	(050)

➤ *Click the Order No. to view the technical data*

A Interface module selection

◆ 16-channel digital direct input - R System — 1 module

Wiring	Compact version	Connection: Screw	Connection: Tension c.	1 LED per ch.	Discon-nectable	Fuse	Order No.	Type
1-wire (signal)		✓					• **9441500000**	RS16ES RSV1,6/V
		✓			⟷		• *9441860000*	RS16ES-I RSV1,6/V
2-wire (signal, + or –)		✓					• **9441700000**	RS16ES-DP RSV1,6/V
		✓				▭	• *9441560000*	RS16ES-DP/F RSV1,6/V
3-wire (signal, + and –)		✓			⟷		• *9441600000*	RS16E-3E/I RSV1,6/V

B Cable selection

◆ Compatible cable

Type	Qty	Order No.
Standard	1	• *7789025xxx*

Note:
The Order No. suffix **xxx** indicates the length of the cable in **dm (= 10 cm)**.

Standard lengths:

Length **L**	Suffix **(xxx)**
• 1,00 m	(010)
• 1,50 m	(015)
• 2,00 m	(020)
• 3,00 m	(030)
• 4,00 m	(040)
• 5,00 m	(050)

➤ *Click the Order No. to view the technical data*

A Interface module selection

◆ 16-channel digital direct input - R System — 1 module

Wiring	Compact version	Connection: Screw	Connection: Tension c.	1 LED per ch.	Discon-nectable	Fuse	Order No.	Type
1-wire (signal)		✓					• **9441500000**	RS16ES RSV1,6/V
		✓			⟷		• *9441860000*	RS16ES-I RSV1,6/V
2-wire (signal, + or –)		✓					• **9441700000**	RS16ES-DP RSV1,6/V
		✓				▭	• *9441560000*	RS16ES-DP/F RSV1,6/V
3-wire (signal, + and –)		✓			⟷		• *9441600000*	RS16E-3E/I RSV1,6/V

B Cable selection

◆ Compatible cable

Type	Qty	Order No.
Standard	1	• *7789025xxx*

Note:
The Order No. suffix **xxx** indicates the length of the cable in **dm (= 10 cm)**.

Standard lengths:

Length **L**	Suffix **(xxx)**
• 1,00 m	(010)
• 1,50 m	(015)
• 2,00 m	(020)
• 3,00 m	(030)
• 4,00 m	(040)
• 5,00 m	(050)

➤ *Click the Order No. to view the technical data*

A Interface module selection

◆ 16-channel digital direct input - H System — 1 module

Wiring	Compact version	Connection: Screw	Connection: Tension c.	1 LED per ch.	Disconnectable	Fuse	Order No.	Type
1-wire (signal)	✓	✓					• **9445700000**	RS 16ES H/V
	✓	✓		✓			• **9445710000**	RS 16ES-L H/V
			✓				• *9447700000*	RS 16ES H/Z
			✓	✓			• *9447710000*	RS 16ES-L H/Z
		✓		✓	✓		• *9445810000*	RS 16ES-S-I-L H/V
2-wire (signal, + or –)	✓	✓					• **9445720000**	RS 16ES-D H/V
	✓	✓		✓			• **9445730000**	RS 16ES-D-L H/V
			✓	✓			• *9447730000*	RS 16ES-D-L H/Z
	✓	✓		✓	✓		• *9445750000*	RS 16ES-D-I-L H/V
			✓	✓	✓		• *9447750000*	RS 16ES-D-I-L H/Z
		✓				✓	• *9445820000*	RS 16ES-D-F H/V
3-wire (signal, + and –)	✓	✓					• **9445760000**	RS 16ES-T H/V
	✓	✓		✓			• **9445770000**	RS 16ES-T-L H/V
			✓	✓			• *9447770000*	RS 16ES-T-L H/Z

B Cable selection

◆ Compatible cable

Type	Qty	Order No.
Standard	1	• *7789019xxx (*)*

(*) 16 channels with same common. Only for positive logic

Note:
The Order No. suffix **xxx** indicates the length of the cable in **dm (= 10 cm)**.

Standard lengths:

Length **L**	Suffix **(xxx)**
• 1,00 m	(010)
• 1,50 m	(015)
• 2,00 m	(020)
• 3,00 m	(030)
• 4,00 m	(040)
• 5,00 m	(050)

➤ *Click the Order No. to view the technical data*

A Interface module selection

◆ 16-channel digital direct input - H System — 1 module

Wiring	Compact version	Connection: Screw	Connection: Tension c.	1 LED per ch.	Disconnectable	Fuse	Order No.	Type
1-wire (signal)	✓	✓					• **9445700000**	RS 16ES H/V
	✓	✓		✓			• **9445710000**	RS 16ES-L H/V
			✓				• *9447700000*	RS 16ES H/Z
			✓	✓			• *9447710000*	RS 16ES-L H/Z
		✓		✓	✓		• *9445810000*	RS 16ES-S-I-L H/V
2-wire (signal, + or –)	✓	✓					• **9445720000**	RS 16ES-D H/V
	✓	✓		✓			• **9445730000**	RS 16ES-D-L H/V
			✓	✓			• *9447730000*	RS 16ES-D-L H/Z
	✓	✓		✓	✓		• *9445750000*	RS 16ES-D-I-L H/V
			✓	✓	✓		• *9447750000*	RS 16ES-D-I-L H/Z
		✓				✓	• *9445820000*	RS 16ES-D-F H/V
3-wire (signal, + and –)	✓	✓					• **9445760000**	RS 16ES-T H/V
	✓	✓		✓			• **9445770000**	RS 16ES-T-L H/V
			✓	✓			• *9447770000*	RS 16ES-T-L H/Z

B Cable selection

◆ Compatible cable

Type	Qty	Order No.
Standard	1	• *7789019xxx (*)*

(*) 16 channels with same common. Only for positive logic

Note:
The Order No. suffix **xxx** indicates the length of the cable in **dm (= 10 cm)**.

Standard lengths:

Length **L**	Suffix **(xxx)**
• 1,00 m	(010)
• 1,50 m	(015)
• 2,00 m	(020)
• 3,00 m	(030)
• 4,00 m	(040)
• 5,00 m	(050)

➤ *Click the Order No. to view the technical data*

A Interface module selection

◆ 16-channel digital direct input - H System — 2 modules

Wiring	Compact version	Connection: Screw	Connection: Tension c.	1 LED per ch.	Disconnectable	Fuse	Order No.	Type
1-wire (signal)	✓	✓					• **9445700000**	RS 16ES H/V
	✓	✓		✓			• **9445710000**	RS 16ES-L H/V
			✓				• *9447700000*	RS 16ES H/Z
			✓	✓			• *9447710000*	RS 16ES-L H/Z
		✓		✓	✓		• *9445810000*	RS 16ES-S-I-L H/V
2-wire (signal, + or –)	✓	✓					• **9445720000**	RS 16ES-D H/V
	✓	✓		✓			• **9445730000**	RS 16ES-D-L H/V
			✓	✓			• *9447730000*	RS 16ES-D-L H/Z
	✓	✓		✓	✓		• *9445750000*	RS 16ES-D-I-L H/V
			✓	✓	✓		• *9447750000*	RS 16ES-D-I-L H/Z
		✓				✓	• *9445820000*	RS 16ES-D-F H/V
3-wire (signal, + and –)	✓	✓					• **9445760000**	RS 16ES-T H/V
	✓	✓		✓			• **9445770000**	RS 16ES-T-L H/V
			✓	✓			• *9447770000*	RS 16ES-T-L H/Z

B Cable selection

◆ Compatible cable

Type	Qty	Order No.
Standard	2	• *7789019xxx (*)*

(*) 16 channels with same common. Only for positive logic

Note:
The Order No. suffix **xxx** indicates the length of the cable in **dm (= 10 cm)**.

Standard lengths:

Length **L**	Suffix **(xxx)**
• 1,00 m	(010)
• 1,50 m	(015)
• 2,00 m	(020)
• 3,00 m	(030)
• 4,00 m	(040)
• 5,00 m	(050)

➤ *Click the Order No. to view the technical data*

A Interface module selection

◆ 8-channel digital direct output - R System — 1 module

Wiring	Compact version	Connection: Screw	Connection: Tension c.	1 LED per ch.	Disconnectable	Fuse	Order No.	Type
2-wire (signal, + or –)							• **9441540000**	RS8ES-DP RSV1,6/V

B Cable selection

◆ Compatible cable

Type	Qty	Order No.
Standard	1	• *7789017xxx (*)*

(*) 8 channels with same common

Note:
The Order No. suffix **xxx** indicates the length of the cable in **dm (= 10 cm)**.

Standard lengths:

Length **L**	Suffix **(xxx)**
• 1,00 m	(010)
• 1,50 m	(015)
• 2,00 m	(020)
• 3,00 m	(030)
• 4,00 m	(040)
• 5,00 m	(050)

➤ *Click the Order No. to view the technical data*

A Relay output module selection

◆ 8-channel digital relay ouput - H System — 1 module

Compact version	Connection: Screw	Connection: Tension c.	Type of contact	Fuse	Force function	E-valve ctrl.	Order No.	Type
⋊⋉	✓		1CO				• **9445000000**	RSM8C-1CO H/V
⋊⋉		✓	1CO				• *9447000000*	RSM8C-1CO H/Z

OR

A1 Direct output module selection

Click here

B Cable selection

◆ Compatible cable

Type	Qty	Order No.
Standard	1	• *7789015xxx (*)*

(*) 8 channels with same common

Note:
The Order No. suffix **xxx** indicates the length of the cable in **dm (= 10 cm)**.

Standard lengths:

Length **L**	Suffix **(xxx)**
• 1,00 m	(010)
• 1,50 m	(015)
• 2,00 m	(020)
• 3,00 m	(030)
• 4,00 m	(040)
• 5,00 m	(050)

Click the Order No. to view the technical data

A Interface module selection

◆ 8-channel digital direct output - R System — 1 module

Wiring	Compact version	Connection		1 LED per ch.	Discon-nectable	Fuse	Order No.	Type
		Screw	Tension c.					
2-wire (signal, + or –)							• **9441540000**	RS8ES-DP RSV1,6/V

B Cable selection

◆ Compatible cable

Type	Qty	Order No.
Standard	1	• *7789017xxx (*)*

(*) 8 channels with same common

Note:
The Order No. suffix **xxx** indicates the length of the cable in **dm (= 10 cm)**.

Standard lengths:

Length **L**	Suffix **(xxx)**
• 1,00 m	(010)
• 1,50 m	(015)
• 2,00 m	(020)
• 3,00 m	(030)
• 4,00 m	(040)
• 5,00 m	(050)

➤ *Click the Order No. to view the technical data*

A Interface module selection

◆ 16-channel digital direct output - R System — 1 module

Wiring	Compact version	Connection: Screw	Connection: Tension c.	1 LED per ch.	Discon-nectable	Fuse	Order No.	Type
1-wire (signal)		✓					• **9441500000**	RS16ES RSV1,6/V
		✓			✓		• *9441860000*	RS16ES-I RSV1,6/V
2-wire (signal, + or –)		✓					• **9441700000**	RS16ES-DP RSV1,6/V
		✓				✓	• *9441560000*	RS16ES-DP/F RSV1,6/V
3-wire (signal, + and –)		✓			✓		• *9441600000*	RS16E-3E/I RSV1,6/V

B Cable selection

◆ Compatible cable

Type	Qty	Order No.
Standard	1	• *7789016xxx*

Note:
The Order No. suffix **xxx** indicates the length of the cable in **dm (= 10 cm)**.

Standard lengths:

Length **L**	Suffix **(xxx)**
• 1,00 m	(010)
• 1,50 m	(015)
• 2,00 m	(020)
• 3,00 m	(030)
• 4,00 m	(040)
• 5,00 m	(050)

➤ *Click the Order No. to view the technical data*

A Interface module selection

◆ 16-channel digital direct output - R System — 1 module

Wiring	Compact version	Connection: Screw	Connection: Tension c.	1 LED per ch.	Discon-nectable	Fuse	Order No.	Type
1-wire (signal)		✓					• **9441500000**	RS16ES RSV1,6/V
		✓			✓		• *9441860000*	RS16ES-I RSV1,6/V
2-wire (signal, + or –)		✓					• **9441700000**	RS16ES-DP RSV1,6/V
		✓				✓	• *9441560000*	RS16ES-DP/F RSV1,6/V
3-wire (signal, + and –)		✓			✓		• *9441600000*	RS16E-3E/I RSV1,6/V

B Cable selection

◆ Compatible cable

Type	Qty	Order No.
Standard	1	• *7789024xxx (*)*

(*) 16 channels with same common

Note:
The Order No. suffix **xxx** indicates the length of the cable in **dm (= 10 cm)**.

Standard lengths:

Length **L**	Suffix **(xxx)**
• 1,00 m	(010)
• 1,50 m	(015)
• 2,00 m	(020)
• 3,00 m	(030)
• 4,00 m	(040)
• 5,00 m	(050)

➤ *Click the Order No. to view the technical data*

A Relay output module selection

◆ 16-channel digital relay ouput - H System — 1 module

Compact version	Connection: Screw	Connection: Tension c.	Type of contact	Fuse	Force function	E-valve ctrl.	Order No.	Type
	✓		1CO				• **9444610000**	RSM16-NV/1CO 24V (-/+)
		✓	1CO				• *9444660000*	RSM16-NZ/1CO 24V (-/+)
✓	✓		1CO				• *9445100000*	RSM16C-1CO H/V
✓		✓	1CO				• *9447100000*	RSM16C-1CO H/Z
✓	✓		1CO				• **1079390000**	RSM16 SLIM-1CO H/V
✓	✓		1CO				• *1094970000*	SUPPORT RSM16 SLIM-1CO H/V
	✓		2CO				• *9445160000*	RSM16-2CO H/V
		✓	2CO				• *9447160000*	RSM16-2CO H/Z
	✓		1CO		✓		• *9445140000*	RSM16-1CO-Fo H/V
	✓		1CO	✓			• *9445120000*	RSM16-1CO-Fu H/V
		✓	1CO	✓			• *9447120000*	RSM16-1CO-Fu H/Z
	✓		1NO			✓	• *9445180000*	RSM16 1NO/CDE-EV 24V- H/V

OR

A1 Direct output module selection

Click here

B Cable selection

◆ Compatible cable

Type	Qty	Order No.
Standard	1	• *7789018xxx*

Note:
The Order No. suffix **xxx** indicates the length of the cable in **dm (= 10 cm)**.

Standard lengths:

Length **L**	Suffix **(xxx)**
• 1,00 m	(010)
• 1,50 m	(015)
• 2,00 m	(020)
• 3,00 m	(030)
• 4,00 m	(040)
• 5,00 m	(050)

➤ *Click the Order No. to view the technical data*

A Relay output module selection

◆ 16-channel digital relay ouput - H System — 1 module

Compact version	Connection: Screw	Connection: Tension c.	Type of contact	Fuse	Force function	E-valve ctrl.	Order No.	Type
	✓		1CO				• **9444610000**	RSM16-NV/1CO 24V (-/+)
		✓	1CO				• *9444660000*	RSM16-NZ/1CO 24V (-/+)
✓	✓		1CO				• *9445100000*	RSM16C-1CO H/V
✓		✓	1CO				• *9447100000*	RSM16C-1CO H/Z
✓	✓		1CO				• **1079390000**	RSM16 SLIM-1CO H/V
✓	✓		1CO				• *1094970000*	SUPPORT RSM16 SLIM-1CO H/V
	✓		2CO				• *9445160000*	RSM16-2CO H/V
		✓	2CO				• *9447160000*	RSM16-2CO H/Z
	✓		1CO		✓		• *9445140000*	RSM16-1CO-Fo H/V
	✓		1CO	✓			• *9445120000*	RSM16-1CO-Fu H/V
		✓	1CO	✓			• *9447120000*	RSM16-1CO-Fu H/Z
	✓		1NO			✓	• *9445180000*	RSM16 1NO/CDE-EV 24V- H/V

OR

A1 Direct output module selection

Click here

B Cable selection

◆ Compatible cable

Type	Qty	Order No.
Standard	1	• *7789018xxx*

Note:
The Order No. suffix **xxx** indicates the length of the cable in **dm (= 10 cm)**.

Standard lengths:

Length **L**	Suffix **(xxx)**
• 1,00 m	(010)
• 1,50 m	(015)
• 2,00 m	(020)
• 3,00 m	(030)
• 4,00 m	(040)
• 5,00 m	(050)

➤ *Click the Order No. to view the technical data*

A Interface module selection

◆ 16-channel digital direct output - H System — 1 module

Wiring	Compact version	Connection: Screw	Connection: Tension c.	1 LED per ch.	Discon-nectable	Fuse	Order No.	Type
1-wire (signal)	✓	✓					• **9445700000**	RS 16ES H/V
	✓	✓		✓			• **9445710000**	RS 16ES-L H/V
			✓				• *9447700000*	RS 16ES H/Z
			✓	✓			• *9447710000*	RS 16ES-L H/Z
		✓		✓	✓		• *9445810000*	RS 16ES-S-I-L H/V
2-wire (signal, + or –)	✓	✓					• **9445720000**	RS 16ES-D H/V
	✓	✓		✓			• **9445730000**	RS 16ES-D-L H/V
			✓	✓			• *9447730000*	RS 16ES-D-L H/Z
	✓	✓		✓	✓		• *9445750000*	RS 16ES-D-I-L H/V
			✓	✓	✓		• *9447750000*	RS 16ES-D-I-L H/Z
		✓				✓	• *9445820000*	RS 16ES-D-F H/V
3-wire (signal, + and –)	✓	✓					• **9445760000**	RS 16ES-T H/V
	✓	✓		✓			• **9445770000**	RS 16ES-T-L H/V
			✓	✓			• *9447770000*	RS 16ES-T-L H/Z

B Cable selection

◆ Compatible cable

Type	Qty	Order No.
Standard	1	• *7789018xxx*

Note:
The Order No. suffix **xxx** indicates the length of the cable in **dm (= 10 cm)**.

Standard lengths:

Length **L**	Suffix **(xxx)**
• 1,00 m	(010)
• 1,50 m	(015)
• 2,00 m	(020)
• 3,00 m	(030)
• 4,00 m	(040)
• 5,00 m	(050)

➤ *Click the Order No. to view the technical data*

A Interface module selection

◆ 16-channel digital direct output - R System — 1 module

Wiring	Compact version	Connection: Screw	Connection: Tension c.	1 LED per ch.	Discon-nectable	Fuse	Order No.	Type
1-wire (signal)		✓					• **9441500000**	RS16ES RSV1,6/V
		✓			✓		• *9441860000*	RS16ES-I RSV1,6/V
2-wire (signal, + or –)		✓					• **9441700000**	RS16ES-DP RSV1,6/V
		✓				✓	• *9441560000*	RS16ES-DP/F RSV1,6/V
3-wire (signal, + and –)		✓			✓		• *9441600000*	RS16E-3E/I RSV1,6/V

B Cable selection

◆ Compatible cable

Type	Qty	Order No.
Standard	1	• *7789024xxx (*)*

(*) 16 channels with same common

Note:
The Order No. suffix **xxx** indicates the length of the cable in **dm (= 10 cm)**.

Standard lengths:

Length **L**	Suffix **(xxx)**
• 1,00 m	(010)
• 1,50 m	(015)
• 2,00 m	(020)
• 3,00 m	(030)
• 4,00 m	(040)
• 5,00 m	(050)

➤ *Click the Order No. to view the technical data*

A Relay output module selection

◆ 16-channel digital relay ouput - H System — 2 modules

Compact version	Connection: Screw	Connection: Tension c.	Type of contact	Fuse	Force function	E-valve ctrl.	Order No.	Type
	✓		1CO				• **9444610000**	RSM16-NV/1CO 24V (-/+)
		✓	1CO				• *9444660000*	RSM16-NZ/1CO 24V (-/+)
✓	✓		1CO				• *9445100000*	RSM16C-1CO H/V
✓		✓	1CO				• *9447100000*	RSM16C-1CO H/Z
✓	✓		1CO				• **1079390000**	RSM16 SLIM-1CO H/V
✓	✓		1CO				• *1094970000*	SUPPORT RSM16 SLIM-1CO H/V
	✓		2CO				• *9445160000*	RSM16-2CO H/V
		✓	2CO				• *9447160000*	RSM16-2CO H/Z
	✓		1CO		✓		• *9445140000*	RSM16-1CO-Fo H/V
	✓		1CO	✓			• *9445120000*	RSM16-1CO-Fu H/V
		✓	1CO	✓			• *9447120000*	RSM16-1CO-Fu H/Z
	✓		1NO			✓	• *9445180000*	RSM16 1NO/CDE-EV 24V- H/V

OR

A1 Direct output module selection

Click here

B Cable selection

◆ Compatible cable

Type	Qty	Order No.
Standard	2	• *7789018xxx*

Note:
The Order No. suffix **xxx** indicates the length of the cable in **dm (= 10 cm)**.

Standard lengths:

Length **L**	Suffix **(xxx)**
• 1,00 m	(010)
• 1,50 m	(015)
• 2,00 m	(020)
• 3,00 m	(030)
• 4,00 m	(040)
• 5,00 m	(050)

➤ *Click the Order No. to view the technical data*

A Interface module selection

◆ 16-channel digital direct input/output - R System — 1 module

Wiring	Compact version	Connection: Screw	Connection: Tension c.	1 LED per ch.	Discon-nectable	Fuse	Order No.	Type
1-wire (signal)		✓					• **9441500000**	RS16ES RSV1,6/V
		✓			✓		• *9441860000*	RS16ES-I RSV1,6/V
2-wire (signal, + or –)		✓					• **9441700000**	RS16ES-DP RSV1,6/V
		✓				✓	• *9441560000*	RS16ES-DP/F RSV1,6/V
3-wire (signal, + and –)		✓			✓		• *9441600000*	RS16E-3E/I RSV1,6/V

B Cable selection

◆ Compatible cable

Type	Qty	Order No.
Standard	1	• *7789014xxx*

Note:
The Order No. suffix **xxx** indicates the length of the cable in **dm (= 10 cm)**.

Standard lengths:

Length **L**	Suffix **(xxx)**
• 1,00 m	(010)
• 1,50 m	(015)
• 2,00 m	(020)
• 3,00 m	(030)
• 4,00 m	(040)
• 5,00 m	(050)

➤ *Click the Order No. to view the technical data*

A Interface module selection

◆ 4-channel analog input/output — 1 module

	Compact version	Connection: Screw	Connection: Tension c.	Common distribution	Discon-nectable	Test point	Order No.	Type
Standard		✓		✓			• **9448000000**	RS4ESA-DP SD/V
		✓		✓	✓	✓	• *9448100000*	RS4ESA/I-M-DP SD/V
	✓	✓					• *8233350000*	RS-SD 15M/C (*)

(*) **Warning:**
Take in consideration the marking of the connector

B Cable selection

◆ Compatible cable *(to select)*

Type	Qty	Order No.
Standard	1	• *7789046xxx (1)*
Standard	1	• *7789026xxx (2)*

*(1) Use this cable for **voltage signals** (single ended).*
*(2) Use this cable for **current signals** (single ended).*

Note:
The Order No. suffix **xxx** indicates the length of the cable in **dm (= 10 cm)**.

Standard lengths:

Length **L**	Suffix **(xxx)**
• 1,00 m	(010)
• 1,50 m	(015)
• 2,00 m	(020)
• 3,00 m	(030)
• 4,00 m	(040)
• 5,00 m	(050)

➤ *Click the Order No. to view the technical data*

A Interface module selection

◆ 4-channel analog input/output — 1 module

	Compact version	Connection: Screw	Connection: Tension c.	Common distribution	Discon-nectable	Test point	Order No.	Type
Standard		✓		✓			• **9448000000**	RS4ESA-DP SD/V
		✓		✓	✓	✓	• *9448100000*	RS4ESA/I-M-DP SD/V
	✓	✓					• *8233350000*	RS-SD 15M/C (*)

(*) **Warning:**
Take in consideration the marking of the connector

B Cable selection

◆ Compatible cable *(to select)*

Type	Qty	Order No.
Standard	1	• *7789047xxx (1)*
Standard	1	• *7789027xxx (2)*

*(1) Use this cable for **voltage signals** (differentials).*
*(2) Use this cable for **current signals** (single ended).*

Note:
The Order No. suffix **xxx** indicates the length of the cable in **dm (= 10 cm)**.

Standard lengths:

Length **L**	Suffix **(xxx)**
• 1,00 m	(010)
• 1,50 m	(015)
• 2,00 m	(020)
• 3,00 m	(030)
• 4,00 m	(040)
• 5,00 m	(050)

➤ *Click the Order No. to view the technical data*

A Interface module selection

◆ 8-channel analog input/output — 1 module

	Compact version	Connection: Screw	Connection: Tension c.	Common distribution	Discon-nectable	Test point	Order No.	Type
Standard		✓		✓			• **9448010000**	RS8ESA-DP SD/V
		✓		✓	✓	✓	• *9448110000*	RS8ESA/I-M-DP SD/V
			✓	✓	✓	✓	• *9449110000*	RS8ESA/I-M-DP SD/Z
	✓	✓					• *8155650000*	RS-SD 25M/C (*)

(*) **Warning:**
Take in consideration the marking of the connector

B Cable selection

◆ Compatible cable *(to select)*

Type	Qty	Order No.
Standard	1	• *7789045xxx (1)*
Standard	1	• *7789028xxx (2)*

*(1) Use this cable for **voltage signals** (single ended).*
*(2) Use this cable for **current signals** (single ended).*

Note:
The Order No. suffix **xxx** indicates the length of the cable in **dm (= 10 cm)**.

Standard lengths:

Length **L**	Suffix **(xxx)**
• 1,00 m	(010)
• 1,50 m	(015)
• 2,00 m	(020)
• 3,00 m	(030)
• 4,00 m	(040)
• 5,00 m	(050)

➤ *Click the Order No. to view the technical data*

A Interface module selection

◆ 4-channel analog input/output — 1 module

	Compact version	Connection: Screw	Connection: Tension c.	Common distribution	Discon-nectable	Test point	Order No.	Type
Standard		✓		✓			• **9448000000**	RS4ESA-DP SD/V
		✓		✓	✓	✓	• *9448100000*	RS4ESA/I-M-DP SD/V
	✓	✓					• *8233350000*	RS-SD 15M/C (*)

(*) **Warning:**
Take in consideration the marking of the connector

B Cable selection

◆ Compatible cable

Type	Qty	Order No.
Standard	1	• *7789029xxx*

Note:
The Order No. suffix **xxx** indicates the length of the cable in **dm (= 10 cm)**.

Standard lengths:

Length **L**	Suffix **(xxx)**
• 1,00 m	(010)
• 1,50 m	(015)
• 2,00 m	(020)
• 3,00 m	(030)
• 4,00 m	(040)
• 5,00 m	(050)

➤ *Click the Order No. to view the technical data*

A Interface module selection

◆ 4-channel analog input/output — 1 module

	Compact version	Connection: Screw	Connection: Tension c.	Common distribution	Discon-nectable	Test point	Order No.	Type
Standard		✓		✓			• **9448000000**	RS4ESA-DP SD/V
		✓		✓	✓	✓	• *9448100000*	RS4ESA/I-M-DP SD/V
	✓	✓					• *8233350000*	RS-SD 15M/C (*)

(*) **Warning:**
Take in consideration the marking of the connector

B Cable selection

◆ Compatible cable

Type	Qty	Order No.
Standard	1	• *7789043xxx*

Note:
The Order No. suffix **xxx** indicates the length of the cable in **dm (= 10 cm)**.

Standard lengths:

Length **L**	Suffix **(xxx)**
• 1,00 m	(010)
• 1,50 m	(015)
• 2,00 m	(020)
• 3,00 m	(030)
• 4,00 m	(040)
• 5,00 m	(050)

➤ *Click the Order No. to view the technical data*

A Interface module selection

◆ 8-channel analog input/output — 1 module

	Compact version	Connection: Screw	Connection: Tension c.	Common distribution	Discon-nectable	Test point	Order No.	Type
Standard		✓		✓			• **9448010000**	RS8ESA-DP SD/V
		✓		✓	✓	✓	• *9448110000*	RS8ESA/I-M-DP SD/V
			✓	✓	✓	✓	• *9449110000*	RS8ESA/I-M-DP SD/Z
	✓	✓					• *8155650000*	RS-SD 25M/C (*)

(*) **Warning:**
Take in consideration the marking of the connector

B Cable selection

◆ Compatible cable

Type	Qty	Order No.
Standard	1	• *7789044xxx*

Note:
The Order No. suffix **xxx** indicates the length of the cable in **dm (= 10 cm)**.

Standard lengths:

Length **L**	Suffix **(xxx)**
• 1,00 m	(010)
• 1,50 m	(015)
• 2,00 m	(020)
• 3,00 m	(030)
• 4,00 m	(040)
• 5,00 m	(050)

➤ *Click the Order No. to view the technical data*

A Interface module selection

◆ 8-channel analog input/output — 1 module

	Compact version	Connection: Screw	Connection: Tension c.	Common distribution	Discon-nectable	Test point	Order No.	Type
Standard		✓		✓			• **9448010000**	RS8ESA-DP SD/V
		✓		✓	✓	✓	• *9448110000*	RS8ESA/I-M-DP SD/V
			✓	✓	✓	✓	• *9449110000*	RS8ESA/I-M-DP SD/Z
	✓	✓					• *8155650000*	RS-SD 25M/C (*)

(*) **Warning:**
Take in consideration the marking of the connector

B Cable selection

◆ Compatible cable

Type	Qty	Order No.
Standard	1	• *7789044xxx*

Note:
The Order No. suffix **xxx** indicates the length of the cable in **dm (= 10 cm)**.

Standard lengths:

Length **L**	Suffix **(xxx)**
• 1,00 m	(010)
• 1,50 m	(015)
• 2,00 m	(020)
• 3,00 m	(030)
• 4,00 m	(040)
• 5,00 m	(050)

➤ *Click the Order No. to view the technical data*

Direct output module selection

◆ 8-channel digital direct output - H System — 1 module

Wiring	Compact version	Connection: Screw	Connection: Tension c.	1 LED per ch.	Disconnectable	Fuse	Order No.	Type
2-wire (signal, + or –)							• **9445530000**	RS 8ES-D-L H/V

Back to:

1769 - OB8

Click the Order No. to view the technical data

Direct output module selection

◆ 16-channel digital direct output - H System — 1 module

Wiring	Compact version	Connection: Screw	Connection: Tension c.	1 LED per ch.	Discon-nectable	Fuse	Order No.	Type
1-wire (signal)	✓	✓					**9445700000**	RS 16ES H/V
	✓	✓		✓			**9445710000**	RS 16ES-L H/V
			✓				*9447700000*	RS 16ES H/Z
			✓	✓			*9447710000*	RS 16ES-L H/Z
		✓		✓	✓		*9445810000*	RS 16ES-S-I-L H/V
2-wire (signal, + or –)	✓	✓					**9445720000**	RS 16ES-D H/V
	✓	✓		✓			**9445730000**	RS 16ES-D-L H/V
			✓	✓			*9447730000*	RS 16ES-D-L H/Z
	✓	✓		✓	✓		*9445750000*	RS 16ES-D-I-L H/V
			✓	✓	✓		*9447750000*	RS 16ES-D-I-L H/Z
		✓				✓	*9445820000*	RS 16ES-D-F H/V
3-wire (signal, + and –)	✓	✓					**9445760000**	RS 16ES-T H/V
	✓	✓		✓			**9445770000**	RS 16ES-T-L H/V
			✓	✓			*9447770000*	RS 16ES-T-L H/Z

Back to:

1769 - OB16
1769 - OB16P

Click the Order No. to view the technical data

Direct output module selection

◆ 16-channel digital direct output - H System — 2 modules

Wiring	Compact version	Connection: Screw	Connection: Tension c.	1 LED per ch.	Disconnectable	Fuse	Order No.	Type
1-wire (signal)	✓	✓					• **9445700000**	RS 16ES H/V
	✓	✓		✓			• **9445710000**	RS 16ES-L H/V
			✓				• *9447700000*	RS 16ES H/Z
			✓	✓			• *9447710000*	RS 16ES-L H/Z
		✓		✓	✓		• *9445810000*	RS 16ES-S-I-L H/V
2-wire (signal, + or –)	✓	✓					• **9445720000**	RS 16ES-D H/V
	✓	✓		✓			• **9445730000**	RS 16ES-D-L H/V
			✓	✓			• *9447730000*	RS 16ES-D-L H/Z
	✓	✓		✓	✓		• *9445750000*	RS 16ES-D-I-L H/V
			✓	✓	✓		• *9447750000*	RS 16ES-D-I-L H/Z
		✓				✓	• *9445820000*	RS 16ES-D-F H/V
3-wire (signal, + and –)	✓	✓					• **9445760000**	RS 16ES-T H/V
	✓	✓		✓			• **9445770000**	RS 16ES-T-L H/V
			✓	✓			• *9447770000*	RS 16ES-T-L H/Z

Back to:

1769 - OB32

Click the Order No. to view the technical data