

Our one piece connectors are also available for RG59, HEC2, RG6 and RG6Q cables. BNC connectors meet SCTE physical requirements.



Part Number	Insertion Loss @ 1GHz	Return Loss (5-1000MHz)	Description	Cable Attachment Style/Identifier
BNCFP59	< .1dB	>30db	BNC - RG59	Crimp, Plug
BNCFP59SLC59	< .1dB	>30db	BNC - RG59	Compression, Plug/Dark Red O-Rings
BNCFP59SLCHEC	< .1dB	>30db	BNC - HEC2 Cable	Compression, Plug/Light Red O-Rings
BNCFP6	< .1dB	>30db	BNC - RG6	Crimp, Plug
BNCFP6SLC6	< .1dB	>30db	BNC - RG6	Compression, Plug/No Etching
BNCFP6SLC6G	< .1dB	>30db	Gold plated BNC - RG6	Compression, Plug/No Etching
BNCFP6SLC6Q	< .1dB	>30db	BNC - RG6 Quad	Compression, Plug/1 Etched Ring
BNCFP6SLC6QG	< .1dB	>30db	Gold plated BNC - RG6 Quad	Compression, Plug/1 Etched Ring

## CONNECTORS -- 75 OHM RCA CONNECTORS, ONE PIECE, FIXED PIN

WSE RCA connectors are intended to work with 75 Ohm cables. They are designed for efficient and reliable home theater and other A/V installations. EZ compression connectors are compatible with a variety of mini coaxial cables. Our one piece connectors are also available for RG59, RG6 and RG6Q cables.



Part Number	Finish	Cable Attachment Style/Identifier
RCAFP	Gold	Crimp, Plug
RCAFP59SLCG	Gold	Compression, Plug
RCAFP59SLC	Nickel body, Gold Pin	Compression, Plug
RCAFP59SLCBH	Nickel body, Gold contact	Crimp, Panel Mount Jack
RCAFP59SLCEZ	Nickel, Gold Pin	Compression, Plug
RCAFP59SLC90EZ	Nickel body, Gold Pin	Compression, 90° Plug
RCAFP59	Nickel body, Gold Pin	Crimp, Plug
RCAFP59SLC59	Nickel body, Gold Pin	Compression, Plug
RCAFP59SLC59G	Gold	Compression, Plug
RCAFP59SLC6	Nickel body, Gold Pin	Compression, Plug
RCAFP59SLC6G	Gold	Compression, Plug
RCAFP59SLC6QG	Gold	Compression, Plug/1 etched Ring

### Specifications

Impedance ..... ~75 Ω  
 Cable Retention Force ..... 40lbs  
 Current Rating ..... 2 Amps  
 Working Voltage ..... <300 Vrms  
 RFI ..... >100dB  
 Conductor/Pin Retention ..... >150 grams