wiePLEX - DIN Rail Mount AC OUTLETS



One Piece Design - No need to order and assemble separate parts, easy installation

Finger Safe Connections - Rising Cage Screw-type Connectors. Allows for increased safety during maintenance

DIN Rail Mountable Design - No need to drill and tap holes to mount

Clear Marking - Terminals are clearly and permanently marked to prevent wiring errors

Mounts In Equipment Cabinets - Ideal for mounting in equipment cabinets where AC power is required, i.e., laptop computers, test equipment, analyzers, electrical tools, etc.





wiePLEX Simplex DIN Rail Mount Single AC Outlet

wiePLEX Duplex DIN Rail Mount Dual AC Outlet

UL ratings CSA ratings Dimensions (mm) W x H x D	Wire strip length	Stranded/Solid 30 - 12 AWG 30 - 12 AWG 36 x 92 x 68	V 125 125	A 15 15 8mm	Stranded/Solid 30 - 12 AWG 30 - 12 AWG 72 x 92 x 68	V 125 125	A 15 15 8mm
Approvals:		SB (4)			\$ G		

Description	Туре	Part No.	Std. Pack	Туре	Part No.	Std. Pad
Simplex DIN Rail Mount AC Outlet	wiePLEX1	34.247.0001.0	1			
Duplex DIN Rail Mount AC Outlet				wiePLEX2	34.247.0002.0	
Wire size	30-12 AWG			30-12 AWG		
Operating Voltage	125 VAC			125 VAC		
Operating Current	15 A			15 A		
Connector Type	Single NEMA 5-15R			Duel NEMA 5-15R		
Number of Positions	1			2		

