


safety



wieland



sensor PRO
SLC Series –
Safety Light Curtains
SLD Series –
Safety Light Grids





SLC – A safety light curtain for every situation

Easy, fast and reliable

SLC series safety light curtains are ideally suited for implementing optoelectronic protective devices. The SLC series is thereby used to protect operators from dangerous areas or as an access control against unauthorized trespassing.

Features

- Safety light curtain AOPD type 4 or type 2
- Beam resolution 14, 20, 30, 40 and 90 mm
- Protection field heights 150 – 1800 mm
- Extensive accessories

Higher equipment availability

- Easy adjustment and stable operation through slim and rigid housing
- Parameterization without PC or DIP switch through simple wiring in the control cabinet
- The integrated Double-Scan technology avoids unwanted shutdown even in harsh operating conditions
- Clear diagnostic and status messages in the 7-segment display ensure shorter downtimes
- Cable lengths up to 100 m with unshielded connection cables ensure greater operational flexibility and reduced costs even under difficult EMC conditions



Finger and hand protection on automated handling systems easily implemented with the intelligent safety relay SNO 4083KM

SLD – the strong safety light grid

Innovative and economical



The SLD series safety light grids are optoelectronic personal protective devices for access protection to hazardous areas on machinery and equipment.

Features

- Safety light grid AOPD type 4
- 2-, 3- and 4-beam resolutions
- Also available as an universal system, i.e. transmitter/receiver in a single unit
- High ranges up to 70m can be implemented
- Extensive accessories



Integrated laser alignment aid




Increased reliability

- Solid housing construction in IP67
- Operating temperature range -30 °C to 55 °C permits implementation even in the harshest environments
- Multi-beam scanning avoids unwanted shutdown
- Mutual interference is avoided through the adjustable range reduction when implementing multiple systems
- Parameterization without PC or DIP switch through simple wiring in the control cabinet

Faster during commissioning, operation and service

- The integrated laser alignment aid (optional) permits precise mounting and reduces the startup times of the SLD system
- Robust device columns with spring-loaded base mounting and integrated alignment aid are available for the free-standing implementation
- Muting applications can be easily implemented with **samos**® or **samos**®PRO



Safely implement simple access protection on equipment with safety relays from the **safe** RELAY series




SLD series

device overview | order numbers

Type				Part No.			
SLD - 4	US	3 - 0 - 00	Example	R1. 6	4	4 . 3	0 00 .0
SLD			Product group				
			SLD = R1.6	R1. 6			.0
			Type				.0
	0		No specification (only MIR)		0		.0
	4		Type 4		4		.0
			Design type				
	TR		Transmitter		1		.0
	ST		Receiver Standard		2		.0
	SL		Receiver Select		3		.0
	US		Universal Standard		4		.0
	UL		Universal Select		5		.0
	MIR		Universal mirror		6		.0
			Number of beams				
		2	2 beams			2	.0
		3	3 beams			3	.0
		4	4 beams ¹⁾			4	.0
			Option				
		0	None			0	.0
		1	Laser alignment aid or reflective element ¹⁾			1	.0
			Range				
		00	No specification (only US + UL)				00 .0
		06	0.5 – 6 m (only MIR)				06 .0
		08	0.5 – 8 m (only MIR)				08 .0
		50	0.5 – 50 m (only ST + SL)				50 .0
		70	20 – 70 m (only ST + SL)				70 .0

¹⁾ only TR, ST + SL

You can find accessories and additional information in our eShop under <https://eshop.wieland-electric.com>
 We will gladly help you during the selection and commissioning process. You can reach our Technical Support desk at **+49 951 9324-999**




You can find additional information on the safety controller of the next generation in our brochure "samos[®]PRO COMPACT"

Order-No. 0881.1






SLD series



SLD Universal – Less cabling expenditure

The safety light grids consist of an integrated SLD universal transmitter/receiver unit and a passive reflector unit without electrical connection.

- 2- and 3-beam systems
- Range 0.5 to 8 m




SLD Standard / SLD Select

The safety light grid and SLD Standard and SLD Select each consist of a transmitter and a receiver unit and are thus suitable for highest ranges.

- 2-, 3- and 4-beam systems
- Ranges 0.5 - 50 m and 20 - 70 m

	SLD Standard	SLD Select	SLD Universal Standard	SLD Universal Select
LED display	✓	✓	✓	✓
Multi-scan technology	✓	✓	✓	✓
Range reduction	✓	✓		
Laser alignment aid (optional)	✓	✓		
Automatic start	✓	✓	✓	✓
Manual start / restart interlock		✓		✓
External device monitoring (EDM)		✓		✓
Transceiver system			✓	✓



SLD - Muting functions with *samos*[®]PRO COMPACT

SLD safety light grids are ideally suited for monitoring material locks, such as in the packaging industry, in combination with the freely configurable muting function blocks of *samos*[®]PRO COMPACT, for example in the packaging industry





SLC series

Faster during commissioning, operation and service

- The wide range of SLC products permits optimal and cost-effective design of protective devices
- Easy to connect via standard M12 connection technology
- Fast installation and removal on the machine through a system configuration in the control cabinet
- Selectable transmission channels and range reduction prevent mutual interference
- Simplified planning of safeguards and less type diversity because every SLC safety light curtain from 0 m to the maximum range can be implemented
- The 3-zone alignment indicator reduces assembly time and simplifies adjustment

Matching functions for every protection task


All important, non-contact safety functions on machines and equipment can be implemented using both Standard and Select designs of the SLC series.

	SLC Standard	SLC Select
LED display	✓	✓
Double-scan technology	✓	✓
Range reduction	✓	✓
Selectable transmission channels	✓	✓
7-segment display		✓
Automatic start	✓	✓
Manual start / restart interlock		✓
External device monitoring (EDM)		✓

◀ With 3-zone alignment indication

Wieland software tools

SISTEMA library



Safe switching on presses with the configurable safety modules **samos**® the wear-free long-life outputs



SLC series

device overview | order numbers

Type		Example		Part No.	
SLC -	4TR 14 - 0600			R1.5	4 1 . 0600 .0
Product group		SLC = R1.5		R1.5	5
Design type					
2TR	Type 2, transmitter			1	.0
2ST	Type 2, receiver Standard			2	.0
2SL	Type 2, receiver Select			3	.0
4TR	Type 4, transmitter			4	.0
4ST	Type 4, receiver Standard			5	.0
4SL	Type 4, receiver Select			6	.0
Resolution					
14	14 mm ¹⁾			1	.0
20	20 mm			2	.0
30	30 mm			3	.0
40	40 mm			4	.0
90	90 mm ²⁾			5	.0
Protective field height					
0150	150 mm			0150	.0
0225	225 mm			0225	.0
0300	300 mm			0300	.0
0450	450 mm			0450	.0
0600	600 mm			0600	.0
0750	750 mm			0750	.0
0900	900 mm			0900	.0
1050	1050 mm			1050	.0
1200	1200 mm			1200	.0
1350	1350 mm			1350	.0
1500	1500 mm			1500	.0
1650	1650 mm			1650	.0
1800	1800 mm			1800	.0

¹⁾ not for SLC-2 types

²⁾ available from protection field height 600 mm

You can find accessories and additional information in our eShop under <https://eshop.wieland-electric.com>
 We will gladly help you during the selection and commissioning process. You can reach our Technical Support desk at +49 951 9324-999



EPLAN – Support during projection

EPLAN data and macros, which are an integral component to support automation projects, can be easily downloaded from the Wieland homepage www.wieland-electric.com



You can receive more information on all our products in the field of safety technology of machines in our **safety** catalog

Order-No. 0860.1



wieland



Company Headquarters:
Wieland Electric GmbH
Brennerstraße 10 – 14
96052 Bamberg, Germany

Phone +49 951 9324-0
Fax +49 951 9324-198
info@wieland-electric.com
www.wieland-electric.com

Technical support:
Phone +49 951 9324-999
Fax +49 951 9326-991
safety@wieland-electric.com



USA
Wieland Electric Inc.
North American Headquarters
2889 Brighton Road
Oakville, Ontario L6H 6C9
Phone +1 905 8298414
Fax +1 905 829 413
www.wielandinc.com



CANADA
Wieland Electric Inc.
North American Headquarters
2889 Brighton Road
Oakville, Ontario L6H 6C9
Phone +1 905 8298414
Fax +1 905 829 413
www.wieland-electric.ca



GREAT BRITAIN
Wieland Electric Ltd.
Riverside Business Center,
Walnut Tree Close
GB Guildford/Surrey GU1 4UG
Phone +44 1483 531213
Fax +44 1483 505029
sales.uk@wieland-electric.com
www.wieland.co.uk



FRANCE
Wieland Electric SARL.
Le Cérame, Hall 6
47, avenue des Genottes
CS 48313,
95803 Cergy-Pontoise Cedex
Phone +33 1 30320707
Fax +33 1 30320717
info.france@wieland-electric.com
www.wieland-electric.fr



SPAIN
Wieland Electric S.L.
C/ Maria Auxiliadora 2, barcos
E-08017 Barcelona
Phone +34 93 2523820
Fax +34 93 2523825
ventas@wieland-electric.com
www.wieland-electric.es



ITALY
Wieland Electric S.r.l.
Via Edison, 209
I-20019 Settimo Milanese
Phone +39 02 48 916357
Fax +39 02 48 920685
info.italy@wieland-electric.com
www.wieland-electric.it



BELGIUM & GD LUXEMBOURG
ATEM-Wieland Electric NV
Bedrijvenpark De Veert 4
B-2830 Willebroek
Phone +32 3 8661800
Fax +32 3 8661828
info.belgium@wieland-electric.com
www.wieland-electric.be



DENMARK
Wieland Electric A/S
Vallørækken 26
DK-4600 Køge
Phone +45 70 266635
Fax +45 70 266637
sales.denmark@wieland-electric.com
www.wieland-electric.dk



SWITZERLAND
Wieland Electric AG
Harzachstrasse 2b
CH-8404 Winterthur
Phone +41 52 2352100
Fax +41 52 2352119
info.swiss@wieland-electric.com
www.wieland-electric.ch



POLAND
Wieland Electric Sp. z o.o.
Św. Antoniego 8
62-080 Swadzim
Phone +48 61 2225400
Fax +48 61 8407166
office@wieland-electric.pl
www.wieland-electric.pl



CHINA
Wieland Electric Trading
Unit 2703 International Soho City
889 Renmin Road,
Huang Pu District
PRC-Shanghai 200010
Phone +86 21 63555833
Fax +86 21 63550090
info-shanghai@wieland-electric.com
www.wieland-electric.cn



JAPAN
Wieland Electric Co, Ltd.
Nisso No. 16 Bldg. 7F
3-8-8 Shin-Yokohama,
Kohoku-ku
Yokohama 222-0033
Phone +81 45 473 5085
Fax +81 45 470 5408
info-japan@wieland-electric.com



GERMANY
Headquarters
Wieland Electric GmbH
Brennerstraße 10 – 14
96052 Bamberg, Germany
Phone +49 951 9324-0
Fax +49 951 9324-198
info@wieland-electric.com
www.wieland-electric.de

Sales Partner:

**You can reach us worldwide in more than 70 countries.
Find the contact address at: www.wieland-electric.com**

Subject to technical modifications!
gesis®, **RST®**, **GST®**, **GST18®**, **podis®**, **samos®** and **saris®**
are registered trademarks of Wieland Electric GmbH

**contacts
are
green.**