WIMA DC-LINK MKP3



Metallized Polypropylene (PP) - Capacitors for DC-Link Applications. Capacitances from 35 µF to 200 µF. Rated Voltages from 700 VDC to 1500 VDC.

Special Features

- Very high volume/capacitance ratio
- Self-healing properties
- With cylindrical plastic case and screw fixing
- Dry construction without electrolyte or oil
- No internel fuse required
- Negative capacitance change versus temperature
- Very low dielectric absorption
- According to RoHS 2011/65/EU
- Customer-specific capacitances or voltages on request

Electrical Data

Capacitance range: $35 \mu F$ to $200 \mu F$ Rated voltages: 700 VDC, 900 VDC, 1100 VDC, 1300 VDC, 1500 VDC

Capacitance tolerances: $\pm 20\%$, $\pm 10\%$, (±5% available subject to special enquiry)

Operating temperature range:

-40° C to +85° C

Insulation resistance at +20° C:

 \geq 5000 sec (M $\Omega \times \mu$ F) (mean value: 20000 sec)

Measuring voltage: 100 V/1 min.

Dielectric loss factor tan δ_0 : 2 x 10⁻⁴

Test voltage: 1.5 U,, 2sec Dielectric absorption:

0.05 % Reliability:

Operational life > 100 000 hours Failure rate < 50 fit (hot spot ≤ 70° C)

Typical Applications

DC capacitors with high capacitances for applications in power electronics also at non-sinusoidal voltages and currents e.g. in

- Wind power systems
- Inverters

Construction


Dielectric:

Polypropylene (PP) film

Capacitor electrodes:

Vacuum-deposited

Internal construction:



Encapsulation:

Solvent-resistant, flame-retardant plastic case with PU-sealing and screw fixing, UL 94 V-0

Terminations:

Screw connection (male or female).

Markina:

Colour: Black. Marking: Gold.


Mounting Recommendation

Excessive mechanical strain, e.g. pressure or shock onto the capacitor body, is to be avoided during mounting and usage of the capacitors.

Packing

Transport-safe packing in cardboard boxes.

For further details and graphs please refer to Technical Information.



The capacitors are non-polarized and are optionally available with "male" and "female" terminations. 0

WIMA DC-LINK MKP3



Continuation

General Data

U _R	C _N	D x L mm	I _{rms} (1 kHz)* A	ESR (1 kHz)* mΩ	R _{th} K/W	L _e nH	Approx.weight g	Part number
700 VDC	150 μF	84.5 x 51	100	0.9	7.0	< 32	430	DCP3K06150G100
	200 "	84.5 x 64	100	1.0	8.5	< 40	510	DCP3K06200G200
900 VDC	100 μF	84.5 x 51	90	1.0	7.2	< 30	430	DCP3N06100G100
	140 "	84.5 x 64	100	1.3	8.5	< 40	510	DCP3N06140G200
1100 VDC	70 μF	84.5 x 51	100	1.1	7.0	< 32	430	DCP3P05700G100
	90 "	84.5 x 64	100	1.2	8.5	< 40	510	DCP3P05900G200
1300 VDC	50 μF	84.5 x 51	60	1. <i>7</i>	7.0	< 35	430	DCP3R25500G100
	70 "	84.5 x 64	50	2.1	8.5	< 40	510	DCP3R25700G200
1500 VDC	35 µ F	84.5 x 51	60	1. <i>7</i>	7.0	< 35	430	DCP3S05350G100
	50 "	84.5 x 64	70	1.9	8.5	< 40	510	DCP3S05500G200


Contacts can handle: peak currents $\hat{1}$ up to 5 kA surge currents I_S up to 20 kA

Customer-specific capacitances or voltages on request


* General guide

Dims. in mm.

female




male




Part number completion:

Tolerance: 20 % = M 10 % = K 5 % = JPacking: bulk = S Connection: male = 0M

 $\mathsf{female} = \mathsf{OF}$





D	L		
84.5	51		
84.5	64		

Rights reserved to amend design data without prior notification.

-WIMA Part Number System



A WIMA part number consists of 18 digits and is composed as follows:

Field 1 - 4: Type description

Field 5 - 6: Rated voltage

Field 7 - 10: Capacitance


Field 11 - 12: Size and PCM

Field 13 - 14: Version code (e.g. Snubber versions)

Field 15: Capacitance tolerance

Packing Field 16:

Field 17 - 18: Pin length (untaped)



Type description:		Rated voltage:	Capacitance:	Size:	Tolerance:
SMD-PET	= SMDT	50 VDC = B0	22 pF = 0022	$4.8 \times 3.3 \times 3$ Size 1812 = KA	$\pm 20\% = M$
SMD-PEN	= SMDN	63 VDC = C0	47 pF = 0047	$4.8 \times 3.3 \times 4$ Size 1812 = KB	$\pm 10\% = K$
SMD-PPS	= SMDI	100 VDC = D0	100 pF = 0100	$5.7 \times 5.1 \times 3.5$ Size $2220 = QA$	$\pm 5\% = J$
FKP 02	= FKPO	250 VDC = FO	150 pF = 0150	$5.7 \times 5.1 \times 4.5$ Size $2220 = QB$	$\pm 2.5\% = H$
MKS 02	=MKS0	400 VDC = G0	220 pF = 0220	$7.2 \times 6.1 \times 3$ Size 2824 = TA	$\pm 1\% = E$
FKS 2	= FKS2	450 VDC = H0	330 pF = 0330	$7.2 \times 6.1 \times 5$ Size 2824 = TB	
FKP 2	= FKP2	520 VDC = H2	470 pF = 0470	$10.2 \times 7.6 \times 5$ Size $4030 = VA$	
FKS 3	= FKS3	600 VDC = 10	680 pF = 0680	$12.7 \times 10.2 \times 6$ Size $5040 = XA$	
FKP 3	= FKP 3	630 VDC = J0	1000 pF = 1100	$15.3 \times 13.7 \times 7$ Size $6054 = YA$	Packing:
MKS 2	=MKS2	700 VDC = KO	1500 pF = 1150	$2.5 \times 7 \times 4.6 \text{ PCM } 2.5 = 0B$	AMMO H16.5 $340 \times 340 = A$
MKP 2	=MKP2	800 VDC = 10	2200 pF = 1220	$3 \times 7.5 \times 4.6 \text{ PCM } 2.5 = 0 \text{C}$	AMMO H16.5 $490 \times 370 = B$
MKS 4	= MKS4	850 VDC = M0	3300 pF = 1330	$2.5 \times 6.5 \times 7.2 \text{ PCM}5 = 1 \text{A}$	AMMO H18.5 $340 \times 340 = C$
MKP 4C	= MKPC	900 VDC = N0	4700 pF = 1470	$3 \times 7.5 \times 7.2 \text{ PCM} 5 = 1B$	AMMO H18.5 $490 \times 370 = D$
MKP 4	=MKP4	1000 VDC = 01	6800 pF = 1680	$2.5 \times 7 \times 10 \text{ PCM} 7.5 = 2A$	REEL H16.5 360 = F
MKP 10	=MKP1	1100 VDC = P0	$0.01 \mu F = 2100$	$3 \times 8.5 \times 10 \text{ PCM } 7.5 = 2B$	REEL H16.5 500 = H
FKP 1	= FKP1	1200 VDC = Q0	$0.022 \mu F = 2220$	$3 \times 9 \times 13 \text{ PCM } 10 = 3A$	REEL H18.5 360 = I
MKP-X2	=MKX2	1250 VDC = RO	$0.047 \mu F = 2470$	$4 \times 9 \times 13 \text{ PCM } 10 = 3C$	REEL H18.5 500 = J
MKP-X1 R	=MKX1	1500 VDC = S0	$0.1 \mu F = 3100$	$5 \times 11 \times 18 \text{ PCM } 15 = 4B$	ROLL H16.5 $= N$
MKP-Y2	=MKY2	1600 VDC = T0	$0.22 \mu F = 3220$	$6 \times 12.5 \times 18 \text{ PCM } 15 = 4 \text{ C}$	ROLL H18.5 = O
MP 3-X2	=MPX2	2000 VDC = U0	$0.47 \mu F = 3470$	$5 \times 14 \times 26.5 \text{ PCM } 22.5 = 5A$	BLISTER W12 180 $= P$
MP 3-X1	=MPX1	2500 VDC = V0	$1 \mu F = 4100$	$6 \times 15 \times 26.5 \text{ PCM } 22.5 = 5B$	BLISTER W12 330 $= Q$
MP 3-Y2	=MPY2	3000 VDC = W0	$2.2 \mu F = 4220$	$9 \times 19 \times 31.5 \text{ PCM } 27.5 = 6A$	BLISTER W16 330 $=$ R
MP 3R-Y2	=MPRY	4000 VDC = X0	$4.7 \mu F = 4470$	$11 \times 21 \times 31.5 \text{ PCM } 27.5 = 6B$	BLISTER W24 330 $=$ T
MKP 4F	=MKPF	6000 VDC = Y0	$10 \mu F = 5100$	$9 \times 19 \times 41.5 \text{ PCM} 37.5 = 7A$	Bulk/TPS Standard = S
Snubber MKP	= SNMP	250 VAC = 0 VV	$22 \mu F = 5220$	$11 \times 22 \times 41.5 \text{ PCM} 37.5 = 7B$	
Snubber FKP	= SNFP	275 VAC = 1 W	$47 \mu F = 5470$	$19 \times 31 \times 56$ PCM $48.5 = 8D$	
GTO MKP	= GTOM	300 VAC = 2VV	$100 \mu F = 6100$	$25 \times 45 \times 57$ PCM 52.5 = 9D	
DC-LINK MKP		305 VAC = AW	$220 \mu F = 6220$		I
DC-LINK MKP 4 = DCP4		350 VAC = BW	$1000 \mu F = 7100$		
DC-LINK MKP 4S = DCPS		$\begin{array}{ccc} 440 \text{ VAC} &= 4W \\ 500 \text{ VAC} &= 5W \end{array}$	$1500 \mu F = 7150$	Version code:	Pin length (untaped)
DC-LINK MKP $5 = DCP5DC$ -LINK MKP $6 = DCP6$		500 VAC = 5W	•••	1	$3.5 \pm 0.5 = C9$
DC-LINK WIKE	o = DCro			Standard = 00	3.3 ±0.3 = C9

The data on this page is not complete and serves only to explain the part number system. Part number information is listed on the pages of the respective WIMA range.

Version A1

Version A1.1.1 = 1BVersion A2

= 1A

=2A

DC-LINK HC

DC-LINK HY

= DCHC

= DCHY

6 - 2 = SD $16 \pm 1 = P1$

Pin length (taped)