

IP-9055 SW4 MXM = OFF SW5 PICMG= OFF	MB-6058	MB-6063	MB-8001,8002,8010 NO SAS	MB-8001,8002,8010 SAS
<b>Slot 0</b>	X8 PCIe 1.0	X8 PCIe 1.0	X8 PCIe 2.0	X8 PCIe 2.0
<b>Slot 1</b>	X8 PCIe 1.0	X8 PCIe 1.0	X8 PCIe 2.0	X8 PCIe 2.0
<b>Slot 2</b>	NA	NA	NA	NA
<b>Slot 3</b>	NA	NA	NA	NA
<b>Slot 4</b>	NA	X4 PCIe 1.0	X4 PCIe 2.0	NA

IP-9055 SW4 MXM = ON SW5 PICMG= ON	MB-6058	MB-6063	MB-8001,8002,8010 NO SAS	MB-8001,8002,8010 SAS
<b>Slot 0</b>	NA	NA	NA	NA
<b>Slot 1</b>	X16 PCIe 1.0	X16 PCIe 1.0	X16 PCIe 2.0	X16 PCIe 2.0
<b>Slot 2</b>	NA	NA	NA	NA
<b>Slot 3</b>	NA	NA	NA	NA
<b>Slot 4</b>	NA	X4 PCIe 1.0	X4 PCIe 2.0	NA

MB-8001,8002,8010 + IP-9035 NO SAS	MB-8003	MB-8003 + IP-9041 SAS	MB-8003 + IP-9041 NO SAS	
X8 PCIe 2.0	X8 PCIe 1.0	X8 PCIe 1.0	X8 PCIe 1.0	PICMG
X8 PCIe 2.0	X8 PCIe 1.0	X8 PCIe 1.0	X8 PCIe 1.0	
X8 PCIe X.X	NA	NA	NA	MXM
X8 PCIe X.X	NA	X4 PCIe 1.0	X8 PCIe 1.0	
X4 PCIe 2.0	X4 PCIe 1.0	X4 PCIe 1.0	X4 PCIe 1.0	

MB-8001,8002,8010 + IP-9035 NO SAS	MB-8003	MB-8003 + IP-9041 SAS	MB-8003 + IP-9041 NO SAS	
NA	NA	NA	NA	PICMG
X16 PCIe 2.0	X16 PCIe 1.0	X16 PCIe 1.0	X16 PCIe 1.0	
NA	NA	NA	NA	MXM
X16 PCIe X.X	NA	X4 PCIe 1.0	X8 PCIe 1.0	
X4 PCIe 2.0	X4 PCIe 1.0	X4 PCIe 1.0	X4 PCIe 1.0	