

Jester 12/24

24 Channel Memory Lighting Control Console

Key Features

- 24 Channel Memory Lighting Console
- Playback stack
- Patching to 512 DMX channels
- DMX in allowing snapshots of all 512 DMX channels
- VGA Monitor Port
- USB storage and keyboard support
- MIDI Notes & Show Control
- Lock Function
- LCD Display for stand-alone use
- Online Help in multiple languages
- Offline Editor (Phantom Jester)
- Remote triggers
- Upgradeable firmware
- External power supply
- 12/24 channels of control
- 24 Submasters
- 12 Auxillary Buttons



Overview

Jester 12/24 is an ideal console for live and recorded playback control in smaller performance venues. With a rich but easy to use feature set, the Jester 12/24 delivers more than you would expect in a compact package.

The three operating modes feature control in preset, program or playback including using a traditional theatre playback stack. The Jester 12/24 is a fully functional memory console complimented with on-board LCD display and plug-in monitor port as standard.

With 12 auxiliary buttons used to trigger DMX devices such as scrollers, smoke machines or strobes, MIDI capabilities, a USB port to back up shows and even a DMX In port for snapshot/backup use, the Jester 12/24 is truly a powerful and affordable choice.

*Monitor not included.







Ordering Information


00-108-00 Jester 12/24 Console

00-766-00 Flightcase Jester 12/24

Supplied Accessories


Power Supply Operating Manual (on CD)

Dimensions



Weight: 4.5Kg

Powering Business Worldwide



Specifications

- Control Channels: Up to 512
- Channel Faders: 24
- Preset Master Faders: 2
- Fade Time Controls: 1 (Split Up/Down times can be programmed)
- Sequence Speed Control: 1
- Sequence Master Fader: 1
- Grand Master Fader: 1
- Blackout Button: 1
 - Flash Buttons: 24
- Midi In/Thru
- VGA Monitor Port
- Audio Input
- Remote Input
- Storage and Keyboard Connections
- Power Supply: External 100-240 Volts 50/60Hz
- DMX Output: 1 Universe
- DMX Input: 1 Universe
- DMX to USITT DMX512-A
- Dimensions: 90mm(H) x 452mm(W) x 278mm(D)
- Weight: 4.5Kg (10lb)
- Operating environment: +5°C to +40°C
- Humidity: 5% to 95% Non condensing

Contact your local Eaton office

Usk House, Lakeside, Llantarnam Park, Cwmbran, Torfaen, NP44 3HD. UK T: +44 (0)1633 838088 F: +44 (0)1633 867880 E: enquiries@zero88.com www.zero88.com

Eaton Industries Manufacturing GmbH Electrical Sector EMEA Route de la Longeraie 71110 Morces. Switzerland

71110 Morges, Switzerland Eaton.eu

© 2015 Eaton All Rights Reserved

Jester_12_24_Datasheet_UK_Rev3_0615

Changes to the products, to the information contained in this document, and to prices are reserved; so are errors and omissions.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

