

Jester 12/24 19" Rack Mount

19" Rack Mount Lighting Control Console

Key Features

- 24 Channel Memory Lighting Console
- 19" Rack Mount
- Playback stack
- Patching to 512 DMX channels
- DMX in allowing snapshots of all 512 DMX channels
- VGA Monitor Port
- USB storage and keyboard support
- MIDI Notes & Show Control
- Lock Function
- LCD Display for stand-alone use
- Online Help in multiple languages
- Offline Editor (Phantom Jester)
- Remote triggers
- Upgradeable firmware
- External power supply
- 12/24 channels of control
- 24 Submasters
- 12 Auxillary Buttons



Overview

Jester 12/24 19" Rack Mount has been tailored specifically for mounting in 19" racks making this unit perfect for installation where space is at a premium. Users include TV and video studios, clubs, small rental and AV applications. The Jester 12/24 19" Rack Mount is simple to use and delivers great features in a very compact package.

The three operating modes feature control in preset, program or playback including using a traditional theatre playback stack. The Jester 12/24 19" Rack Mount is a fully functional memory console complimented with on-board LCD display and plug-in monitor port as standard.

With 12 auxiliary buttons used to trigger DMX devices such as scrollers, smoke machines or strobes, MIDI capabilities, a USB port to back up shows and even a DMX In port for snapshot/backup use, the Jester 12/24 19" Rack Mount is truly a powerful and affordable choice.










Ordering Information

00-128-00 Jester 12/24 19" Rack Mount 00-766-00 Flightcase Jester 12/24

Supplied Accessories

Power Supply Operating Manual (on CD)

Dimensions



Weight: 4.5Kg

Specifications

Control Channels: Up to 512

Channel Faders: 24Preset Master Faders: 2

Fade Time Controls: 1 (Split Up/Down times can be programmed)

Sequence Speed Control: 1
Sequence Master Fader: 1
Grand Master Fader: 1
Blackout Button: 1
Flash Buttons: 24

Midi In/ThruVGA Monitor Port

Audio Input

Remote Input

• Storage and Keyboard Connections

Power Supply: External 100-240 Volts 50/60Hz

DMX Output: 1 UniverseDMX Input: 1 Universe

DMX to USITT DMX-512 1990 Protocol

Dimensions: 90mm(H) x 483mm(W) x 278mm(D)

Weight: 4.5Kg (10lb)

Operating environment: +5°C to +40°C

• Humidity: 5% to 95% Non condensing

Contact your local Eaton office

Usk House, Lakeside, Llantarnam Park, Cwmbran, Torfaen, NP44 3HD. UK

T: +44 (0)1633 838088 F: +44 (0)1633 867880 E: enquiries@zero88.com www.zero88.com



Route de la Longeraie 71110 Morges, Switzerland Eaton.eu

© 2015 Eaton All Rights Reserved

Jester_12_24_RM_Datasheet_UK_Rev3_0615

Changes to the products, to the information contained in this document, and to prices are reserved; so are errors and omissions.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



