

Solution XL

Lighting Control Console

Key Features

- 296 devices
- USB support for show files storage and touchscreen
- 4 universe optically isolated DMX outputs, or Art-Net and sACN
- ZerOS Operating Software
- Colour Picker
- 12 LCDs
- RDM ready
- Optional hardware upgrade enables SMPTE/ MIDI/ChilliNet and Remote Switches
- Submaster playback faders with scenes or chases
- Comprehensive effects system
- Support for iOS[®], Android[™], Windows Mobile and Windows PC remote displays
- Fixture Library with over 3100 types
- Shows cross loadable with other ZerOS consoles and importable from original Frog Series and ASCII format
- Cue stack (Playback X) playback for full theatrical playback
- USB pluggable Wings available



Overview

Solution XL shares the feature set of the Solution console built into a larger platform of 296 devices and 600 submasters making it attractive for the largest multi-functional venues.

Shows recorded with the Solution series consoles can be easily transferred between any ZerOS family console. With the option of a SMPTE/MIDI/ChilliNet upgrade, the Solution Series consoles can be used to control architectural or multimedia environments. An offline editor is available allowing users to prepatch shows, edit cues, palettes and submasters or simply check timings.

The Solution console supports numerous Ethernet protocols including Art-Net, sACN and a powerful remote device system meaning it is possible to use an iOS, Android, Windows Mobile or Windows PC device together with WiFi to control the desk remotely; truly a comprehensive control capability.









Ordering Information

00-869-00 Solution XL Lighting Control Console

00-864-00 Solution XL Flightcase

12-123-99 SMPTE, MIDI, ChilliNet & Remote Upgrade

00-887-00 Phantom ZerOS Tracking Backup

Unlock Dongle


0020-000007-00 Wing

9805-000059-00 Wing Flightcase

Supplied Accessories

Dust Cover USB Memory Stick Quick Start Manual User Manual CD

Dimensions



Weight: 26.0Kg

Specifications

Fixtures: 296

Control Channels: 2048, patchable to any combination of fixtures /dimmers.

of fixtures/dimmers

DMX Output: 4 x DMX512-A opto- isolated via 4 x XLR 5 fixed

socket, overvoltage protected. RDM Ready

 Ethernet protocols (RJ45 port): Art-Net (4 universes), sACN (4 universes), Zero Wire DMX, LightConverse, Capture,

WYSIWYG, Remotes, Tracking Backup

• Submaster Faders: 600 (30 faders x 20 pages) Submasters

also available via DMX In Channel Faders: 96

DMX Input: 1x DMX512-A

• Grand Master & Blackout Button: Yes

• Channel Preset Master Faders: 2

• Fixture Control Wheels: 3

• On-board LCDs: 12x negative mode blue, white LED backlight

• Memories: 10,000

Palettes: 1600 (400 each of Colour/Beam/ Position/Effects)

Groups: 400Macros: 400Online Help: Yes

 Power Supply (supplied): External Power Supply, +12VDC, +5VDC. Mains inlet via CEE22 connector, connection to lighting

desk via 4 pole locking XLR with switch on desk

• Supply Voltage: 100-260VAC, 47-63Hz

Audio Input: Stereo 1/4", Jack socket, 100mV - 10V

Monitor Output: XGA output via standard 15pin D connector.
Upto 4 additional monitors available via Ethernet remote

• USB Ports: 4 x USB ports 1 on front panel, 3 on rear panel

• Data Storage, Mouse, Keyboard, Touch screens via USB

 Remotes: via Ethernet, iOS, Android, Windows Mobile and Windows PC devices are supported

Dimensions: 115mm(H) x 1205mm(W) x 575mm(D)

Weight: 26.0Kg (57lb)

• Operating environment: +5°C to +40°C (41°F to 104°F)

• Humidity: 5% to 95% Non-condensing

Contact your local Eaton office

Usk House, Lakeside, Llantarnam Park, Cwmbran, Torfaen, NP44 3HD. UK

T: +44 (0)1633 838088 F: +44 (0)1633 867880 E: enquiries@zero88.com www.zero88.com

Eaton Industries Manufacturing GmbH Electrical Sector EMEA

Electrical Sector EMEA Route de la Longeraie 71110 Morges, Switzerland Eaton.eu

© 2015 Eaton All Rights Reserved

Solution_XL_Datasheet_UK_Rev3_0615

Changes to the products, to the information contained in this document, and to prices are reserved; so are errors and omissions.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



