

Solution

Lighting Control Console

Key Features

- 248 devices
- USB support for show files storage and touchscreen
- 4 universe optically isolated DMX outputs, or Art-Net and sACN
- ZerOS Operating Software
- Colour Picker
- 8 LCDs
- RDM ready
- Optional hardware upgrade enables SMPTE/ MIDI/ChilliNet and Remote Switches
- Comprehensive effects system
- Submaster playback faders with scenes or chases
- Support for iOS[®], AndroidTM, Windows Mobile and Windows PC remote displays
- Fixture Library with over 3100 types
- Shows cross loadable with other ZerOS consoles and importable from original Frog Series and ASCII format
- Cue stack (Playback X) playback for full theatrical playback
- USB pluggable Wings available



Overview


Solution is a fully featured, comprehensive and robust lighting console built on the high performance ZerOS operating software platform. Solution offers simple hands on control of conventional generic and moving light parameters across 248 devices and 2048 channels with submaster and cue stack control.

ZerOS' powerful effects system can be relied upon to deliver truly unique effects, from simple chases to rainbows and fly-ins. Manipulate colour, beam and position with offset and rotation parameters to create almost limitless effect pallets.

Networking, external touchscreen and multimedia support combined with multi functional keys, offline editing and a comprehensive fixture library, completes an outstanding control package for the more demanding rental and multi-purpose user.









Ordering Information

00-868-00 Solution Lighting Control Console

00-863-00 Solution Flightcase

12-123-99 SMPTE, MIDI, ChilliNet & Remote Upgrade

00-887-00 Phantom ZerOS Tracking Backup

Unlock Dongle


0020-000007-00 Wing

9805-000059-00 Wing Flightcase

Supplied Accessories

Dust Cover USB Memory Stick Quick Start Manual User Manual CD

Dimensions



Weight: 16.0Kg

Specifications

Fixtures: 248

Control Channels: 2048, patchable to any combination of fixtures/dimmers

DMX Output: 4 x DMX512-A opto- isolated via 4 x XLR 5 fixed

socket, overvoltage protected. RDM Enabled

Ethernet protocols (RJ45 port): Art-Net (4 universes), sACN (4 universes), Zero Wire DMX, LightConverse, Capture,

WYSIWYG, Remotes, Tracking Backup

DMX Input: 1x DMX512-A

Submaster Faders: 200 (10 faders x 20 pages). Submasters

also available via DMX In

Channel Faders: 48

Grand Master & Blackout Button: Yes Channel Preset Master Faders: 2

Fixture Control Wheels: 3

On-board LCDs: 8x negative mode blue, white LED backlight

Memories: 10,000

Palettes: 1600 (400 each of Colour/Beam/ Position/Effects)

Groups: 400 Macros: 400 Online Help: Yes

Power Supply (supplied): External Power Supply, +12VDC,

+5VDC

Mains inlet via CEE22 connector, connection to lighting desk via 4 pole locking XLR with switch on desk

Supply Voltage: 100-260VAC, 47-63Hz

Audio Input: Stereo 1/4", Jack socket, 100mV - 10V

Monitor Output: XGA output via standard 15pin D connector

Upto 4 additional monitors available via Ethernet remote

USB Ports: 4 x USB ports (1 on front panel, 3 on rear panel)

Data Storage, Mouse, Keyboard, Touch screens via USB

Remotes: via Ethernet, iOS, Android, Windows Mobile and

Windows PC devices are supported

Dimensions: 115mm(H) x 765mm(W) x 575mm(D)

Weight: 16.0Kg (35lb)

Operating environment: +5°C to +40°C (41°F to 104°F)

Humidity: 5% to 95% Non-condensing

Contact your local Eaton office

Usk House, Lakeside, Llantarnam Park, Cwmbran, Torfaen, NP44 3HD. UK

T: +44 (0)1633 838088 F: +44 (0)1633 867880 E: enquiries@zero88.com www.zero88.com

Eaton Industries Manufacturing GmbH Electrical Sector EMEA

Route de la Longeraie 71110 Morges, Switzerland Eaton.eu

@ 2015 Faton All Rights Reserved

Solution_Datasheet_UK_Rev3_0615

Changes to the products, to the information contained in this document, and to prices are reserved; so are errors and omissions.

Eaton is a registered trademark

All other trademarks are property of their respective owners



