

Order Code	A (mm)
705820015	1.5
705820020	2.0
705820025	2.5
705820030	3.0
705820035	3.5
705850040	4.0
705820045	4.5
705820050	5.0
705820055	5.5
705820060	6.0
705820065	6.5
705820070	7.0
705820075	7.5
705820080	8.0
705820085	8.5
705820090	9.0
705820095	9.5
705820100	10.0
705820105	10.5
705820110	11.0
705820115	11.5
705820120	12.0
705850125	12.5
705820130	13.0
705820135	13.5
702820140	14.0
705820145	14.5
705820150	15.0
705820155	15.5
705820160	16.0
705820170	17.0
705820180	18.0

DIM.	TOL
5 mm DOWN	±0,2
5~20 mm	±0,3
20~40 mm	±0,4
40~60 mm	±0,5
60~100 mm	±0,8
100 mm UP	±1,0


Würth Elektronik eiSos GmbH & Co. KG
EMC & Inductive Solutions

Max-Eyth-Str. 1
74638 Waldenburg
Germany
Tel. +49 79 42 945 - 0

www.we-online.com
eiSos@we-online.com

CREATED
D. Fandrey

CHECKED
S. Klingler

PROJECTION METHOD  SCALE 8 : 1

DESCRIPTION
**AsSLED
Spacer for 3mm and 5mm LED**

MATERIAL Nylon 66 UL94 V-2, black
GENERAL TOLERANCE DIN ISO 2768 T1m

ORDER CODE
705820xxx

WEIGHT STATUS
Released

REV DATE
1.0 2015-02-11

PAGE
DE 1 / 1