




SGS-THOMSON
MICROELECTRONICS

TS3V3704

3V MICROPOWER QUAD VOLTAGE COMPARATORS

- DEDICATED TO 3.3V OR BATTERY SUPPLY
(specified at 3V and 5V)
- PUSH-PULL CMOS OUTPUT (NO EXTERNAL PULL-UP RESISTOR REQUIRED)
- EXTREMELY LOW SUPPLY CURRENT :
 $7\mu A$ typ / comparator
- WIDE SINGLE SUPPLY RANGE
2.7V to 16V
- EXTREMELY LOW INPUT CURRENTS :
1pA TYP
- INPUT COMMON-MODE VOLTAGE RANGE
INCLUDES GND
- FAST RESPONSE TIME : $2\mu s$ typ for
5mV overdrive
- PIN-TO-PIN AND FUNCTIONALLY
COMPATIBLE WITH BIPOLAR LM339




ORDER CODES

Part Number	Temperature Range	Package	
		N	D
TS3V3704I	-40°C, +125°C	●	●

3704-01.TBL

PIN CONNECTIONS (top view)




DESCRIPTION

The TS3V3704 is a micropower quad CMOS voltage comparator with extremely low consumption of $7\mu A$ typ / comparator (20 times less than bipolar LM339). The push-pull CMOS output stage allows power and space saving by eliminating the external pull-up resistor required by usual open-collector output comparators.

Thus response times remain similar to the LM339.

■ 7929237 0076184 1T? ■

SCHEMATIC DIAGRAM (for 1/4 TS3V3704)



MAXIMUM RATINGS

Symbol	Parameter	Value	Unit
V_{CC+}	Supply Voltage - (note 1)	18	V
V_{id}	Differential Input Voltage - (note 2)	± 18	V
V_i	Input Voltage - (note 3)	18	V
V_o	Output Voltage	18	V
I_o	Output Current	20	mA
T_{oper}	Operating Free-Air Temperature Range TS3V3704I	-40 to +125	°C
T_{stg}	Storage Temperature Range	-65 to +150	°C

Notes : 1. All voltage values, except differential voltage, are with respect to network ground terminal.
 2. Differential voltages are the non-inverting input terminal with respect to the inverting input terminal.
 3. The magnitude of the input and the output voltages must never exceed the magnitude of the positive supply voltage.
 4. Short circuit from outputs to V_{CC+} can cause excessive heating and eventual destruction.

3704-02 TBL

OPERATING CONDITIONS

Symbol	Parameter	Value	Unit
V_{CC+}	Supply Voltage	2.7 to 16	V
V_{icm}	Common Mode Input Voltage Range	0 to $V_{CC+} - 1.5$	V

3704-03 TBL

ELECTRICAL CHARACTERISTICS $V_{CC^+} = 3V, V_{CC^-} = 0V, T_{amb} = 25^\circ C$ (unless otherwise specified)

Symbol	Parameter	Min.	Typ.	Max.	Unit
V_{IO}	Input Offset Voltage - (note 1) $V_{IC} = 1.5V$ $T_{min} \leq T_{amb} \leq T_{max}$.			5 6.5	mV
I_{IO}	Input Offset Current - (note 2) $V_{IC} = 1.5V$ $T_{min} \leq T_{amb} \leq T_{max}$.		1	300	pA
I_{IB}	Input Bias Current - (note 2) $V_{IC} = 1.5V$ $T_{min} \leq T_{amb} \leq T_{max}$.		1	600	pA
V_{ICM}	Input Common Mode Voltage Range $T_{min} \leq T_{amb} \leq T_{max}$.	0 to $V_{CC^+} - 1.2$ 0 to $V_{CC^+} - 1.5$			V
CMR	Common-mode Rejection Ratio $V_{IC} = V_{ICM}$ min.		80		dB
SVR	Supply Voltage Rejection Ratio $V_{CC^+} = 3V$ to $5V$		75		dB
V_{OH}	High Level Output Voltage $V_{ID} = 1V, I_{OH} = -4mA$ $T_{min} \leq T_{amb} \leq T_{max}$.	2 1.8	2.4		V
V_{OL}	Low Level Output Voltage $V_{ID} = -1V, I_{OL} = 4mA$ $T_{min} \leq T_{amb} \leq T_{max}$.		300 400 450	400 450	mV
I_{CC}	Supply Current (each comparator) No load - Outputs low $T_{min} \leq T_{amb} \leq T_{max}$.		7	20 25	μA
t_{PLH}	Response Time Low to High $V_{IC} = 0V, f = 10kHz, C_L = 50pF$, Overdrive = 5mV TTL Input		1.2 0.7		μs
t_{PHL}	Response Time High to Low $V_{IC} = 0V, f = 10kHz, C_L = 50pF$, Overdrive = 5mV TTL Input		2 0.15		μs

Note : 1. The specified offset voltage is the maximum value required to drive the output up to 4.5V or down to 0.3V.
 2. Maximum values including unavoidable inaccuracies of the industrial test.

374-04 TAB


ELECTRICAL CHARACTERISTICS $V_{CC^+} = 5V, V_{CC^-} = 0V, T_{amb} = 25^\circ C$ (unless otherwise specified)

Symbol	Parameter	Min.	Typ.	Max.	Unit
V_{IO}	Input Offset Voltage - (note 1) $V_{IC} = 2.5V$ $T_{min} \leq T_{amb} \leq T_{max}$.		1.2	5 6.5	mV
I_{IO}	Input Offset Current - (note 2) $V_{IC} = 2.5V$ $T_{min} \leq T_{amb} \leq T_{max}$.		1	300	pA
I_{IB}	Input Bias Current - (note 2) $V_{IC} = 2.5V$ $T_{min} \leq T_{amb} \leq T_{max}$.		1	600	pA
V_{ICM}	Input Common Mode Voltage Range $T_{min} \leq T_{amb} \leq T_{max}$.	0 to $V_{CC^+} - 1.2$ 0 to $V_{CC^+} - 1.5$			V
CMR	Common-mode Rejection Ratio $V_{IC} = V_{ICM}$ min.		80		dB
SVR	Supply Voltage Rejection Ratio $V_{CC^+} = +5V$ to $+10V$		90		dB
V_{OH}	High Level Output Voltage $V_{ID} = 1V, I_{OH} = -4mA$ $T_{min} \leq T_{amb} \leq T_{max}$.		4.5 4.3	4.7	V
V_{OL}	Low Level Output Voltage $V_{ID} = -1V, I_{OL} = 4mA$ $T_{min} \leq T_{amb} \leq T_{max}$.		200	300 375	mV
I_{CC}	Supply Current (per comparator) No load - Outputs low $T_{min} \leq T_{amb} \leq T_{max}$.		9	20 25	μA
t_{PLH}	Response Time Low to High $V_{IC} = 0V, f = 10kHz, C_L = 50pF,$ Overdrive = 5mV TTL Input		1.2 0.7		μs
t_{PHL}	Response Time High to Low $V_{IC} = 0V, f = 10kHz, C_L = 50pF,$ Overdrive = 5mV TTL Input		2 0.15		μs

374.05 Tab

- Note : 1. The specified offset voltage is the maximum value required to drive the output up to 4.5V or down to 0.3V.
 2. Maximum values including unavoidable inaccuracies of the industrial test.


PACKAGE MECHANICAL DATA
14 PINS - PLASTIC DIP



PM-DIP14.EPS

DIP14.TBL

Dimensions	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
a1	0.51			0.020		
B	1.39		1.65	0.055		0.065
b		0.5			0.020	
b1		0.25			0.010	
D			20			0.787
E		8.5			0.335	
e		2.54			0.100	
e3		15.24			0.600	
F			7.1			0.280
i			5.1			0.201
L		3.3			0.130	
Z	1.27		2.54	0.050		0.100

PACKAGE MECHANICAL DATA
14 PINS - PLASTIC MICROPACKAGE (SO)


PM-SO14-EPS

Dimensions	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A			1.75			0.069
a ₁	0.1		0.2	0.004		0.008
a ₂			1.6			0.063
b	0.35		0.46	0.014		0.018
b ₁	0.19		0.25	0.007		0.010
C		0.5			0.020	
c ₁			45° (typ.)			
D	8.55		8.75	0.336		0.334
E	5.8		6.2	0.228		0.244
e		1.27			0.050	
e ₃		7.62			0.300	
F	3.8		4.0	0.150		0.157
G	4.6		5.3	0.181		0.208
L	0.5		1.27	0.020		0.050
M			0.68			0.027
S			8° (max.)			

SO14-TBL

Information furnished is believed to be accurate and reliable. However, SGS-THOMSON Microelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No licence is granted by implication or otherwise under any patent or patent rights of SGS-THOMSON Microelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SGS-THOMSON Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of SGS-THOMSON Microelectronics.

© 1995 SGS-THOMSON Microelectronics - All Rights Reserved

SGS-THOMSON Microelectronics GROUP OF COMPANIES

 Australia - Brazil - France - Germany - Hong Kong - Italy - Japan - Korea - Malaysia - Malta - Morocco - The Netherlands
 Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A.

ORDER CODE