

9097250 TOSHIBA (DISCRETE/OPTO)

67C 08884 D T-33-01

TO-126 (S)



(5) TO-126 (S) PACKAGE SERIES

Application

Type No.	V _{CEO}	P _C T _{C=25°C}	h _{FE}		V _{CE(sat)} MAX.			f _T TYP.			Cob TYP.	TO-126 CROSS REFERENCE NO.	
			I _C	V _{CE}	I _C	V _{CE}	I _C	I _B	V _{CE}	I _C			f _T
	(V)	(W)	(A)	(V)	(A)	(V)	(A)	(mA)	(MHz)	(V)	(A)	(pF)	(V)
2SC3423	150	5	0.05	10	10m	1	10m	1	200	10	10m	1.8/2.5	10
2SC3424	250	5	0.05	20	25m	1.5	10m	1	80	10	10m	-	-
2SC3619	300	5	0.1	10	20m	1	10m	1	70	10	20m	3	20
2SC3620	300	5	0.15	10	50m	1	10m	20	110	10	30m	3.5	50
2SC3419	40	5	0.8	2	50m	0.8	0.5	50	100	2	0.5	10/20	10
2SC3425	400	10	0.8	5	0.1	0.5	0.1	10	-	-	-	-	-
2SC3421	120	10	1	5	0.1	1	0.5	50	120	5	0.1	15/30	10
2SC3621	150	10	1.5	5	0.2	1.5	0.5	50	20MIN	5	0.2	-	-
2SC3422	40	10	3	2	0.5	0.8	2	0.2	100	2	0.5	35	10
2SC3420	20	10	5	2	0.5	1	4	100	100	2	0.5	40	10
2SA1357	20	10	5	2	0.5	1	4	100	170	2	0.5	62	10
2SD1508	30	10	1.5	2	0.15	1.5	1	1	-	-	-	-	-
2SB1067	80	10	2	2	1	1.5	1	1	10/50	2	0.5	20/30	10

Low V_{CE(sat)}

DARLINGTON