

3V Logic Output Temperature Sensor with Programmable Hysteresis

FEATURES

- User Programmable Hysteresis and Temperature Set Point
- Easily Programs with Two External Resistors
 - Wide Temperature Detection Range TC07CxA 0°C to +70°C TC07ExA - 40°C to +85°C TC07VxA - 40°C to +125°C
- Small 8-Pin MSOP and 8-Pin SOIC Packages
- Cost Effective

APPLICATIONS

- Power Supply Over-Temperature Detection
- Consumer Equipment
- Temperature Regulators
- Computer Equipment

ORDERING INFORMATION

Part No.	Package	Temp. Range		
TC07COA	8-Pin SOIC	0°C to +70°C		
TC07CUA	8-Pin MSOP	0°C to +70°C		
TC07EOA	8-Pin SOIC	– 40°C to +85°C		
TC07EUA	8-Pin MSOP	– 40°C to +85°C		
TC07VOA	8-Pin SOIC	– 40°C to +125°C		
TC07VUA	8-Pin MSOP	– 40°C to +125°C		

FUNCTIONAL BLOCK DIAGRAM



GENERAL DESCRIPTION

The TC07 is a programmable, logic output temperature detector that operates from power supply levels as low as 2.7V. Programming is accomplished with external resistors connected from the temperature setpoint input (T_{SET}) and the hysteresis control input (H_{SET}) to V_{DD} .

Complementary outputs (OUT and \overline{OUT}) are driven active when temperature exceeds the temperature threshold programmed by the resistor on T_{SET}. The states of these outputs are maintained (latched) until temperature falls below threshold programmed by the resistor on H_{SET}.

The TC07 is useful over a maximum temperature range of -40° C to $+125^{\circ}$ C (TC07VxA). It features low (< 130µA) supply current and small physical size 8-pin MSOP and 8-pin SOIC packages, making it suitable for a wide variety of applications.

PIN CONFIGURATION



TC07

ABSOLUTE MAXIMUM RATINGS*

Supply Voltage	7V
Input Voltage Any Input (GND - 0.3V) to (V _{DD}	+ 0.3V)
Operating Temperature 40°C to	+125°C
Maximum Chip Temperature	+150°C
Storage Temperature 65°C to	+150°C
Lead Temperature (Soldering, 10 sec)	+300°C

* Stresses above those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only and functional operation of the device at these or any other conditions above those indicated in the operation sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

ELECTRICAL CHARACTERISTICS: T_A = Over Operational Temperature Range, unless otherwise specified.

Symbol	Parameter	Conditions	Min	Тур	Max	Unit
V _{DD}	Supply Voltage Range		2.7		5.5	V
I _{DD}	Supply Current	2.7V < V _{CC} < 5.5V	_	130	300	μA
V _{OH}	Output Voltage (High)	I _{OUT} = 500μA	0.8 x V _{DD}	_	—	V
V _{OL}	Output Voltage (Low)	I _{OUT} = 1mA	—		0.25 x V _{DD}	V
Н	Minimum Hysteresis	H _{SET} < T _{SET}	- 5		—	°C
T _{SET}	Absolute Accuracy	T = Programmed Temperature	T – 3	T ± 1	T + 3	°C
H _{SET}	Absolute Accuracy	T = Programmed Temperature	T – 5	T ± 1	T + 5	°C

DETAILED DESCRIPTION

The TC07 programs with resistors connected from the T_{SET} and H_{SET} inputs to V_{DD} . Output pins OUT and \overline{OUT} are driven active when temperature exceeds the setting determined by the programming resistor on T_{SET} . The outputs are maintained (latched) in their active states until temperature drops below the setting determined by the programming resistor on H_{SET} (Figure 1).



Figure 1. TC07 Output Waveforms

APPLICATIONS

Trip Point Programming

The resistor values required to achieve the desired trip-point temperatures on T_{SET} and H_{SET} are calculated using the formula below:

$$R_{TRIP} = 0.6 \text{ x } T^{2.13}$$

Where:

R_{TRIP} = Programming resistor value in Ohms
T = Desired trip point temperature in degrees
Kelvin.

For example, to program the TC07 outputs to go active at 50°C and inactive at 30°C, the T_{SET} and H_{SET} programming resistors are calculated as follows:

$$\begin{split} T_{SET} &= 0.6 \; x \; ((50 + 273.15)^{2.13}) = 132.8 \text{k} \Omega \\ H_{SET} &= 0.6 \; x \; ((30 + 273.15)^{2.13}) = 115.9 \text{k} \Omega \end{split}$$

Resistance values for T_{SET} and H_{SET} can be approximated using Figure 2. Care must be taken to ensure the H_{SET} programming resistor is a smaller value than the T_{SET} programming resistor. The temperature programmed on H_{SET} must be at least 5°C lower than the temperature value programmed by T_{SET} . That is: $H_{SET} \leq T_{SET} - 5$ °C.



Figure 2. Programming Resistor Values vs. Temperature

Cooling and Heating Applications

The TC07 can be used to control a DC fan as shown in Figure 3. The fan turns on when the sensed temperature rises above T_{SET} and remains on until the temperature falls below H_{SET} . The amount of "over-cooling" performed by the fan is dependent on the programmed hysteresis.

Figure 4 shows the TC07 acting as a heater thermostat. Circuit operation is identical to that of the cooling fan application.





3V Logic Output Temperature Sensor with Programmable Hysteresis

TC07

PACKAGE DIMENSIONS





WORLDWIDE SALES AND SERVICE

AMERICAS

Corporate Office 2355 West Chandler Blvd. Chandler, AZ 85224-6199 Tel: 480-792-7200 Fax: 480-792-7277 Technical Support: 480-792-7627 Web Address: http://www.microchip.com **Rocky Mountain**

2355 West Chandler Blvd. Chandler, AZ 85224-6199 Tel: 480-792-7966 Fax: 480-792-7456

Atlanta

500 Sugar Mill Road, Suite 200B Atlanta, GA 30350 Tel: 770-640-0034 Fax: 770-640-0307 Austin Analog Product Sales

8303 MoPac Expressway North Suite A-201 Austin, TX 78759 Tel: 512-345-2030 Fax: 512-345-6085

Boston

2 Lan Drive, Suite 120 Westford, MA 01886 Tel: 978-692-3848 Fax: 978-692-3821

Boston

Analog Product Sales Unit A-8-1 Millbrook Tarry Condominium 97 Lowell Road Concord, MA 01742 Tel: 978-371-6400 Fax: 978-371-0050

Chicago

333 Pierce Road, Suite 180 Itasca, IL 60143 Tel: 630-285-0071 Fax: 630-285-0075

Dallas 4570 Westgrove Drive, Suite 160 Addison, TX 75001

Tel: 972-818-7423 Fax: 972-818-2924 Dayton

Two Prestige Place, Suite 130 Miamisburg, OH 45342 Tel: 937-291-1654 Fax: 937-291-9175

Detroit

Tri-Atria Office Building 32255 Northwestern Highway, Suite 190 Farmington Hills, MI 48334 Tel: 248-538-2250 Fax: 248-538-2260

Los Angeles

18201 Von Karman, Suite 1090 Irvine, CA 92612 Tel: 949-263-1888 Fax: 949-263-1338

Mountain View

Analog Product Sales 1300 Terra Bella Avenue Mountain View, CA 94043-1836 Tel: 650-968-9241 Fax: 650-967-1590

New York

150 Motor Parkway, Suite 202 Hauppauge, NY 11788 Tel: 631-273-5305 Fax: 631-273-5335 San Jose Microchip Technology Inc. 2107 North First Street, Suite 590 San Jose, CA 95131 Tel: 408-436-7950 Fax: 408-436-7955 Toronto 6285 Northam Drive, Suite 108

Mississauga, Ontario L4V 1X5, Canada Tel: 905-673-0699 Fax: 905-673-6509

ASIA/PACIFIC

China - Beijing Microchip Technology Beijing Office Unit 915 New China Hong Kong Manhattan Bldg. No. 6 Chaoyangmen Beidajie Beijing, 100027, No. China Tel: 86-10-85282100 Fax: 86-10-85282104 China - Shanghai Microchip Technology Shanghai Office Room 701, Bldg. B Far East International Plaza No. 317 Xian Xia Road Shanghai, 200051 Tel: 86-21-6275-5700 Fax: 86-21-6275-5060 Hong Kong Microchip Asia Pacific RM 2101, Tower 2, Metroplaza 223 Hing Fong Road Kwai Fong, N.T., Hong Kong Tel: 852-2401-1200 Fax: 852-2401-3431 India

Microchip Technology Inc. India Liaison Office **Divyasree Chambers** 1 Floor, Wing A (A3/A4) No. 11, OíShaugnessey Road Bangalore, 560 025, India Tel: 91-80-2290061 Fax: 91-80-2290062

Japan

Microchip Technology Intl. Inc. Benex S-1 6F 3-18-20, Shinyokohama Kohoku-Ku, Yokohama-shi Kanagawa, 222-0033, Japan Tel: 81-45-471- 6166 Fax: 81-45-471-6122 Korea Microchip Technology Korea 168-1, Youngbo Bldg. 3 Floor Samsung-Dong, Kangnam-Ku Seoul, Korea Tel: 82-2-554-7200 Fax: 82-2-558-5934

ASIA/PACIFIC (continued)

Singapore

Microchip Technology Singapore Pte Ltd. 200 Middle Road #07-02 Prime Centre Singapore, 188980 Tel: 65-334-8870 Fax: 65-334-8850 Taiwan Microchip Technology Taiwan 11F-3, No. 207 Tung Hua North Road Taipei, 105, Taiwan Tel: 886-2-2717-7175 Fax: 886-2-2545-0139

EUROPE

Australia Microchip Technology Australia Pty Ltd Suite 22, 41 Rawson Street Epping 2121, NSW Australia Tel: 61-2-9868-6733 Fax: 61-2-9868-6755 Denmark Microchip Technology Denmark ApS Regus Business Centre Lautrup hoj 1-3 Ballerup DK-2750 Denmark Tel: 45 4420 9895 Fax: 45 4420 9910 France Arizona Microchip Technology SARL Parc díActivite du Moulin de Massy 43 Rue du Saule Trapu Batiment A - ler Etage 91300 Massy, France Tel: 33-1-69-53-63-20 Fax: 33-1-69-30-90-79 Germany Arizona Microchip Technology GmbH Gustav-Heinemann Ring 125 D-81739 Munich, Germany Tel: 49-89-627-144 0 Fax: 49-89-627-144-44 Germany Analog Product Sales Lochhamer Strasse 13 D-82152 Martinsried, Germany Tel: 49-89-895650-0 Fax: 49-89-895650-22 Italy Arizona Microchip Technology SRL Centro Direzionale Colleoni Palazzo Taurus 1 V. Le Colleoni 1 20041 Agrate Brianza Milan, Italy Tel: 39-039-65791-1 Fax: 39-039-6899883 **United Kingdom** Arizona Microchip Technology Ltd. 505 Eskdale Road Winnersh Triangle Wokingham Berkshire, England RG41 5TU Tel: 44 118 921 5869 Fax: 44-118 921-5820

All rights reserved. © 2001 Microchip Technology Incorporated. Printed in the USA. 1/01 Printed on recycled paper.

01/09/01

Information contained in this publication regarding device applications and the like is intended through suggestion only and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications. No representation or warranty is given and no liability is assumed by Microchip Technology Incorporated with respect to the accuracy or use of such information, or infringement of patents or other intellectual property rights arising from such use or otherwise. Use of Microchipis products as critical components in life support systems is not authorized except with express written approval by Microchip. No licenses are conveyed, implicitly or otherwise, except as maybe explicitly expressed herein, under any intellec-tual property rights. The Microchip logo and name are registered trademarks of Microchip Technology Inc. in the U.S.A. and other countries. All rights reserved. All other trademarks mentioned herein are the property of their respective companies.