



Enlarge

Shrouded Banana Plug to Safety Test Prod  
 BU-6262-M-39-\* (Silicone)  
 BU-6262-N-39-\* (PVC - 1000V, 20 Amp)

- IEC 1010 compliant
- Nine-leaf beryllium copper, nickel-plated cage springs
- Insulated right angle 4 mm plug Stainless steel tip with 8-32 thread
- Molded housing
- [Product Data Sheet](#)
- [Send us your questions about this product](#)



No. 31602



No. 31603



No. 31604

Pressfit Insulated Banana jacks (1000V, 15Amp)

BU-31602-\* Solder Pin Connection

BU-31603-\* Spade Connection

BU-31604-\* Crimp Terminal

BU-31605-\* Solder Cup

BU-31606-\* Amp Lug

- Quick mounting in 7/16" (10.9 mm) diameter
- IEC 1010 compliant
- Nickel-plated brass
- Accepts 4 mm shrouded/unshrouded plugs
- Stainless steel tip with 8-32 thread
- Molded housing
- [Product Data Sheet](#)
- [Send us your questions about this product](#)



No. 31605



No. 31606

\* represents color: 0=Black 2=Red 4=Yellow 5=Green 6=Blue 9=White

[Up](#) | [Test Leads](#) | [Accessories](#) | [Oscilloscope Probes](#) | [Kits](#)

©2003 Mueller Electric Company. All rights reserved.  
 Problems with the site should be reported to the [webmaster](#).