

## NTE1838 & NTE1856 Integrated Circuit Color TV Video/Chroma/Deflection Circuit

### **Description:**

The NTE1839 and NTE1856 are small-sized multifunctional integrated circuits containing the “video, chroma, deflection” circuit of NTSC color TVs in a 30-Lead DIP type package. Besides being small-sized, they have such features as fewer external components and fewer adjustments. required. The NTE1838/NTE1856 can be used in conjunction with the NTE1728 for “VIF•SIF” use or the NTE1773/NTE1797 for “vertical output” use to perform all color TV signal processings.

The NTE1856 contains a peak clip circuit in the video circuit making it well suited for use in small-sized TV sets while the NTE1838 contains no peak clip circuit and is suited for large-sized TV sets.

### **Features:**

- Small-Sized Package
- Minimum Number of External Components Required
- Fewer Adjustments Required (Non-Adjusting of Functions Shown Below)
  - Chroma VCO (APC)
  - Horizontal OSC (H-Hold)
  - Vertical OSC (V-Hold)
- Multifunctional

### **Absolute Maximum Ratings:** ( $T_A = +25^\circ\text{C}$ unless otherwise specified)

Maximum Supply Voltage, $V_{16\text{max}}$ .....	14V
Maximum Supply Current, $I_{22\text{max}}$ .....	15mA
Allowable Power Dissipation ( $T_A \leq +65^\circ\text{C}$ ), $P_{d\text{max}}$ .....	1100mW
Operating Temperature Range, $T_{\text{opr}}$ .....	$-20^\circ$ to $+85^\circ\text{C}$
Storage Temperature Range, $T_{\text{stg}}$ .....	$-55^\circ$ to $+125^\circ\text{C}$

### **Recommended Operating Conditions:** ( $T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Recommended Supply Voltage	$V_{16}$		9.0	12.0	14.0	V
Recommended Supply Current	$I_{22}$		8.5	10.0	15.0	mA

**Electrical Characteristics:** ( $T_A = +25^\circ\text{C}$ ,  $V_{16} = 12\text{V}$ ,  $I_{22} = 10\text{mA}$  unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
<b>Chroma</b>						
ACC Amplitude Characteristic	ACC <sub>1</sub>		-3	0	+3	dB
	ACC <sub>2</sub>		-7	0	+2	dB
ACC Phase Characteristic	ACC $\phi$ <sub>1</sub>		-	0	$\pm 3$	deg
	ACC $\phi$ <sub>2</sub>		-	0	$\pm 7$	deg
Maximum B-Y Demodulation Output	B-Y <sub>max</sub>		5.0	-	-	V <sub>PP</sub>
Unicolor Amplitude Characteristic	$\Delta\text{GU}$		-	17	-	dB
Tint Change Range	$\Delta\text{T}$		-	110	-	deg
APC Pull-In Range	f <sub>APC</sub>		$\pm 300$	-	-	
Color Difference Output DC Voltage	E <sub>RGB</sub>		6.7	7.2	7.7	V
Color Difference DC Difference Voltage	E $\Delta$ <sub>RGB</sub>		-	-	$\pm 300$	mV
R-Y Relative Demodulation Angle	$\angle\text{R-Y/B-Y}$		-	104	-	deg
G-Y Relative Demodulation Angle	$\angle\text{G-Y/B-Y}$		-	-122	-	deg
R-Y Demodulation Ratio	R-Y/B-Y		-	0.9	-	
G-Y Demodulation Ratio	G-Y/B-Y		-	0.3	-	
<b>Video</b>						
Video Tone Control Characteristic	G <sub>pmin</sub>		-5	-3	-1	dB
	G <sub>pmax</sub>		12	15	18	dB
Video Voltage Gain	V <sub>G</sub>		12	15	18	dB
Contrast Variable Range	$\Delta\text{G}_C$		-	18	-	dB
Frequency Response	$\Delta\text{G}_V$	f = 5MHz	-5	-	-	dB
<b>Synchronization, Deflection</b>						
Sync Separation Input DC Level	V <sub>S•S</sub>		-	9.3	-	V
Vertical Free-Running Frequency	f <sub>V</sub>		-	f <sub>H</sub> /296.5	-	Hz
Vertical Blanking Pulse Width	T <sub>BL</sub>		-	19H	-	
Vertical Drive Stage Voltage Gain	V <sub>G</sub>		-	16	-	dB
Horizontal Free-Running Frequency	f <sub>H</sub>		-	15.734	-	kHz
Horizontal Drive Output Pulse Width	T <sub>H</sub>		-	24.5	-	$\mu\text{s}$
Horizontal Sync Pull-In Range	f <sub>PULL</sub>		$\pm 400$	-	-	Hz

### Pin Connection Diagram

