

1.25MHz, Over-The-Top Micropower, Rail-to-Rail Input and Output Op Amp in SOT-23

FEATURES

- Operates with Inputs Above V^+
- Rail-to-Rail Input and Output
- Micropower: 300 μ A Supply Current Max
- Operating Temperature Range: -40°C to 125°C
- Low Profile (1mm) ThinSOT™ Package
- Gain Bandwidth product: 1.25MHz
- Slew Rate: 0.42V/ μ s
- Low Input Offset Voltage: 800 μ V Max
- Single Supply Input Range: 0V to 18V
- High Output Current: 18mA Min
- Specified on 3V, 5V and ± 5 V Supplies
- Output Shutdown on 6-Lead Version
- Reverse Battery Protection to 18V
- High Voltage Gain: 1500V/mV

APPLICATIONS

- Portable Instrumentation
- Battery- or Solar-Powered Systems
- Sensor Conditioning
- Supply Current Sensing
- Battery Monitoring
- MUX Amplifiers
- 4mA to 20mA Transmitters

DESCRIPTION



The LT[®]1783 is a 1.25MHz op amp available in the small SOT-23 package that operates on all single and split supplies with a total voltage of 2.5V to 18V. The amplifier draws less than 300 μ A of quiescent current and has reverse battery protection, drawing negligible current for reverse supply voltages up to 18V.

The input range of the LT1783 includes ground, and a unique feature of this device is its Over-The-Top™ operation capability with either or both of its inputs above the positive rail. The inputs handle 18V both differential and common mode, independent of supply voltage. The input stage incorporates phase reversal protection to prevent false outputs from occurring even when the inputs are 9V below the negative supply.

The LT1783 can drive loads up to 18mA and still maintain rail-to-rail capability. A shutdown feature on the 6-lead version can disable the part, making the output high impedance and reducing quiescent current to 5 μ A. The LT1783 op amp is available in the 5- and 6-lead SOT-23 packages. For applications requiring lower power, refer to the LT1782.

LT, LTC and LT are registered trademarks of Linear Technology Corporation. ThinSOT and Over-The-Top are trademarks of Linear Technology Corporation.

TYPICAL APPLICATION



LT1783

ABSOLUTE MAXIMUM RATINGS (Note 1)

| | | | |
|---|----------------|--|----------------|
| Total Supply Voltage (V^+ to V^-) | 18V | Specified Temperature Range (Note 4) | |
| Input Differential Voltage | 18V | LT1783C | -40°C to 85°C |
| Input Pin Voltage to V^- | +24V/-10V | LT1783I | -40°C to 85°C |
| Shutdown Pin Voltage Above V^- | 18V | LT1783H | -40°C to 125°C |
| Shutdown Pin Current | ± 10 mA | Junction Temperature | 150°C |
| Output Short-Circuit Duration (Note 2) | Indefinite | Storage Temperature Range | -65°C to 150°C |
| Operating Temperature Range (Note 3) | | Lead Temperature (Soldering, 10 sec) | 300°C |
| LT1783C | -40°C to 85°C | | |
| LT1783I | -40°C to 85°C | | |
| LT1783H | -40°C to 125°C | | |

PACKAGE/ORDER INFORMATION

| | | | |
|--|-------------------------------------|--|-------------------------------------|
| <p>TOP VIEW</p> <p>S5 PACKAGE 5-LEAD PLASTIC SOT-23</p> <p>$T_{JMAX} = 150^\circ\text{C}$, $\theta_{JA} = 250^\circ\text{C/W}$</p> | ORDER PART NUMBER | <p>TOP VIEW</p> <p>S6 PACKAGE 6-LEAD PLASTIC SOT-23</p> <p>$T_{JMAX} = 150^\circ\text{C}$, $\theta_{JA} = 230^\circ\text{C/W}$</p> | ORDER PART NUMBER |
| | LT1783CS5 LT1783IS5 LT1783HS5 | | LT1783CS6 LT1783IS6 LT1783HS6 |
| | S5 PART MARKING | | S6 PART MARKING |
| | LTLF LTLG LTXR | | LTIU LTIV LTXS |

Consult factory for parts specified with wider operating temperature ranges.

ELECTRICAL CHARACTERISTICS

The ● denotes specifications which apply over the specified temperature range, otherwise specifications are $T_A = 25^\circ\text{C}$. $V_S = 3\text{V}, 0\text{V}$; $V_S = 5\text{V}, 0\text{V}$, $V_{CM} = V_{OUT} = \text{half supply}$, for the 6-lead part $V_{PIN5} = 0\text{V}$, pulse power tested unless otherwise specified. (Note 4)

| SYMBOL | PARAMETER | CONDITIONS | LT1783C/LT1783I | | | UNITS |
|----------|-------------------------------------|--|-----------------|------|------|------------------------------|
| | | | MIN | TYP | MAX | |
| V_{OS} | Input Offset Voltage | $T_A = 25^\circ\text{C}$ $0^\circ\text{C} \leq T_A \leq 70^\circ\text{C}$ $-40^\circ\text{C} \leq T_A \leq 85^\circ\text{C}$ | | 400 | 800 | μV |
| | | | ● | | 950 | μV |
| | | | ● | | 1100 | μV |
| | Input Offset Voltage Drift (Note 9) | | ● | 2 | 5 | $\mu\text{V}/^\circ\text{C}$ |
| I_{OS} | Input Offset Current | $V_{CM} = 18\text{V}$ (Note 5) | ● | 4 | 8 | nA |
| | | | ● | | 7 | μA |
| I_B | Input Bias Current | $V_{CM} = 18\text{V}$ (Note 5) SHDN or $V_S = 0\text{V}$, $V_{CM} = 0\text{V}$ to 18V | ● | 45 | 80 | nA |
| | | | ● | 35 | 60 | μA |
| | | | ● | 0.1 | | nA |
| | Input Bias Current Drift | | ● | 0.06 | | nA/ $^\circ\text{C}$ |
| | Input Noise Voltage | 0.1Hz to 10Hz | | 0.6 | | μV_{p-p} |
| e_n | Input Noise Voltage Density | $f = 1\text{kHz}$ | | 20 | | nV/ $\sqrt{\text{Hz}}$ |
| i_n | Input Noise Current Density | $f = 1\text{kHz}$ | | 0.14 | | pA/ $\sqrt{\text{Hz}}$ |

ELECTRICAL CHARACTERISTICS

The ● denotes specifications which apply over the specified temperature range, otherwise specifications are $T_A = 25^\circ\text{C}$. $V_S = 3\text{V}$, 0V ; $V_S = 5\text{V}$, 0V , $V_{\text{CM}} = V_{\text{OUT}} = \text{half supply}$, for the 6-lead part $V_{\text{PIN5}} = 0\text{V}$, pulse power tested unless otherwise specified. (Note 4)

| SYMBOL | PARAMETER | CONDITIONS | LT1783C/LT1783I | | | UNITS | |
|-------------------|--------------------------------------|--|-----------------|------|-------------|----------------------|---------------|
| | | | MIN | TYP | MAX | | |
| R_{IN} | Input Resistance | Differential | ● | 0.65 | 1.3 | $\text{M}\Omega$ | |
| | | Common Mode, $V_{\text{CM}} = 0\text{V}$ to $(V_{\text{CC}} - 1\text{V})$ | ● | | 1 | $\text{G}\Omega$ | |
| | | Common Mode, $V_{\text{CM}} = 0\text{V}$ to 18V | ● | 0.3 | 0.5 | $\text{M}\Omega$ | |
| C_{IN} | Input Capacitance | | | 5 | pF | | |
| | Input Voltage Range | | ● | 0 | 18 | V | |
| CMRR | Common Mode Rejection Ratio (Note 5) | $V_{\text{CM}} = 0\text{V}$ to $V_{\text{CC}} - 1\text{V}$ | ● | 90 | 100 | dB | |
| | | $V_{\text{CM}} = 0\text{V}$ to 18V (Note 8) | ● | 68 | 80 | dB | |
| PSRR | Power Supply Rejection Ratio | $V_S = 3\text{V}$ to 12.5V , $V_{\text{CM}} = V_O = 1\text{V}$ | ● | 90 | 100 | dB | |
| A_{VOL} | Large-Signal Voltage Gain | $V_S = 3\text{V}$, $V_O = 500\text{mV}$ to 2.5V , $R_L = 10\text{k}$ | ● | 200 | 1500 | V/mV | |
| | | $V_S = 3\text{V}$, $0^\circ\text{C} \leq T_A \leq 70^\circ\text{C}$ | ● | 133 | | V/mV | |
| | | $V_S = 3\text{V}$, $-40^\circ\text{C} \leq T_A \leq 85^\circ\text{C}$ | ● | 100 | | V/mV | |
| | | $V_S = 5\text{V}$, $V_O = 500\text{mV}$ to 4.5V , $R_L = 10\text{k}$ | ● | 400 | 1500 | V/mV | |
| | | $V_S = 5\text{V}$, $0^\circ\text{C} \leq T_A \leq 70^\circ\text{C}$ | ● | 250 | | V/mV | |
| | | $V_S = 5\text{V}$, $-40^\circ\text{C} \leq T_A \leq 85^\circ\text{C}$ | ● | 200 | | V/mV | |
| V_{OL} | Output Voltage Swing LOW | No Load | ● | | 3 | 8 | mV |
| | | $I_{\text{SINK}} = 5\text{mA}$ | ● | | 200 | 400 | mV |
| | | $V_S = 5\text{V}$, $I_{\text{SINK}} = 10\text{mA}$ | ● | | 330 | 600 | mV |
| V_{OH} | Output Voltage Swing HIGH | $V_S = 3\text{V}$, No Load | ● | 2.91 | 2.94 | V | |
| | | $V_S = 3\text{V}$, $I_{\text{SOURCE}} = 5\text{mA}$ | ● | 2.6 | 2.8 | V | |
| | | $V_S = 5\text{V}$, No Load | ● | 4.91 | 4.94 | V | |
| | | $V_S = 5\text{V}$, $I_{\text{SOURCE}} = 10\text{mA}$ | ● | 4.5 | 4.74 | V | |
| I_{SC} | Short-Circuit Current (Note 2) | $V_S = 3\text{V}$, Short to GND | | 5 | 10 | mA | |
| | | $V_S = 3\text{V}$, Short to V_{CC} | | 15 | 30 | mA | |
| | | $V_S = 5\text{V}$, Short to GND | | 15 | 30 | mA | |
| | | $V_S = 5\text{V}$, Short to V_{CC} | | 20 | 40 | mA | |
| | Minimum Supply Voltage | | ● | | 2.5 | 2.7 | V |
| | Reverse Supply Voltage | $I_S = -100\mu\text{A}$ | ● | 18 | | V | |
| I_S | Supply Current (Note 6) | $0^\circ\text{C} \leq T_A \leq 70^\circ\text{C}$ | ● | | 210 | 300 | μA |
| | | $-40^\circ\text{C} \leq T_A \leq 85^\circ\text{C}$ | ● | | | 350 | μA |
| | | | ● | | | | 375 |
| | Supply Current, SHDN | $V_{\text{PIN5}} = 2\text{V}$, No Load (Note 10) | ● | | 5 | 18 | μA |
| I_{SHDN} | Shutdown Pin Current | $V_{\text{PIN5}} = 0.3\text{V}$, No Load (Note 10) | ● | | 0.5 | | nA |
| | | $V_{\text{PIN5}} = 2\text{V}$, No Load (Note 10) | ● | | 2 | 8 | μA |
| | | $V_{\text{PIN5}} = 5\text{V}$, No Load (Note 10) | | | 5 | | μA |
| | Shutdown Output Leakage Current | $V_{\text{PIN5}} = 2\text{V}$, No Load (Note 10) | ● | | 0.05 | 1 | μA |
| | Maximum Shutdown Pin Current | $V_{\text{PIN5}} = 18\text{V}$, No Load (Note 10) | ● | | 10 | 30 | μA |
| V_L | Shutdown Pin Input Low Voltage | (Note 10) | ● | | | 0.3 | V |
| V_H | Shutdown Pin Input High Voltage | (Note 10) | ● | 2 | | V | |
| t_{ON} | Turn-On Time | $V_{\text{PIN5}} = 5\text{V}$ to 0V , $R_L = 10\text{k}$ (Note 10) | | | 25 | μs | |
| t_{OFF} | Turn-Off Time | $V_{\text{PIN5}} = 0\text{V}$ to 5V , $R_L = 10\text{k}$ (Note 10) | | | 3 | μs | |
| GBW | Gain Bandwidth Product (Note 5) | $f = 5\text{kHz}$ | | 750 | 1250 | kHz | |
| | | $0^\circ\text{C} \leq T_A \leq 70^\circ\text{C}$ | ● | 600 | | kHz | |
| | | $-40^\circ\text{C} \leq T_A \leq 85^\circ\text{C}$ | ● | 550 | | kHz | |

ELECTRICAL CHARACTERISTICS

The ● denotes specifications which apply over the specified temperature range, otherwise specifications are $T_A = 25^\circ\text{C}$. $V_S = 3\text{V}$, 0V ; $V_S = 5\text{V}$, 0V , $V_{\text{CM}} = V_{\text{OUT}} = \text{half supply}$, for the 6-lead part $V_{\text{PIN5}} = 0\text{V}$, pulse power tested unless otherwise specified. (Note 4)

| SYMBOL | PARAMETER | CONDITIONS | LT1783C/LT1783I | | | UNITS |
|--------|--------------------------------|---|-----------------|-------|------|------------------|
| | | | MIN | TYP | MAX | |
| SR | Slew Rate (Note 7) | $A_V = -1$, $R_L = \infty$ $0^\circ\text{C} \leq T_A \leq 70^\circ\text{C}$ $-40^\circ\text{C} \leq T_A \leq 85^\circ\text{C}$ | ● | 0.24 | 0.42 | V/ μs |
| | | | ● | 0.21 | | V/ μs |
| | | | ● | 0.019 | | V/ μs |
| FPBW | Full-Power Bandwidth (Note 11) | $V_{\text{OUT}} = 2V_{\text{P-P}}$ | | 66 | | kHz |
| t_S | Settling Time | $V_S = 5\text{V}$, $\Delta V_{\text{OUT}} = 2\text{V}$ to 0.1%, $A_V = -1$ | | 12 | | μs |
| THD | Distortion | $V_S = 3\text{V}$, $V_O = 2V_{\text{P-P}}$, $A_V = 1$, $R_L = 10\text{k}$, $f = 1\text{kHz}$ | | 0.001 | | % |

The ● denotes specifications which apply over the specified temperature range, otherwise specifications are $T_A = 25^\circ\text{C}$. $V_S = \pm 5\text{V}$, $V_{\text{CM}} = 0\text{V}$, $V_{\text{OUT}} = 0\text{V}$, for the 6-lead part $V_{\text{PIN5}} = V^-$, pulse power tested unless otherwise specified. (Note 4)

| SYMBOL | PARAMETER | CONDITIONS | LT1783C/LT1783I | | | UNITS |
|-------------------|-------------------------------------|--|-----------------|--------|--------|------------------------------|
| | | | MIN | TYP | MAX | |
| V_{OS} | Input Offset Voltage | $T_A = 25^\circ\text{C}$ $0^\circ\text{C} \leq T_A \leq 70^\circ\text{C}$ $-40^\circ\text{C} \leq T_A \leq 85^\circ\text{C}$ | ● | 500 | 900 | μV |
| | | | ● | | 1050 | μV |
| | | | ● | | 1200 | μV |
| | Input Offset Voltage Drift (Note 9) | | ● | 2 | 5 | $\mu\text{V}/^\circ\text{C}$ |
| I_{OS} | Input Offset Current | | ● | 4 | 8 | nA |
| I_B | Input Bias Current | | ● | 40 | 80 | nA |
| | Input Bias Current Drift | | ● | 0.06 | | nA/ $^\circ\text{C}$ |
| | Input Noise Voltage | 0.1Hz to 10Hz | | 1 | | $\mu\text{V}_{\text{P-P}}$ |
| e_n | Input Noise Voltage Density | $f = 1\text{kHz}$ | | 20 | | nV/ $\sqrt{\text{Hz}}$ |
| i_n | Input Noise Current Density | $f = 1\text{kHz}$ | | 0.14 | | pA/ $\sqrt{\text{Hz}}$ |
| R_{IN} | Input Resistance | Differential Common Mode, $V_{\text{CM}} = -5\text{V}$ to 13V | ● | 0.65 | 1.3 | M Ω |
| | | | ● | 0.3 | 0.5 | M Ω |
| C_{IN} | Input Capacitance | | | 5 | | pF |
| | Input Voltage Range | | ● | -5 | 13 | V |
| CMRR | Common Mode Rejection Ratio | $V_{\text{CM}} = -5\text{V}$ to 13V | ● | 68 | 80 | dB |
| A_{VOL} | Large-Signal Voltage Gain | $V_O = \pm 4\text{V}$, $R_L = 10\text{k}$ $0^\circ\text{C} \leq T_A \leq 70^\circ\text{C}$ $-40^\circ\text{C} \leq T_A \leq 85^\circ\text{C}$ | ● | 70 | 160 | V/mV |
| | | | ● | 50 | | V/mV |
| | | | ● | 40 | | V/mV |
| V_{OL} | Output Voltage Swing LOW | No Load $I_{\text{SINK}} = 5\text{mA}$ $I_{\text{SINK}} = 10\text{mA}$ | ● | -4.997 | -4.992 | V |
| | | | ● | -4.8 | -4.6 | V |
| | | | ● | -4.67 | -4.4 | V |
| V_{OH} | Output Voltage Swing HIGH | No Load $I_{\text{SOURCE}} = 5\text{mA}$ $I_{\text{SOURCE}} = 10\text{mA}$ | ● | 4.91 | 4.94 | V |
| | | | ● | 4.6 | 4.8 | V |
| | | | ● | 4.5 | 4.74 | V |
| I_{SC} | Short-Circuit Current (Note 2) | Short to GND $0^\circ\text{C} \leq T_A \leq 70^\circ\text{C}$ | ● | 18 | 30 | mA |
| | | | ● | 15 | | mA |
| PSRR | Power Supply Rejection Ratio | $V_S = \pm 1.5\text{V}$ to $\pm 9\text{V}$ | ● | 90 | 100 | dB |
| I_S | Supply Current | $0^\circ\text{C} \leq T_A \leq 70^\circ\text{C}$ $-40^\circ\text{C} \leq T_A \leq 85^\circ\text{C}$ | ● | 230 | 325 | μA |
| | | | ● | | 375 | μA |
| | | | ● | | 400 | μA |
| | Supply Current, SHDN | $V_{\text{PIN5}} = -3\text{V}$, $V_S = \pm 5\text{V}$, No Load (Note 10) | ● | 6 | 20 | μA |
| I_{SHDN} | Shutdown Pin Current | $V_{\text{PIN5}} = -4.7\text{V}$, $V_S = \pm 5\text{V}$, No Load (Note 10) | ● | 0.5 | | nA |
| | | $V_{\text{PIN5}} = -3\text{V}$, $V_S = \pm 5\text{V}$, No Load (Note 10) | ● | 2 | 8 | μA |

ELECTRICAL CHARACTERISTICS

The ● denotes specifications which apply over the specified temperature range, otherwise specifications are $T_A = 25^\circ\text{C}$. $V_S = \pm 5\text{V}$, $V_{CM} = 0\text{V}$, $V_{OUT} = 0\text{V}$, for the 6-lead part $V_{PIN5} = V^-$, pulse power tested unless otherwise specified. (Note 4)

| SYMBOL | PARAMETER | CONDITIONS | LT1783C/LT1783I | | | UNITS |
|-----------|---------------------------------|---|-----------------|------|------|------------------|
| | | | MIN | TYP | MAX | |
| | Maximum Shutdown Pin Current | $V_{PIN5} = 9\text{V}$, $V_S = \pm 9\text{V}$ (Note 10) | ● | 10 | 30 | μA |
| | Shutdown Output Leakage Current | $V_{PIN5} = -7\text{V}$, $V_S = \pm 9\text{V}$, No Load (Note 10) | ● | 0.05 | 1 | μA |
| V_L | Shutdown Pin Input Low Voltage | $V_S = \pm 5\text{V}$ (Note 10) | ● | | -4.7 | V |
| V_H | Shutdown Pin Input High Voltage | $V_S = \pm 5\text{V}$ (Note 10) | ● | -2.8 | | V |
| t_{ON} | Turn-On Time | $V_{PIN5} = 0\text{V}$ to -5V , $R_L = 10\text{k}$ (Note 10) | ● | 25 | | μs |
| t_{OFF} | Turn-Off Time | $V_{PIN5} = -5\text{V}$ to 0V , $R_L = 10\text{k}$ (Note 10) | ● | 3 | | μs |
| GBW | Gain Bandwidth Product | $f = 5\text{kHz}$ | ● | 800 | 1300 | kHz |
| | | $0^\circ\text{C} \leq T_A \leq 70^\circ\text{C}$ | ● | 700 | | kHz |
| | | $-40^\circ\text{C} \leq T_A \leq 85^\circ\text{C}$ | ● | 625 | | kHz |
| SR | Slew Rate | $A_V = -1$, $R_L = \infty$, $V_O = \pm 4\text{V}$, Measured at $V_O = \pm 2\text{V}$ | ● | 0.26 | 0.45 | V/ μs |
| | | $0^\circ\text{C} \leq T_A \leq 70^\circ\text{C}$ | ● | 0.23 | | V/ μs |
| | | $-40^\circ\text{C} \leq T_A \leq 85^\circ\text{C}$ | ● | 0.21 | | V/ μs |
| FPBW | Full-Power Bandwidth (Note 11) | $V_{OUT} = 8V_{P-P}$ | | 18 | | kHz |
| t_S | Settling Time | $\Delta V_{OUT} = 4\text{V}$ to 0.1%, $A_V = 1$ | | 10 | | μs |

The ● denotes specifications which apply over the full operating temperature range of $-40^\circ\text{C} \leq T_A \leq 125^\circ\text{C}$. $V_S = 3\text{V}$, 0V ; $V_S = 5\text{V}$, 0V ; $V_{CM} = V_{OUT} = \text{half supply}$, for the 6-lead part $V_{PIN5} = 0\text{V}$, pulse power tested unless otherwise specified. (Note 4)

| SYMBOL | PARAMETER | CONDITIONS | LT1783H | | | UNITS |
|-----------|-------------------------------------|--|---------|------|------|---------------|
| | | | MIN | TYP | MAX | |
| V_{OS} | Input Offset Voltage | | ● | 400 | 850 | μV |
| | Input Offset Voltage Drift (Note 9) | | ● | | 3 | mV |
| I_{OS} | Input Offset Current | $V_{CM} = 18\text{V}$ (Note 5) | ● | | 15 | nA |
| | | | ● | | 10 | μA |
| I_B | Input Bias Current | $V_{CM} = 18\text{V}$ (Note 5) | ● | | 150 | nA |
| | | | ● | | 150 | μA |
| | Input Voltage Range | | ● | 0.3 | 18 | V |
| CMRR | Common Mode Rejection Ratio | $V_{CM} = 0.3\text{V}$ to $V_{CC} - 1\text{V}$ | ● | 76 | | dB |
| | | $V_{CM} = 0.3\text{V}$ to 18V | ● | 60 | | dB |
| A_{VOL} | Large-Signal Voltage Gain | $V_S = 3\text{V}$, $V_O = 500\text{mV}$ to 2.5V , $R_L = 10\text{k}$ | ● | 200 | 1500 | V/mV |
| | | $V_S = 5\text{V}$, $V_O = 500\text{mV}$ to 4.5V , $R_L = 10\text{k}$ | ● | 50 | 1500 | V/mV |
| V_{OL} | Output Voltage Swing LOW | No Load | ● | | 15 | mV |
| | | $I_{SINK} = 5\text{mA}$ | ● | | 800 | mV |
| | | $V_S = 5\text{V}$, $I_{SINK} = 10\text{mA}$ | ● | | 1200 | mV |
| V_{OH} | Output Voltage Swing HIGH | $V_S = 3\text{V}$, No Load | ● | 2.85 | | V |
| | | $V_S = 3\text{V}$, $I_{SOURCE} = 5\text{mA}$ | ● | 2.30 | | V |
| | | $V_S = 5\text{V}$, No Load | ● | 4.85 | | V |
| | | $V_S = 5\text{V}$, $I_{SOURCE} = 10\text{mA}$ | ● | 4 | | V |
| PSRR | Power Supply Rejection Ratio | $V_S = 3\text{V}$ to 12.5V , $V_{CM} = V_O = 1\text{V}$ | ● | 80 | | dB |
| | Minimum Supply Voltage | | ● | 2.7 | | V |
| | Reverse Supply Voltage | $I_S = -100\mu\text{A}$ | ● | 18 | | V |

ELECTRICAL CHARACTERISTICS

The ● denotes specifications which apply over the full operating temperature range of $-40^{\circ}\text{C} \leq T_A \leq 125^{\circ}\text{C}$. $V_S = 3\text{V}, 0\text{V}; V_S = 5\text{V}, 0\text{V}; V_{CM} = V_{OUT} = \text{half supply}$, for the 6-lead part $V_{PIN5} = 0\text{V}$, pulse power tested unless otherwise specified. (Note 4)

| SYMBOL | PARAMETER | CONDITIONS | LT1783H | | | UNITS |
|------------|------------------------------|--|---------|------|------------|--------------------------------|
| | | | MIN | TYP | MAX | |
| I_S | Supply Current | | | 210 | 300 600 | μA μA |
| | Supply Current, SHDN | $V_{PIN5} = 2\text{V}$, No Load (Note 10) | ● | | 25 | μA |
| I_{SHDN} | Shutdown Pin Current | $V_{PIN5} = 0.3\text{V}$, No Load (Note 10) $V_{PIN5} = 2\text{V}$, No Load (Note 10) | ● ● | 0.5 | 12 | nA μA |
| | Output Leakage Current | $V_{PIN5} = 2\text{V}$, No Load (Note 10) | ● | | 2.5 | μA |
| | Maximum Shutdown Pin Current | $V_{PIN5} = 18\text{V}$, No Load (Note 10) | ● | | 40 | μA |
| GBW | Gain Bandwidth Product | $f = 5\text{kHz}$ (Note 5) | ● | 750 | 1250 | kHz |
| | | | | 400 | | kHz |
| SR | Slew Rate | $A_V = -1, R_L = \infty$ (Note 7) | | 0.24 | 0.42 | $\text{V}/\mu\text{s}$ |
| | | | ● | 0.12 | | $\text{V}/\mu\text{s}$ |

The ● denotes specifications which apply over the full operating temperature range of $-40^{\circ}\text{C} \leq T_A \leq 125^{\circ}\text{C}$. $V_S = \pm 5\text{V}, V_{CM} = 0\text{V}, V_{OUT} = 0\text{V}, V_{SHDN} = V^-$, $T_A = -40^{\circ}\text{C}$ to 125°C , for the 6-lead part $V_{PIN5} = V^-$, pulse power tested unless otherwise specified. (Note 4)

| SYMBOL | PARAMETER | CONDITIONS | LT1783H | | | UNITS |
|------------|-------------------------------------|--|---------|------------|------------|--------------------------------|
| | | | MIN | TYP | MAX | |
| V_{OS} | Input Offset Voltage | | | 500 | 950 | μV |
| | Input Offset Voltage Drift (Note 9) | | ● | | 3.1 | mV |
| | | | ● | | 15 | $\mu\text{V}/^{\circ}\text{C}$ |
| I_{OS} | Input Offset Current | | ● | | 15 | nA |
| I_B | Input Bias Current | | ● | | 150 | nA |
| CMRR | Common Mode Rejection Ratio | $V_{CM} = -4.7\text{V}$ to 13V | ● | 60 | | dB |
| A_{VOL} | Large-Signal Voltage Gain | $V_O = \pm 4\text{V}, R_L = 10\text{k}$ | | 70 | 160 | V/mV |
| | | | ● | 10 | | V/mV |
| V_O | Output Voltage Swing | No Load $I_{OUT} = \pm 5\text{mA}$ $I_{OUT} = \pm 10\text{mA}$ | ● | ± 4.85 | | V |
| | | | ● | ± 4.20 | | V |
| | | | ● | ± 3.80 | | V |
| PSRR | Power Supply Rejection Ratio | $V_S = \pm 1.5\text{V}$ to $\pm 9\text{V}$ | ● | 80 | | dB |
| | Minimum Supply Voltage | | ● | ± 1.35 | | V |
| I_S | Supply Current | | | 230 | 325 650 | μA μA |
| | Supply Current, SHDN | $V_{PIN5} = -3\text{V}, V_S = \pm 5\text{V}$, No Load (Note 10) | ● | | 25 | μA |
| I_{SHDN} | Shutdown Pin Current | $V_{PIN5} = -4.7\text{V}, V_S = \pm 5\text{V}$, No Load (Note 10) $V_{PIN5} = -3\text{V}, V_S = \pm 5\text{V}$, No Load (Note 10) | ● ● | 0.5 | 12 | nA μA |
| | Maximum Shutdown Pin Current | $V_{PIN5} = 9\text{V}, V_S = \pm 9\text{V}$ (Note 10) | ● | | 45 | μA |
| | Output Leakage Current | $V_{PIN5} = -7\text{V}, V_S = \pm 9\text{V}$, No Load | ● | | 3 | μA |
| V_L | Shutdown Pin Input Low Voltage | $V_S = \pm 5\text{V}$ | ● | | -4.7 | V |
| V_H | Shutdown Pin Input High Voltage | $V_S = \pm 5\text{V}$ | ● | -2.8 | | V |
| GBW | Gain Bandwidth Product | $f = 5\text{kHz}$ | ● | 800 | 1300 | kHz |
| | | | | 425 | | kHz |
| SR | Slew Rate | $A_V = -1, R_L = \infty, V_O = 4\text{V}$ Measured at $V_O = \pm 2\text{V}$ | | 0.26 | 0.45 | $\text{V}/\mu\text{s}$ |
| | | | ● | 0.14 | | $\text{V}/\mu\text{s}$ |

ELECTRICAL CHARACTERISTICS

Note 1: Absolute Maximum Ratings are those values beyond which the life of a device may be impaired.

Note 2: A heat sink may be required to keep the junction temperature below absolute maximum.

Note 3: The LT1783C and LT1873I are guaranteed functional over the operating temperature range of -40°C to 85°C . The LT1783H is guaranteed functional over the operating temperature range of -40°C to 125°C .

Note 4: The LT1783C is guaranteed to meet specified performance from 0°C to 70°C . The LT1783C is designed, characterized and expected to meet specified performance from -40°C to 85°C but is not tested or QA sampled at these temperatures. The LT1783I is guaranteed to meet specified performance from -40°C to 85°C . The LT1783H is guaranteed to meet specified performance from -40°C to 125°C .

Note 5: $V_S = 5\text{V}$ limits are guaranteed by correlation to $V_S = 3\text{V}$ and $V_S = \pm 5\text{V}$ or $V_S = \pm 9\text{V}$ tests.

Note 6: $V_S = 3\text{V}$ limits are guaranteed by correlation to $V_S = 5\text{V}$ and $V_S = \pm 5\text{V}$ or $V_S = \pm 9\text{V}$ tests.

Note 7: Guaranteed by correlation to slew rate at $V_S = \pm 5\text{V}$, and GBW at $V_S = 3\text{V}$ and $V_S = \pm 5\text{V}$ tests.

Note 8: This specification implies a typical input offset voltage of 1.8mV at $V_{CM} = 18\text{V}$ and a maximum input offset voltage of 7.2mV at $V_{CM} = 18\text{V}$.


Note 9: This parameter is not 100% tested.

Note 10: Specifications apply to 6-lead SOT-23 with shutdown.

Note 11: Full-power bandwidth is calculated from the slew rate. $\text{FPBW} = \text{SR}/2\pi V_P$.


TYPICAL PERFORMANCE CHARACTERISTICS

Supply Current vs Supply Voltage




1783 G01

Minimum Supply Voltage




1783 G02

Output Voltage vs Large Input Voltage




1783 G02a

Input Bias Current vs Common Mode Voltage




1783 G03

Output Saturation Voltage vs Load Current (Output High)



1783 G04


Output Saturation Voltage vs Load Current (Output Low)



1783 G05


TYPICAL PERFORMANCE CHARACTERISTICS

Output Saturation Voltage vs Input Overdrive




1783 G06

Output Short-Circuit Current vs Temperature




1783 G06a

0.1Hz to 10Hz Noise Voltage




1783 G07

Noise Voltage Density vs Frequency




1783 G08

Input Noise Current vs Frequency




1783 G09

Gain and Phase Shift vs Frequency




1783 G10

Gain Bandwidth Product vs Temperature



1783 G11


Slew Rate vs Temperature



1783 G12


TYPICAL PERFORMANCE CHARACTERISTICS

Gain Bandwidth Product and Phase Margin vs Supply Voltage




1783 G13

Gain Bandwidth and Phase Margin vs Load Resistance




1783 G14

PSRR vs Frequency




1783 G15

CMRR vs Frequency




1783 G16

Output Impedance vs Frequency




1783 G17

Disabled Output Impedance vs Frequency (Note 8)




1783 G17a

Settling Time to 0.1% vs Output Step



1783 G18


Capacitive Load Handling Overshoot vs Capacitive Load



1783 G19


TYPICAL PERFORMANCE CHARACTERISTICS

Undistorted Output Swing vs Frequency




1783 G20

Total Harmonic Distortion + Noise vs Frequency




1783 G21

Total Harmonic Distortion + Noise vs Load Resistance




1783 G22

Total Harmonic Distortion + Noise vs Output Voltage Amplitude




1783 G23

Open-Loop Gain




1783 G24

Supply Current vs SHDN Pin Voltage



1783 G25


Large-Signal Response



$V_S = \pm 5V$
 $A_V = 1$
 $C_L = 15pF$

1783 G26

Small-Signal Response



$V_S = \pm 5V$
 $A_V = 1$
 $C_L = 15pF$

1783 G27

APPLICATIONS INFORMATION

Supply Voltage

The positive supply pin of the LT1783 should be bypassed with a small capacitor (typically $0.1\mu\text{F}$) within an inch of the pin. When driving heavy loads, an additional $4.7\mu\text{F}$ electrolytic capacitor should be used. When using split supplies, the same is true for the negative supply pin.

The LT1783 is protected against reverse battery voltages up to 18V. In the event a reverse battery condition occurs, the supply current is less than 1nA.

Inputs

The LT1783 has two input stages, NPN and PNP (see the Simplified Schematic), resulting in three distinct operating regions as shown in the Input Bias Current vs Common Mode typical performance curve.

For input voltages about 0.8V or more below V^+ , the PNP input stage is active and the input bias current is typically -40nA . When the input common mode voltage is within 0.5V of the positive rail, the NPN stage is operating and the input bias current is typically 80nA . Increases in temperature will cause the voltage at which operation switches from the PNP input stage to the NPN input stage to move towards V^+ . The input offset voltage of the NPN stage is untrimmed and is typically 1.8mV.

A Schottky diode in the collector of the input transistors, along with special geometries for these NPN transistors, allow the LT1783 to operate with either or both of its inputs above V^+ . At about 0.3V above V^+ , the NPN input transistor is fully saturated and the input bias current is typically $30\mu\text{A}$ at room temperature. The input offset voltage is typically 1.8mV when operating above V^+ . The LT1783 will operate with its inputs 18V above V^- regardless of V^+ .

The inputs are protected against excursions as much as 10V below V^- by an internal 1k resistor in series with each input and a diode from the input to the negative supply. The input stage of the LT1783 incorporates phase reversal protection to prevent the output from phase reversing for inputs up to 9V below V^- . There are no clamping diodes between the inputs and the maximum differential input voltage is 18V.

Output

The output of the LT1783 can swing to within 60mV of the positive rail with no load and within 3mV of the negative rail with no load. When monitoring input voltages within 60mV of the positive rail or within 3mV of the negative rail, gain should be taken to keep the output from clipping. The LT1783 can sink and source over 30mA at $\pm 5\text{V}$ supplies, sourcing current is reduced to 10mA at 3V total supplies as noted in the Electrical Characteristics.

The LT1783 is internally compensated to drive at least 400pF of capacitance under any output loading conditions. A $0.22\mu\text{F}$ capacitor in series with a 150Ω resistor between the output and ground will compensate these amplifiers for larger capacitive loads, up to 10,000pF, at all output currents.

Distortion

There are two main contributors to distortion in op amps: output crossover distortion as the output transitions from sourcing to sinking current, and distortion caused by nonlinear common mode rejection. If the op amp is operating inverting, there is no common mode induced distortion. If the op amp is operating in the PNP input stage (input is not within 0.8V of V^+), the CMRR is very good,

APPLICATIONS INFORMATION

typically 100dB. When the LT1783 switches between input stages, there is significant nonlinearity in the CMRR. Lower load resistance increases the output crossover distortion but has no effect on the input stage transition distortion. For lowest distortion, the LT1783 should be operated single supply, with the output always sourcing current and with the input voltage swing between ground and $(V^+ - 0.8V)$. See the Typical Performance Characteristics curves, "Total Harmonic Distortion + Noise vs Output Voltage Amplitude."

Gain


The open-loop gain is almost independent of load when the output is sourcing current. This optimizes perfor-

mance in single supply applications where the load is returned to ground. The typical performance curve of open-loop gain for various loads shows the details.

Shutdown


The 6-lead part includes a shutdown feature that disables the part, reducing quiescent current and making the output high impedance. The part can be shut down by bringing the SHDN pin 1.2V or more above V^- . When shut down, the supply current is about $5\mu A$ and the output leakage current is less than $1\mu A$ ($V^- \leq V_{OUT} \leq V^+$). In normal operation, the SHDN pin can be tied to V^- or left floating. See the Typical Performance Characteristics curves, "Supply Current vs Shutdown Voltage."

SIMPLIFIED SCHEMATIC




TYPICAL APPLICATION


Protected Fault Conditions




REVERSE BATTERY



INPUT OVERVOLTAGE



INPUT DIFFERENTIAL VOLTAGE



INPUTS BELOW GROUND




1783 TA03

PACKAGE DESCRIPTION

**S5 Package
5-Lead Plastic SOT-23**

(Reference LTC DWG # 05-08-1633)
(Reference LTC DWG # 05-08-1635)

| | SOT-23 (Original) | SOT-23 (ThinSOT) |
|-----------|------------------------------------|---|
| A | $\frac{.90 - 1.45}{(.035 - .057)}$ | $\frac{1.00 \text{ MAX}}{(.039 \text{ MAX})}$ |
| A1 | $\frac{.00 - .15}{(.00 - .006)}$ | $\frac{.01 - .10}{(.0004 - .004)}$ |
| A2 | $\frac{.90 - 1.30}{(.035 - .051)}$ | $\frac{.80 - .90}{(.031 - .035)}$ |
| L | $\frac{.35 - .55}{(.014 - .021)}$ | $\frac{.30 - .50 \text{ REF}}{(.012 - .019 \text{ REF})}$ |



- NOTE:
1. CONTROLLING DIMENSION: MILLIMETERS
 2. DIMENSIONS ARE IN $\frac{\text{MILLIMETERS}}{\text{INCHES}}$
 3. DRAWING NOT TO SCALE
 4. DIMENSIONS ARE INCLUSIVE OF PLATING
 5. DIMENSIONS ARE EXCLUSIVE OF MOLD FLASH AND METAL BURR
 6. MOLD FLASH SHALL NOT EXCEED .254mm
 7. PACKAGE EIAJ REFERENCE IS:
SC-74A (EIAJ) FOR ORIGINAL
JEDEC MO-193 FOR THIN




PACKAGE DESCRIPTION

S6 Package 6-Lead Plastic SOT-23

(Reference LTC DWG # 05-08-1634)

(Reference LTC DWG # 05-08-1636)


| | SOT-23 (Original) | SOT-23 (ThinSOT) |
|----|------------------------------------|---|
| A | $\frac{.90 - 1.45}{(.035 - .057)}$ | $\frac{1.00 \text{ MAX}}{(.039 \text{ MAX})}$ |
| A1 | $\frac{.00 - 0.15}{(.00 - .006)}$ | $\frac{.01 - .10}{(.0004 - .004)}$ |
| A2 | $\frac{.90 - 1.30}{(.035 - .051)}$ | $\frac{.80 - .90}{(.031 - .035)}$ |
| L | $\frac{.35 - .55}{(.014 - .021)}$ | $\frac{.30 - .50 \text{ REF}}{(.012 - .019 \text{ REF})}$ |



- NOTE:
1. CONTROLLING DIMENSION: MILLIMETERS
 2. DIMENSIONS ARE IN $\frac{\text{MILLIMETERS}}{\text{(INCHES)}}$
 3. DRAWING NOT TO SCALE
 4. DIMENSIONS ARE INCLUSIVE OF PLATING
 5. DIMENSIONS ARE EXCLUSIVE OF MOLD FLASH AND METAL BURR
 6. MOLD FLASH SHALL NOT EXCEED .254mm
 7. PACKAGE EIAJ REFERENCE IS:
SC-74A (EIAJ) FOR ORIGINAL
JEDEL MO-193 FOR THIN

TYPICAL APPLICATION

Current Source



RELATED PARTS

| PART NUMBER | DESCRIPTION | COMMENTS |
|---------------|---|--|
| LT1782 | Micropower, Over-The-Top SOT-23 Rail-to-Rail Input and Output Op Amp | SOT-23 Package, Micropower 40µA per Amplifier, Rail-to-Rail Input and Output , 200kHz GBW |
| LT1490/LT1491 | Dual/Quad Over-The-Top Micropower Rail-to-Rail Input and Output Op Amps | Single Supply Input Range: -0.4V to 44V, Micropower 50µA per Amplifier, Rail-to-Rail Input and Output , 200kHz GBW |
| LT1636 | Single Over-The-Top Micropower Rail-to-Rail Input and Output Op Amp | 55µA Supply Current, V_{CM} Extends 44V Above V_{EE} , Independent of V_{CC} , MSOP Package, Shutdown Function |
| LT1638/LT1639 | Dual/Quad, 1.2MHz, 0.4V/µs, Over-The-Top Micropower Rail-to-Rail Input and Output Op Amps | 170µA Supply Current, Single Supply Input Range: -0.4V to 44V, Rail-to-Rail Input and Output |