

TENTATIVE TOSHIBA PHOTOCOUPLER GaAs IRED & PHOTO-MOS FET / PHOTO-TRANSISTOR

## TLP270D

MOBILE / NOTE PCs

PDA's

MULTIMEDIA TV's

MODEMS

TLP270D has many multi-functions in DAA circuits for modems, which is a fully integrated design photocoupler in a 14pin (SOP16).

### ① Photorelay

Dial pulsing switch, Hookswitch

- 1 Form A
- Peak Off-State Voltage : 200 V (MIN.)
- Trigger LED Current : 3 mA (MAX.)
- On-State Current : 150 mA (MAX.)

### ② Photocoupler

Ring detection


- Collector-Emitter Voltage : 80 V (MIN.)
- Current Transfer Ratio : 50% (MIN.)

### ③ Darlington Transistor

Electronic inductor

- Collector-Emitter Voltage : 30 V (MIN.)
- Collector Current : 150 mA (MAX.)

Unit in mm



Weight : 0.2 g

## ④ Bridge Rectifier

Polarity protection

- Reverse Voltage : 30 V (MIN.)
- Forward Voltage : 1.7 V (MAX.)

## ⑤ Zener Diode


Ring detection protector

- Zener Voltage : 22~32 V

(Common)

- Isolation Voltage : 1500 Vrms (MIN.)
- UL Recognized : UL1577, File No. E67349

## PIN CONFIGURATION (TOP VIEW)



## PHOTORELAY (1-Form-A)

## MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	RATING	UNIT
LED	Forward Current	I <sub>F</sub>	50	mA
	Forward Current Derating (Ta ≥ 25°C)	ΔI <sub>F</sub> / °C	−0.5	mA / °C
	Peak Forward Current (100 μs pulse, 100 pps)	I <sub>FP</sub>	1	A
	Reverse Voltage	V <sub>R</sub>	5	V
	Junction Temperature	T <sub>j</sub>	125	°C
DETECTOR	Off-State Output Terminal Voltage	V <sub>OFF</sub>	200	V
	On-State RMS Current	I <sub>ON</sub>	150	mA
	On-State RMS Current Derating (Ta ≥ 25°C)	ΔI <sub>ON</sub> / °C	−1.5	mA / °C
	Junction Temperature	T <sub>j</sub>	125	°C

## INDIVIDUAL ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
LED	Forward Voltage	V <sub>F</sub>	I <sub>F</sub> = 10 mA	1.0	1.15	1.3	V
	Reverse Current	I <sub>R</sub>	V <sub>R</sub> = 5 V	—	—	10	μA
	Capacitance	C <sub>T</sub>	V = 0, f = 1 MHz	—	30	—	pF
DETECTOR	Off-State Current	I <sub>OFF</sub>	V <sub>OFF</sub> = 200 V	—	—	1	μA
	Capacitance	C <sub>OFF</sub>	V = 0, f = 1 MHz	—	90	—	pF

## COUPLED ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Trigger LED Current	I <sub>FT</sub>	I <sub>ON</sub> = 150 mA	—	1	3	mA
On-State Resistance	R <sub>ON</sub>	I <sub>ON</sub> = 150 mA, I <sub>F</sub> = 5 mA	—	5	8	Ω

## SWITCHING CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Turn-on Time	t <sub>ON</sub>	R <sub>L</sub> = 200 Ω, V <sub>CC</sub> = 20 V, I <sub>F</sub> = 5 mA	—	—	1.5	ms
Turn-off Time	t <sub>OFF</sub>		—	—	1	

## PHOTOCOUPLER (AC-Input Transistor output)

## MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	RATING	UNIT
LED	Forward Current	I <sub>F</sub>	±50	mA
	Forward Current Derating (Ta ≥ 25°C)	ΔI <sub>F</sub> / °C	−0.5	mA / °C
	Pulse Forward Current (100 μs pulse, 100 pps)	I <sub>FP</sub>	1	A
	Junction Temperature	T <sub>j</sub>	125	°C
DETECTOR	Collector-Emitter Voltage	V <sub>CEO</sub>	80	V
	Emitter-Collector Voltage	V <sub>ECO</sub>	7	V
	Collector Current	I <sub>C</sub>	50	mA
	Collector Power Dissipation (1 Circuit)	P <sub>C</sub>	150	mW
	Collector Power Dissipation Derating (Ta ≥ 25°C) (1 Circuit)	ΔP <sub>C</sub> / °C	−1.5	mW / °C
	Junction Temperature	T <sub>j</sub>	125	°C

## INDIVIDUAL ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
LED	Forward Voltage	V <sub>F</sub>	I <sub>F</sub> = ±10 mA	1.0	1.15	1.3	V
	Capacitance	C <sub>T</sub>	V = 0, f = 1 MHz	—	60	—	pF
DETECTOR	Collector-Emitter Breakdown Voltage	V <sub>(BR) CEO</sub>	I <sub>C</sub> = 0.5 mA	80	—	—	V
	Emitter-Collector Breakdown Voltage	V <sub>(BR) ECO</sub>	I <sub>E</sub> = 0.1 mA	7	—	—	V
	Collector Dark Current	I <sub>D</sub>	V <sub>CE</sub> = 48 V (Ambient Light : 100 lx)	—	0.01 (2)	0.1 (20)	μA
			V <sub>CE</sub> = 48 V, Ta = 85°C (Ambient Light : 100 lx)	—	2 (4)	50 (50)	μA
	Capacitance	C <sub>CE</sub>	V = 0, f = 1 MHz	—	10	—	pF

COUPLED ELECTRICAL CHARACTERISTICS ( $T_a = 25^\circ\text{C}$ )

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Current Transfer Ratio (CTR)	$I_C / I_F$	$I_F = 5 \text{ mA}$ , $V_{CE} = 5 \text{ V}$ Rank GB	50	—	—	%
			100	—	—	
Saturated CTR	$I_C / I_F$ (sat)	$I_F = 1 \text{ mA}$ , $V_{CE} = 0.4 \text{ V}$ Rank GB	—	60	—	%
			30	—	—	
Collector-Emitter Saturation Voltage	$V_{CE}(\text{sat})$	$I_C = 2.4 \text{ mA}$ , $I_F = 8 \text{ mA}$	—	—	0.4	V
		$I_C = 0.2 \text{ mA}$ , $I_F = 1 \text{ mA}$ Rank GB	—	0.2	—	
			—	—	0.4	
Off-State Collector Current	$I_C(\text{off})$	$V_F = 0.7 \text{ V}$ , $V_{CE} = 48 \text{ V}$	—	—	10	$\mu\text{A}$

SWITCHING CHARACTERISTICS ( $T_a = 25^\circ\text{C}$ )

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Rise Time	$t_r$	$V_{CC} = 10 \text{ V}$ , $I_C = 2 \text{ mA}$ , $R_L = 100 \Omega$	—	2	—	$\mu\text{s}$
Fall Time	$t_f$		—	3	—	
Turn-on Time	$t_{\text{on}}$		—	3	—	
Turn-off Time	$t_{\text{off}}$		—	3	—	
Turn-on Time	$t_{\text{ON}}$	$R_L = 1.9 \text{ k}\Omega$ , $V_{CC} = 5 \text{ V}$ , $I_F = 16 \text{ mA}$	—	2	—	
Storage Time	$t_s$		—	25	—	
Turn-off Time	$t_{\text{OFF}}$		—	40	—	

ZENER DIODEINDIVIDUAL ELECTRICAL CHARACTERISTICS ( $T_a = 25^\circ\text{C}$ )

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Zener Voltage	$V_Z$	—	22	27	32	V

DARLINGTON TRANSISTOR

## MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Collector-Base Voltage	V <sub>CBO</sub>	30	V
Collector-Emitter Voltage	V <sub>CEO</sub>	30	V
Emitter-Base Voltage	V <sub>EBO</sub>	10	V
Collector Current	I <sub>C</sub>	0.15	A
Base Current	I <sub>B</sub>	20	mA
Collector Power Dissipation	P <sub>C</sub>	350	mW
Junction Temperature	T <sub>j</sub>	125	°C

## INDIVIDUAL ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Collector Off Current		I <sub>CBO</sub>	V <sub>CB</sub> = 30 V, I <sub>E</sub> = 0	—	—	10	μA
Emitter Off Current		I <sub>EBO</sub>	V <sub>EB</sub> = 10 V, I <sub>C</sub> = 0	—	—	10	μA
Collector-Emitter Breakdown Voltage		V <sub>(BR)</sub> CEO	I <sub>C</sub> = 10 mA, I <sub>B</sub> = 0	30	—	—	V
DC Current Gain		h <sub>FE</sub>	V <sub>CE</sub> = 2 V, I <sub>C</sub> = 150 mA	4000	—	—	
Collector-Emitter Saturation Voltage		V <sub>CE</sub> (sat)	I <sub>C</sub> = 0.15 A, I <sub>B</sub> = 1 mA	—	—	1.5	V
Switching Time	Turn-on Time	t <sub>on</sub>	I <sub>B</sub> = 1 mA, V <sub>CC</sub> = 15 V, R <sub>L</sub> = 15 Ω	—	0.20	—	μs
	Storage Time	t <sub>stg</sub>		—	0.6	—	
	Fall Time	t <sub>f</sub>		—	0.3	—	

BRIDGE RECTIFIER

## MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Repetitive Peak Reverse Voltage	V <sub>RRM</sub>	30	V
Average Output Rectified Current	I <sub>O</sub>	0.15	A
Peak One Cycle Surge Forward Current	I <sub>FSM</sub>	0.5	A
Junction Temperature	T <sub>j</sub>	125	°C

## INDIVIDUAL ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Forward Voltage	V <sub>FM</sub>	I <sub>FM</sub> = 0.12 A	—	—	1.7	V
Repetitive Peak Reverse Current	I <sub>RRM</sub>	V <sub>RRM</sub> = Rated	—	—	10	μA

PACKAGE (Common)

## MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Total Package Power Dissipation	P <sub>T</sub>	650	mW
Storage Temperature Range	T <sub>stg</sub>	−55~100	°C
Operating Temperature Range	T <sub>opr</sub>	−20~85	°C
Lead Soldering Temperature (10 s)	T <sub>sol</sub>	260	°C
Isolation Voltage (AC, 1 min., R.H. ≤ 60%) (Note 1)	BV <sub>S</sub>	1500	V <sub>rms</sub>

(Note 1) : Device considered a two-terminal device : Pins 1,  
2, 3, 4, 5, 6, 7 and 8 shorted together and pins  
10, 11, 12, 13, 14 and 15 shorted together.

## ISOLATION CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Capacitance Input to Output	C <sub>S</sub>	V <sub>S</sub> = 0, f = 1 MHz	—	0.8	—	pF
Isolation Resistance	R <sub>S</sub>	V <sub>S</sub> = 500 V, R.H. ≤ 60%	5 × 10 <sup>10</sup>	10 <sup>14</sup>	—	Ω
Isolation Voltage	BV <sub>S</sub>	AC, 1 minute	1500	—	—	V <sub>rms</sub>
		AC, 1 second, in oil	—	3000	—	
		DC, 1 minute, in oil	—	3000	—	V <sub>dc</sub>

**RESTRICTIONS ON PRODUCT USE**

000707EBC

- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc..
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in this document shall be made at the customer's own risk.
- Gallium arsenide (GaAs) is a substance used in the products described in this document. GaAs dust and fumes are toxic. Do not break, cut or pulverize the product, or use chemicals to dissolve them. When disposing of the products, follow the appropriate regulations. Do not dispose of the products with other industrial waste or with domestic garbage.
- The products described in this document are subject to the foreign exchange and foreign trade laws.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.