




AM80912-085

RF & MICROWAVE TRANSISTORS AVIONICS APPLICATIONS

- REFRACTORY/GOLD METALLIZATION
- EMITTER SITE BALLASTED
- 5:1 VSWR CAPABILITY
- LOW THERMAL RESISTANCE
- INPUT/OUTPUT MATCHING
- OVERLAY GEOMETRY
- METAL/CERAMIC HERMETIC PACKAGE
- $P_{OUT} = 80 \text{ W MIN. WITH } 7.27 \text{ dB GAIN}$



SO42
hermetically sealed

ORDER CODE
AM80912-085


BRANDING
80912-085

DESCRIPTION

The AM80912-085 is designed for specialized avionics applications including JTIDS, where power is provided under pulse formats utilizing short pulse widths and high burst or overall duty cycles.

The AM80912-085 is housed in a unique BIG-PAC™ Hermetic Metal/Ceramic package with internal input/output impedance matching.

PIN CONNECTION



1. Collector
2. Base

3. Emitter
4. Base

ABSOLUTE MAXIMUM RATINGS ($T_{CASE} = 25^\circ\text{C}$)

Symbol	Parameter	Value	Unit
P_{DISS}	Power Dissipation* ($T_C \leq 100^\circ\text{C}$)	300	W
I_c	Device Current*	8.0	A
V_{CC}	Collector-Supply Voltage*	40	V
T_j	Junction Temperature (Pulsed RF Operation)	250	$^\circ\text{C}$
T_{STG}	Storage Temperature	- 65 to +200	$^\circ\text{C}$

THERMAL DATA

$R_{th(j-c)}$	Junction -Case Thermal Resistance*	0.75	$^\circ\text{C/W}$
---------------	------------------------------------	------	--------------------

* Applies only to rated RF amplifier operation

ELECTRICAL SPECIFICATION ($T_{CASE} = 25\text{ }^{\circ}\text{C}$)**STATIC**

Symbol	Test Conditions	Min.	Typ.	Max.	Unit
BV_{CBO}	$I_C = 25\text{mA}$ $I_E = 0\text{mA}$	55			V
BV_{EBO}	$I_C = 0\text{mA}$ $I_E = 10\text{mA}$	3.5			V
BV_{CER}	$I_C = 25\text{mA}$ $R_{BE} = 10\Omega$	55			V
I_{CES}	$V_{BE} = 0\text{V}$ $V_{CE} = 35\text{V}$			20	mA
h_{FE}	$V_{CE} = 5\text{V}$ $I_C = 3\text{A}$	20		200	

DYNAMIC


Symbol	Test Conditions	Min.	Typ.	Max.	Unit
P_{OUT}	$f = 960 - 1215\text{MHz}$ $P_{IN} = 15\text{ W}$ $V_{CC} = 35\text{V}$	80			W
G_P	$f = 960 - 1215\text{MHz}$ $P_{IN} = 15\text{ W}$ $V_{CC} = 35\text{V}$	7.27			dB
η_C	$f = 960 - 1215\text{MHz}$ $P_{IN} = 15\text{ W}$ $V_{CC} = 35\text{V}$	35			%

Note: Pulse format: 6.4 μS on 6.6 μS off, repeat for 3.3 ms, then off for 4.5125 ms
Duty Cycle: Burst 49.2%, overall 20.8%

IMPEDANCE DATA

TYPICAL INPUT
IMPEDANCE


$P_{IN} = 15\text{ W}$
 $V_{CC} = 35\text{ V}$
 Normalized to 20 ohms




FREQ.	$Z_{IN}(\Omega)$	$Z_{CL}(\Omega)$
L = 960 MHz	$3.0 + j 5.0$	$7.0 - j 5.0$
• = 1025 MHz	$3.5 + j 6.0$	$5.3 - j 3.0$
M = 1090 MHz	$5.5 + j 5.5$	$3.7 - j 1.8$
• = 1150 MHz	$5.5 + j 5.0$	$3.3 - j 2.0$
H = 1215 MHz	$5.3 + j 4.5$	$3.0 - j 2.5$

TYPICAL COLLECTOR
LOAD IMPEDANCE

$P_{IN} = 15\text{ W}$
 $V_{CC} = 35\text{ V}$
 Normalized to 20 ohms



TEST CIRCUIT SCHEMATIC




TEST CIRCUIT COMPONENT PART LIST

C1, C2	0.6 - 4.5 pF GIGA-TRIM VARIABLE CAPACITOR
C3	100 pF SURFACE MOUNT CERAMIC CHIP CAPACITOR
C4	1000 pF RESIN SEALED #8-32 THREADED FEEDTHRU CAPACITOR
C5	100 μF / 63 V ALUMINUM ELECTROLYTIC AXIAL LEAD CAPACITOR
L1, L2	INDUCTOR 4 TURNS #26 AWG, ID = 0.0625 [1.58] SOLID TINNED BUS BAR WIRE
PCB	0.025 inch thick Al ₂ O ₃ , εr = 9.6

SO42 (.400 X .400 2/L HERM. W/FLG.) MECHANICAL DATA

DIM.	mm			Inch		
	MIN.	TYP.	MAX	MIN.	TYP.	MAX
A	0.51		0.76	0.020		0.030
B		6.35			0.250	
C	9.55		10.06	0.376		0.396
D	2.79		3.30	0.110		0.130
E	10.03		10.34	0.395		0.407
F		4.90			0.193	
G		11.43			0.450	
H		3.18			0.125	
I	16.26		16.76	0.640		0.660
J	22.61		23.11	0.890		0.910
K	10.03		10.54	0.395		0.415
L	0.10		0.18	0.004		0.006
M	1.32		1.83	0.052		0.072
N	2.84		3.35	0.112		0.132
P			5.84			0.230
Q	22.35		23.37	0.880		0.920



Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is registered trademark of STMicroelectronics
® 2001 STMicroelectronics - All Rights Reserved

All other names are the property of their respective owners.

STMicroelectronics GROUP OF COMPANIES
Australia - Brazil - China - Finland - France - Germany - Hong Kong - India - Italy - Japan - Malaysia - Malta - Morocco -
Singapore - Spain - Sweden - Switzerland - United Kingdom - U.S.A.

<http://www.st.com>