

FEATURES/BENEFITS

- 5V tolerant inputs and outputs
- Bus Hold feature holds last active state during 3-state operation
- $10\mu A$ I_{CCQ} quiescent power supply current
- Hot insertable
- 2.0V–3.6V V_{CC} supply operation
- $\pm 24mA$ balanced output drive
- Power down high impedance inputs and outputs
- $t_{PD} = 4.5ns$ max.
- Input hysteresis for noise immunity
- Meets or exceeds JEDEC Standard 36 specifications
- Multiple power and ground pins for low noise
- Operating temperature range:
 $-40^{\circ}C$ to $85^{\circ}C$
- Latch-up performance exceeds 500mA
- ESD performance:
 Human body model > 2000V
 Machine model > 200V
- Packages available:
 48-pin TSSOP
 48-pin SSOP

DESCRIPTION

The LVCH16374A is a 16-bit buffered register with three-state output that is ideal for driving address and data buses. The output enable ($x\overline{OE}$) and clock ($xCLK$) controls are organized to operate each device as two 8-bit registers, or one 16-bit register with common clock. Easy board layout is facilitated by the use of flow-through pinouts and byte enable controls provide architectural flexibility for systems designers. The QS74LVCH16374A provides Bus Hold circuitry on the data inputs retains the last active state during 3-state operation, eliminating the need for external pull-up resistors. The 3.3V LVC family features low power, low switching noise, and fast switching speeds for low power portable applications as well as high-end advanced workstation applications. To accommodate hot-plug or live insertion applications, this product is designed not to load an active bus when V_{CC} is removed. However, during power up or power down sequence, \overline{OE} should be tied to V_{CC} to ensure high-impedance state on the outputs.

Figure 1. Functional Block Diagram




Figure 2. Pin Configuration
(All Pins Top View)




Table 1. Pin Description

Name	I/O	Description
xDx	I	Data Inputs (Bus Hold Inputs)
xOx	O	Data Outputs
xCLK	I	Clock Input
xOE	I	Output Enable

Table 2. Function Table

Inputs			Internal Q Value	Outputs xOx	Function
xOE	xCLK	xDx			
H	X	X	X	Hi-Z	Disable Outputs
L	↑	L	L	L	Load Input Data
L	↑	H	H	H	Enable Outputs
H	↑	L	L	Hi-Z	Load Input Data
H	↑	H	H	Hi-Z	Disable Outputs

Table 3. Absolute Maximum Ratings

Supply Voltage to Ground	-0.5V to 7.0V
DC Output Voltage V_{OUT}	
Outputs HIGH-Z	-0.5V to 7.0V
Outputs Active	-0.5V to $V_{CC} + 0.5V$
DC Input Voltage V_{IN}	-0.5V to 7.0V
DC Input Diode Current with $V_{IN} < 0$	-50mA
DC Output Diode Current	
$V_O < 0$	-50mA
$V_O > V_{CC}$	50mA
DC Output Source/Sink Current (I_{OH}/I_{OL})	$\pm 50mA$
DC Supply Current per Supply Pin	$\pm 100mA$
DC Ground Current per Ground Pin	$\pm 100mA$
T_{STG} Storage Temperature	-65°C to 150°C

Note: Stresses greater than those listed under ABSOLUTE MAXIMUM RATINGS may cause permanent damage to this device resulting in functional or reliability type failures.

Table 4. Recommended Operating Conditions

Symbol	Parameter		Min	Max	Unit
V_{CC}	Supply Voltage, Operating		2.0	3.6	V
	Supply Voltage, Data Retention Only		1.5	3.6	
V_{IH}	Input HIGH Voltage	$V_{OL} = 2.7$ to 3.6V	2.0	—	V
V_{IL}	Input LOW Voltage	$V_{CC} = 2.7$ to 3.6V	—	0.8	V
V_{IN}	Input Voltage		0	5.5	V
V_{OUT}	Output Voltage in Active State		0	V_{CC}	V
	Output Voltage in "OFF" State		0	5.5	
I_{OH}	Output Current HIGH	$V_{CC} = 3.0$ –3.6V	—	-24	mA
		$V_{CC} = 2.7V$		-12	
I_{OL}	Output Current LOW	$V_{CC} = 3.0$ –3.6V	—	24	mA
		$V_{CC} = 2.7V$	—	12	
$\Delta t/\Delta v$	Input Transition Slew Rate		—	10	ns/V
T_A	Operating Free Air Temperature		-40	85	°C

Table 5. DC Electrical Characteristics Over Operating RangeIndustrial Temperature Range, $T_A = -40^\circ\text{C}$ to 85°C

Symbol	Parameter	Test Conditions		Min	Typ ⁽¹⁾	Max	Unit
V_{OH}	Output HIGH Voltage	$V_{CC} = 2.7\text{V}$, $I_{OH} = -100\mu\text{A}$	$V_{CC} = 0.2$	—	—	—	V
		$V_{CC} = 2.7\text{V}$, $I_{OH} = -12\text{mA}$	2.2	—	—	—	
		$V_{CC} = 3.0\text{V}$, $I_{OH} = -12\text{mA}$	2.4	—	—	—	
		$V_{CC} = 3.0\text{V}$, $I_{OH} = -24\text{mA}$	2.2	—	—	—	
V_{OL}	Output LOW Voltage	$V_{CC} = 2.7\text{V}$, $I_{OL} = 100\mu\text{A}$	—	—	0.2	—	V
		$V_{CC} = 2.7\text{V}$, $I_{OL} = 12\text{mA}$	—	—	0.4	—	
		$V_{CC} = 3.0\text{V}$, $I_{OL} = 24\text{mA}$	—	—	0.55	—	
V_{IK}	Input Clamp Voltage	$V_{CC} = 2.7\text{V}$, $I_{IN} = -18\text{mA}$	—	—	-0.7	-1.2	V
I_I	Input Leakage Current	$V_I = 0\text{V}$, $V_I = 5.5\text{V}$, $V_{CC} = 3.6\text{V}$	—	—	±1.0	—	μA
$ I_{BH} $	Bus Hold Inputs Overdrive Current ^(2,3)	$V_{CC} = 3.6\text{V}$, $V_{IN} = 0\text{V}$ or $V_{IN} = V_{CC}$	—	—	50	—	μA
		$V_{CC} = 3.6\text{V}$, $0.8\text{V} < V_{IN} < 2.0\text{V}$	—	—	500 ⁽⁴⁾	—	
I_{BHH} I_{BHL}	Bus Hold Input Sustaining Current	$V_{CC} = 3\text{V}$	$V_{IN} = 2.0\text{V}$	-75	—	—	μA
			$V_{IN} = 0.8\text{V}$	75	—	—	
I_{OZ}	High-Z I/O Leakage	$V_O = 0\text{V}$, $V_O = 5.5\text{V}$, $V_I = V_{IH}$ or V_{IL} , $V_{CC} = 3.6\text{V}$	—	—	±1.0	—	μA
I_{OFF}	Power Off Leakage	$V_{CC} = 0\text{V}$, V_I or $V_O = 5.5\text{V}$	—	—	10	—	μA
I_{CC}	Quiescent Power Supply Current	$V_{CC} = 3.6\text{V}$, $V_{IN} = V_{CC}$ or GND	—	0.1	10	—	μA
ΔI_{CC}	Quiescent Power Supply Current per Control Inputs at TTL HIGH	$V_{CC} = 3.6\text{V}$, $V_{IN} = V_{CC} - 0.6\text{V}^{(5)}$	—	2.0	3.0	—	μA
	Quiescent Power Supply Current per Bus Hold Inputs at TTL HIGH	$V_{CC} = 3.6\text{V}$, $V_{IN} = V_{CC} - 0.6\text{V}^{(5)}$	—	75	500	—	μA

Notes:

1. Typical values are at $V_{CC} = 3.3\text{V}$ and $T_A = 25^\circ\text{C}$.
2. These parameters are guaranteed by characterization, but not production tested.
3. Pins with Bus Hold are identified in the pin description.
4. An external driver must provide at least $|I_{BH}|$ during transition to guarantee that the Bus Hold input will change state.
5. Per TTL driven input. All other inputs at V_{CC} or GND.

TEST CIRCUIT AND WAVEFORMS

Figure 3. Test Circuit




Figure 4. Setup, Hold, and Release Timing




Figure 6. Pulse Width




Figure 5. Enable and Disable Timing






Figure 7. Propagation Delay



Notes:

1. Input Control Enable = LOW and Input Control Disable = HIGH.
2. Pulse Generator for All Pulses: Rate $\leq 1.0\text{MHz}$; $Z_{OUT} \leq 50\Omega$; $t_F, t_R \leq 2.5\text{ns}$.

ORDERING INFORMATION



Now an  IDT™ Company