# **ANALOG DEVICES**

# 96-Bit, 220 MHz True-Color Video RAM-DAC

# ADV7160/ADV7162

#### **FEATURES**

96-Bit Pixel Port for  $1600 \times 1280 \times 24$  Screen Resolution 220 MHz, 24-Bit (30-Bit Gamma Corrected) True-Color Triple 10-Bit "Gamma Correcting" D/A Converters 2% (max) DAC to DAC Color Matching Triple  $256 \times 10$  (256 x 30) Color Palette RAM On-Board User Definable Cursor ( $64 \times 64 \times 2$ ) **Three Color Overlay Cursor Palette RAM** Fully Programmable On-Board PLL RS-343A/RS-170 Compatible RGB Analog Outputs **Tri-Level SYNC Functionality TTL Compatible Digital Inputs** Standard MPU I/O Interface Programmable Pixel Port: 24-Bit, 16-Bit, 15-Bit & 8-Bit (Pseudo) **Pixel Data Serializer:** Multiplexed Pixel Input Ports; 2:1, 4:1, 8:1 +5 V CMOS Monolithic Construction

160-Lead Plastic Quad Flatpack (QFP): ADV7162 160-Lead "Thermally Enhanced" QFP (PQUAD): ADV7160

ADV is a registered trademark of Analog Devices, Inc.

#### MODES OF OPERATION

 $1600\times1200\times30/24$ -Bit Resolution @ 85 Hz Screen Refresh  $1600\times1200\times16/15$ -Bit Resolution @ 85 Hz Screen Refresh  $1600\times1200\times$  8-Bit Resolution @ 85 Hz Screen Refresh

#### APPLICATIONS

Windows Accelerators High Resolution, True Color Graphics Professional Color Prepress Imaging Digital TV (HDTV, Digital Video)

SPEED G	RADES
@ 220	MHz
@ 170	MHz
@ 140	MHz

#### **GENERAL DESCRIPTION**

The ADV7160/ADV7162® is a 96-bit pixel port Video RAM-DAC with color enhanced triple 10-bit DACs. The device also includes a PLL and  $64 \times 64$  hardware cursor. The ADV7160/ ADV7162 is specifically designed for use in the graphics subsystem of high performance, color graphics workstations and windows accelerators.

(Continued on page 15)



#### REV.0

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices.

© Analog Devices, Inc., 1995

One Technology Way, P.O. Box 9106, Norwood. MA 02062-9106, U.S.A. Tel: 617/329-4700 Fax: 617/326-8703

	CDECIEICATIONC	• $(V_{AA}^1 = +5 V; V_{REF} = +1.235 V; R_{SET} = 280$	$\Omega$ . IOR, IOG, IOB (R <sub>L</sub> = 37.5 $\Omega$ ,
AUV/IOU/AUV/IOZ—	<b>3LEPILIPALINU</b>	$C_L = 10 \text{ pF}$ ). All specifications $T_{MIN}$ to $T_N$	<sub>MAX</sub> <sup>2</sup> unless otherwise noted.)

Parameter	Min	Тур	Max	Units	Test Conditions/Comments
STATIC PERFORMANCE					(DAC Gain Setting = 3996)
Resolution (Each DAC)			10	Bits	
Accuracy (Each DAC)					
Integral Nonlinearity			$\pm 1$	LSB	
Differential Nonlinearity			$\pm 1$	LSB	Guaranteed Monotonic
Gray Scale Error			±5	% Gray Scale	
Coding				Binary	
DIGITAL INPLITS					
Input High Voltage V	2			V	
Input I ny Voltage, V	2		0.8	V	
Input Low Voltage, V <sub>INL</sub>			+10	v u A	V = 0.4 V  or  2.4 V
Input Canacitance		10	$\pm 10$	μA	$v_{\rm IN} = 0.4$ v or 2.4 v
		10		рг	
CLOCK INPUTS (CLOCK, CLOCK)					
Input High Voltage, V <sub>INH</sub>	$V_{AA} - 1.0$			V	
Input Low Voltage, V <sub>INL</sub>			$V_{AA} - 1.6$	V	
Input Current, I <sub>IN</sub>			$\pm 10$	μA	$V_{IN} = 0.4 V \text{ or } 2.4 V$
Input Current, I <sub>IN</sub> (JTAG Inputs)			$\pm 50$	μA	$V_{IN} = 0.4 V \text{ or } 2.4 V$
Input Capacitance, C <sub>IN</sub>		10		pF	
DIGITAL OUTPUTS					
Output High Voltage, VOH	2.4			V	$I_{\text{SOURCE}} = 400  \mu\text{A}$
Output Low Voltage, Vol			0.4	V	$I_{SDW} = 3.2 \text{ mA}$
Floating-State Leakage Current			20	uА	
Floating-State Output Capacitance		20		pF	
				P-	$(\mathbf{DAC} C \text{ oin Setting} = 3006)$
Croy Scale Current Bange	15		22	m 1	(DAC Gain Setting – 5990)
Gray Scale Current Range	15		22	IIIA	
White Level Deleting to Plank	17.60	10.05	20.40		
White Level Relative to Black	17.09	19.05	20.40		
White Level Relative to Black	10.74	17.02	18.50	mA	
Black Level Relative to Blank	0.95	1.44	1.90	mA	0 D: 11 1
Blank Level	0	с С	50	μΑ	Sync Disabled
Blank Level	6.29	7.62	8.96	mA	Sync Enabled
Sync Level	0	с С	50	μΑ	
I fi-Sync Level Relative to Blank	0.29	1.02	8.90	mA	
LSB Size		17.22	2	μΑ	
DAC to DAC Matching		1	3	% •	
Output Compliance, V <sub>OC</sub>	0	20	+1.4	V	
Output Impedance, R <sub>OUT</sub>		30	20	KΩ	
Output Capacitance, C <sub>OUT</sub>			30	рг	$I_{OUT} = 0 \text{ mA}$
VOLTAGE REFERENCE					
Voltage Reference Range, V <sub>REF</sub>	1.14	1.235	1.26	V	$V_{REF} = 1.235$ V for Specified Performance
Input Current, I <sub>VREF</sub>		5		μA	
POWER REQUIREMENTS					
V <sub>AA</sub>		5		V	
I <sub>AA</sub> <sup>3</sup>			475	mA	For 220 MHz Operation (ADV7160)
			440	mA	For 170 MHz Operation (ADV7160)
			410	mA	For 140 MHz Operation (ADV7160)
$I_{AA}^{3}$			450	mA	For 220 MHz Operation (ADV7162)
1111			400	mA	For 170 MHz Operation (ADV7162)
			360	mA	For 140 MHz Operation (ADV7162)
Power Supply Rejection Ratio		0.1		%/%	$COMP = 0.1 \mu F$
DYNAMIC PERFORMANCE					· ·
Clock and Data Feedthrough <sup>4, 5</sup>		_30		dB	
Glitch Impulse		- <u>50</u> 50		nV secs	
DAC to $DAC$ Crosstalle <sup>6</sup>		)0 )2		AB	
DAG to DAG GROSStalk		-23		uD	

NOTES <sup>1</sup>±5% for all versions. <sup>2</sup>Temperature range ( $T_{MIN}$  to  $T_{MAX}$ ): 0°C to +70°C. <sup>3</sup>Pixel Port is continuously clocked with data corresponding to a linear ramp.  $T_J = 100$ °C. <sup>4</sup>Clock and data feedthrough is a function of the amount of overshoot and undershoot on the digital inputs. Glitch impulse includes clock and data feedthrough. <sup>5</sup>TTL input values are 0 V to 3 V, with input rise/fall times ≤3 ns, measured the 10% and 90% points. Timing reference points at 50% for inputs and outputs.

<sup>6</sup>DAC to DAC Crosstalk is measured by holding one DAC high while the other two are making low to high and high to low transitions.

Specifications subject to change without notice.

 $\label{eq:timescale} \textbf{TIMING CHARACTERISTICS}^{1} \quad \begin{array}{l} (V_{AA}{}^2=+5 \ V; \ V_{REF}=+1.235 \ V; \ R_{SET}=280 \ \Omega. \ \ \text{IOR, IOG, IOB} \ (R_L=37.5 \ \Omega, \ C_L=10 \ \text{pF}). \ \ \text{All specifications $T_{MIN}$ to $T_{MAX}{}^3$ unless otherwise noted.)} \end{array}$ 

Parameter	220 MHz Version	170 MHz Version	140 MHz Version	Units	Conditions/Comments
f <sub>CLOCK</sub>	220	170	140	MHz max	Pixel CLOCK Rate
t <sub>1</sub>	4.5	5.88	7.14	ns min	Pixel CLOCK Cycle Time
t <sub>2</sub>	2.0	2.5	2.86	ns min	Pixel CLOCK High Time
t <sub>3</sub>	2.0	2.5	2.86	ns min	Pixel CLOCK Low Time
t <sub>4</sub>	10	10	10	ns max	Pixel CLOCK to LOADOUT Delay
f <sub>LOADIN</sub>					LOADIN Clocking Rate
2:1 Multiplexing	110	85	70	MHz max	
4:1 Multiplexing	55	42.5	35	MHz max	
8:1 Multiplexing	27.5	21.25	17.5	MHz max	
t <sub>5</sub>					LOADIN Cycle Time
2:1 Multiplexing	9.1	11.77	14.29	ns min	
4:1 Multiplexing	18.18	23.53	28.58	ns min	
8:1 Multiplexing	36.36	47.1	57.16	ns min	
t <sub>6</sub>					LOADIN High Time
2:1 Multiplexing	4	5	6	ns min	
4:1 Multiplexing	8	9	12	ns min	
8:1 Multiplexing	15	18	23	ns min	
t <sub>7</sub>					LOADIN Low Time
2:1 Multiplexing	4	5	6	ns min	
4:1 Multiplexing	8	9	12	ns min	
8:1 Multiplexing	15	18	23	ns min	
t <sub>8</sub>	0	0	0	ns min	Pixel Data Setup Time
t <sub>9</sub>	5	5	5	ns min	Pixel Data Hold Time
t <sub>10</sub>	0	0	0	ns min	LOADOUT to LOADIN Delay
$\tau - t_{11}^{5}$	τ-5	τ-5	τ-5	ns max	LOADOUT to LOADIN Delay
$t_{PD}^{6}$					Pipeline Delay
2:1 Multiplexing	9	9	9	CLOCKs	$(1 \times \text{CLOCK} = t_1)$
4:1 Multiplexing	11	11	11	CLOCKs	
8:1 Multiplexing	15	15	15	CLOCKs	
t <sub>12</sub>	10	10	10	ns max	Pixel CLOCK to PRGCKOUT Delay
t <sub>13</sub>	5	5	5	ns max	SCKIN to SCKOUT Delay
t <sub>14</sub>	5	5	5	ns min	BLANK to SCKIN Setup Time
t15	0	0	0	ns min	BLANK to SCKIN Hold Time

#### **CLOCK CONTROL AND PIXEL PORT<sup>4</sup>**

#### ANALOG OUTPUTS<sup>7</sup>

Parameter	220 MHz Version	170 MHz Version	140 MHz Version	Units	Conditions/Comments
t <sub>16</sub> t <sub>17</sub> t <sub>18</sub> t <sub>SK</sub>	25 1 25 2 0	25 1 25 2 0	25 1 25 2 0	ns typ ns typ ns typ ns max ns typ	Analog Output Delay Analog Output Rise/Fall Time Analog Output Transition Time RGB Analog Output Skew

#### MPU PORT<sup>8,9</sup>

Parameter	220 MHz Version	170 MHz Version	140 MHz Version	Units	Conditions/Comments
t <sub>19</sub>	0	0	0	ns min	$R/\overline{W}$ , C0, C1 to $\overline{CE}$ Setup Time
t <sub>20</sub>	10	10	10	ns min	$R/\overline{W}$ , C0, C1 to $\overline{CE}$ Hold Time
t <sub>21</sub>	45	45	45	ns min	CE Low Time
t <sub>22</sub>	25	25	25	ns min	CE High Time
$t_{23}^{8}$	5	5	5	ns min	$\overline{\text{CE}}$ Asserted to Data-Bus Driven
$t_{24}^{9}$	45	45	45	ns max	CE Asserted to Data Valid
$t_{25}^{9}$	20	20	20	ns max	CE Disabled to Data-Bus Three-Stated
$t_{26}^{9}$	5	5	5	ns min	CE Disabled to Data Invalid
t <sub>27</sub>	20	20	20	ns min	Write Data (D0–D9) Setup Time
t <sub>28</sub>	5	5	5	ns min	Write Data (D0–D9) Hold Time

NOTES

General Notes

<sup>1</sup>TTL input values are 0 to 3 volts, with input rise/fall times  $\leq$  3 ns, measured between the 10% and 90% points.

ECL inputs (CLOCK,  $\overline{\text{CLOCK}}$ ) are  $V_{AA}$ -0.8 V to  $V_{AA}$ -1.8 V, with input rise/fall times  $\leq 2$  ns, measured between the 10% and 90% points.

Timing reference points at 50% for inputs and outputs.

Analog output load  $\leq 10 \text{ pF}$ .

Data-Bus (D0-D9) loaded as shown in Figure 1.

Digital output load for LOADOUT, PRGCKOUT & SCKOUT ≤ 30 pF.

 $^{2}\pm5\%$  for all versions

<sup>3</sup>Temperature range ( $T_{MIN}$  to  $T_{MAX}$ ); 0°C to +70°C. Notes on PIXEL PORT

<sup>4</sup>Pixel Port consists of the following inputs:

Pixel Inputs: RED [A, B, C, D] GREEN [A, B, C, D] BLUE [A, B, C, D]

 Palette Selects:
 PS0 [A, B, C, D];
 PS1[A, B, C, D]

 Pixel Controls:
 SYNC, BLANK, TRISYNC, ODD/EVEN

 Clock Inputs:
 CLOCK, CLOCK, LOADIN, SCKIN

 Clock Outputs:
 LOADOUT, PRGCKOUT, SCKOUT

 ${}^{5}\tau$  is the LOADOUT Cycle Time and is a function of the Pixel CLOCK Rate and the Multiplexing Mode:

2:1 multiplexing;  $\tau = \text{CLOCK} \times 2$ =  $2 \times t_1$ ns

4:1 multiplexing;  $\tau = CLOCK \times 4$  $= 4 \times t_1$ ns

 $\tau = CLOCK \times 8$ 8:1 multiplexing;  $= 8 \times t_1$ ns

<sup>6</sup>These fixed values for Pipeline Delay are valid under conditions where t<sub>10</sub> and τ-t<sub>11</sub> are met. If either t<sub>10</sub> or τ-t<sub>11</sub> are not met, the part will operate but the Pipeline Delay is increased.

Notes on ANALOG OUTPUTS

<sup>7</sup>Output delay measured from the 50% point of the rising edge of CLOCK to the 50% point of full-scale transition.

Output rise/fall time measured between the 10% and 90% points of full-scale transition.

Transition time measured from the 50% point of full scale transition to the output remaining within 2% of the final output value. (Transition time does not include clock and data feedthrough).

Notes on MPU PORT

<sup>8</sup>t<sub>23</sub> and t<sub>24</sub> are measured with the load circuit of Figure 1 and defined as the time required for an output to cross 0.4 V or 2.4 V.

<sup>9</sup>t<sub>25</sub> and t<sub>26</sub> are derived from the measured time taken by the data outputs to change by 0.5 V when loaded with the circuit of Figure 1. The measured numbers are then extrapolated back to remove the effects of charging the 100 pF capacitor. This means that the times t<sub>25</sub> and t<sub>26</sub>, quoted in the Timing Characteristics are the true values for the device and as such are independent of external loading capacitances.

Specifications subject to change without notice.



Figure 1. Load Circuit for Databus Access and Relinquish Times

# $\label{eq:timescale} \textbf{TIMING CHARACTERISTICS (Cont.)}^1 \quad (V_{AA}{}^2 = +5 \text{ V}; \ V_{REF} = +1.235 \text{ V}; \ R_{SET} = 280 \ \Omega. \ \text{IOR, IOG, IOB (R}{}_{L} = 37.5 \ \Omega, \ C_{L} = 10 \ \text{pF}). \\ \text{All specifications T}_{\text{MIN}} \ \text{to T}_{\text{MAX}}{}^3 \ \text{unless otherwise noted.)}$

#### JTAG PORT

Parameter	All Versions	Units	Conditions/Comments
PLL PERFORMANCE <sup>4</sup>			
Jitter	250	ps rms	1σ
PLL REFERENCE INPUT			
PLL <sub>REF</sub> Frequency	900	kHz min	
	40	MHz max	
$V_{IH}$	2.0	V max	
V <sub>IL</sub>	0.8	V min	
PLL <sub>REF</sub> Period	25	ns min	
	1.67	µs max	
PLL <sub>REF</sub> Duty Cycle	40	% min	
	60	% max	
JTAG PERFORMANCE			
TCK Frequency, t <sub>29</sub>	20	MHz max	
TCK High Time, t <sub>30</sub>	15	ns min	
$\overline{\text{TCK}}$ Low Time, $t_{31}$	15	ns min	
TDI, TMS Setup Time, t <sub>32</sub>	15	ns max	
TDI, TMS Hold Time, t <sub>33</sub>	15	ns max	
Digital Input to $\overline{\text{TCK}}$ Setup Time, $t_{34}$	15	ns max	
Digital Input to TCK Hold Time, t <sub>35</sub>	15	ns max	
TCLK to TDO Drive, t <sub>36</sub>	0	ns min	
TCLK to TDO Valid, t <sub>37</sub>	20	ns min	
TCLK to TDO Three-State, t <sub>38</sub>	5	ns min	
	15	ns max	

NOTES  $^{1}$ TTL input values are 0 to 3 volts, with input rise/fall times  $\leq$  3 ns, measured between the 10% and 90% points. Timing reference points at 50% for inputs and outputs.  $^{2}\pm5\%$  for all versions.

<sup>3</sup>Temperature range ( $T_{MIN}$  to  $T_{MAX}$ ); 0°C to +70°C. <sup>4</sup>Jitter is measured by triggering on the output clock, delayed by 15 µs and then measuring the time period from the trigger edge to the next edge of the output clock after the delay. This measurement is repeated multiple times and the RMS value is determined.

Specifications subject to change without notice.



Figure 2. JTAG Timing

## **Timing Waveforms**



Figure 3. LOADOUT vs. Pixel Clock Input (CLOCK, CLOCK)



Figure 4. LOADIN vs. Pixel Input Data



Figure 5. Pixel Input to Analog Output Pipeline with Minimum LOADOUT to LOADIN Delay (8:1 Multiplex Mode)



Figure 6. Pixel Input to Analog Output Pipeline with Maximum LOADOUT to LOADIN Delay (8:1 Multiplex Mode)



Figure 7. Pixel Input to Analog Output Pipeline with Minimum LOADOUT to LOADIN Delay (4:1 Multiplex Mode)

![](_page_7_Figure_3.jpeg)

Figure 8. Pixel Input to Analog Output Pipeline with Maximum LOADOUT to LOADIN Delay (4:1 Multiplex Mode)

![](_page_8_Figure_1.jpeg)

Figure 9. Pixel Input to Analog Output Pipeline with Minimum LOADOUT to LOADIN Delay (2:1 Multiplex Mode)

![](_page_8_Figure_3.jpeg)

Figure 10. Pixel Input to Analog Output Pipeline with Maximum LOADOUT to LOADIN Delay (2:1 Multiplex Mode)

![](_page_9_Figure_1.jpeg)

Figure 11. Pixel Clock Input vs. Programmable Clock Output (PRGCKOUT)

![](_page_9_Figure_3.jpeg)

Figure 12. Video Data Shift Clock Input (SCKIN) & BLANK vs. Video Data Shift Clock Output (SCKOUT)

![](_page_9_Figure_5.jpeg)

Figure 13. Analog Output Response vs. CLOCK

![](_page_10_Figure_1.jpeg)

Figure 14. Microprocessor Port (MPU) Interface Timing

#### ABSOLUTE MAXIMUM RATINGS<sup>1</sup>

V <sub>AA</sub> to GND	V
Voltage on Any Digital Pin $\ldots$ GND – 0.5 V to V <sub>AA</sub> + 0.5	V
Ambient Operating Temperature $(T_A) \dots 0^{\circ}C$ to $+70^{\circ}$	Ъ
Storage Temperature $(T_S)$ 65°C to +150°	Ъ
Junction Temperature (T <sub>J</sub> ) +150°	Ъ
Lead Temperature (Soldering, 10 secs) +260°	Ъ
Vapor Phase Soldering (1 minute) +220°	Ъ
Analog Outputs to $\text{GND}^2$ $\text{GND} - 0.5 \text{ V}$ to V	AA

#### NOTES

<sup>1</sup>Stresses above those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those listed in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability. <sup>2</sup>Analog Output Short Circuit to any Power Supply or Common can be of an indefinite duration.

#### **ORDERING INFORMATION<sup>1, 2, 3</sup>**

Dot Clock Speed							
220 MHz	170 MHz	140 MHz					
ADV7160KS220 <sup>3</sup> ADV7162KS220 <sup>4</sup>	ADV7160KS170 <sup>3</sup> ADV7162KS170 <sup>4</sup>	ADV7160KS140 <sup>3</sup> ADV7162KS140 <sup>4</sup>					

NOTES

<sup>1</sup>All devices are specified for 0°C to +70°C operation.

<sup>2</sup>Contact Sales Office for latest information on package design.

<sup>3</sup>ADV7160 is packaged in a 160-pin plastic power quad flatpack, QFP with heatsink embedded.

<sup>4</sup>ADV7162 is packaged in a standard 160-pin plastic quad flatpack, QFP.

#### CAUTION

ESD (electrostatic discharge) sensitive device. Electrostatic charges as high as 4000 V readily accumulate on the human body and test equipment and can discharge without detection. Although the ADV7160/ADV7162 features proprietary ESD protection circuitry, permanent damage may occur on devices subjected to high energy electrostatic discharges. Therefore, proper ESD precautions are recommended to avoid performance degradation or loss of functionality.

![](_page_10_Picture_16.jpeg)

#### 160-Lead QFP Configuration

![](_page_10_Figure_18.jpeg)

Pin No.	Mnemonic	Pin No.	Mnemonic	Pin No.	Mnemonic	Pin No.	Mnemonic
1	G2 <sub>A</sub>	41	CLOCK	81	D9	121	R1 <sub>C</sub>
2	G2 <sub>B</sub>	42	SCKIN	82	D8	122	R1 <sub>D</sub>
3	G2 <sub>C</sub>	43	SCKOUT	83	D7	123	R2 <sub>A</sub>
4	G2 <sub>D</sub>	44	$V_{AA}$	84	D6	124	R2 <sub>B</sub>
5	G3 <sub>A</sub>	45	PRGCKOUT	85	D5	125	R2 <sub>C</sub>
6	G3 <sub>B</sub>	46	GND	86	D4	126	R2 <sub>D</sub>
7	G3 <sub>C</sub>	47	LOADOUT	87	D3	127	R3 <sub>A</sub>
8	G3 <sub>D</sub>	48	LOADIN	88	D2	128	R3 <sub>B</sub>
9	G4 <sub>A</sub>	49	$B0_A$	89	D1	129	R3 <sub>C</sub>
10	G4 <sub>B</sub>	50	B0 <sub>B</sub>	90	D0	130	R3 <sub>D</sub>
11	G4 <sub>C</sub>	51	$B0_{C}$	91	C1	131	R4 <sub>A</sub>
12	G4 <sub>D</sub>	52	B0 <sub>D</sub>	92	C0	132	V <sub>AA</sub>
13	G5 <sub>A</sub>	53	B1 <sub>A</sub>	93	$R/\overline{W}$	133	V <sub>AA</sub>
14	G5 <sub>B</sub>	54	B1 <sub>B</sub>	94	CE	134	GND
15	G5 <sub>C</sub>	55	B1 <sub>C</sub>	95	TCK	135	GND
16	G5 <sub>D</sub>	56	B1 <sub>D</sub>	96	TMS	136	R4 <sub>B</sub>
17	G6 <sub>A</sub>	57	B2 <sub>A</sub>	97	GND	137	R4 <sub>C</sub>
18	G6 <sub>B</sub>	58	B2 <sub>B</sub>	98	V <sub>AA</sub>	138	R4 <sub>D</sub>
19	G6 <sub>C</sub>	59	B2 <sub>C</sub>	99	TDO	139	R5 <sub>A</sub>
20	G6 <sub>D</sub>	60	B2 <sub>D</sub>	100	TDI	140	R5 <sub>B</sub>
21	G7 <sub>A</sub>	61	B3 <sub>A</sub>	101	SYNCOUT	141	R5 <sub>C</sub>
22	V <sub>AA</sub>	62	B3 <sub>B</sub>	102	TRISYNC	142	R5 <sub>D</sub>
23	V <sub>AA</sub>	63	B3 <sub>C</sub>	103	ODD/EVEN	143	R6 <sub>A</sub>
24	GND	64	B3 <sub>D</sub>	104	SYNC	144	R6 <sub>B</sub>
25	GND	65	$B4_A$	105	BLANK	145	R6 <sub>C</sub>
26	V <sub>AA</sub>	66	$B4_B$	106	V <sub>REF</sub>	146	R6 <sub>D</sub>
27	GND	67	$B4_{C}$	107	IOB	147	R7 <sub>A</sub>
28	PLL <sub>REF</sub>	68	$B4_D$	108	COMP	148	R7 <sub>B</sub>
29	G7 <sub>B</sub>	69	B5 <sub>A</sub>	109	R <sub>SET</sub>	149	R7 <sub>C</sub>
30	G7 <sub>C</sub>	70	$B5_B$	110	V <sub>AA</sub>	150	GND
31	G7 <sub>D</sub>	71	B5 <sub>C</sub>	111	V <sub>AA</sub>	151	V <sub>AA</sub>
32	PS0 <sub>A</sub>	72	B5 <sub>D</sub>	112	GND	152	R7 <sub>D</sub>
33	PS0 <sub>B</sub>	73	B6 <sub>A</sub>	113	IOG	153	G0 <sub>A</sub>
34	PS0 <sub>C</sub>	74	B6 <sub>B</sub>	114	IOR	154	G0 <sub>B</sub>
35	PS0 <sub>D</sub>	75	B6 <sub>C</sub>	115	R0 <sub>A</sub>	155	G0 <sub>C</sub>
36	PS1 <sub>A</sub>	76	$B6_D$	116	R0 <sub>B</sub>	156	G0 <sub>D</sub>
37	PS1 <sub>B</sub>	77	B7 <sub>A</sub>	117	R0 <sub>C</sub>	157	G1 <sub>A</sub>
38	PS1 <sub>C</sub>	78	$B7_B$	118	R0 <sub>D</sub>	158	G1 <sub>B</sub>
39	PS1 <sub>D</sub>	79	B7 <sub>C</sub>	119	R1 <sub>A</sub>	159	G1 <sub>C</sub>
40	CLOCK	80	B7 <sub>D</sub>	120	R1 <sub>B</sub>	160	G1 <sub>D</sub>

#### ADV7160/ADV7162 PIN ASSIGNMENTS

#### PIN FUNCTION DESCRIPTION

Mnemonic	Function				
$\overline{\text{RED}} \ (\text{R0}_{\text{A}} \dots \text{R0}_{\text{B}} - \text{R7}_{\text{A}} \dots$	R7 <sub>D</sub> ), GREEN $(G0_A \dots G0_D - G7_A \dots G7_D)$ , BLUE $(B0_A \dots B0_D - B7_A \dots B7_D)$ : Pixel Port (TTL Compatible Inputs): 96 pixel select inputs, with 8 bits each for Red, Green and Blue. Each bit is multiplexed [A-D] 4:1 or 2:1. It can be configured for 24-Bit True-Color Data, 8-Bit Pseudo-Color Data, 16-Bit True-Color and 15-Bit True-Color Data formats. In 8-Bit Pseudo-Color Mode, there is a special case whereby 8:1 multiplexing is also available. It will be explained in more detail later. Pixel Data is latched into the device on the rising edge of LOADIN.				
$PS0_A \dots PS0_D$ , $PS1_A \dots PS$	<sup>1</sup> <sub>D</sub> Palette Priority Selects (TTL Compatible Inputs): The eight PS inputs provide two Bits after input multiplexing. These pixel port select inputs can be configured for three separate functions. In Overlay Mode, these inputs provide a three color overlay function. With any value other than "00" on the overlay inputs, the color displayed comes from the overlay palette instead of the main pixel inputs. For the ADV7160, in Bypass Mode, PS1 specifies for each pixel whether it should pass through the Color Matrix and Color Palette or bypass the Matrix and Palette. PS0 acts as an overlay input. (This mode is not available for the ADV7162.) Palette Select Mode is used to multiplex the RGB outputs of a number of devices. When the palette mode inputs match the PS bits in the mode register, the part operates as normal. When there is a mismatch, the RGB outputs are switched to zero, allowing the RGB outputs of another device to drive the monitor.				
LOADIN	Pixel Data Load Input (TTL Compatible Input): This input latches the multiplexed pixel data, in- cluding PS0-PS1, BLANK, TRISYNC, SYNC and ODD/EVEN into the device.				
LOADOUT	Pixel Data Load Output (TTL Compatible Output): This output control signal runs at a divided down frequency of the pixel clock. Its frequency is a function of the multiplex rate. It can be used to directly or indirectly drive LOADIN. $f_{LOADOUT} = f_{CLOCK}/M$ where				
	(M = 2 for 2:1 Multiplex Mode) (M = 4 for 4:1 Multiplex Mode) (M = 8 for 8:1 Multiplex Mode)				
PRGCKOUT	Programmable Clock Output (TTL Compatible Output): This output control signal runs at a divided down frequency of the pixel Clock. Its frequency is user programmable and is determined by bits CR30 and CR31 of Command Register 3. $f_{PRGCKOUT} = f_{CLOCK}/N$ where N = 4, 8, 16 & 32				
SCKIN	Video Shift Clock Input (TTL Compatible Input): The signal on this input is internally gated synchronously with the BLANK signal. The resultant output, SCKOUT, is a video clocking signal that is stopped during video blanking periods. It is normally driven by a divided down version of the CLOCK frequency.				
SCKOUT	Video Shift Clock Output (TTL Compatible Output): This output is a synchronously gated version of SCKIN and BLANK. SCKOUT is a video clocking signal that is stopped during video blanking periods.				
CLOCK, <u>CLOCK</u>	Clock Inputs (ECL Compatible Inputs): These differential clock inputs are designed to be driven by ECL logic levels configured for single supply (+5 V) operation. The clock rate is normally the pixel clock rate of the system.				
PLL <sub>REF</sub>	PLL Clock Input (TTL Compatible Input): This clock input is designed to be driven by TTL logic levels. The PLL is then configured to output a specific frequency depending on the PLL Registers. See PLL section for more detail.				
BLANK	Composite Blank (TTL Compatible Input): This video control signal drives the analog outputs to the blanking level.				
SYNC	Composite-Sync Input (TTL Compatible Input): This video control signal drives any of the analog outputs to the SYNC level. It is only asserted during the blanking period. CR22 in Command Register 2 must be set if SYNC is to be decoded onto the IOG analog output, CR41 in Command Register 4 must be set if SYNC is to be decoded onto the IOR analog output, CR42 in Command Register 4 must be set if SYNC is to be decoded onto the IOB analog output, otherwise the SYNC input is ignored.				

Mnemonic	Function	Function							
SYNCOUT	$\frac{\text{Composite-Sy}}{\text{SYNC}}$ . The c	Composite-Sync Output (TTL Compatible Output). This video output is a delayed version of $\overline{SYNC}$ . The delay corresponds to the number of pipeline stages of the device.							
TRISYNC	Composite-Sy CR17 in Con goes to the tri-	Composite-Sync HDTV Control (TTL Compatible Output). This video input is enabled using Bit CR17 in Command Register 1. When TRISYNC is low, any DAC output which has Sync enabled, goes to the tri-sync level. As with the SYNC input, it should only be activated while BLANK is low.							
D9–D0	Data Bus (TT trol informatic data or 8-bit c data (8+2) as through a resis	Data Bus (TTL Compatible Input/Output Bus). Data, including color palette values and device con- trol information is written to and read from the device over this 10-bit, bidirectional databus. 10-bit data or 8-bit data can be used. The databus can be configured for either 10-bit parallel data or byte data (8+2) as well as standard 8-bit data. Any unused bits of the data bus should be terminated through a resistor to either the digital power plane ( $V_{CC}$ ) or GND.							
ODD/EVEN	Odd/Even Co displayed. It i laced display r should change an even field a	Odd/Even Control (TTL Compatible Input). This input indicates which field of the frame is being displayed. It is required to ensure proper operation of the ADV7160/ADV7162 cursor when inter- laced display mode is selected. It is ignored when noninterlaced display mode is selected. This input should change only during the vertical blank period. It is assumed that an odd field will always follow an even field and vice versa							
CE	Chip Enable ( from the devic	TTL Con	npatible Input). This input must be at e data bus (D0–D9). Internally, data is	Logic "0" when y s latched on the r	writing to or reading ising edge of $\overline{CE}$ .				
$R/\overline{W}$	Read/Write Corread from the data to the part	Read/Write Control (TTL Compatible Input). This input determines whether data is written to or read from the device's registers and color palette RAM. $R/\overline{W}$ and $\overline{CE}$ must be at Logic "0" to write data to the part. $R/\overline{W}$ must be at Logic "1" and $\overline{CE}$ at Logic "0" to read from the device.							
C0, C1	Command Co eration being p inputs is latch	Command Controls (TTL Compatible Inputs). These inputs determine the type of read or write operation being performed on the device over the data bus, (see Interface Truth Table). Data on these inputs is latched on the falling edge of $\overline{CE}$ .							
IOR, IOG, IOB	Red, Green & are specified to	Red, Green & Blue Current Outputs (High Impedance Current Sources). These RGB video outputs are specified to directly drive RS-343A and RS-170 video levels into doubly terminated 75 $\Omega$ loads.							
V <sub>REF</sub>	Voltage Refere this input. Ar recommended	Voltage Reference Input (Analog Input): An external 1.235 V voltage reference is required to drive this input. An AD589 (2-terminal voltage reference) or equivalent is recommended. (Note: It is not recommended to use a resistor network to generate the voltage reference.)							
R <sub>SET</sub>	Output Full S ground contro 280 $\Omega$ , with 3' Gain as shown	cale Adju ols the abs 7.5 $\Omega$ terr n, the requ	st Control (Analog Input). A resistor colute amplitude of the output video signination and using CR43 and CR44 of uired Video Standard can be achieved.	connected betwee mal. For a value Command Regis	on this pin and analog of $R_{SET}$ of nominally ster 4 to set the DAC				
	<b>CR44</b> 0 0 1 1	<b>CR43</b> 0 1 0 1	Video Standard RS343A, Sync & Pedestal RS343A, Sync & No Pedestal RS343A, No Sync & No Pedestal RS170, Sync & Pedestal	DAC Gain 3996 4224 4311 5592	<b>Black to White</b> 660 mV 17.62 mA 699 mV 18.63 mA 714 mV 19.05 mA 925 mV 24.67 mA				
	Alternatively,	R <sub>SET</sub> can	be calculated by the following equation	1:					
	$R_{SET} rac{DAC \; Gain  imes V_{REF}}{Black \; to \; White \; Current}$								
COMP	Compensatior	Pin. A	$0.1 \ \mu F$ capacitor should be connected b	etween this pin a	nd V <sub>AA</sub> .				
$V_{AA}$	Power Supply together to on	(+5 V± e commo	5%). The part contains multiple power n +5 V filtered analog power supply.	er supply pins, all	should be connected				
GND:	Analog Groun system's groun	d. The p nd plane.	art contains multiple ground pins, all	should be connec	eted together to the				
TMS, TCK, TDI, TDO	These four pir See Appendix	ns control 6 for mo	the JTAG test access port. re detail						

#### (Continued from page 1)

The ADV7160/ADV7162 integrates a number of graphic functions onto one device allowing 24-bit direct True-Color (30-bit Corrected-Color) operation at the maximum screen resolution of 1600 × 1280 at a refresh rate of 85 Hz. The ADV7160/ ADV7162 integrates a 256 × 30 Color Palette RAM with three high speed, 10-bit, digital-to analog converters (RGB DACs). It also contains a user-definable, X-Windows compatible,  $64 \times$  $64 \times 2$  cursor generator and associated RAM. An on-board Overlay Palette RAM is also included. The device's 96-bit Programmable Pixel Port enables various data formats to be input to the part. An on-board clock and synchronization circuit controls all clocking functions for both the part and graphics subsystem.

There are two video data paths through the ADV7160/ADV7162. One routes the data from the pixel port through the RAM to the DACs, the other bypasses the RAM and routes data direct from the pixel port to the DACs. Either path can be selected on a pixel by pixel basis. This allows for the overlay of an active video window on a graphics background.

The on-board palette priority select inputs enable multiple palette devices to be connected together for use in multipalette and window applications. The part is controlled and programmed through the microprocessor (MPU) port. The 30 bits of resolution, associated with the color look-up table and triple 10-bit DAC, realizes 24-bit True-Color resolution, while also allowing for the on-board implementation of linearization algorithms, such as Gamma-Correction and Monitor Callibration. This allows effective 30-bit True-Color operation.

The on-chip video clock controller circuit generates all the internal clocking and some additional external clocking signals. The high accuracy, low jitter on board PLL eliminates the need for an external high speed clock generator. The PLL can be programmed to produce a pixel clock that is a multiple of the PLL reference clock.

The ADV7162 is packaged in a standard plastic 160-pin quad flatpack (QFP).

The ADV7160 is packaged in a plastic 160-pin power quad flatpack (PQUAD). Superior thermal distribution is achieved by the inclusion of a copper heatslug, within the standard package outline, to which the die is attached. This part is ideally suited for high performance applications where external environmental conditions are unpredictable and uncontrollable.

### CIRCUIT DETAILS AND OPERATION

#### **OVERVIEW**

Digital video or pixel data is latched into the ADV7160/ADV7162 over the devices Pixel Port. This data acts as a pointer to onboard Color Palette RAM. The data at the RAM address pointed to is latched to the digital-to-analog converters (DACs) and output as an RGB analog video signal.

For the purposes of clarity of description, the ADV7160/ADV7162 is broken down into three separate functional blocks. These are:

- 1. Pixel Port and Clock Control Circuit
- 2. MPU Port, Registers and Color Palette

3. Digital-to-Analog Converters and Video Outputs

#### Pixel Port & Clock Control Circuit

The Pixel Port of the ADV7160/ADV7162 is directly interfaced to the video/graphics pipeline of a computer graphics subsystem. It is connected directly or through a gate array to the video RAM of the systems Frame-Buffer (video memory). The pixel port on the device consists of:

Color Data	RED, GREEN, BLUE
Pixel Controls	<u>SYNC, BLANK, TRISYNC</u>
Palette Selects	$PS0_{A-D}$ , $PS1_{A-D}$

The associated clocking signals for the pixel port include:

Clock Inputs	CLOCK, $\overline{\text{CLOCK}}$ , $\text{PLL}_{\text{REF}}$ ,
	LOADIN, SCKIN
Clock Outputs	LOADOUT, PRGCKOUT,
	SCKOUT

These on-board clock control signals are included to simplify interfacing between the part and the frame buffer. Either two control input signals CLOCK and  $\overline{\text{CLOCK}}$  (ECL Levels) or

one TTL input signal  $PLL_{REF}$  are required to get the part operational. No additional signals or external glue logic are required to get the Pixel Port and Clock Control Circuit of the part operational.

![](_page_14_Figure_23.jpeg)

![](_page_14_Figure_24.jpeg)

#### Pixel Port (Color Data)

The ADV7160/ADV7162 has 96 color data inputs. The part has four (for 4:1 multiplexing) 24-bit wide direct color data inputs. These are user programmed to support a number of color data formats including 24-bit True-Color, 16-bit True-Color, 15-bit True-Color in 4:1 and 2:1 multiplex modes, and 8-bit Pseudo-Color (see "Multiplexing" section) in 8:1, 4:1 and 2:1 multiplex modes.

Color data is latched into the parts pixel port on every rising edge of LOADIN (see Timing Waveform, Figure 4). The required frequency of LOADIN is determined by the multiplex rate, where  $f_{LOADIN} = f_{CLOCK}/8$  8:1 multiplex mode

$f_{LOADIN} = f_{CLOCK}/8$	8:1 multiplex mode
$f_{LOADIN} = f_{CLOCK}/4$	4:1 multiplex mode
$f_{LOADIN} = f_{CLOCK}/2$	2:1 multiplex mode

Other pixel data signals latched into the device by LOADIN include  $\overline{SYNC}$ ,  $\overline{BLANK}$ ,  $\overline{TRISYNC}$  and  $PSO_{A-D} - PS1_{A-D}$ .

Internally, data is pipelined through the part by the differential pixel clock inputs, CLOCK and CLOCK or by the internal pixel clock generated by the PLL on-board. The LOADIN control signal need only have a frequency synchronous relationship to the pixel CLOCK (see "Pipeline Delay & On-Board Calibration" section). A completely phase independent LOADIN signal can be used with the ADV7160/ADV7162, allowing the CLOCK to occur anywhere during the LOADIN cycle.

Alternatively, the LOADOUT signal of the ADV7160/ADV7162 can be used. LOADOUT can be connected either directly or indirectly to LOADIN. Its frequency is automatically set to the correct LOADIN requirement.

#### **SYNC**, **BLANK**

The BLANK and SYNC video control signals drive the analog outputs to the Blank and Sync levels respectively. These signals are latched into the part on the rising edge of LOADIN. The SYNC information is encoded onto the IOG analog signal when Bit CR22 of Command Register 2 is set to "1," the IOR analog signal when Bit CR41 of Command Register 4 is set to "1" and the IOB analog signal when Bit CR42 of Command Register 4 is set to "1." The SYNC input is ignored if CR22, CR41 and CR42 are set to logic "0."

#### **SYNCOUT**

In some applications where it is not permissible to encode <u>SYNC</u> on green (IOG), blue (IOB), or red (IOR), <u>SYNCOUT</u> can be used as a separate TTL digital <u>SYNC</u> output. This has the advantage over an independent (of the ADV7160/ADV7162) <u>SYNC</u> in that it does not necessitate knowing the absolute pipeline delay of the part. This allows complete independence between LOADIN/Pixel Data and CLOCK. The <u>SYNC</u> input is connected to the device as normal with Bit CR22 of Command Register 2, Bit CR41 of Command Register 4 and Bit <u>CR42</u> of Command Register 4 are set to "0" thereby preventing <u>SYNC</u> from being encoded <u>onto IOG</u>, IOR and IOB. The output signal generates a TTL <u>SYNCOUT</u> with correct pipeline delay which is capable of directly driving the composite <u>SYNC</u> signal of a computer monitor.

#### TRISYNC

This input is used to generate a HDTV Sync on any of the DAC outputs. Bit CR17 of Command Register 1 is set to "1", enabling TRISYNC. When TRISYNC is low, the analog output which has Sync enabled goes to the tri-sync level.

#### PS0<sub>A-D</sub>-PS1<sub>A-D</sub> (Palette Priority Select Inputs)

These multifunctional TTL compatible inputs can be configured for three separate functions. The eight PS inputs are multiplexed to provide two bits which are used to provide one of three different functions. The function is selected by Bit CR14 and Bit CR15 of Command Register 1.

CR15	CR14	Color Mode
0	0	Palette Select Mode
0	1	Bypass Mode Control (ADV7160 Only)
1	0	Overlay Color Mode
1	1	Ignore PS Inputs

However, in 8:1 Mode, for 8-Bit Pseudo Color, the unused Blue Pixel Inputs are used to provide 8 extra PS inputs. The bypass mode is unavailable in this case.

#### Palette Select Mode

These pixel port select inputs effectively determine whether the devices RGB analog outputs are turned-on or shut down. When the analog outputs are shut down, IOR, IOG and IOB are forced to 0 mA regardless of the state of the pixel and control data inputs. This state is determined on a pixel by pixel basis as the PS0–PS1 inputs are multiplexed in exactly the same format as the pixel port color data. These controls allow for switching between multiple palette devices. If the values of PS0 and PS1 match the values programmed into bits MR16 and MR17 of the Mode Register, then the device is selected, if there is no match the device is effectively shut down.

#### Bypass Mode Control (ADV7160 Only)

In this mode PS1 is used to switch between one of the color modes through the Color Palette and one of the Palette Bypass modes on a pixel by pixel basis. The color mode through the palette is selected using Bits CR27–CR24 of Command Register 2. The Bypass Color Mode is selected using Bits CR17 and CR16 of Command Register 1. PS1 then switches between the Palette Color Mode, and the Bypass Color Mode. The PS0 input continues to act as an overlay input, allowing Overlay Color 1 to be displayed.

PS0	PS1	Color Mode
0	0	Palette Color Mode (CR27–CR24)
0	1	Bypass Color Mode (CR17-CR16)
1	х	Overlay Color 1

This mode is not available if using the ADV7162.

#### **Overlay Color Mode**

In this mode, the PS inputs provide control for a three color overlay. Whenever the value other than "00" is placed on the overlay inputs, the corresponding overlay color is displayed. When the overlay inputs contain "00" the color is specified by the main pixel inputs.

#### CLOCK CONTROL CIRCUIT

The ADV7160/ADV7162 has an integrated Clock Control Circuit (Figure 16). This circuit is capable of both generating the ADV7160/ADV7162's internal clocking signals as well as external graphics subsystem clocking signals. Total system synchronization can be attained by using the parts output clocking signals to drive the controlling graphics processor's master clock as well as the video frame buffers shift clock signals.

#### CLOCK, CLOCK Inputs

The Clock Control Circuit is driven by the pixel clock inputs, CLOCK and  $\overline{\text{CLOCK}}$ . These inputs can be driven by a differential ECL oscillator running from a +5 V supply.

![](_page_16_Figure_0.jpeg)

*Figure 16. Clock Control Circuit of the ADV7160/ADV7162* 

## CLOCK CONTROL SIGNALS LOADOUT

The ADV7160/ADV7162 generates a LOADOUT control signal which runs at a divided down frequency of the pixel CLOCK. The frequency is automatically set to the programmed multiplex rate, controlled by CR37 and CR36 of Command Register 3.

$f_{LOADOUT} = f_{CLOCK}/8$	8:1 multiplex mode
$f_{LOADOUT} = f_{CLOCK}/4$	4:1 multiplex mode
$f_{LOADOUT} = f_{CLOCK}/2$	2:1 multiplex mode

The LOADOUT signal is used to directly drive the LOADIN pixel latch signal of the ADV7160/ADV7162. This is most simply achieved by tying the LOADOUT and LOADIN pins together. Alternatively, the LOADOUT signal can be used to drive the frame buffer's shift clock signals, returning to the LOADIN input delayed with respect to LOADOUT.

If it is not necessary to have a known fixed number of pipeline delays, then there is no limitation on the delay between LOADOUT and LOADIN (LOADOUT(1) and LOADOUT(2)). LOADIN and Pixel Data must conform to the setup and hold times ( $t_8$  and  $t_9$ ).

If however, it is required that the ADV7160/ADV7162 has a fixed number of pipeline delays ( $t_{PD}$ ) LOADOUT and LOADIN must conform to timing specifications  $t_{10}$  and  $\tau$ - $t_{11}$  as illustrated in Figures 5 to 10.

### ADV7160/ADV7162

![](_page_16_Figure_9.jpeg)

#### Figure 17. LOADOOUT vs Pixel Clock

#### Pipeline Delay and Onboard Calibration

The ADV7160/ADV7162 has a fixed number of pipeline delays ( $t_{PD}$ ), so long as timings  $t_{10}$  and  $\tau$ - $t_{11}$  are met. However, if a fixed number of pipeline delays is not a requirement, timings  $t_{10}$  and  $\tau$ - $t_{11}$  can be ignored, a calibration cycle must be run and there is no restriction on LOADIN to LOADOUT timing. If timings  $t_{10}$  and  $\tau$ - $t_{11}$  are not met, the part will function correctly though with an increased number of pipeline delays. The ADV7160/ADV7162 has on-board calibration circuitry which synchronizes pixel data and LOADIN with the internal ADV7160/ADV7162 clocking signals. Calibration can be performed in two ways. During the device's initialization sequence by toggling two bits of the Mode Register, MR10 followed by MR15 or by writing a "1" to Bit CR10 of Command Register 1 and a "0" to MR15 which executes a calibration on every Vertical Sync.

#### PRGCKOUT

The PRGCKOUT control signal outputs a user programmable clock frequency. It is a divided down frequency of the pixel CLOCK (see Figure 11). The rising edge of PRGCKOUT is synchronous to the rising edge of LOADOUT.

$$f_{PRGCKOUT} = f_{CLOCK}/N$$

where N = 4, 8, 16 or 32.

One application of the PRGCKOUT is to use it as the master clock frequency of the graphics subsystems processor or controller.

#### SCKIN, SCKOUT

These video memory signals are used to minimize external support chips. Figure 18 illustrates the function that is provided. An input signal applied to SCKIN is synchronously AND-ed with the video blanking signal ( $\overline{BLANK}$ ). The resulting signal is output on SCKOUT. Figure 12 of the Timing Waveform section shows the relationship between SCKOUT, SCKIN and  $\overline{BLANK}$ .

![](_page_16_Figure_20.jpeg)

Figure 18. SCKOUT Generation Circuit

The SCKOUT signal is essentially the video memory shift control signal. It is stopped during the screen retrace. Figure 19 shows a suggested frame buffer to ADV7160/ADV7162 interface. This is a minimum chip solution and allows the ADV7160/ADV7162 control the overall graphics system clocking and synchronization.

![](_page_17_Figure_2.jpeg)

Figure 19. ADV7160/ADV7162 Interface Using SCKIN and SCKOUT

#### PLL

The on-board PLL can be used as an alternative clock source. This eliminates the need for an external high speed clock generator such as a crystal oscillator. With the PLL, it is possible to generate an internal clock whose frequency is a multiple of the PLL reference frequency (PLL<sub>REF</sub>). Internal PLL operation is selected by setting CR56 of Command Register 5 to Logic "1." The PLL registers can be programmed to set up the frequency required.

The block diagram of the Phase Locked Loop is shown in Figure 20. The blocks consist of a phase frequency detector, a charge pump, a loop filter, a voltage controlled oscillator and a programmable divider.

![](_page_17_Figure_7.jpeg)

#### Figure 20. PLL Block Diagram

The phase frequency detector drives the voltage controlled oscillator (VCO), to a frequency that will cause the two inputs to the phase frequency detector to be matched in frequency and phase. The corresponding output of the VCO can be calculated as:

#### $VCO = PLL_{REF}$ <u>Feedback Divider</u> Reference Divider

The Reference Divider is set by a combination of the contents of the PLL R Register and the RSEL bit. The PLL R Register has a resolution of 7 bits. It is programmed by setting the PLL R Register located at Control Register address 00CH. The PLL R Register can be set from 01H to 7FH. It should not be set to 00H. If this register contains 00H, then the PLL stops. Therefore, the Reference Divider can be set from 3 to 129 in steps of one, or from 130 to 258 in steps of two by setting the RSEL bit. The RSEL bit is accessed by changing Bit PCR1 of the PLL Control Register. The Feedback Divider is set by a combination of the contents of the PLL V Register, the VSEL bit and the S value. The S value is set up in PCR7 and PCR6 of the PLL Command Register. This S value allows a better resolution when setting the Feedback Divider value. The PLL V Register has a resolution of 7 bits. It is programmed by setting the PLL V Register located at Control Register address 00FH .The

PLL V Register can be set from 01H to 7FH. It should not be set to 00H. If this register contains 00H, then the PLL stops. Therefore the feedback divider can be set from 12 to 519 in steps of one, or from 520 to 1038 in steps of two by setting the VSEL bit. The VSEL bit is accessed by changing bit PCR2 of the PLL Control Register. The P counter divides the output from the oscillator by 1, 2, 4 or 8 as determined by PSEL1 and PSEL0 which are set in bits PCR5 and PCR4 of the PLL Control Register. This post-scaler is useful in the generation of lower frequencies as the VCO has been optimized for high frequency operation.

![](_page_17_Figure_13.jpeg)

Figure 21. PLL Transfer Function

The transfer function of the PLL can be summarized by the block diagram shown in Figure 21.

To optimize the performance of the on-board PLL, the following criteria should be followed:

900 kHz	$< PLL_{REF}$	< 40 MHz
300 kHz	$< F_{PD}$	< 10 MHz
120 MHz	$< F_{VCO}$	< 260 MHz

For  $F_{VCO}$  > 220 MHz,  $V_{SEL}$  should be programmed to logic "0."

Any lower frequency output can be achieved by using the output divider.

A jitter performance graph as a function of both  $F_{PD}$  and  $F_{VCO}$  is illustrated in Figure 22. It can be seen that jitter decreases with increasing  $F_{VCO}$  and also that jitter decreases with increasing  $F_{PD}$ . For each  $F_{OUT}$ , the user should firstly maximize  $F_{VCO}$  using the output divider and then pick PLL<sub>REF</sub> and reference divide to maximize FPD. When generating multiple output frequencies from one PLL<sub>REF</sub> value, an iterative process should be used to find the PLL<sub>REF</sub> value that gives the best trade off between jitter performance and  $F_{OUT}$  accuracy.

![](_page_17_Figure_21.jpeg)

Figure 22. PLL Jitter

#### **COLOR VIDEO MODES**

The ADV7160/ADV7162 supports a number of color video modes all at the maximum video rate.

Command bits CR27–CR24 of Command Register 2 along with bit MR11 of Mode Register 1 determine the color mode. Seven color modes use the Color Palette, and three of them bypass the palette and control the DACs directly.

#### 24-Bit True Color

#### (CR27, CR26, CR25, CR24 = 1, 1, 1, 0)

The part is set to 24-bit/30-bit "Gamma" True-Color operation with MR11 set to Logic "1" and direct 24-bit True-Color operation with MR11 set to Logic "0." The pixel port accepts 24 bits of color data which is directly mapped to the Look-Up Table RAM. With MR11 set to Logic "1," the Look-Up Table is configured as a 256 location by 30 bits deep RAM (10 bits each for Red, Green and Blue), the RAM is preloaded with a user determined, nonlinear function, such as a gamma correction curve and the output of the RAM drives the DACs with 30-bit data. With MR11 set to Logic "0," the Look-Up Table is configured as a 256 location by 24 bits deep RAM (8 bits each for Red, Green and Blue), the RAM is preloaded with a linear function and the output of the RAM drives the DACs with 24bit data.

![](_page_18_Figure_7.jpeg)

Figure 23. 24-Bit to 30-Bit True-Color Configuration

#### 16-Bit True Color

#### (CR27, CR26, CR25, CR24 = 1, 0, 1, 1)

The part is set to 16-bit True-Color operation. The pixel port accepts 16 bits of color data which is mapped to the 5 LSBs of each of the red and blue palettes of the Look-Up-Table RAM, and 6 LSBs of the green palette of the Look-Up-Table RAM. With MR11 set to Logic "1," the Look-Up Table is configured as a 64 location by 30 bits deep RAM (10 bits each for Red, Green and Blue) and the output of the RAM drives the DACs with 30-Bit data, allowing the display of 16-bit Gamma-Corrected True-Color Images. With MR11 set to Logic "0," the Look-Up Table is configured as a 64 location by 24 bits deep RAM (8 bits each for Red, Green and Blue); and the output of the RAM drives the DACs with 24-bit data, allowing the display of 16-bit True-Color Images.

#### 15-Bit True Color

#### (CR27, CR26, CR25, CR24 = 1, 1, 0, 0 or 1, 1, 0, 1)

The part is set to 15-bit True-Color operation. The pixel port accepts 15 bits of color data which is mapped to the 5 LSBs of each of the red, green and blue palettes of the Look-Up Table RAM. With MR11 set to Logic "1," the Look-Up Table is configured as a 32 location by 30 bits deep RAM (10 bits each for Red, Green and Blue) and the output of the RAM drives the

DACs with 30-bit data, allowing the display of 15-bit Gamma-Corrected True-Color Images. With MR11 set to Logic "0," the Look-Up Table is configured as a 32 location by 24 bits deep RAM (8 bits each for Red, Green and Blue) and the output of the RAM drives the DACs with 24-bit data, allowing the display of 15-bit True-Color Images.

![](_page_18_Figure_16.jpeg)

Figure 24. 15-Bit to 24-Bit True-Color Configuration

#### 8-Bit Pseudo Color

(CR27, CR26, CR25, CR24 = 0, 0, 0, 0 or 0, 1, 0, 0 or 1, 0, 0, 0) This mode sets the part into 8-bit Pseudo-Color operation. The pixel port accepts 8 bits of pixel data, from either the red, blue or green channel. With MR11 set to Logic "1," a 30-bit word is indexed in the Look-Up Table RAM. The Look-Up Table is configured as a 256 location by 30 bits deep RAM (10 bits each for Red, Green and Blue). The output of the RAM drives the DACs with 30-bit data. With MR11 set to Logic "0," a 24-Bit word is indexed in the Look-Up Table RAM. The Look-Up Table is configured as a 256 location by 24 bits deep RAM (8 bits each for Red, Green and Blue). The output of the RAM drives the DACs with 24-bit data. This mode allows for the display of 256 simultaneous colors out of a total palette of millions of addressable colors.

![](_page_18_Figure_20.jpeg)

Figure 25. 8-Bit to 30-Bit Pseudo-Color Configuration

#### PIXEL PORT MAPPING

The pixel data to the ADV7160/ADV7162 is automatically mapped in the parts pixel port as determined by the pixel data mode programmed (Bits CR27–CR24 of Command Register 2).

Pixel data in the 24-bit True-Color modes is directly mapped to the 24 color inputs R7–R0, G7–G0 and B7–B0.

There is one mode of operation for 16-bit True Color. Data is input to the device over the red and green color ports (R7–R0 and G7–G0) and is internally mapped to LUT Locations 0–63 according to Figure 26. (Note: Data on unused pixel inputs is ignored.)

![](_page_19_Figure_1.jpeg)

Figure 26. 16-Bit True-Color Mapping using R7–R0 and G7–G0

![](_page_19_Figure_3.jpeg)

Figure 27. 15-Bit True Color Mapping using R7–R3, G7–G3 and B7–B3

![](_page_19_Figure_5.jpeg)

*Figure 28. 15-Bit True-Color Mapping using R6–R0 and G7–G0* 

The part has two modes of operation for 15-bit True Color. In the first mode, data is input to the device over the red, green and blue channel (R7–R3, G7–G3 and B7–B3) and is internally mapped to Locations 0 to 31 of the Look-Up Table (LUT) according to Figure 27.

In the second mode, data is input to the device over just two of the color ports, red and green (R7–R0 and G7–G0) and is internally mapped to LUT Locations 0 to 31 according to Figure 30. (Note: Data on unused pixel inputs is ignored.)

There are three modes of operation for 8-bit Pseudo Color. Each mode maps the input pixel data differently. Data can be input into one of the three color channels, R7–R0 or G7–G0 or B7–B0.

In 24-bit Palette Bypass Mode, the red, blue and green color channels bypass the Pixel Mask and the Color Palette. Each 8bit color channel is mapped onto the 8 MSBs of the corresponding 10-bit DAC input. The two LSBs on each DAC are zeros. The Bypass Mode can be selected in two ways, by using CR27– CR24 of Command Register 2 or on a pixel by pixel basis using the PS inputs (ADV7160 only).

In 16-bit Palette Bypass Mode, the color channels bypass the Pixel Mask and the Color Palette. The 8-bits of red pixel data and 8-bits of green pixel data are mapped onto the 5 MSBs of the red and blue DAC input and the 6 MSBs of the green DAC input as shown in Figure 29. The remaining LSBs on each DAC are zeros. The Bypass Mode can be selected in two ways, by using CR27–CR24 of Command Register 2 or on a pixel by pixel basis using the PS inputs (ADV7160 only).

![](_page_20_Figure_1.jpeg)

#### Multiplexing

The on-board multiplexers of the ADV7160/ADV7162 eliminate the need for external data serializer circuits. Multiple video memory devices can be connected, in parallel, directly to the device. Figure 31 shows four memory banks of 50 MHz memory connected to the ADV7160, running in 4:1 multiplex mode, giving a resultant pixel or dot clock rate of 200 MHz. Instead of having to provide a new pixel at the input every 5 ns, four pixels are provided together every 20 ns. The input multiplexer takes the four pixels latched in parallel, and selects them one at a time to produce a pixel stream at the pixel clock rate. In 4:1 mode, the pixels are selected in the sequence A, B, C, D, cycling continuously. In 2:1 mode, the A and B pixels are selected. The 8:1 mode is only available in 8-bit Pseudo-Color Mode. BLANK, SYNC, ODD/EVEN and TRISYNC are not multiplexed and can only change on a 1, 2, 4 or 8 pixel boundary depending on the multiplex mode.

On the rising edge of LOADIN, all the pixel port inputs are latched into the ADV7160/ADV7162. The LOADIN frequency must be a divided down frequency of the pixel clock frequency. This can be achieved using LOADOUT to directly drive LOADIN as LOADOUT provides the correct frequency required, or drive LOADIN after delay through some external circuitry.

![](_page_20_Figure_5.jpeg)

### Figure 31. Direct Interfacing of Video Memory to ADV7160/ADV7162

#### 8-Bit Pseudo Color in 8:1 Multiplexing Mode

When 8:1 Multiplexing Mode is selected by setting Bit CR37 of Command Register 3 to Logic "1" and bit CR36 of Command Register 3 to Logic "0," the ADV7160/ADV7162 goes into 8-Bit Pseudo-Color Mode irrespective of the Color Mode selected by Bits CR27 to CR24 in Command Register 2. Hence LOADOUT operates at  $f_{CLOCK}/8$ . Eight 8-bit pixels are latched in parallel by the rising edge of LOADIN. These 8-bit pixels are then selected, one at a time, to produce an 8-bit pixel stream which passes through the Pixel Mask to address the LUT. The order the eight 8-bit pixels are displayed is GA, RA, GB, RB, GC, RC, GD, RD.

![](_page_20_Figure_9.jpeg)

*Figure 29. 16-Bit True-Color in Bypass Mode using R7–R0 and G7–G0* 

![](_page_20_Figure_11.jpeg)

Fiigure 30. 15-Bit True-Color in Bypass Mode using R6–R0 and G7–G0

The unused Blue pixel inputs are used, in this mode, to provide 8 extra PS inputs. These PS inputs provide 2 bits after 8:1 multiplexing. The PS inputs can be used as Overlay or Palette Select inputs.

![](_page_21_Figure_2.jpeg)

Figure 32. 8-Bit Pseudo Color in 8:1 Multiplexing Mode

### **MICROPROCESSOR (MPU PORT)**

The ADV7160/ADV7162 supports a standard MPU Interface. All the functions of the part are controlled via this MPU port. Direct access is gained to the Address Register, Mode Register and all the Control Registers as well as the Color Palette. The following sections describe the setup for reading and writing to all of the devices registers.

#### **MPU** Interface

The MPU interface (Figure 33) consists of a bidirectional, 10bit wide databus and interface control signals  $\overline{CE}$ , C0, C1 and  $R/\overline{W}$ . The 10-bit wide databus is user configurable as illustrated.

Data-Bus Width	RAM/DAC Resolution	Read/Write Mode	
10-Bit	10-Bit	10-Bit Parallel	
10-Bit	8-Bit	8-Bit Parallel	
8-Bit	10-Bit	8 + 2 Byte	
8-Bit	8-Bit	8-Bit Parallel	

Table I. Data-Bus Width

#### **Register Mapping**

The ADV7160/ADV7162 contains a number of on-board registers including the Mode Register (MR17–MR10), Address Register (A10–A0) and many Control Registers as well as Color Palette Registers. These registers control the entire operation of the part. Figure 34 shows the internal register configuration.

Control lines C1 and C0 determine which register the MPU is accessing. C1 and C0 also determine whether the Address Register is pointing to the color registers and Look-Up Table RAM or the control registers. If C1, C0 = 1, 0 the MPU has access to whatever control register is pointed to by the Address Register (A10–A0). If C1, C0 = 0, 1 the MPU has access to the Look-Up Table RAM (Color Palette) or the Overlay Palette through the associated color registers. The  $\overline{CE}$  input latches data to or from the part.

The  $R/\overline{W}$  control input determines between read or write accesses. The truth tables show all modes of access to the various registers and color palette for both the 8-bit wide databus configuration and 10-bit wide data bus configuration. It should be noted that after power-up, the devices MPU port is automatically set to 10-bit wide operation (see Power-On Reset section).

![](_page_21_Figure_14.jpeg)

Figure 33. MPU Port and Register Configuration

![](_page_22_Figure_1.jpeg)

Figure 34. Internal Register Configuration and Address Decoding

#### **Power-On Reset**

On power-up, the ADV7160/ADV7162 executes a power-on reset operation. This initializes the pixel port such that the pixel sequence ABCD starts at A. The Mode Register (MR17–MR10), Command Register 2 (CR27–CR20), Command Register 3 (CR37–CR30) have all bits set to a Logic "1" and Address Register, Command Register 1 (CR17–CR10), Command Register 4 (CR47–CR40) and Command Register 5 (CR57–CR50) have all bits set to a Logic "0."

The output clocking signals are also set during this reset period.

PRGCKOUT = CLOCK/32

LOADOUT = 
$$CLOCK/4$$
:

The power-on reset is activated when  $V_{AA}$  goes from 0 V to 5 V This reset is active for 1  $\mu$ s. The ADV7160/ADV7162 should not be accessed during this reset period. The pixel clock should be applied at power-up.

#### **Color Palette Accesses**

The Color Palette consists of 256 RAM locations, each location containing 30 bits of color information. Data is written to the color palette by firstly writing to the address register of the color palette location to be modified. The MPU performs three successive write cycles for each of the red, green and blue registers (10-bit or 8-bit). Figures 35 to 38 illustrate write operations for a 10-bit databus using the DACs in 8-bit and 10-bit mode and write operations for an 8-bit databus using the DACs in 8-bit and 10-bit mode. An internal pointer moves from red to green to blue after each write is completed. This pointer is reset to red after a blue write or whenever the address register is written. During the blue write cycle, the three bytes of red, green and

blue are concatenated into a single 30-bit/24-bit word and written to the RAM location as specified in the address register (A10–A0).

The address register then automatically increments to point to the next RAM location and a similar red, green and blue palette write sequence is performed. The address register resets to 000H following a blue write cycle to color palette RAM location 0FFH. The three color overlay palette is located in address space above the main color palette. To access the Overlay Palette, the Address Register must first be written with address 101H. From then on, the colors are accessed in the same way as the main Color Palette, with the Address Register incrementing after each blue access.

Data is read from the Color Palette by firstly writing to the address register of the color palette location to be read. The MPU performs three successive read cycles from each of the red, green and blue locations (10-bit or 8-bit) of the RAM. Figures 35 to 38 illustrate read operations for a 10-bit databus using the DACs in 8-bit and 10-bit mode and read operations for an 8-bit databus using the DACs in 8-bit and 10-bit mode. An internal pointer moves from red to green to blue after each read is completed. This pointer is reset to red after a blue read or whenever the address register is written. The address register then automatically increments to point to the next RAM location and a similar red, green and blue palette read sequence is performed. The address register resets to 000H following a blue read cycle of color palette RAM location 0FFH. Similarly for the Overlay Palette, the Address Register must first be written with address 101H. From then on, the colors are read in the same way as the main Color Palette, with the Address Register incrementing after each blue access.

![](_page_23_Figure_12.jpeg)

Figure 35. 8-Bit Data Bus Using 10-Bit DACs

#### **Register Accesses**

The MPU can write to or read from all of the ADV7160/ ADV7162's registers. C0 and C1 determine whether the Mode Register or Address Register is being accessed. Access to these

registers is direct. The Control Registers are accessed indirectly. The Address Register must point to the desired Control Register. Figure 33 and Figures 35 to 38 illustrate the structure and protocol for device communication over the MPU port.

![](_page_24_Figure_4.jpeg)

R/W	C1	C0	Palette Write
0 0 0 0 0	0 0 0 0 0	0 0 1 1 1 1	Write to Address Register (Lo-Byte) Write to Address Register (Hi-Byte) Write Red Data (R9–R0) Write Green Data (G9–G0) Write Blue Data (B9–B0) Write Red Data (R9–R0)
R/W	C1	C0	Palette Read
0 0 1 1 1	0 0 0 0 0	0 0 1 1 1	Write to Address Register (Lo-Byte) Write to Address Register (Hi-Byte) Read Red Data (R9–R0) Read Green Data (G9–G0) Read Blue Data (B9–B0) Read Red Data (R9–R0)

.

#### Figure 36. 8-Bit Databus Using 8-Bit DACs

![](_page_24_Figure_7.jpeg)

#### Figure 37. 10-Bit Databus Using 10-Bit DACs

![](_page_24_Figure_9.jpeg)

Figure 38. 10-Bit Databus Using 8-Bit DACS

#### **REGISTER PROGRAMMING**

The following section describes each register, including Address Register, Mode Register and each of the Control Registers in terms of its configuration.

#### Address Register (A10-A0)

As illustrated in the previous tables, the C1 and C0 control inputs, in conjunction with this address register specify which control register, or color palette location is accessed by the MPU port. The Address Register is 11 bits wide and can be read from as well as written to. To access the Address Register, two consecutive MPU accesses with C1 and C0 set to Logic "0" are required. The first one accesses the low byte; and when a second access of the same type is performed, i.e., two consecutive reads or two consecutive writes, the high byte is accessed. If the type of access is changed, or if an access to a different register is inserted between the first and the second, then the second access will access the low byte again. When writing to or reading from the color palette on a sequential basis, only the start address needs to be written. After a red, green and blue write sequence, the address register is automatically incremented.

#### Mode Register (MR1)

The mode register is a 10-bit wide register. However for programming purposes, it may be considered as an 8-bit wide register (MR19 and MR18 are both reserved). It is denoted as MR17–MR10 for simplification purposes.

Figure 39 shows the various operations under the control of the mode register. This register can be read from as well written to. In read mode, if MR19 and MR18 are read back, they are both returned as zeros.

#### MODE REGISTER BIT DESCRIPTION Reset Control (MR10)

This bit is used to reset the pixel port sampling sequence. This ensures that the pixel sequence ABCD starts at A. It is reset by writing a "1" followed by a "0" followed by a "1." This bit must run this cycle during the initialization sequence.

#### **RAM-DAC** Resolution Control (MR11)

When this is programmed with a "1," the RAM is 30 bits deep (10 bits each for red, green and blue), and each of the three DACs is configured for 10-bit resolution. When MR11 is programmed with a "0," the RAM is 24 bits deep (8 bits each for red, green and blue), and the DACs are configured for 8-bit resolution. The two LSBs of the 10-bit DACs are pulled down to zero in 8-bit RAM-DAC mode.

#### MPU Data Bus Width (MR12)

This bit determines the width of the MPU port. It is configured as either a 10-bit wide (D9–D0) or 8-bit wide (D7–D0) bus. Ten-bit data can be written to the device when configured 8-bit wide mode. The 8 MSBs are first written on D7–D0, then the two LSBs are written over D1–D0. Bits D9–D8 are zeros in 8bit mode.

#### **Operational Mode Control (MR14-MR13)**

When MR14 and MR13 are "0" the part operates in normal mode.

#### Calibrate LOADIN (MR15)

This bit automatically calibrates the on-board LOADIN/ LOADOUT synchronization circuit. A "0" to "1" transition initiates calibration. This bit is set to "0" in normal operation. See "Pipeline Delay & Calibration" section. This bit must run this cycle during the initialization sequence.

#### Palette Select Match Bits Control (MR17-MR16)

These bits allow multiple palette devices to work together. When bits PS1 and PS0 match MR17 and MR16 respectively, the device is selected. If these bits do not match, the device is not selected and the analog video outputs drive 0 mA. See "Palette Priority Select Inputs" section.

#### **CONTROL REGISTERS**

A large bank of registers plus the  $64 \times 64$  cursor image can be accessed through the Control Register. Access is made first by writing the Address Register with the appropriate address to point to the particular Control Register (see Figure 34), and

![](_page_25_Figure_22.jpeg)

Figure 39. Mode Register 1 (MR1) (MR19–MR10)

then performing an MPU access to the Control Register. When accessing Control Registers in the range 200H to 204H, and when accessing the cursor image, the Address Register autoincrements after each register access. On accessing the last cursor image location at address 7FFH, the address register reverts to address 000H. The Address Register also auto-increments after a blue access, when accessing color registers in the address range 303H to 304H.

#### **ID Register**

#### (Address Reg (A10-A0) = 003H)

This is an 8-bit wide "Identification" read-only register. For the ADV7160 it will always return the hexadecimal value 76H. For the ADV7162 it will always return the hexadecimal value 79H.

#### **Pixel Mask Register**

#### (Address Reg (A10-A0) = 004H)

The contents of the pixel mask register are individually bit-wise logically ANDed with the Red, Green and Blue pixel input stream of data. It is an 8-bit read/write register with D0 corresponding to R0, G0 and B0. For normal operation, this register is set with FFH.

#### **COMMAND REGISTER 1 (CR1)**

#### (Address Reg (A10-A0) = 005H)

This register contains a number of control bits as shown in the diagram. CR1 is a 10-bit wide register. However for programming purposes, it may be considered as an 8-bit wide register (CR19 to CR18 reserved).

Figure 40 shows the various operations under the control of CR1. This register can be read from as well written to. In write mode zero should be written to CR12. In read mode, CR19 and CR18 are returned as zeros.

#### COMMAND REGISTER 1-BIT DESCRIPTION Calibration Control (CR10)

This bit automatically calibrates the on-board LOADIN/ LOADOUT synchronization circuit on every vertical Sync. MR15 of Mode Register MR1 must be set to "0."

#### Hi-Byte Control (CR13)

This bit enables access to the Hi Byte of the Address Register. When CR13 is set to Logic "0", the part is compatible to the ADV7150. To access the hi-byte of the address register, this bit is set to Logic "1."

#### PS Function Control (CR15-CR14)

These bits control the functions of the PS inputs. They are used to enable the Overlay Mode, Bypass Mode or the Palette Select Mode. In Palette Select Mode (CR15 and CR14 = "0"), these inputs are used to multiplex the RGB outputs of a number of devices. On a pixel by pixel basis, PS1 and PS0 are compared against the PS match bits, MR17 and MR16. If they match, then the part behaves normally. If they don't match, then the analog output currents are switched to zero for that clock cycle, thus allowing another device, whose PS match bits match during this time, to drive the monitor. In Bypass Mode (CR15 = "0," CR14 = "1"), PS1 is used to switch between one of the color modes through the Color Palette and one of the Palette Bypass Modes, on a pixel by pixel basis. The color mode through the palette is selected using CR17 and CR16. It is illegal to program CR27 to CR24 to select one of the bypass modes when using the PS bits to select a bypass mode at the pixel rate. This switching on a pixel by pixel basis is only allowed when using an ADV7160 device. Therefore, for the ADV7162, this mode (CR15 = "0," CR14 = "1"), is reserved and should not be used.

In Overlay Mode (CR15 = "1," CR14 = "0"), the PS inputs provide control for a three color overlay. Whenever a value other than "00" is placed on the overlay inputs, the corresponding overlay color is displayed. When the overlay inputs contain "00," the color is specified by the pixel inputs.

When CR15 and CR14 = "1," the PS inputs are completely ignored. There is no overlay, no bypass switching and the RGB outputs are enabled.

#### Bypass Color Mode Control (CR17-CR16)

These bits control the mode during bypass switching. There are three different modes: 24-bit Bypass, 16-bit Bypass or 15-bit Bypass Mode.

![](_page_26_Figure_22.jpeg)

Figure 40. Command Register 1 (CR1) (CR19–CR10)

![](_page_27_Figure_1.jpeg)

Figure 41. Command Register 2 (CR2) (CR29–CR20)

#### COMMAND REGISTER 2 (CR2) (Address Reg (A10–A0) = 006H)

This register contains a number of control bits as shown in the diagram. CR2 is a 10-bit wide register. However for programming purposes, it may be considered as an 8-bit wide register (CR29 and CR28 are both reserved).

Figure 41 shows the various operations under the control of CR2. This register can be read from as well written to. In write mode zero should be written to CR21 and CR20. In read mode, CR29 and CR28 are returned as zeros.

#### COMMAND REGISTER 2-BIT DESCRIPTION SYNC Recognition Control on Green (CR22)

This bit specifies whether the video  $\overline{\text{SYNC}}$  Input is to be encoded onto the IOG analog output or ignored.

#### Pedestal Enable Control (CR23)

This bit specifies whether a 0 IRE or a 7.5 IRE blanking pedestal is to be generated on the video outputs.

#### True-Color/Bypass/Pseudo-Color Mode Control (CR27-CR24)

These 4 bits specify the various color modes. These include a 24-bit true-color and bypass mode, one 16-bit true-color and bypass mode, two 15-bit true-color modes, one 15-bit bypass mode and three 8-bit pseudo color modes.

#### COMMAND REGISTER 3 (CR3) (Address Reg (A10-A0) = 007H)

This register contains a number of control bits as shown in the diagram. CR3 is a 10-bit wide register. However for programming purposes, it may be considered as an 8-bit wide register (CR39 and CR38 are both reserved).

Figure 42 shows the various operations under the control of CR3. This register can be read from as well written to. In write mode zero should be written to CR35. In read mode, CR39 and CR38 are returned as zeros.

#### COMMAND REGISTER 3 BIT DESCRIPTION PRGCKOUT Frequency Control (CR31-CR30)

These bits specify the output frequency of the PRGCKOUT output. PRGCKOUT is a divided down version of the pixel CLOCK.

#### **BLANK** Pipeline Delay Control (CR34-CR32)

These bits specify the additional pipeline delay that can be added to the  $\overline{BLANK}$  function, relative to the overall device pipeline delay (t<sub>PD</sub>). As the  $\overline{BLANK}$  control normally enters the Video DAC from a shorter pipeline than the video pixel data, this control is useful in de-skewing the pipeline differential.

#### Pixel Multiplex Control (CR37-CR36)

These bits specify the device's multiplex mode. It therefore also determines the frequency of the LOADOUT signal. LOADOUT is a divided down version of the pixel CLOCK.

![](_page_28_Figure_1.jpeg)

Figure 42. Command Register 3 (CR3) (CR39–CR30)

#### COMMAND REGISTER 4 (CR4) (ADDRESS REG (A10-A0) = 008H)

This register contains a number of control bits as shown in the diagram. CR4 is a 10-bit wide register. However for programming purposes, it may be considered as an 8-bit wide register (CR49 and CR48 are both reserved).

Figure 43 shows the various operations under the control of CR4. This register can be read from as well written to. In read mode, CR49 and CR48 are both returned as zeros.

#### COMMAND REGISTER 4-BIT DESCRIPTION HDTV SYNC Enable (CR40)

This bit specifies whether the video  $\overline{\text{TRISYNC}}$  Input is to be encoded, enabling the DAC outputs to generate a Tri-Level Sync.

#### **SYNC** Recognition Control on Red (CR41)

This bit specifies whether the video  $\overline{SYNC}$  Input is to be encoded onto the IOR analog output or ignored.

#### **SYNC** Recognition Control on Blue (CR42)

This bit specifies whether the video SYNC Input is to be encoded onto the IOB analog output or ignored.

#### Gain Control (CR44-CR43)

These bits specifies the amount of gain on the DAC depending on the standard required. See "DAC and Video Outputs" section for more detail. For gain settings that have no pedestal, the pedestal is automatically disabled independently of CR23.

#### Signature Clock Control (CR45)

This bit enables or disables the clock to the signature analyzer.

![](_page_28_Figure_16.jpeg)

Figure 43. Command Register 4 (CR4) (CRF49–CR40)

#### Signature Reset Control (CR46)

Taking CR46 low then high resets the signature analyzer. This is done to give a known starting point before acquiring a signature.

#### Signature Acquire Control (CR47)

This bit should be set to Logic "1" for normal operation. See "Test Diagnostic" section for more information.

#### **COMMAND REGISTER 5 (CR5)**

#### (Address Reg (A10-A0) = 00DH)

This register contains one control bit CR56. CR5 is a 10-bit wide register. However for programming purposes, it may be considered as an 8-bit wide register (CR59 and CR58 are both reserved).

This register can be read from as well written to. Control Bit CR56 selects either external clock or internal PLL operation. If the internal PLL is to be used, Logic "1" should be written to CR56. This should be set up immediately after power up. In write mode, zero should be written to CR57 and CR55–CR50. In read mode, CR59 and CR58 are both returned as zeros.

#### PLL COMMAND REGISTER (PCR)

#### (Address Reg (A10–A0) = 009H)

This register contains a number of control bits as shown in the diagram. PCR is a 10-bit wide register. However, for programming purposes, it may be considered as an 8-bit wide register (PCR9 and PCR8 are both reserved).

Figure 44 shows the various operations under the control of PCR. This register can be read from as well written to. In write mode zero should be written to PCR3. In read mode PCR9 and PCR8 are returned as zeros.

#### PLL Control (PCR0)

This bit enables or disables PLL.

#### **RSEL Bit Control (PCR1)**

This bit enables or disables RSEL, which together with the contents of the PLL R Register affect the reference divider value of the PLL. Reference Divider =  $(1 + RSEL) \times (R+2)$ .

#### **VSEL Bit Control (PCR2)**

This bit enables or disables VSEL, which together with the contents of the PLL V Register and the PLL S value affect the feedback divider value of the PLL. Feedback Divider =  $(1 + \overline{VSEL}) \times (4(V + 2) + S)$ .

#### Output Divide Control (PCR5-PCR4)

These bits control the PLL output divider. This post-scaler is used in the generation of lower frequencies.

#### PLL S Control (PCR7-PCR6)

These bits set up the S value in the PLL transfer function. This extra value provides extra control in setting the feedback divider value of the PLL.

#### **Status Register**

#### (Address Reg (A10-A0) = 00AH)

This register is a read only 10-bit register. However SR9–SR8 are reserved bits, containing zeros and SR7–SR1 are undefined bits and should be masked in software on read back. Therefore, SR0 is the only relevant Bit in the Status Register and contains a Logic "1" if one, or more of the IOR, IOG, and IOB outputs exceed the internal voltage of the SENSE comparator circuit . It can be used to determine the presence of a CRT monitor. With some diagnostic code, the presence of loading on the individual RGB lines can be determined. The reference is generated by a voltage divider from the external voltage reference on the  $V_{REF}$  pin. For the proper operation, the following levels should be applied to the comparator by the IOR, IOG and IOB outputs:

DAC Low Voltage  $\leq 250 \text{ mV}$ DAC High Voltage  $\geq 450 \text{ mV}$ 

#### **Revision Register**

#### (Address Reg (A10-A0) = 01BH)

This register is a read only register containing the revision of silicon.

#### PLL R Register

#### (Address Reg (A10-A0) = 00CH)

This register is a read only 10-bit register. However, R9–R8 are reserved bits, containing zeros. Bit R7 is a read only bit. This bit should be masked in software on readback as its value may be indeterminate. Therefore, the PLL R Register may be treated as a 7-bit wide register. This register, together with the RSEL Bit in the PLL Control Register, controls the reference divider of the on-board PLL.

![](_page_29_Figure_33.jpeg)

Figure 44. Command Register (PCR) (PCR9–PCR0)

#### PLL V Register (Address Reg (A10-A0) = 00FH)

This register is a read only 10-bit register. However V9–V8 are reserved bits, containing zeros. Bit V7 is a read only bit. This bit should be masked in software on readback as its value may be indeterminate. Therefore, the PLL V Register may be treated as a 7-bit wide register. This register, together with the VSEL Bit in the PLL Control Register, controls the feedback divider of the on-board PLL.

#### $64 \times 64$ Cursor

The ADV7160/ADV7162 has a  $64 \times 64$  cursor generator on board. Several of the control registers control the cursor. These will be described in detail. The Cursor-X and Cursor-Y registers specify the position the cursor is to be placed on the screen. The origin (0, 0) of the cursor is top left. The position of the cursor is taken relative to this point, allowing the Cursor-X and Cursor-Y registers to be programmed with negative numbers and thus allow the cursor to be partially or completely off the screen. The cursor can work as an X-11 or XGA cursor, controlled by Bits CCR0 and CCR1 of the Cursor Control Register.

The screen X and Y coordinates are measured from the rising edge of  $\overline{\text{BLANK}}$ . The first pixel after the rising edge of  $\overline{\text{BLANK}}$  corresponds to the origin (0, 0). The Vertical retrace time is extracted from the composite  $\overline{\text{SYNC}}$  and  $\overline{\text{BLANK}}$  inputs. The start of Vertical Retrace is recognized by counting a second rising edge on  $\overline{\text{SYNC}}$  while  $\overline{\text{BLANK}}$  remains low. The next rising edge on  $\overline{\text{BLANK}}$  is the start of line 0.

#### Cursor X-Lo and Cursor X-Hi Register (Address Reg (A10–A0) = 200H and 201H)

These 8-bit registers together form a 16-bit 2s complement representation of the cursor x-coordinate on the screen. The valid range for the cursor x-coordinate is  $\pm$ FFFH. The negative number representation allows for part or all of the cursor to be displayed off the left-hand edge of the screen

#### Cursor Y-Lo and Cursor Y-Hi Register (Address Reg (A10-A0) = 202H and 203H)

These 8-bit registers together form a 16-bit 2s complement representation of the cursor x-coordinate on the screen. The valid range for the cursor x-coordinate is  $\pm$ FFFH. The negative number representation allows for part or all of the cursor to be displayed off the top/left of the screen.

When accessing the cursor X and Y registers, the Address Register auto-increments after each access. There are no restrictions on updating the cursor coordinate registers other than they must all be written in the order X-Low, X-Hi, Y-Low, Y-Hi to update the coordinates. Only one cursor is displayed per frame, at the last X and Y coordinates written. Access to these registers is independent of the databus being configured for 8- or 10-bit operation.

#### Cursor Color 1 and Cursor Color 2 Register (Address Reg (A10-A0) = 304H and 303H)

Each of these color registers are 30 bits wide, made up of 10 bits for Red, 10 bits for Green and 10 bits for Blue. Access to these registers behaves in the same way as access to the Color Palette with respect to the different combinations of 10/8-bit databus and 10/8-bit DAC resolution.

#### **Cursor Image**

#### (Address Reg (A10-A0) = 400H-7FFH)

This region contains the  $64 \times 64 \times 2$ -bit Cursor Image. Eight

bits are stored at each address. With two bits per cursor pixel, four horizontally adjacent pixels are stored at each address. As each address location in the Cursor Image is filled, the progression is from left to right until a line is filled and top to bottom until all the lines are filled. The cursor can be displayed on both an interlaced and noninterlaced system, as controlled by CCR3 of the Cursor Control Register. On an interlaced system, only one cursor can be displayed per field. The ODD/EVEN input indicates which field of the frame is being displayed.

#### **Cursor Y Coordinate Even**

The Even field starts with line 0 of the cursor image on line Y of the frame. Subsequent even lines of the cursor image are displayed on subsequent lines of the Even field. On the Even field, the frame line counter starts at 0 and increments by 2 at the end of every Even field line. The Odd field starts with line 1 of the cursor image on line Y + 1 of the frame. Subsequent odd lines of the cursor image are displayed on subsequent lines of the Odd field. On the Odd field, the frame line counter starts at 1 and increments by 2 at the end of every Odd field line.

#### Cursor Y Coordinate Odd

The Even field starts with line 1 of the cursor image on line Y + 1 of the frame. Subsequent even lines of the cursor image are displayed on subsequent lines of the Even field. On the Even field, the frame line counter starts at 1 and increments by 2 at the end of every Even field line. The Odd field starts with line 0 of the cursor image on line Y of the frame. Subsequent odd lines of the cursor image are displayed on subsequent lines of the Odd field. On the Odd field, the frame line counter starts at 0 and increments by 2 at the end of every Odd field line.

#### Cursor Control Register (Address Reg (A10–A0) = 204H)

This register contains a number of control bits. CCR is a 10-bit wide register. However for programming purposes, it may be considered as an 8-bit wide register (CCR8 and CCR9 are both reserved). In write mode zero should be written to CCR4 to CCR7. In read mode, CCR8 and CCR9 are all returned as zeros.

Figure 45 shows the various operations under the control of CCR.

#### CURSOR CONTROL REGISTER BIT DESCRIPTION CURSOR MODE CONTROL (CCR1-CCR0)

These bits specify which type of cursor is being used. Each cursor pixel value controls the color differently in each mode.

Table II.

Bit 1	Bit 0	X-11 Cursor	XGA Cursor
0	0	Transparent	Color 1
0	1	Transparent	Color 2
1	0	Color 1	Transparent
1	1	Color 2	Bit-Wise Complement

#### **Cursor Enable Control (CCR2)** This bit turns the cursor on and off.

#### Interlace Control (CCR3)

This bit determines whether the cursor is being used in interlaced or noninterlaced mode.

![](_page_31_Figure_1.jpeg)

Figure 45. Cursor Control Register (CCR) (CCR9–CCR0)

### DIGITAL-TO-ANALOG CONVERTER (DACS) AND VIDEO OUTPUTS

The ADV7160/ADV7162 contains three high speed video DACs. The DAC outputs are represented as the three primary analog color signals IOR (red video), IOG (green video) and IOB (blue video).

![](_page_31_Figure_5.jpeg)

#### DACs and Analog Outputs

The part contains three matched 10-bit digital-to-analog converters. The DACs are designed using an advanced, high speed, segmented architecture. The bit currents corresponding to each digital input are routed to either IOR, IOG, IOB (bit = "1") or GND.

The analog video outputs are high impedance current sources. Each of the these three RGB current outputs are specified to directly drive a 37.5  $\Omega$  load (doubly terminated 75  $\Omega$ ).

#### Reference Input and R<sub>SET</sub>

An external 1.23 V voltage reference is required to set up the analog outputs of the ADV7160/ADV7162. The reference voltage is connected to the  $V_{REF}$  input.

A resistor  $R_{SET}$  is connected between the  $R_{SET}$  input of the part and ground. For specified performance,  $R_{SET}$  has a value of 280  $\Omega$ . This corresponds to the generation of RS-343A video levels (with SYNC on IOG and Pedestal = 7.5 IRE) into a doubly terminated 75  $\Omega$  load. In this example DAC Gain has a value of 3996 and is set using CR43 and CR44 of Command Register 4. Figure 47 illustrates the resulting video waveform and the Video Output Truth Table illustrates the corresponding control input stimuli. On the ADV7160/ADV7162 SYNC can be encoded on any of the analog signals, however in practice, SYNC is generally encoded on either the IOG output or on all of the video outputs.

![](_page_31_Figure_12.jpeg)

![](_page_31_Figure_13.jpeg)

Figure 47. Composite Video Waveform SYNC Decoded; Pedestal = 7.5 IRE; DAC Gain = 3996

Description	O/P with Sync Enabled (mA)	O/P with Sync Disabled (mA)	SYNC	BLANK	DAC Input Data
WHITE LEVEL	26.67	19.05	1	1	3FFH
VIDEO	Video + 9.05	Video + 1.44	1	1	Data
VIDEO to BLANK	Video + 1.44	Video + 1.44	0	1	Data
BLACK LEVEL	9.05	1.44	1	1	000H
BLACK to BLANK	1.44	1.44	0	1	000H
BLANK LEVEL	7.62	0	1	0	xxxH
SYNC LEVEL	0	0	0	0	xxxH

Table III. Video Output Truth Table

#### Variations on RS-343A

Various other video output configurations can be implemented by the ADV7160/ADV7162, including RS-170. The table shows calculated values of DAC Gain for some of the most common variants on the RS-343A standard. The associated waveforms are shown in the diagrams.

Gain	Video Signal
4224	RS343A, $\overline{\text{SYNC}}$ decoded on output; Pedestal = 0 IRE
5592	RS170, SYNC decoded; Pedestal = 7.5 IRE

![](_page_32_Figure_6.jpeg)

![](_page_32_Figure_7.jpeg)

![](_page_32_Figure_8.jpeg)

Figure 49. Composite Video Waveform SYNC and TRISYNC decoded; Pedestal = 7.5 IRE; DAC Gain = 5592

![](_page_32_Figure_10.jpeg)

Figure 50. Composite Video Waveform Pedestal = 0 IRE; DAC Gain = 4311

#### **Output Currents**

The various output currents are set by  $V_{REF}$ ,  $R_{SET}$  and the DAC gain. By programming the Command Register Bits and choosing the correct DAC Gain value, video waveforms conforming to the common variations on RS-170 and RS-343A, as well as HDTV standards may be generated. The currents generated can be summarized as:

 $I_{OUT} = I_{DAC} + I_{BLANK} + I_{SYNC} + I_{TRISYNC}$  $I_{DAC} (mA) = \frac{DAC GAIN \times V_{REF}}{R_{SET}}$  $I_{BLANK} (mA) = 0.0817 \times I_{DAC}$  $I_{SYNC} (mA) = 0.4322 \times I_{DAC}$  $I_{TRISYNC} (mA) = 0.4322 \times I_{DAC}$ 

#### **APPENDIX** 1

#### BOARD DESIGN AND LAYOUT CONSIDERATIONS

The ADV7160/ADV7162 is a highly integrated circuit containing both precision analog and high speed digital circuitry. It has been designed to minimize interference effects on the integrity of the analog circuitry by the high speed digital circuitry. It is imperative that these same design and layout techniques be applied to the system level design such that high speed, accurate performance is achieved. The "Recommended Analog Circuit Layout" shows the analog interface between the device and monitor.

The layout should be optimized for lowest noise on the ADV7160/ADV7162 power and ground lines by shielding the digital inputs and providing good decoupling. The lead length between groups of  $V_{AA}$  and GND pins should by minimized so as to minimize inductive ringing.

#### **Ground Planes**

The ground plane should encompass all ADV7160/ADV7162 ground pins, voltage reference circuitry, power supply bypass circuitry for the ADV7160/ADV7162, the analog output traces, and all the digital signal traces leading up to the ADV7160/ADV7162. The ground plane is the graphics board's common ground plane.

#### **Power Planes**

The ADV7160/ADV7162 and any associated analog circuitry should have it's own power plane, referred to as the analog power plane ( $V_{AA}$ ). This power plane should be connected to the regular PCB power plane ( $V_{CC}$ ) at a single point through a ferrite bead. This bead should be located within three inches of the ADV7160/ADV7162.

The PCB power plane should provide power to all digital logic on the PC board, and the analog power plane should provide power to all ADV7160/ADV7162 power pins and voltage reference circuitry.

Plane-to-plane noise coupling can be reduced by ensuring that portions of the regular PCB power and ground planes do not overlay portions of the analog power plane, unless they can be arranged such that the plane-to-plane noise is common mode.

#### Supply Decoupling

For optimum performance, bypass capacitors should be installed using the shortest leads possible, consistent with reliable operation, to reduce the lead inductance. Best performance is obtained with 0.1  $\mu$ F ceramic capacitor decoupling. Each group of V<sub>AA</sub> pins on the ADV7160/ADV7162 must have at least one 0.1  $\mu$ F decoupling capacitor to GND. These capacitors should be placed as close as possible to the device.

It is important to note that while the ADV7160/ADV7162 contains circuitry to reject power supply noise, this rejection decreases with frequency. If a high frequency switching power supply is used, the designer should pay close attention to reducing power supply noise and consider using a three terminal voltage regulator for supplying power to the analog power plane.

#### **Digital Signal Interconnect**

The digital inputs to the ADV7160/ADV7162 should be isolated as much as possible from the analog outputs and other analog circuitry. Also, these input signals should not overlay the analog power plane.

Due to the high clock rates involved, long clock lines to the ADV7160/ADV7162 should be avoided to reduce noise pickup. Any active termination resistors for the digital inputs should be connected to the regular PCB power plane ( $V_{CC}$ ), and not the analog power plane.

#### Analog Signal Interconnect

The ADV7160/ADV7162 should be located as close as possible to the output connectors to minimize noise pickup and reflections due to impedance mismatch.

The video output signals should overlay the ground plane, and not the analog power plane, to maximize the high frequency power supply rejection.

Digital Inputs, especially Pixel Data Inputs and clocking signals (CLOCK, LOADOUT, LOADIN, etc.) should never overlay any of the analog signal circuitry and should be kept as far away as possible.

For best performance, the analog outputs (IOR, IOG, IOB) should each have a 75  $\Omega$  load resistor connected to GND. These resistors should be placed as close as possible to the ADV7160/ADV7162 so as to minimize reflections.

![](_page_34_Figure_1.jpeg)

NOTES:

1. ALL RESISTERS ARE 1% METAL FILM 2. 0.1µF AND 0.01µF CAPACITORS ARE CERAMIC 3. ADDITIONAL DIGITAL CIRCUITRY OMITTED FOR CLARITY

Recommended Analog Circuit Layout

#### APPENDIX 2

![](_page_35_Figure_2.jpeg)

![](_page_35_Figure_3.jpeg)

#### **APPENDIX 3**

#### **10-BIT DACs AND GAMMA CORRECTION**

#### **10-Bit DACs**

10-Bit RAM-DAC resolution allows for nonlinear video correction, in particular Gamma Correction. The ADV7160/ADV7162 allows for an increase in color resolution from 24-bit to 30-bit effective color without the necessity of a 30-bit deep frame buffer. In true-color mode, for example, the part effectively operates as a 24-bit to 30-bit color look-up table.

Up to now we have assumed that there exists a linear relationship between the actual RGB values input to a monitor and the intensity produced on the screen. This, however, is not the case. Half scale digital input (1000 0000) might correspond to only 20% output intensity on the CRT (Cathode Ray Tube). The intensity ( $I_{CRT}$ ) produced on a CRT by an input value  $I_{IN}$  is given by:

$$I_{CRT} = (I_{IN})^{\circ}$$

where c ranges from 2.0 to 2.8.

If the individual values of c for red, green and blue are known, then so called "Gamma Correction" can be applied to each of the three video input signals  $(I_{IN})$ ; therefore:

 $I_{IN(corrected)} = k(I_{IN})^{1/c}$ 

Traditionally, there has been a trade-off between implementing a nonlinear graphics function, such as gamma correction, and color dynamic range. The ADV7160/ADV7162 overcomes this by increasing the individual color resolution of each of the red, green and blue primary colors from 8 bits per color channel to 10 bits per channel (24 bits to 30 bits).

The table highlights the loss of resolution when 8-bit data is gamma-corrected to a value of 2.7 and quantized in a traditional 8-bit system. Note that there is no change in the 8-bit quantized data for linear changes in the input data over much of the transfer function. On the other hand, when quantized to 10 bits via the 10-bit RAMs and 10-bit DACs of the ADV7160/ADV7162, all changes on the input 8-bit data are reflected in corresponding changes in the 10-bit data.

The graph shows a typical gamma curve corresponding to a gamma value of 2.7. This is programmed to the red, green and blue RAMs of the color look-up table instead of the more traditional linear function. Different curves corresponding to any particular gamma value can be independently programmed to each of the red, green and blue RAMs.

Other applications of the 10-bit RAM-DAC include closed-loop monitor color calibration.

GAMMA CORRECTION							
8 Bits vs. 10 Bits							
mmo							

.....

8-Bit Data	Gamma Corrected (2.7)	Quantized to 8 Bits	Quantized to 10 Bits
240	0.977797	250	1001
241	0.979304	250	1002
242	0.980807	251	1004
243	0.982306	251	1005
244	0.983801	251	1007
245	0.985292	252	1008
246	0.986780	252	1010
247	0.988264	252	1011
248	0.989744	253	1013
249	0.991220	253	1015
250	0.992693	254	1016
251	0.994161	254	1018
252	0.995626	254	1019
253	0.997088	255	1021
254	0.998546	255	1022
255	1.000000	255	1023

![](_page_36_Figure_16.jpeg)

Gamma Correction Curve (Gamma Value = 2.7)

#### **APPENDIX 4**

#### INITIALIZATION AND PROGRAMMING

#### ADV7160/ADV7162 INITIALIZATION

After power has been supplied, the ADV7160/ADV7162 must be initialized. The Mode Register and Control Registers must then be set up. The values written to the various registers will be determined by the desired operating mode of the part, i.e., True-Color/Pseudo-Color, 4:1 Muxing/2:1 Muxing, PLL on/off, Bypass Mode on/off etc...

The following section gives a recommended initialization of the ADV7160/ADV7162 and an example of the ADV7162 operating in a specific mode.

ADV7	160/ADV7162 Initialization	<b>C</b> 1	<b>C</b> 0	R/W	Comment
Write	(xx000xx1)* to Mode Register (MR1)	1	1	0	Resets ADV7160/62
Write	(xx000xx0)* to Mode Register (MR1)	1	1	0	
Write	(xx000xx1)* to Mode Register (MR1)	1	1	0	
Write	05H to Address Register (A7–A0)	0	0	0	Address Reg points to Command Register 1 (CR1)
Write	(xxxx100x)* to Command Register 1 (CR1)	0	0	0	Address Reg points to CR1 for high byte access
Write Write Write	06H to Address Register (A7–A0) 00H to Address Register (A10–A8) (xxxxxx00)* to Command Reg 2 (CR2)	0 0 1	0 0 0	0 0 0	Address Reg points to Command Register 2 (CR2) Setup CR2 as required
Write Write Write	07H to Address Register (A7–A0) 00H to Address Register (A10–A8) (xx0xxxxx)* to Command Reg 3 (CR3)	0 0 1	0 0 0	0 0 0	Address Reg points to Command Register 3 (CR3) Setup CR3 as required
Write Write Write	08H to Address Register (A7–A0) 00H to Address Register (A10–A8) (xxxxxxx)* to Command Reg 4 (CR4)	0 0 1	0 0 0	0 0 0	Address Reg points to Command Register 4 (CR4) Setup CR4 as required
Write Write Write	0DH to Address Register (A7–A0) 00H to Address Register (A10–A8) (0x000000)* to Command Reg 5 (CR5)	0 0 1	0 0 0	0 0 0	Address Reg points to Command Register 5 (CR5) Setup CR 5 as required
Write Write Write	04H to Address Register (A7–A0) 00H to Address Register (A10–A8) (xxxxxxx)* to Pixel Mask Register	0 0 1	0 0 0	0 0 0	Address Reg points to Pixel Mask Register Set up Pixel Mask as required
Write	04H to Address Register (A7–A0)	0	0	0	Necessary only if CCR to be used
Write	02H to Address Register (A10–A8)	0	0	0	Address Reg points to Cursor Control Register (CCR)
Write	(xxxxxxx)* to Cursor Control Register	1	0	0	Set up CCR as required
Write	0FH to Address Register (A7–A0)	0	0	0	Necessary only if PLL to be used
Write	00H to Address Register (A10–A8)	0	0	0	Address Reg points to PLL V Register
Write	(xxxxxxx)* to PLL V Register	1	0	0	Set up V as required
Write	0CH to Address Register (A7–A0)	0	0	0	Necessary only if PLL to be used
Write	00H to Address Register (A10–A8)	0	0	0	Address Reg points to PLL R Register
Write	(xxxx0xxx)* to PLL R Register	1	0	0	Set up R as required
Write	09H to Address Register (A7–A0)	0	0	0	Necessary only if PLL to be used
Write	00H to Address Register (A10–A8)	0	0	0	Address Reg points to PLL Command Register (PCR)
Write	(xxxxxxx)* to PLLCommand Register	1	0	0	Set up PCR as required
Write	(xx0xxxxx)* to Mode Register (MR1)	1	1	0	Necessary only if manual claibration is required Toggles MR15
Write	(xx1xxxxx)* to Mode Register (MR1)	1	1	0	
Write	(xx0xxxxx)* to Mode Register (MR1)	1	1	0	

\*x represents either a 0 or 1 value that the bit should be set to, depending on the desired operating mode of the ADV7160/ADV7162.

#### Example

Color Mode: 24-Bit Gamma Corrected Tr Multiplexing: 2:1, Databus: 10-Bit, RAM SYNC: on Green, Pedestal: 0 IRE, Calibr	ue Col M-DA( ration:	or (3) C Res Ever	0-Bits) t solution: y Vertica	hrough Color Palette 10-Bit, al Sync, Internal PLL: 220 MHz (Reference = 15 MHz)
Register Initialization	<b>C</b> 1	<b>C</b> 0	R/W	Comment
Write 07H to Mode Register (MR1) Write 06H to Mode Register (MR1) Write 07H to Mode Register (MR1)	1 1 1	1 1 1	0 0 0	Resets ADV7162* 10-Bit Data Bus, 10-Bit DAC Resolution
Write 05H to Address Register (A7–A0) Write 09H to Command Register 1 (CR1)	0 0	0 0	0 0	Address Reg points to Command Register 1 (CR1) High byte access, Calibrate every Vertical Sync
Write 06H to Address Register (A7–A0) Write 00H to Address Register (A10–A8) Write E4H to Command Reg 2 (CR2)	0 0 1	0 0 0	0 0 0	Address Reg points to Command Register 2 (CR2) 24-Bit True Color, 0 IRE, Sync on Green
Write 07H to Address Register (A7–A0) Write 00H to Address Register (A10–A8) Write 40H to Command Reg 3 (CR3)	0 0 1	0 0 0	0 0 0	Address Reg points to Command Register 3 (CR3) 2:1 Muxing, PRGCKOUT = CLOCK ÷ 4
Write 08H to Address Register (A7–A0) Write 00H to Address Register (A10–A8) Write 00H to Command Reg 4 (CR4)	0 0 1	0 0 0	0 0 0	Address Reg points to Command Register 4 (CR4) DAC GAIN = 3996
Write0DH to Address Register (A7–A0)Write00H to Address Register (A10–A8)Write40H to Command Reg 5 (CR5)	0 0 1	0 0 0	0 0 0	Address Reg points to Command Register 5 (CR5) Internal PLL to be used
Write04H to Address Register (A7–A0)Write00H to Address Register (A10–A8)WriteFFH to Pixel Mask Register	0 0 1	0 0 0	0 0 0	Address Reg points to Pixel Mask Register Set up Pixel Mask
Write 0FH to Address Register (A7–A0) Write 00H to Address Register (A10–A8) Write 09H to PLL V Register	0 0 1	0 0 0	0 0 0	Address Reg points to PLL V Register Set up V value
Write 0CH to Address Register (A7–A0) Write 00H to Address Register (A10–A8) Write 01H to PLL R Register	0 0 1	0 0 0	0 0 0	Address Reg points to PLL R Register Set up R value
Write09H to Address Register (A7–A0)Write00H to Address Register (A10–A8)Write06H to PLL Command Register	0 0 1	0 0 0	0 0 0	Address Reg points to PLL Command Register (PCR) Set up PCR as required
Color Palette RAM Initialization	<b>C</b> 1	<b>C</b> 0	R/W	Comment
Write 00H to Address Register (A7–A0) Write 00H to Address Register (A10–A8) Write 00H (red data) to RAM location (00H) Write 00H (green data) to RAM location (00H) Write 00H (blue data) to RAM location (00H) Write 01H (red data) to RAM location (01H) Write 01H (green data) to RAM location (01H) Write 01H (blue data) to RAM location (01H)	0 0 0 0 0 0 0 0	0 0 1 1 1 1 1 1 1	0 0 0 0 0 0 0 0	Points to Color Palette RAM (Initializes Palette RAM (to a Linear Ramp** ( ( (
Write FFH (red data) to RAM location (FFH) Write FFH (green data) to RAM location (FFH) Write FFH (blue data) to RAM location (FFH)	0 0 0	1 1 1	0 0 0	( ( ( ( RAM Initialization Complete

\*These command lines reset the ADV7162. The pipelines for each of the Red, Green & Blue pixel inputs are synchronously reset to the Multiplexer's "A" input. Mode Register bit MR10 is written by a "1" followed by "0" followed by "1." \*\*This sequence of instructions would, of course, normally be coded using some form of loop instruction.

#### **APPENDIX 5**

#### SIGNATURE ANALYZER

![](_page_39_Figure_3.jpeg)

#### **Signature Register**

The ADV7160/ADV7162 contains onboard circuitry that enables both device and system level test diagnostics. The ADV7160/ ADV7162 has a signature analyzer in the pixel datapath, just before the DAC decoders. The signature analyzer consists of a 33-bit linear feedback shift register. The 30-bit pixel value is fed as a parallel input into the analyzer. The signature analyzer only accumulates a signature during active display time when BLANK is high. Bit CR45 to CR47 of Command Register 4 control the signature analyzer. When CR45 of Command Register 4 is set to Logic "1," the clock to the signature analyzer is enabled. Toggling CR46 low and then high resets the signature analyzer. This is done to give a known starting point before acquiring a signature. CR47 of Command Register 4 controls the feedback inputs to the analyzer. When CR47 of Command Register 4 is a Logic "0," the feedback is disabled and on each clock cycle, the 30-bit pixel value is latched directly into the analyzer. To acquire a signature as the analyzer is clocked, CR47 of Command Register 4 is set to Logic "1." To acquire a signature the following procedure must be followed:

- 1. CR45 and CR47 of Command Register 4 are set to Logic "1" during vertical retrace and CR46 of Command Register 4 is toggled to reset the analyzer.
- 2. A signature is acquired during the following active screen.

3. CR45 of Command Register 4 is set to Logic "0" during the following vertical retrace and the acquired signature is read. At least 20 clock cycles should be allowed for the final pixels of the frame to travel down the pipeline of the ADV7160/ADV7162 before the signature clock is disabled.

The signature analyzer is read from control registers 010H to 013H. These are read only 10-bit registers. The access to these registers depends whether the part is in 8-bit or 10-bit data bus mode and operates in the same way as accessing the color palette.

Address											
Register	CONTROL										
(A10–A0)	REGISTERS	CO	NTE	NTS							
0013H	Signature Misc Register	0	0	0	0	0	0	0	S32	S31	<b>S</b> 0
0012H	Signature Blue Register	S10	<b>S</b> 9	<b>S</b> 8	<b>S</b> 7	<b>S</b> 6	S5	<b>S</b> 4	S3	S2	S1
0011H	Signature Green Register	S20	S19	S18	S17	S16	S15	S14	S13	S12	S11
0010H	Signature Red Register	<b>S</b> 30	S29	S28	S27	S26	S25	S24	S23	S22	S21

	<b>y</b>	(,	
тоі —			
V CF	R1	G1	B1_
CE	R1 <sub>R</sub>	G1 <sub>B</sub>	B1 <sub>B</sub>
R/W	R1c	G1c	B1c
0	R1p	G1 <sub>D</sub>	B1
C1	R2	G2	B2
D9 D8	R2p	G2p	
D7	R2a	G20	в В2С
D6	R2-	62-	B2D
D5		G3.	B3
D4		G3A C3	B3p
D3	R3B	OSB CO	B3o
D2	R3C	G3C	B3
D1	R3 <sub>D</sub>	G3 <sub>D</sub>	DSD P4
D0	R4 <sub>A</sub>	G4 <sub>A</sub>	B4 <sub>A</sub>
THREE-STATE CONTROL	R4 <sub>B</sub>	G4 <sub>B</sub>	B4B
LOADIN	R4 <sub>C</sub>	G4 <sub>C</sub>	B4 <sub>C</sub>
SCKIN	R4 <sub>D</sub>	G4 <sub>D</sub>	B4 <sub>D</sub>
SCKOUT	R5 <sub>A</sub>	G5 <sub>A</sub>	B5 <sub>A</sub>
CLOCK	R5 <sub>B</sub>	G5 <sub>B</sub>	B5 <sub>B</sub>
CLOCK	R5 <sub>C</sub>	G5 <sub>C</sub>	B5 <sub>C</sub>
LOADOUT	R5 <sub>D</sub>	G5 <sub>D</sub>	B5 <sub>D</sub>
PRGCKOUT	R6 <sub>A</sub>	G6 <sub>A</sub>	B6 <sub>A</sub>
PS0 <sub>A</sub>	R6 <sub>B</sub>	G6 <sub>B</sub>	B6 <sub>B</sub>
PS0 <sub>B</sub>	R6c	G6 <sub>C</sub>	B6 <sub>C</sub>
PS0 <sub>C</sub>	R6n	G6n	B6 <sub>D</sub>
PS0 <sub>D</sub>	R7	G7	B7 <sub>A</sub>
PS1 <sub>A</sub>		G7	B7 <sub>B</sub>
PS1 <sub>B</sub>	R7c	GTc	B7 <sub>C</sub>
PS1 <sub>C</sub>	R7p	G75	B7D
PS1 <sub>D</sub>	G0.	B0.	TRISYNC
R0 <sub>A</sub>	CO <sub>A</sub>	B0_	ODD/EVEN
R0 <sub>B</sub>	GOB	Blo	SYNC
R0 <sub>C</sub>	GUC	B0p	BLANK
R0 <sub>D</sub>	, GUD		SYNCOUT
L	J L		— БОО

### **APPENDIX 6**

JTAG TEST PORT (IEEE1149.1)

#### JTAG Boundary Scan Chain

#### JTAG Test Port

JTAG Test Port is a 4-pin interface consisting of: TCK: Test Clock TMS: Test Mode Select TDI: Test Data Input TDO: Test Data Output

To put the ADV7160/ADV7162 into the required mode, the Instruction Register must be loaded.

INSTRUCTION	INSTRUCTION REGISTER CODE
EXTEST	000
SAMPLE/PRELOAD	001
IDCODE	010
PRIVATE 1	011
BYPASS	100
BYPASS	101
BYPASS	110
BYPASS	111

The ADV7160 implementation has the mandatory instructions: Bypass, Sample/Preload and Extest, and the optional instruction: IDCode. There is also one private instruction: Private1. The Private1 instruction is for internal use in production test only.

The IDCode is a 32-bit number which can be scanned out through TDO. Its contents are defined below:

	VERSION (4 BITS)	PART NUMBER (16 BITS)	MANUFACTURER ID (11 BITS)	LSB
ADV7160	1H	2776H	0E5H	1H
ADV7162	1H	2779H	0E5H	1H

The Boundary Scan Chain is a fundamental feature of the JTAG Test Port. It allows all the digital input and output pins on the part to be connected into a shift register between the TDI and TDO pins. The digital pins can be sampled, or controlled over the JTAG port to carry out testing. The is no boundary scan cell on the PLL<sub>REF</sub> pin. The Three-State Control cell controls the three-state status of the microport databus. There are 131 cells in total on the Boundary Scan Chain.

#### **APPENDIX** 7

#### THERMAL AND ENVIRONMENTAL CONSIDERATIONS

The ADV7160/ADV7162 is a very highly integrated monolithic silicon device. This high level of integration, in such a small package, inevitably leads to consideration of thermal and environmental conditions which the ADV7160/ADV7162 must operate in. Reliability of the device is enhanced by keeping it as cool as possible. In order to avoid destructive damage to the device, the absolute maximum junction temperature of 150°C must never be exceeded. Certain applications, depending on ambient temperature and pixel data rates may require forced air cooling or external heatsinks. The following data is intended as a guide in evaluating the operating conditions of a particular application so that optimum device and system performance is achieved.

It should be noted that information on package characteristics published herein may not be the most up to date at the time of reading this. Advances in package compounds and manufacture will inevitably lead to improvements in the thermal data. Please contact your local sales office for the most up-to-date information.

#### **Power Dissipation**

The diagrams show graphs of power dissipation in watts versus pixel clock frequency for the ADV7160 and ADV7162. When using the ADV7162 in Bypass Mode, the Pixel Mask Register should be programmed to 00H to reduce power further.

![](_page_41_Figure_7.jpeg)

The "Typical On-Screen Pattern" corresponds every CLOCK edge (00H, FFH, 00H, ...). The "Typical On-Screen Pattern" corresponds to linear changes in the pixel input (i.e., a Black to White Ramp). In general, color images tend to approximate this characteristic.

#### Typical Power Dissipation vs. Pixel Rate

#### **Package Characteristics**

The tables of thermal characteristics show typical information for the ADV7160 (160-Lead Plastic Power QFP) and AD7162 (160-Lead Plastic QFP) using various values of Airflow.

Junction-to-Case  $(\theta_{JC})$  Thermal Resistance for this particular part is:

 $\begin{array}{l} \theta_{JC} \ (AD7160) = 0.4^{\circ}C/W \\ \theta_{JC} \ (AD7162) = 6.7^{\circ}C/W \\ (Note: \ \theta_{JC} \ is \ independent \ of \ airflow.) \end{array}$ 

#### Heatsinks

The maximum silicon junction temperature should be limited to  $100^{\circ}$ C. Temperatures greater than this will reduce long-term device reliability. To ensure that the silicon junction temperature stays within prescribed limits, the addition of an external heatsink may be necessary. Heatsinks will reduce  $\theta_{JA}$  as shown in the Thermal Characteristics vs. Airflow table.

Table A. Thermal Characteristics vs. Airflow-ADV7160\*

Air Velocity (Linear Feet/min	0 (Still Air)	50	100	200
θ <sub>IA</sub> °C/W				
No Heatsink	25.5	23	21	19
EG&G D10100-28 Heatsink	23	20	18	16
Thermalloy 2290 Heatsink	19	17	15	12

\*These figures do not include thermal conduction through the package leads into the PCB. Thermal conduction through the leads can provide up to  $10^{\circ}$ C/W reduction in  $\theta_{JA}$ .

Table B. Thermal Characteristics vs. Airflow-ADV7162\*

Air Velocity (Linear Feet/min)	0 (Still Air)	50	100	200
θ <sub>IA</sub> °C/W				
No Heatsink	37	32	30	28
EG&G D10850-40 Heatsink	28	24	22	19
EG&G D10851-36 Heatsink	32	24	19	14

\*These figures do not include thermal conduction through the package leads into the PCB. Thermal conduction through the leads can provide up to  $5^{\circ}$ C/W reduction in  $\theta_{IA}$ .

#### **Thermal Model**

The junction temperature of the device in a specific application is given by:

$$T_{\rm J} = T_{\rm A} + P_{\rm D} \left(\theta_{\rm JC} + \theta_{\rm CA}\right) \tag{1}$$

or

$$T_{J} = T_{A} + P_{D} (\theta_{JA})$$
<sup>(2)</sup>

where:

 $T_I$  = Junction Temperature of Silicon (°C)

- $T_A$  = Ambient Temperature (°C)
- $P_D$  = Power Dissipation (W)
- $\theta_{IC}$  = Junction to Case Thermal Resistance (°C/W)
- $\theta_{CA}$  = Case to Ambient Thermal Resistance (°C/W)
- $\theta_{IA}$  = Junction to Ambient Thermal Resistance (°C/W)

#### Package Enhancements for ADV7160

The standard PQFP package has been enhanced to a PowerQuad2 package. This supports an improved thermal performance compared to standard PQFP. In this case, the die is attached to a heat slug so that the power that is dissipated can be conducted to the external surface of the package. This provides a highly efficient path for the transfer of heat to the package surface. The package configuration also provides and efficient thermal path from the ADV7160 to the Printed Circuit Board.

#### PAGE INDEX

Tania Daga
1 opic Page
FEATURES1
GENERAL DESCRIPTION 1 & 15
ADV7160/ADV7162 BLOCK DIAGRAM
ADV7160/ADV7162 SPECIFICATIONS
ADV7160/ADV7162 TIMING CHARACTERISTICS 3-5
TIMING WAVEFORMS 5 11
ABSOLUTE MAXIMUM RATINGS
PIN CONFIGURATIONS
PIN FUNCTION DESCRIPTION 13-14
CIRCUIT DETAILS AND OPERATION
PIXEL PORT
CLOCK CONTROL CIRCUIT
CLOCK CONTROL SIGNALS 17-18
PIXEL PORT MAPPING 19-21
MULTIPLEXING 21-22
MPU PORT
INTERNAL REGISTER CONFIGURATION
COLOR PALETTE ACCESS
ON-CHIP REGISTERS 26
Address Register 26
Mada Dagistar
ID Register
Pixel Mask Register
Command Register 1
Command Register 2
Command Register 3 28-29
Command Register 4 29-30
Command Register 5
PLI Command Register 30
PLI R Register 30
DI I V Pagister 21
Status Degister 20
Devicing Devictor
CURSOR DESCRIPTION
Cursor X-Low and X-High Register
Cursor Y-Low & Y-High Register
Cursor Image
Cursor Y Coordinate Even
Cursor Y Coordinate Odd
Cursor Control Register
DACS & VIDEO OUTPUTS 32-33
APPENDIX 1
Poord Design and Layout Considerations 24.25
ADDENIDING
APPENDIX 2
Typical Frame Buffer Interface
APPENDIX 3
10-Bit DACs and Gamma Correction
APPENDIX 4
Initialization and Programming
APPENDIX 5
Signature Analyzer 40
APPENDIX 6
ITAG Test Port 41
ADDENIDIY 7
Thermal and Environmental Constitutions 40
Infinitian and Environmental Considerations
INDEA
OUTLINE DIMENSIONS

### FIGURE INDEX Figure Title

Figure	Title
1	Load C

1	Load Circuit for Data-Bus Access & Relinquish Times
2	ITAG Port Timing
2	I OADOUT vs. Pivel Clock Input
1	LOADIN va Bival Input Data
4	D' 11 v. A 1 O v. D' 1' '1 M'
2	Pixel Input to Analog Output Pipeline with Minimum
	LOADOUT to LOADIN Delay (8:1 Mode)
6	Pixel Input to Analog Output Pipeline with Maximum
	LOADOUT to LOADIN Delay (8:1 Mode)
7	Pixel Input to Analog Output Pipeline with Minimum
	LOADOUT to LOADIN Delay (4.1 Mode)
0	Pivel Input to Anglog Output Pipeline with Maximum
0	I OADOUT to I OADIN Dalay (4.1 Mode)
•	Dial Dial Control Dial (4:1 Mode)
9	Pixel Input to Analog Output Pipeline with Minimum
	LOADOUT to LOADIN Delay (2:1 Mode)
10	Pixel Input to Analog Output Pipeline with Maximum
	LOADOUT to LOADIN Delay (2:1 Mode)
11	Pixel Clock Input vs. Programmable Clock Output
12	SCKIN vs. SCKOUT
12	Analag Output Baspanaa va Bival Claak
13	Analog Output Response vs, Fixel Clock
14	MPU Timing
15	Multiplexed Color Inputs
16	Clock Control Circuit
17	LOADOUT vs. Pixel Clock
18	SCKOUT Generation Circuit
19	Interface Using SCKIN and SCKOUT
20	PLI Block Diagram
20	PLI Transfor Eurotion
21	
22	PLL Jitter
23	24-Bit to 30-Bit True Color Configuration
24	15-Bit to 24-Bit True Color Configuration
25	8-Bit to 30-Bit Pseudo Color Configuration
26	16-Bit Tue Color Mapping Using R7-R0 and G7-G0
27	15-Bit True Color Mapping Using R7–R3, G7–G3 and
	B7_B3
28	15 Bit True Color Manning Using P6 P0 and G7 C0
20	16 Bit True Color (Presse) Using P7 D0 and C7 C0
29	15 D' T C L (D L) U D C D C L C C C
30	15-Bit True Color (Bypass) Using R6–R0 and G7–G0
31	Direct Interfacing of Video Memory
32	8-Bit Pseudo Color in 8:1 Multiplexing Mode
33	MPU Port and Register Configuration
34	Internal Register Configuration and Address Decoding
35	8-Bit Databus Using 10-Bit DACs
36	8-Bit Databus Using 8-Bit DACs
37	10-Bit Databus Using 10-Bit DACs
20	10 Dit Databus Using 9 Dit DACs
20	10-Bit Databus Using 6-Bit DACs
39	Mode Register I
40	Command Register 1
41	Command Register 2
42	Command Register 3
43	Command Register 4
44	PLL Command Register
45	Cursor Control Register
46	DAC Output Termination
10	Composite Video Wayeform SVNC decoded:
41	Dedected = 7.5 IDE: DAC Cein = 2006
10	Pedestal = $7.5$ IRE; DAC Gain = $3996$
48	
	Composite Video Waveform, SYNC decoded;
	Pedestal = 0 IRE; DAC Gain = 4224
49	Composite Video Waveform, SYNC decoded; Pedestal = 0 IRE; DAC Gain = 4224 Composite Video Waveform, SYNC & TRISYNC
49	Composite Video Waveform, SYNC decoded; Pedestal = 0 IRE; DAC Gain = 4224 Composite Video Waveform, SYNC & TRISYNC decoded; Pedestal = 7.5 IRE; DAC Gain = 5592
49 50	Composite Video Waveform, SYNC decoded; Pedestal = 0 IRE; DAC Gain = 4224 Composite Video Waveform, SYNC & TRISYNC decoded; Pedestal = 7.5 IRE; DAC Gain = 5592 Composite Video Waveform, Pedestal = 0 IRE;
49 50	Composite Video Waveform, SYNC decoded; Pedestal = 0 IRE; DAC Gain = 4224 Composite Video Waveform, SYNC & TRISYNC decoded; Pedestal = 7.5 IRE; DAC Gain = 5592 Composite Video Waveform, Pedestal = 0 IRE; DAC Gain = 4311

#### **OUTLINE DIMENSIONS**

Dimensions shown in inches and (mm).

![](_page_43_Figure_3.jpeg)

S-160 160-Lead Plastic Quad Flatpack

C2013-6-4/95