

## 15W DC-DC CONVERTER


Type	V <sub>in</sub>	V <sub>out</sub>	I <sub>out</sub>
GS15T48-5	40 to 60 V	5 V	3 A

### DESCRIPTION

The GS15T48-5 is a 15W DC-DC converter designed to provide a 5V/3A isolated output from a 48V input in a metal package.

High frequency forward switching configuration ensures high efficiency (80% typ.); input filter minimizes reflected input current and continuous short-circuit protection is provided.


The integral heatsink allows a large power handling capability and it features also an effective shielding to minimize EMI.



### ELECTRICAL CHARACTERISTICS (T<sub>amb</sub> = 25°C unless otherwise specified)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
V <sub>i</sub>	Input Voltage	V <sub>o</sub> = 5V I <sub>o</sub> = 0 to 3A	40	48	60	V
I <sub>i</sub>	Input Current	V <sub>i</sub> = 48V I <sub>o</sub> = 3A		400		mA
I <sub>ir</sub>	Input Reflected Current	V <sub>i</sub> = 48V V <sub>o</sub> = 5V I <sub>o</sub> = 3A		50	80	mApp
I <sub>iq</sub>	Input Quiescent Current	V <sub>i</sub> = 48V V <sub>o</sub> = 5V I <sub>o</sub> = 0A		20		mA
V <sub>o</sub>	Output Voltage	V <sub>i</sub> = 40 to 60V I <sub>o</sub> = 0 to 3A	4.75	5	5.25	V
δV <sub>o</sub>	Line Regulation	V <sub>i</sub> = 40 to 60V I <sub>o</sub> = 3A		10	20	mV
δV <sub>o</sub>	Load Regulation	V <sub>i</sub> = 48V I <sub>o</sub> = 0 to 3A		10	20	mV
V <sub>or</sub>	Output Ripple Voltage	V <sub>i</sub> = 48V I <sub>o</sub> = 3A		20	50	mVpp
I <sub>o</sub>	Output Current	V <sub>i</sub> = 40 to 60V	0		3	A
I <sub>osc</sub>	Output Short-circuit Current	V <sub>i</sub> = 48V		5	6	A
V <sub>is</sub>	Isolation Voltage		750			Vdc
f <sub>s</sub>	Switching Frequency	V <sub>i</sub> = 40 to 60V I <sub>o</sub> = 0 to 3A		250		kHz
η	Efficiency	V <sub>i</sub> = 48V I <sub>o</sub> = 3A		80		%
R <sub>thc</sub>	Thermal Resistance Case to Ambient	T <sub>amb</sub> = 25°C V <sub>i</sub> = 48V I <sub>o</sub> = 3A		8		°C/W
T <sub>cmax</sub>	Maximum Case Temperature				+85	°C
T <sub>stg</sub>	Storage Temperature Range		-40		+105	°C

CONNECTION DIAGRAM AND MECHANICAL DATA



PIN DESCRIPTION

Pin	Function	Description
1	+ Input	DC input voltage (48V nom.)
2	- Input	Return for input voltage
3	Case	Case connection
4	- Output	Negative isolated output voltage
5	+ Output	Positive isolated output voltage

Information furnished is believed to be accurate and reliable. However, SGS-THOMSON Microelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of SGS-THOMSON Microelectronics. Specification mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SGS-THOMSON Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of SGS-THOMSON Microelectronics.

© 1994 SGS-THOMSON Microelectronics – All Rights Reserved

SGS-THOMSON Microelectronics GROUP OF COMPANIES  
Australia - Brazil - France - Germany - Hong Kong - Italy - Japan - Korea - Malaysia - Malta - Morocco - The Netherlands -  
Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A.