

MAX8863/64 Pin-Compatible, Low-Dropout, 120mA Linear Regulators

FEATURES

- Low Cost
- Pin-Compatible with MAX8863/8864
- Stable with Any Type of Capacitors
- Low, 55mV Dropout Voltage @ 50mA lout
- Low, 50µA Operating Supply Current (Even in Dropout)
- 140µsec (typ.) Turn-On Response Time from SHDN
- Low, 350µV_{RMS} Output Noise
- Miniature External Components
- Thermal Overload Protection
- Output Current Limit
- Low-Power Shutdown Mode

APPLICATIONS

- Cordless, PCS, and Cellular Telephones
- PCMCIA Cards
- Modems
- Hand-Held Instruments
- Palmtop Computers
- Electronic Planners

TYPICAL APPLICATION



GENERAL DESCRIPTION

Delivering up to 120mA, the TC1188 and TC1189 are fixed output, low-dropout linear regulators that operate from a +2.5V to +6.0V input range. The 50μ A supply current remains independent of load, making these devices ideal for battery-operated portable equipment.

The output of the TC1188/1189 is preset at 3.15V, 2.84V, 2.80V or 1.80V. (Other output voltage options are available — contact Microchip Technology for more information.) In addition to low-power shutdown, short-circuit protection, and thermal shutdown protection, the TC1189 includes an auto-discharge function that actively discharges the output voltage to ground when the device is in shutdown mode. Both devices are pin-compatible with the Maxim MAX8863/8864 LDOs and are available in SOT-23-5 packages.

ORDERING INFORMATION

Part No.	Package	Temp. Range
TC1188xECT	SOT-23-5	-40°C to +85°C
TC1189xECT	SOT-23-5	-40°C to +85°C

NOTES: 1.The "X" denotes a suffix for output voltage - see table below 2. SOT-23A-5 is equivalent to the EIAJ (SC-74A) 3.Other output voltages available. Please contact Microchip

Technology Inc. for details

Suffix	Output Voltage
Q	1.80
R	2.80
S	2.84
Т	3.15

PIN CONFIGURATION



TC1188 TC1189

ABSOLUTE MAXIMUM RATINGS*

Input Voltage	6.5V
Output Short-Circuit Duration	Infinite
SET to GND	–0.3V to +6.5V
SHDN to GND	–6.5V to +6.5V
SHDN to IN	6.5V to +0.3V
Output Voltage	. (–0.3V) to (V _{IN} + 0.3V)
Continuous Power Dissipation (T _A	= +70°C)
SOT-23-5 (derate 7.1 mW/°C	above +70°C)
`	

Operating Temperature Range	–40°C to 85°C
Storage Temperature Range	–65°C to +160°C
Lead Temperature (Soldering, 10 sec) .	+300°C

* Stresses above those listed under Absolute Maximum Ratings may cause permanent damage to the device. These are stress ratings only and functional operation of the device at these or any other conditions above those indicated in the operational sections of the specifications is not implied. Exposure to Absolute Maximum Rating Conditions for extended periods may affect device reliability.

ELECTRICAL CHARACTERISTICS:	$(V_{IN} = +3.6V, GND = 0V, T_A = T_{MIN}$ to T_{MAX} , unless otherwise specified.
Typical values are at $T_A = +25^{\circ}C.$) (Note 1)	

Symbol	Parameter	Test Conditions			Min	Тур	Max	Unit
VIN	Input Voltage (Note 2)	$V_{OUT} \ge 2.5V$			V _{OUT} + .5V		6.0	V
		$V_{OUT} = 1.8V$			2.7	_	6.0	
V _{OUT}	Output Voltage	$0mA \le I_{OUT} \le 50mA$		Т	3.05	3.15	3.25	V
				S	2.75	2.84	2.93	
				R	2.70	2.80	2.88	
				Q	1.745	1.80	1.85	
lout	Maximum Output Current				120			mA
I _{LIM}	Current Limit (Note 3)				—	280		mA
I _{IN}	Input Current	$I_{OUT} = 0$			—	50	90	μA
	Dropout Voltage (Note 4)	I _{OUT} = 1mA			_	1.1		mV
		I _{OUT} = 50mA			—	55	120	
		I _{OUT} = 100mA			_	110	240	
ΔV_{LNR}	Line Regulation	$V_{IN} = V_{OUT} + 0.5V \text{ to}$	o 6.0V		-0.10	.001	0.10	%/V
		I _{OUT} = 1mA			_	_	_	
ΔV_{LDR}	Load Regulation	I _{OUT} = 0mA to 50mA	L .		_	0.01	0.040	%/mA
	Output Voltage Noise	10Hz to 1MHz	$C_{OUT} = 1 \mu F$		_	350	_	μV _{RMS}
			$C_{OUT} = 100 \mu F$		—	220	_	
t _{WK}	Wake Up Time	V _{IN} = 3.6V			_	10	_	μsec
		$C_{IN} = 1\mu F, C_{OUT} = 1$	μF					
	(from Shutdown Mode)	I _L = 30mA, (See Fig	j . 1)					
t _S	Settling Time	$V_{IN} = 3.6V$			—	140	_	μsec
		$C_{IN} = 1\mu F, C_{OUT} = 1$	lμF					
	(from Shutdown Mode)	$I_L = 30 \text{mA}$, (See Fig	j. 1)					
Shutdown								
V _{IH}	SHDN Input Threshold				2.0	—	-	V
VIL					—	_	0.4	
I _{SHDN}	SHDN Input Bias Current	$V_{SHDN} = V_{IN}$	T _A = +25°C		-	0	100	nA
			$T_A = T_{MAX}$		—	50	—	
IQSHDN	Shutdown Supply Current	$V_{OUT} = 0V$	$T_A = +25^{\circ}C$		-	.002	1	μA
			$T_A = T_{MAX}$		—	0.02		
	Shutdown to Output	$C_{OUT} = 1\mu F$, no load			-	1	—	msec
	Discharge Delay (TC1189)	To 10% of V _{OUT}						
Thermal Pro	tection							
T _{SHDN}	Thermal Shutdown Temperat	ture			-	170	—	°C
ΔT_{SHDN}	Thermal Shutdown Hysteresi	S			—	20	—	°C

MAX8863/64 Pin-Compatible Low-Dropout, 120mA Linear Regulators

NOTES: 1.Limits are 100% production tested at $T_A = +25^{\circ}$ C. Limits over the operating temperature range are ensured through correlation using Statistical Quality Control (SQC) Methods.

2.Validated by line regulation test.

3.Not tested. For design purposes, the current limit should be considered 150mA minimum to 410mA maximum.

4. The dropout voltage is defined as (V_{IN} - V_{OUT}) when V_{OUT} is 100mV below the value of V_{OUT} for V_{IN} = V_{OUT} +2V.

PIN DESCRIPTION

Pin Number	Name	Description
1	SHDN	Active-Low Shutdown Input. A logic low reduces the supply current to 0.1nA. On the TC1189, a logic low also causes the output voltage to discharge to GND. Connect to IN for normal operation.
2	GND	Ground. This pin also functions as a heatsink. Solder to large pads or the circuit board ground plane to maximize thermal dissipation.
3	IN	Regulator Input. Supply voltage can range from +2.5V (+2.7V for V_{OUT} = 1.8V) to +6.0V. Bypass with 1µF to GND (see <i>Capacitor Selection and Regulator Stability</i>).
4	OUT	Regulator Output. Sources up to 120mA. Bypass with a 1µF, <1 Ω typical ESR capacitor to GND.
5	GND	Connect to GND.

DETAILED DESCRIPTION

The TC1188/1189 are fixed output, low-dropout, lowquiescent current linear regulators designed specifically for portable, battery-operated equipment such as cellular phones, cordless phones, and modems. A 1.20V reference, error amplifier, MOSFET driver, P-channel pass transistor, comparator, and internal feedback voltage divider comprise the TC1188/1189 (see Figure 2).

The bandgap reference is connected to the error amplifier's inverting input. The error amplifier then compares the reference with the selected feedback voltage and amplifies the difference. The MOSFET driver, reading the error signal, applies the correct drive to the P-channel pass transistor. If the feedback voltage is lower than the reference, the pass-transistor is pulled lower to allow more current through, and to increase the output voltage. Conversely, if the feedback voltage is higher than the reference, the pass-transistor is pulled up, which allows less current through to the output.

Turn On Response

The turn on response is defined as two separate response categories, Wake Up Time (t_{WK}) and Settling Time (t_s).

The TC1188/89 have a fast Wake Up Time (10μ sec typical) when released from shutdown. See Figure 1 for the **Wake Up Time** designated as t_{WK} . The **Wake Up Time** is defined as the time it takes for the output to rise to 2% of the V_{OUT} value after being released from shutdown.



Figure 1: Wake Up Response Time

The total turn on response is defined as the **Settling Time** (ts), see Figure 1. **Settling Time** (inclusive with t_{WK}) is defined as the condition when the output is within 2% of its fully enabled value (140µsec typical) when released from shutdown. The settling time of the output voltage is dependent on load conditions and output capacitance on V_{OUT} (RC response).

Internal P-Channel Pass Transistor

Featuring a 1.1Ω P-channel MOSFET pass transistor, the TC1188/1189 offers longer battery life than similar designs using PNP pass transistors, which waste current in dropout when the pass transistor saturates. PNP-based regulators also use high base-drive currents under large loads. The P-channel MOSFET, however, does not require a base drive current, which reduces quiescent current. The TC1188/1189 use only 50µA of quiescent current.



Figure 2. Functional Block Diagram

Shutdown

Low input on SHDN shuts down the TC1188/1189 by turning off the pass transistor, control circuit, reference, and all biases. This reduces the supply current to 0.1nA, typical. For normal operation, connect SHDN to IN. When the TC1189 is placed in shutdown mode, the output voltage is actively discharged to ground.

Current Limit

The current limiter on the TC1188/1189 monitors and controls the pass transistor's gate voltage. It estimates the output current, limiting it to 280mA. The current limit should be considered 150mA (min) to 410mA (max) for design purposes. The output can be shorted to ground indefinitely without damaging the device.

Thermal Overload Protection

The TC1188/1189 features thermal overload protection, which limits total power dissipation. The thermal sensor signals the shutdown logic to turn off the pass transistor when the junction temperature exceeds $T_J = +170^{\circ}$ C. This allows the IC's junction temperature to cool by 20°C before the thermal sensor turns the pass transistor back on. This results in a pulsed output during continuous thermal overload conditions.

This feature is designed to protect the TC1188/1189 during thermal events. High load currents and high inputoutput differential voltages may cause a momentary overshoot of 2% to 8% for 200msec when the load is removed. This can be avoided by raising the minimum load current from 0 μ A (+125°C) to 100 μ A (+150°C). The maximum junction temperature rating of +150°C should not be exceeded for continuous operation.

Operating Region and Power Dissipation

The TC1188/1189's maximum power dissipation depends on the thermal resistance of the case and circuit board, the rate of air flow, and the temperature difference between the die junction and ambient air. The devices' power dissipation is P = I_{OUT} (V_{IN} - V_{OUT}); resulting maximum power dissipation is :

$$\mathsf{P}_{\mathsf{MAX}} = (\mathsf{T}_{\mathsf{J}} - \mathsf{T}_{\mathsf{A}}) / \Theta_{\mathsf{JA}}$$

where $(T_J - T_A)$ is the temperature difference between the devices' die junction and the surrounding air, and Θ_{JA} is the thermal resistance of the chosen package to the surrounding air.

The devices' GND pin provides an electrical connection to ground and channels heat away. The GND pin should be connected to ground with a large pad or ground plane.

TC1188 TC1189

MAX8863/64 Pin-Compatible Low-Dropout, 120mA Linear Regulators

APPLICATIONS INFORMATION

Capacitor Selection and Regulator Stability

A 1 μ F capacitor on the input, and a 1 μ F capacitor on the output should generally be used on the TC1188/1189. For better supply-noise rejection and transient response, larger input capacitor values and lower ESR should be used. If the device is several inches from the power source or if large, fast transients are expected, a higher-value input capacitor (10 μ F) may be required.

Using large output capacitors may improve load-transient response, stability, and power-supply rejection. A minimum of 1μ F is recommended for stable operation over the full temperature range with load currents up to 120mA.

Noise

During normal operation, the TC1188/1189 have low $(350\mu V_{RMS})$ output noise. The ADC's power-supply rejection specifications should be considered for applications that include analog-to-digital converters of greater than 12 bits.

Power-Supply Rejection and Operation from Sources Other than Batteries

Power-supply rejection for the TC1188/1189 is 62dB at low frequencies, rolling off above 300Hz. Power supply noise rejection is primarily controlled by the output capacitor at frequencies of more than 20KHz.

Supply noise rejection and transient response can be improved when operating from sources other than batteries by increasing the values of the input and output capacitors, and using passive filtering techniques.

Load Transient Considerations

With the TC1188/1189, typical overshoot for step changes in the load current from 0mA to 50mA is 12 mV. To lessen transient spikes, increase the output capacitor's value, and decrease its ESR.

Input-Output (Dropout) Voltage

A regulator's dropout voltage determines the lowest usable supply voltage. This determines the useful end-of-life battery voltage for battery-powered systems. Since the TC1188/1189 uses a P-channel MOSFET pass transistor, the devices' dropout voltage is a function of $R_{DS(ON)}$ multiplied by the load current.

MAX8863/64 Pin-Compatible Low-Dropout, 120mA Linear Regulators

TC1188 TC1189

TYPICAL CHARACTERISTICS



MAX8863/64 Pin-Compatible Low-Dropout, **120mA Linear Regulators**

TC1188 TC1189



MARKINGS



(1) & (2) = part number code + temperature range and voltage

TC1188 (V)	Code
1.80	G4
2.80	G3
2.84	G2
3.15	G1
TC1189 (V)	Code
TC1189 (V) 1.80	Code H4
TC1189 (V) 1.80 2.80	Code H4 H3
TC1189 (V) 1.80 2.80 2.84	Code H4 H3 H2

(3) represents year and guarter code

(4) represents lot ID number

TIME (100µs/Div)

TAPING FORM



TYPICAL CHARACTERISTICS (CONT.)

MAX8863/64 Pin-Compatible Low-Dropout, 120mA Linear Regulators

TC1188 TC1189

PACKAGE DESCRIPTION





WORLDWIDE SALES AND SERVICE

AMERICAS

Corporate Office 2355 West Chandler Blvd. Chandler, AZ 85224-6199 Tel: 480-792-7200 Fax: 480-792-7277 Technical Support: 480-792-7627 Web Address: http://www.microchip.com Rocky Mountain 2355 West Chandler Blvd. Chandler, AZ 85224-6199 Tel: 480-792-7966 Fax: 480-792-7456 Atlanta 500 Sugar Mill Road, Suite 200B Atlanta, GA 30350 Tel: 770-640-0034 Fax: 770-640-0307 Austin Analog Product Sales 8303 MoPac Expressway North Suite A-201 Austin, TX 78759 Tel: 512-345-2030 Fax: 512-345-6085 Boston 2 Lan Drive, Suite 120 Westford, MA 01886 Tel: 978-692-3848 Fax: 978-692-3821 Boston Analog Product Sales Unit A-8-1 Millbrook Tarry Condominium 97 Lowell Road Concord, MA 01742 Tel: 978-371-6400 Fax: 978-371-0050 Chicago 333 Pierce Road, Suite 180 Itasca, IL 60143 Tel: 630-285-0071 Fax: 630-285-0075 Dallas 4570 Westgrove Drive, Suite 160 Addison, TX 75001 Tel: 972-818-7423 Fax: 972-818-2924 Dayton Two Prestige Place, Suite 130 Miamisburg, OH 45342 Tel: 937-291-1654 Fax: 937-291-9175 Detroit Tri-Atria Office Building 32255 Northwestern Highway, Suite 190 Farmington Hills, MI 48334

Tel: 248-538-2250 Fax: 248-538-2260 Los Angeles 18201 Von Karman, Suite 1090

Irvine, CA 92612 Tel: 949-263-1888 Fax: 949-263-1338 Mountain View

Analog Product Sales

Malog Frouder Gales 1300 Terra Bella Avenue Mountain View, CA 94043-1836 Tel: 650-968-9241 Fax: 650-967-1590

New York

150 Motor Parkway, Suite 202 Hauppauge, NY 11788 Tel: 631-273-5305 Fax: 631-273-5335 **San Jose** Microchip Technology Inc. 2107 North First Street, Suite 590 San Jose, CA 95131 Tel: 408-436-7950 Fax: 408-436-7955 **Toronto** 6285 Northam Drive, Suite 108 Mississauga, Ontario L4V 1X5, Canada Tel: 905-673-0699 Fax: 905-673-6509

ASIA/PACIFIC

China - Beijing Microchip Technology Beijing Office Unit 915 New China Hong Kong Manhattan Bldg. No. 6 Chaoyangmen Beidajie Beijing, 100027, No. China Tel: 86-10-85282100 Fax: 86-10-85282104 China - Shanghai Microchip Technology Shanghai Office Room 701, Bldg. B Far East International Plaza No. 317 Xian Xia Road Shanghai, 200051 Tel: 86-21-6275-5700 Fax: 86-21-6275-5060 Hong Kong Microchip Technology Hongkong Ltd. Unit 901, Tower 2, Metroplaza Kwai Fong, N.T., Hong Kong Tel: 852-2401-1200 Fax: 852-2401-3431 India Microchip Technology Inc. India Liaison Office **Divyasree Chambers** 1 Floor, Wing A (A3/A4) No. 11, OiShaugnessey Road Bangalore, 560 025, India Tel: 91-80-2290061 Fax: 91-80-2290062 Japan Microchip Technology Intl. Inc. Benex S-1 6F 3-18-20, Shinyokohama Kohoku-Ku, Yokohama-shi Kanagawa, 222-0033, Japan Tel: 81-45-471- 6166 Fax: 81-45-471-6122 Korea Microchip Technology Korea 168-1, Youngbo Bldg. 3 Floor Samsung-Dong, Kangnam-Ku Seoul, Korea Tel: 82-2-554-7200 Fax: 82-2-558-5934

ASIA/PACIFIC (continued)

Singapore Microchip Technology Singapore Pte Ltd. 200 Middle Road #07-02 Prime Centre Singapore, 188980 Tel: 65-334-8870 Fax: 65-334-8850 **Taiwan** Microchip Technology Taiwan 11F- 3, No. 207 Tung Hua North Road Taipei, 105, Taiwan Tel: 886-2-2717-7175 Fax: 886-2-2545-0139

EUROPE

Australia Microchip Technology Australia Pty Ltd Suite 22, 41 Rawson Street Epping 2121, NSW Australia Tel: 61-2-9868-6733 Fax: 61-2-9868-6755 Denmark Microchip Technology Denmark ApS Regus Business Centre Lautrup hoj 1-3 Ballerup DK-2750 Denmark Tel: 45 4420 9895 Fax: 45 4420 9910 France Arizona Microchip Technology SARL Parc díActivite du Moulin de Massy 43 Rue du Saule Trapu Batiment A - ler Etage 91300 Massy, France Tel: 33-1-69-53-63-20 Fax: 33-1-69-30-90-79 Germany Arizona Microchip Technology GmbH Gustav-Heinemann Ring 125 D-81739 Munich, Germany Tel: 49-89-627-144 0 Fax: 49-89-627-144-44 Germany Analog Product Sales Lochhamer Strasse 13 D-82152 Martinsried, Germany Tel: 49-89-895650-0 Fax: 49-89-895650-22 Italy Arizona Microchip Technology SRL Centro Direzionale Colleoni Palazzo Taurus 1 V. Le Colleoni 1 20041 Agrate Brianza Milan, Italy Tel: 39-039-65791-1 Fax: 39-039-6899883 **United Kingdom** Arizona Microchip Technology Ltd. 505 Eskdale Road Winnersh Triangle Wokingham Berkshire, England RG41 5TU Tel: 44 118 921 5869 Fax: 44-118 921-5820

All rights reserved. © 2001 Microchip Technology Incorporated. Printed in the USA. 1/01

01/09/01

Information contained in this publication regarding device applications and the like is intended through suggestion only and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications. No representation or warranty is given and no liability is assumed by Microchip Technology Incorporated with respect to the accuracy or use of such information, or infringement of patents or other intellectual property rights arising from such use or otherwise. Use of Microchip's products as critical components in life support systems is not authorized except with express written approval by Microchip. No licenses are conveyed, implicitly or otherwise, except as maybe explicitly expressed herein, under any intellec-tual property rights. The Microchip logo and name are registered trademarks of Microchip Technology Inc. in the U.S.A. and other countries. All rights reserved. All other trademarks mentioned herein are the property of their respective companies. All rights reserved. © 2001 Microchip Technology Incorporated. Printed in the USA. 1/01 Printed on recycled paper.