
Single BiCMOS rail-to-rail micropower comparator

Features

- Rail-to-rail inputs
- Open drain output
- Supply operation from 2.7V to 10V
- Typical supply current: 6 μ A @ 5V
- Response time of 0.5 μ s at 5V
- Low input current
- ESD protection: 2kV (HBM), 200V (MM)
- Available in tiny SOT23-5 package


Applications

- Battery-powered systems
- Notebooks and PDAs
- PCMCIA cards
- Cellulare and mobile communication
- Alarm and security systems
- Replacement of amplifiers used in comparator configuration for better performance

Description


The TS7221 is a micropower comparator featuring rail-to-rail input performance in a tiny SOT23-5 package. This comparator is ideally suited to space and weight-critical applications. It is fully specified at 2.7V, 5V and 10V operation over the industrial temperature range (-40°C to +85°C).

The TS7221 features an open drain output stage. The speed-to-power ratio makes this device ultra-versatile for a wide range of applications.



L
SOT23-5L

TS7221 Open drain output



1 Absolute maximum ratings

Table 1. Absolute maximum ratings

Symbol	Parameter	Value	Unit
ESD	Human body model (HBM)	2000	V
	Machine model (MM)	200	
V_{ID}	Differential input voltage	$(V_{CC}^-) - 0.3$ to $(V_{CC}^+) + 0.3$	V
V_{IN}	Input voltage ⁽¹⁾	$(V_{CC}^-) - 0.3$ to $(V_{CC}^+) + 0.3$	V
V_{OUT}	Output voltage	12	V
V_{CC}	Supply voltage	12	V
I_{IN}	Current at input pins ⁽¹⁾	± 5	mA
I_{OUT}	Current at output pin	± 30	mA
T_{Lead}	Lead temperature (soldering 10 seconds, Pb-free package)	260	°C
T_{stg}	Storage temperature	-65 to +150	°C
T_J	Junction temperature	150	°C
P_D	Power dissipation ⁽²⁾ SOT23-5	500	mW

1. The magnitude of input voltages must never exceed 0.3V beyond the supply voltage.

2. $T_J = 150^\circ\text{C}$, $T_{AMB} = 25^\circ\text{C}$ with $R_{TH-JA} = 250^\circ\text{C/W}$ for SOT23-5 package.

Table 2. Operating conditions

Symbol	Parameter	Value	Unit
V_{CC}	Supply voltage	2.7 to 10	V
T_{amb}	Ambient temperature	-40 to +85	°C
V_{icm}	Common mode input voltage range	$(V_{CC}^-) - 0.3$ to $(V_{CC}^+) + 0.3$	V

2 Electrical characteristics

Table 3. Electrical characteristics at $V_{CC}^+ = 2.7V$, $T_{amb} = 25^\circ C$ (unless otherwise specified)⁽¹⁾

Symbol	Parameter	Min.	Typ.	Max.	Unit
V_{IO}	Input offset voltage (full common mode range) – TS7221A at $T_{min} \leq T_{amb} \leq T_{max}$ – TS7221B at $T_{min} \leq T_{amb} \leq T_{max}$			7 10 15 18	mV
ΔV_{IO}	Input offset voltage drift with temperature		6		$\mu V/^\circ C$
I_{IB}	Input bias current ⁽²⁾ at $T_{min} \leq T_{amb} \leq T_{max}$		1	300 600	pA
I_{IO}	Input offset current ⁽²⁾ at $T_{min} \leq T_{amb} \leq T_{max}$		1	150 300	pA
CMRR	Common-mode rejection ratio ($0 < V_{icm} < 2.7V$)		65		dB
PSRR	Power supply rejection ratio ($2.7 < V_{CC} < 10V$)		80		dB
A_{VD}	Voltage gain ⁽³⁾		240		dB
V_{icm}	Input common mode voltage range at $T_{min} \leq T_{amb} \leq T_{max}$	-0.3 0.0		3 2.7	V
I_{OH}	High level output voltage ($I_N^+ = 0.5V$, $I_N^- = 0V$ & $OUT = 10V$)		0.1	500	nA
V_{OL}	Low level output voltage, $I_{sink} = 5mA$ at $T_{min} \leq T_{amb} \leq T_{max}$		0.2	0.35 0.45	V
I_{CC}	Supply current Output low Output high		6 8	12 14	μA
T_{PLH}	Response time low to high ($V_{ic} = 1.35V$, $C_L = 50pF$, $R_L = 10k\Omega$) Overdrive = 10mV Overdrive = 100mV		1.5 0.6		μs
T_{PHL}	Response time high to low ($V_{ic} = 1.35V$, $C_L = 50pF$, $R_L = 10k\Omega$) Overdrive = 10mV Overdrive = 100mV		1.5 0.5		μs
T_F	Fall time $C_L = 50pF$, $R_L = 5k\Omega$, Overdrive = 10mV		0.3		μs
T_R	Rise time $C_L = 50pF$, $R_L = 5k\Omega$, Overdrive = 10mV		0.3		μs

1. Limits are 100% production tested at $+25^\circ C$. Behavior at the temperature range limits is guaranteed through correlation and by design.
2. Maximum values include unavoidable inaccuracies of industrial testing.
3. Design evaluation.

Table 4. Electrical characteristics for $V_{CC}^+ = 5V$, $T_{amb} = 25^\circ C$ (unless otherwise specified)⁽¹⁾

Symbol	Parameter	Min.	Typ.	Max.	Unit
V_{IO}	Input offset voltage (full common mode range) – TS7221A at $T_{min} \leq T_{amb} \leq T_{max}$ – TS7221B $T_{min} \leq T_{amb} \leq T_{max}$			7 10 15 18	mV
ΔV_{IO}	Input offset voltage drift with temperature		6		$\mu V/^\circ C$
I_{IB}	Input bias current ⁽²⁾ at $T_{min} \leq T_{amb} \leq T_{max}$		1	300 600	pA
I_{IO}	Input offset current ⁽²⁾ at $T_{min} \leq T_{amb} \leq T_{max}$		1	150 300	pA
CMRR	Common-mode rejection ratio ($0 < V_{icm} < 5V$)		70		dB
PSRR	Power supply rejection ratio ($2.7 < V_{CC} < 10V$)		80		dB
A_{VD}	Voltage gain ⁽³⁾		240		dB
V_{icm}	Input common mode voltage range at $T_{min} \leq T_{amb} \leq T_{max}$	-0.3 0.0		5.3 5.0	V
I_{OH}	High level output voltage ($I_N^+ = 0.5V$, $I_N^- = 0V$ & $OUT = 10V$)		0.1	500	nA
V_{OL}	Low level output voltage, $I_{sink} = 5mA$ at $25^\circ C$ at $T_{min} \leq T_{amb} \leq T_{max}$		0.2	0.40 0.55	V
I_{CC}	Supply current Output low Output high		6 8	12 14	μA
T_{PLH}	Response time low to high ($V_{ic} = 2.5V$, $C_L = 50pF$, $R_L = 10k\Omega$) Overdrive = 10mV Overdrive = 100mV		2 0.5		μs
T_{PHL}	Response time high to low ($V_{ic} = 2.5V$, $C_L = 50pF$, $R_L = 10k\Omega$) Overdrive = 10mV Overdrive = 100mV		2 0.4		μs
T_F	Fall time $C_L = 50pF$, $R_L = 5k\Omega$, Overdrive = 10mV		0.3		μs
T_R	Rise time $C_L = 50pF$, $R_L = 5k\Omega$, Overdrive = 10mV		0.3		μs

1. Limits are 100% production tested at $+25^\circ C$. Behavior at the temperature range limits is guaranteed through correlation and by design.
2. Maximum values include unavoidable inaccuracies of industrial testing.
3. Design evaluation.

Table 5. Electrical characteristics for $V_{CC}^+ = 10V$, $T_{amb} = 25^\circ C$ (unless otherwise specified)⁽¹⁾

Symbol	Parameter	Min.	Typ.	Max.	Unit
V_{IO}	Input offset voltage (full common mode range) – TS7221A at $T_{min} \leq T_{amb} \leq T_{max}$ – TS7221B $T_{min} \leq T_{amb} \leq T_{max}$			7 10 15 18	mV
ΔV_{IO}	Input offset voltage drift with temperature		6		$\mu V/^\circ C$
I_{IB}	Input bias current ⁽²⁾ at $T_{min} \leq T_{amb} \leq T_{max}$		1	300 600	pA
I_{IO}	Input offset current ⁽²⁾ at $T_{min} \leq T_{amb} \leq T_{max}$		1	150 300	pA
CMRR	Common-mode rejection ratio ($0 < V_{icm} < 10V$)		75		dB
PSRR	Power supply rejection ratio ($2.7 < V_{CC} < 10V$)		80		dB
A_{VD}	Voltage gain ⁽³⁾		240		dB
V_{ICM}	Input common mode voltage range at $T_{min} \leq T_{amb} \leq T_{max}$	-0.3 0.0		10.3 10.0	V
I_{OH}	High level output voltage ($I_{N^+}=0.5V$, $I_{N^-}=0V$ & $OUT=10V$)		0.1	500	nA
V_{OL}	Low level output voltage, $I_{sink} = 5mA$ at $T_{min} \leq T_{amb} \leq T_{max}$		0.2	0.40 0.55	V
I_{CC}	Supply current Output low Output high		7 10	14 16	μA
T_{PLH}	Response time low to high ($V_{ic} = 5V$, $C_L = 50pF$, $R_L=10k\Omega$) Overdrive = 10mV Overdrive = 100mV		3 0.5		μs
T_{PHL}	Response time high to low ($V_{ic} = 5V$, $C_L = 50pF$, $R_L=10k\Omega$) Overdrive = 10mV Overdrive = 100mV		4 0.4		μs
T_F	Fall time $C_L = 50pF$, $R_L=5k\Omega$, Overdrive = 10mV		0.3		μs
T_R	Rise time $C_L = 50pF$, $R_L=5k\Omega$, Overdrive = 10mV		0.3		μs

1. Limits are 100% production tested at $+25^\circ C$. Behavior at the temperature range limits is guaranteed through correlation and by design.
2. Maximum values include unavoidable inaccuracies of industrial testing.
3. Design evaluation.

Figure 1. Supply current vs. supply voltage (output low)




Figure 2. Supply current vs. supply voltage (output high)






Figure 3. Output sinking current vs. output voltage at $V_{CC} = +2.7V$, $V_{CC} = +5V$ Figure 4. V_{IO} vs. V_{ICM} and temperature at $V_{CC} = 2.7V$ Figure 5. V_{IO} vs. V_{ICM} and temperature at $V_{CC} = 5V$ Figure 6. V_{IO} vs. V_{ICM} and temperature at $V_{CC} = 10V$ 

Figure 7. T_{PLH} vs V_{icm} at $V_{CC} = 10V$ and 10mV overdrive Figure 8. T_{PLH} vs V_{icm} at $V_{CC} = 10V$ and 100mV overdrive




Figure 9. T_{PLH} vs V_{icm} at $V_{CC} = 5V$ and 10mV overdrive Figure 10. T_{PLH} vs V_{icm} at $V_{CC} = 5V$ and 100mV overdrive




Figure 11. T_{PHL} vs V_{icm} at $V_{CC} = 10V$ and 10mV overdrive Figure 12. T_{PHL} vs V_{icm} at $V_{CC} = 10V$ and 100mV overdrive




Figure 13. T_{PHL} vs V_{icm} at $V_{CC}=5V$ and 10mV overdrive





Figure 14. T_{PHL} vs V_{icm} at $V_{CC}=5V$ and 100mV overdrive



3 Package information

In order to meet environmental requirements, STMicroelectronics offers these devices in ECOPACK® packages. These packages have a lead-free second level interconnect. The category of second level interconnect is marked on the package and on the inner box label, in compliance with JEDEC Standard JESD97. The maximum ratings related to soldering conditions are also marked on the inner box label. ECOPACK is an STMicroelectronics trademark. ECOPACK specifications are available at: www.st.com.

Figure 15. SOT23-5L package mechanical data

Ref.	Dimensions					
	Millimeters			Mils		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	0.90		1.45	35.4		57.1
A1	0.00		0.15	0.00		5.9
A2	0.90		1.30	35.4		51.2
b	0.35		0.50	13.7		19.7
C	0.09		0.20	3.5		7.8
D	2.80		3.00	110.2		118.1
E	2.60		3.00	102.3		118.1
E1	1.50		1.75	59.0		68.8
e		0.95			37.4	
e1		1.9			74.8	
L	0.35		0.55	13.7		21.6

The figure includes two mechanical drawings of the SOT23-5L package. The left drawing is a side view showing dimensions A (total width), A1 (lead width), A2 (body width), b (lead thickness), C (lead height), and L (lead length). The right drawing is a top view showing dimensions D (body length), E (body width), E1 (lead width), e (pitch), and e1 (total pitch).

4 Ordering information

Table 6. Order codes

Part number	Temperature range	Package	Packing	Marking
TS7221AILT	-40°C, +85°C	SOT23-5L	Tape & reel	K518
TS7221BILT				K519
TS7221AIYLT ⁽¹⁾		SOT23-5L (automotive grade)		K522
TS7221BIYLT ⁽¹⁾				K523

1. Qualified and characterized according to AEC Q100 and Q003 or equivalent, advanced screening according to AEC Q001 & Q 002 or equivalent.

5 Revision history

Table 7. Document revision history

Date	Revision	Changes
1-Dec-2002	1	Initial release
1-Sep-2005	2	Update of datasheet presentation and format. Change of T_{lead} temperature in Table 1 on page 2 , to reflect change to Pb-free package. Corrections to V_{icm} upper rail parameters in Electrical characteristics tables. Addition of Pb-free information in Section 3: Package information on page 9 . Correction to package mechanical data given in Figure 15 on page 9 .
26-Mar-2007	3	Added automotive grade part numbers in Section 4: Ordering information on page 10 .
5-Jul-2007	4	Corrected automotive grade part numbers in Table 6: Order codes .

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED ST REPRESENTATIVE, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2007 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com

