

# E-Series Surface Mount Mixer

## 200 - 3000 MHz

## EMRS-30, EMRSJ-30

V3.00

### Features

- LO Power: +7 dBm
- Up to +1 dBm RF
- Surface Mount

### Specifications @ 25°C

Frequency Range		
RF		200 - 3000 MHz
LO		200 - 3000 MHz
IF		DC - 1000 MHz
Conversion Loss (dB)	Typical	Maximum
200 - 3000 MHz	7.5	9.8
Isolation (dB)	Typical	Minimum
LO to RF		
200 - 3000 MHz	24	17
LO to IF		
200 - 3000 MHz	20	7

### Operating Characteristics

Impedance	50 Ohms Nominal
RF input for 1dB Compression	+ 1 dBm
DC Polarity	Positive

### Ordering Information

<b>Part No.</b>	<b>Packaging</b>
EMRS-30	SM-41 in Tubes
EMRSJ-30	SM-57 in Tubes


### Absolute Maximum Ratings

Parameter	Absolute Maximum
RF Power	50 mW
Peak IF Current	40 mA
Storage Temperature	-55°C to 100°C
Operating Temperature	-55°C to 100°C
Pin Temperature (10 Seconds)	260°C

### Pin Configuration (Typical)


Function	Pin No.
LO	1
RF	4
IF	5
Ground	2,3,6

### SM-41



Dimensions in ( ) are in mm.  
 Unless Otherwise Noted: .x = ±0.04 (1.00)  
 .xx = ±0.02 (0.50)  
 .xxx = ±0.010 (0.250)

### SM-57



Dimensions in ( ) are in mm.  
 Unless Otherwise Noted: .x = ±0.04 (1.00)  
 .xx = ±0.02 (0.50)  
 .xxx = ±0.010 (0.250)

Specifications Subject to Change Without Notice.

S 0739 C, S 1106 A

M/A-COM, Inc.

1

North America: Tel. (800) 366-2266 ■ Asia/Pacific: Tel. +81 (03) 3226-1671 ■ Europe: Tel. +44 (1344) 869 595  
 Fax (800) 618-8883 Fax +81 (03) 3226-1451 Fax +44 (1344) 300 020