

# E-Series 4-Way 0° Power Divider

## 5 - 750 MHz

**ES-4-7**

V3.00

### Features

- 4 Way
- 0°
- Surface Mount

### Specifications @ 25°C

Frequency Range	5 - 750 MHz		
Insertion Loss	Typical	Maximum	
	5 - 50 MHz	0.5 dB	0.8 dB
	50 - 375 MHz	0.7 dB	1.1 dB
	375 - 750 MHz	0.8 dB	1.5 dB
Isolation	Typical	Minimum	
	5 - 50 MHz	35 dB	20 dB
	50 - 375 MHz	35 dB	20 dB
	375 - 750 MHz	23 dB	15 dB
Amplitude Unbalance	Maximum		
	5 - 50 MHz	0.1 dB	
	50 - 375 MHz	0.2 dB	
	375 - 750 MHz	0.5 dB	
Phase Unbalance	Maximum		
	5 - 50 MHz	1°	
	50 - 375 MHz	5°	
	375 - 750 MHz	10°	
Input and Output Return Loss	Minimum		
	15 dB		

### Operating Characteristics

Impedance	50 Ohms Nominal
-----------	-----------------


### Ordering Information

<b>Part No.</b>	<b>Packaging</b>
ES-3-1X1	Tube
ES-3-1X1TR	Forward Tape and Reel

### Absolute Maximum Ratings

Parameter	Absolute Maximum
Maximum Power Rating	1 Watt
Internal Load Dissipation	0.125 Watt
Pin Temp (10 sec)	260°C
Storage Temperature	-55°C to 100°C
Operating Temperature	0°C to 70°C

### SM-46



Dimensions in ( ) are in mm.  
 Unless Otherwise Noted: .x = ±0.04 (1.00)  
 .xx = ±0.02 (0.50)  
 .xxx = ±0.010 (0.250)

### Pin Configuration

Function	Pin No.
Ground	1,5,7
Input	3
Port 1	2
Port 2	4
Port 3	6
Port 4	8

Specifications Subject to Change Without Notice.

**M/A-COM, Inc.**

North America: Tel. (800) 366-2266 ■ Asia/Pacific: Tel. +81 (03) 3226-1671 ■ Europe: Tel. +44 (1344) 869 595  
 Fax (800) 618-8883 Fax +81 (03) 3226-1451 Fax +44 (1344) 300 020