

Two-Way Power Divider, 10 - 2000 MHz

DS-/DSS-313


Features

- Fully Hermetic Package
- Loss: 0.6 dB Typical Midband
- Isolation: 28 dB Typical Midband
- VSWR: 1.2:1 Typical Midband
- Impedance: 50 Ohms Nominal
- Maximum Power Rating or Input Power: 250 mW Max.
- Internal Load Dissipation: 50 mW Max.
- MIL-STD-202 Screening Available

Description

A Power Divider is ideally a loss less reciprocal device which can also perform vector summation of two or more signals and thus is sometimes called a power combiner or summer.


SF-1 (DSS-313)



Pin Configuration (DSS-313)

Pin No.	Function	Pin No.	Function
1	Σ	3	GND
2	Output C	4	Output D

FP-2 (DS-313)



Pin Configuration (DS-313)

Pin No.	Function	Pin No.	Function
1	Σ	5	GND
2	GND	6	GND
3	GND	7	GND
4	Output C	8	Output D

DS-313 Electrical Specifications¹: $T_A = -55^{\circ}\text{C}$ to $+85^{\circ}\text{C}$

Parameter	Test Conditions	Frequency	Units	Min	Typ	Max
Insertion Loss	Less Coupling	20 - 1000 MHz	dB	—	—	1.1
		10 - 1500 MHz	dB	—	—	1.3
		1500 - 2000 MHz	dB	—	—	1.8
Isolation	—	20 - 1000 MHz	dB	23	—	—
		10 - 1500 MHz	dB	18	—	—
		1500 - 2000 MHz	dB	12	—	—
Amplitude Balance	—	20 - 1000 MHz	dB	—	—	0.3
		10 - 1500 MHz	dB	—	—	0.4
		1500 - 2000 MHz	dB	—	—	0.6
Phase Balance	—	20 - 1000 MHz	°	—	—	4
		10 - 1500 MHz	°	—	—	6
		1500 - 2000 MHz	°	—	—	8
VSWR	All Ports	20 - 1000 MHz	Ratio	—	—	1.5:1
		10 - 1500 MHz	Ratio	—	—	1.6:1
		1500 - 2000 MHz	Ratio	—	—	1.8:1

DSS-113 Electrical Specifications¹: $T_A = -55^{\circ}\text{C}$ to $+85^{\circ}\text{C}$

Parameter	Test Conditions	Frequency	Units	Min	Typ	Max
Insertion Loss	Less Coupling	20 - 1000 MHz	dB	—	—	1.1
		10 - 1500 MHz	dB	—	—	1.3
		1500 - 2000 MHz	dB	—	—	1.8
Isolation	—	20 - 1000 MHz	dB	22	—	—
		10 - 1500 MHz	dB	18	—	—
		1500 - 2000 MHz	dB	12	—	—
Amplitude Balance	—	20 - 1000 MHz	dB	—	—	0.3
		10 - 1500 MHz	dB	—	—	0.4
		1500 - 2000 MHz	dB	—	—	0.6
Phase Balance	—	20 - 1000 MHz	°	—	—	5
		10 - 1500 MHz	°	—	—	8
		1500 - 2000 MHz	°	—	—	11
VSWR	All Ports	20 - 1000 MHz	Ratio	—	—	1.5:1
		10 - 1500 MHz	Ratio	—	—	1.6:1
		1500 - 2000 MHz	Ratio	—	—	1.8:1

1. All specifications apply with 50 ohm source and load impedance.

M/A-COM Inc. and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice. M/A-COM makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does M/A-COM assume any liability whatsoever arising out of the use or application of any product(s) or information.

Visit www.macom.com for additional data sheets and product information.


■ North America: Tel. (800) 366-2266
 ■ Asia/Pacific: Tel.+81-44-844-8296, Fax +81-44-844-8298
 ■ Europe: Tel. +44 (1344) 869 595, Fax+44 (1344) 300 020

tyco / Electronics


M/A-COM

Typical Performance Curves


Insertion Loss - Ports S-C, S-D



Isolation - Ports C-D



VSWR



Ordering Information

Part Number	Package
DS-313 PIN	FP-2
DSS-313 PIN	SF-1

M/A-COM Inc. and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice. M/A-COM makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does M/A-COM assume any liability whatsoever arising out of the use or application of any product(s) or information.

Visit www.macom.com for additional data sheets and product information.

- North America: Tel. (800) 366-2266
- Asia/Pacific: Tel.+81-44-844-8296, Fax +81-44-844-8298
- Europe: Tel. +44 (1344) 869 595, Fax+44 (1344) 300 020