


[English](#) [日本語](#)
Electronics
a vital part of your world
**Find
Answers:**

Tuesday, 13 September, 2005

CATALOG
Cross Reference

[Competitive Products](#)
[Military Spec P/Ns](#)
[Tyco Brand P/Ns](#)

- [Part Number Search](#)
- [Document Search](#)
- [Product Type Search](#)
- [Product Family Search](#)
- [Alphabetical Search](#)
- [RoHS/ELV Compliance & Alternates](#)
- [CAD Model Search](#)
- [Brand Search](#)
- [Tool Search](#)
- [Multiple Part Comparison](#)
- [Lead Free Solutions](#)
- [Help/Glossary](#)

[Home](#)

e-bulletin newsletter
SUBSCRIBE NOW!
 click here

Ribbon Cable Connector System (AMP-LATCH)

↳ Pin and Pinless Headers (AMP-LATCH)

AMP **3-1437064-9**  Active
Not ELV or RoHS Compliant
(Corporate P/N: 3-1437064-9)
Search for Compliant (RoHS/ELV)
Alternates
Search for Parts

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information

General Information	eCommerce	Related Part Information
<ul style="list-style-type: none"> ✦ General Info ✦ Sales Info ✦ Assembly Subcontractors 	<ul style="list-style-type: none"> ✦ Pricing ✦ Product Availability 	<ul style="list-style-type: none"> ✦ Tooling

Searchable Features:

Brand:	AMP
RoHS/ELV Compliance:	Not ELV/RoHS compliant
Lead Free Solder Processes:	Wave solder capable to 240° C, Wave solder capable to 265° C
Connector Type:	Pin Headers
Number of Positions:	34
Centerline, Matrix (mm [in]):	2.54 x 2.54 [.100 x .100]
PCB Mount Angle:	Vertical
PCB Retention Feature:	Without

Other Properties:

Post Size (mm [in]):	0.64 [.025]
Contact Shape:	Square
Daisy Chain:	With
Profile:	Low
Shrouded:	Yes
Mating Polarization:	Yes
Housing Material:	Thermoplastic
Housing Flammability Rating:	UL 94V-0
Housing Color:	Blue
Contact Material:	Phosphor Bronze
Shrouded End Dimension (mm [in]):	3.81 [0.150]

Mating Polarization Method:	Center, Dual Polarizing Bar
Termination Post Length (mm [in]):	6.10 [0.240]
Mating Connector Lock:	Without
Housing Style:	4-Sided
Ejection Latches:	With
Temperature Rating:	Standard
Contact Mating Area Plating:	Gold (30) over Nickel

[Copyright and Privacy Statement](#)
Visit [Tyco International Ltd.](#)

[[Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#)]