


[English](#) [日本語](#)
Electronics
a vital part of your world
**Find
Answers:**

Monday, 26 September, 2005

CATALOG

 → [Cross Reference](#)
[Competitive Products](#)
[Military Spec P/Ns](#)
[Tyco Brand P/Ns](#)

 → [Part Number Search](#)

 → [Document Search](#)

 → [Product Type Search](#)

 → [Product Family Search](#)

 → [Alphabetical Search](#)

 → [RoHS/ELV Compliance &](#)
[Alternates](#)

 → [CAD Model Search](#)

 → [Brand Search](#)

 → [Tool Search](#)

 → [Multiple Part Comparison](#)

 → [Lead Free Solutions](#)

 → [Help/Glossary](#)
[Home](#)

 e-bulletin newsletter
SUBSCRIBE NOW!
 click here

Flexible Film Products

 ↳ **FLEXSTRIP® Jumpers**

FST-22A-7  **Active**
**Directive 2000/53/EC
Compliant**
ELV Compliant
(Corporate P/N: 8-1437187-4)
[Search for Compliant \(RoHS/ELV\)](#)
[Alternates](#)
[Search for Parts](#)

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information

General Information	eCommerce	Related Part Information
↳ General Info ↳ Sales Info	↳ Pricing ↳ Product Availability	↳ Tooling

Searchable Features:

Brand:	Tyco Electronics
RoHS/ELV Compliance:	ELV compliant
Lead Free Solder Processes:	Not reviewed for lead free solder process
Centerline (mm [in]):	2.54 [0.100]
Insulation Material:	Teflon
Insulation Length (mm [in]):	50.80 [2.000]
Pin Arrangement (Left):	A
Pin Arrangement (Right):	A
Number of Conductors:	7

Other Properties:

Operating Temperature (°C [°F]):	-40 – +150 [-40 – +302]
Current Rating (Amps.):	3
Impedance ():	106
Voltage Rating (VAC):	300

[Copyright and Privacy Statement](#)

Visit [Tyco International Ltd.](#)

[[Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#)]