




## ST19WR02

### Dual Contactless Smartcard MCU With 2 Kbytes EEPROM

DATA BRIEF

#### Product features

- Enhanced 8-bit CPU with extended addressing modes
- 64 KBytes user ROM with partitioning
- 1 KBytes user RAM with partitioning
- 2 KBytes user EEPROM with partitioning plus 128 Bytes user OTP and 64 Bytes ST OTP areas:
  - Highly reliable CMOS EEPROM submicron technology
  - Error Correction Code for single bit fail correction within a byte
  - 10 year data retention
  - 500,000 Erase/Write cycles endurance
  - 1 to 32 Bytes Erase or Program in 1 ms
- Security firewalls for memories, and DES accelerator.
- Very high security features including EEPROM Flash programming and clock management.
- 2x8-bit timers with interrupt capability
- Hardware DES accelerator with library support for symmetrical algorithms:
  - DES, triple DES, Desx computations and CBC chaining mode..
- ISO 3309 CRC calculation block
- FIPS 140-2 compliant Random Number Generator with two Gun registers (Generators of Unpredictable Number)
- 2.7 V to 5.5 V supply voltage
- External clock frequency up to 10 MHz
- High performance provided using internal clock frequency
- Unique serial number on each die
- Power-saving standby mode
- Contact assignment compatible ISO 7816-2
- Serial access I/O, ISO 7816-3 compatible



- ESD protection greater than 5000 V

Function	Speed <sup>(1)</sup>
Triple DES (with keys loaded)	50 $\mu$ s
Single DES (with keys loaded)	37 $\mu$ s

1. Best performance achieved using 15 MHz clock frequency

#### Contactless specific features

- Based on ISO 14443 type B
- 13.56 MHz carrier frequency
- High speed data transfer up to 424 kbits/s
- RF frame up to 256 Bytes
- 10% amplitude modulation reception (reader to card)
- BPSK - NRZ load modulation (card to reader)
- Interface with RF readers supported through a library of embedded software functions compatible with ISO 14443 standard
- ESD protection on antenna pads greater than 5000 V

## Hardware description

The product, member of the ST19W platform, is a serial access microcontroller specially designed for cost-effective secure portable applications.

It is manufactured using an advanced highly reliable ST CMOS EEPROM technology.

It is based on the STMicroelectronics 8-bit CPU already implemented on the ST19X product family and includes on-chip memories: User ROM, User RAM and EEPROM with state-of-the-art security features. ROM, RAM and EEPROM memories can be configured into partitions with customized access rules.

An additional ST ROM contains all ST provided functions and libraries.


Access from any memory area to another are protected by hardware firewalls. Access rules are user-defined and can be selected by mask options.

The chip includes a DES accelerator which is accessible via cryptographic software libraries located in ST ROM.

As with all the other ST19W products, a serial interface fully compatible with the ISO 7816 standard for Smartcard applications is available.

A CRC calculation block is also available and is directly accessible by the User.

### Block Diagram



## Software development

Software development and firmware generation (ROM and options) are supported by a comprehensive set of development tools, dedicated at development and validation of software:

- Smartcard ICs Emulator
- ST19X simulation package
- ScDevTools environment for Windows™ NT, 2000, and XP based stations
- Powerful C/C++ compiler and debugger are also available (third-party tools)
- RF contactless demokit based on ISO 14443 type B standards

## Revision history

Date	Revision	Changes
08-Apr-2004	1	Initial release.
27-Jan-2006	2	Reformatted and restructured document. Electrical Characteristics updated - See <a href="#">Triple DES (with keys loaded)</a> and <a href="#">Single DES (with keys loaded)</a> on page 1.

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics.  
All other names are the property of their respective owners

© 2006 STMicroelectronics - All rights reserved  
BULL CP8 Patents

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan -  
Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

[www.st.com](http://www.st.com)