



**SGS-THOMSON**  
MICROELECTRONICS

**BD533FI**  
**BD534FI**

## COMPLEMENTARY SILICON POWER TRANSISTORS


### ■ SGS-THOMSON PREFERRED SALESTYPES

#### DESCRIPTION

The BD533FI, is a silicon epitaxial-base NPN transistor mounted in ISOWATT220 plastic package.


They are intended for use in medium power linear and switching applications.

The complementary PNP type is the BD534FI.



ISOWATT220

#### INTERNAL SCHEMATIC DIAGRAM



#### ABSOLUTE MAXIMUM RATINGS

Symbol	Parameter	Value		Unit
		NPN	BD533FI	
PnP	BD534FI			
$V_{CBO}$	Collector-Base Voltage ( $I_E = 0$ )	45		V
$V_{CES}$	Collector-Emitter Voltage ( $V_{BE} = 0$ )	45		V
$V_{CEO}$	Collector-Emitter Voltage ( $I_B = 0$ )	45		V
$V_{EBO}$	Emitter-Base Voltage ( $I_C = 0$ )	5		V
$I_C, I_E$	Collector and Emitter Current	8		A
$I_B$	Base Current	1		A
$P_{tot}$	Total Dissipation at $T_c \leq 25^\circ\text{C}$	25		W
$T_{stg}$	Storage Temperature	-65 to 150		$^\circ\text{C}$
$T_j$	Max. Operating Junction Temperature	150		$^\circ\text{C}$

For PNP types voltage and current values are negative.

## THERMAL DATA

$R_{thj-case}$	Thermal Resistance Junction-case	Max	5	$^{\circ}\text{C}/\text{W}$
$R_{thj-amb}$	Thermal Resistance Junction-ambient	Max	62.5	$^{\circ}\text{C}/\text{W}$

ELECTRICAL CHARACTERISTICS ( $T_{case} = 25^{\circ}\text{C}$  unless otherwise specified)

Symbol	Parameter	Test Conditions		Min.	Typ.	Max.	Unit
$I_{CES}$	Collector Cut-off Current ( $V_{BE} = 0$ )	$V_{CE} = 45 \text{ V}$				0.1	mA
$I_{CBO}$	Collector Cut-off Current ( $I_E = 0$ )	$V_{CB} = 45 \text{ V}$				0.1	mA
$I_{EBO}$	Emitter Cut-off Current ( $I_C = 0$ )	$V_{EB} = 5 \text{ V}$				1	mA
$V_{CEO(sus)*}$	Collector-Emitter Sustaining Voltage	$I_C = 100 \text{ mA}$		45			V
$V_{CE(sat)*}$	Collector-Emitter Saturation Voltage	$I_C = 2 \text{ A}$ $I_C = 6 \text{ A}$	$I_B = 0.2 \text{ A}$ $I_B = 0.6 \text{ A}$		0.8	0.8	V V
$V_{BE*}$	Base-Emitter Voltage	$I_C = 2 \text{ A}$	$V_{CE} = 2 \text{ V}$			1.5	V
$\beta_{FE*}$	DC Current Gain	$I_C = 10 \text{ mA}$ $I_C = 500 \text{ mA}$ $I_C = 2 \text{ A}$	$V_{CE} = 5 \text{ V}$ $V_{CE} = 2 \text{ V}$ $V_{CE} = 2 \text{ V}$	20 40 25			
$f_T$	Transition Frequency	$I_C = 500 \text{ mA}$	$V_{CE} = 1 \text{ V}$	3	12		MHz

\* Pulsed: Pulse duration = 300  $\mu\text{s}$ , duty cycle  $\leq 2\%$

For PNP types voltage and current values are negative.

## ISOWATT220 MECHANICAL DATA

DIM.	mm			inch		
	MIN.	TYP.	MAX.	MIN.	TYP.	MAX.
A	4.4		4.6	0.173		0.181
B	2.5		2.7	0.098		0.106
D	2.5		2.75	0.098		0.108
E	0.4		0.7	0.015		0.027
F	0.75		1	0.030		0.039
F1	1.15		1.7	0.045		0.067
F2	1.15		1.7	0.045		0.067
G	4.95		5.2	0.195		0.204
G1	2.4		2.7	0.094		0.106
H	10		10.4	0.393		0.409
L2		16			0.630	
L3	28.6		30.6	1.126		1.204
L4	9.8		10.6	0.385		0.417
L6	15.9		16.4	0.626		0.645
L7	9		9.3	0.354		0.366
Ø	3		3.2	0.118		0.126

