



D Series Miniature Power Rocker Switches



Contact Rating: 10 amps at 125 VAC; 5 amps at 250 VAC, UL/CSA; 10 (8) amps at 125 VAC; 5 (3) amps at 250 VAC, T85, VDE. Actuator: Nylon, black with on/off markings. Housing: Nylon, black. Movable Contacts: Coin silver, silver plated. Stationary Contacts and Terminals: Copper, silver plated. Mounting Hole: SPDT and SPST — 0.754" (19.40) x 0.508" (12.90) for 0.073" (1.85) thick panel; DPDT — 0.754" (19.40) x 0.587" (22.53) for 0.073" (1.85) thick panel.

Stock No.	Mfr.'s Type	Fig.	Description	Switch Function	EACH		
					1-99	100-499	500-999
676-9391	D102J12S215PQA	A	SPDT	On-None-Off	2.21	1.96	1.80
676-9392	D501J12S215PQA	A	SPDT	On-None-On	1.99	1.74	1.59
676-9393	D502J12S216PQA	A	SPST	On-None-Off	1.54	1.36	1.26
676-9394	D601J12S215PQA	B	DPDT	On-None-On	3.20	2.85	2.60
676-5106	D501J12S2APDF	C	SPDT	On-None-On	3.36	2.99	2.73
676-5107	D501J12S215PDF	A	SPDT	On-None-On	2.51	2.22	2.04
676-5108	D601J12S215PDF	B	DPDT	On-None-On	4.13	3.67	3.36



E Series Panel-Mounted Sealed Rocker and Lever Handle Switches

Contact Rating: 7.5 amps at 125 VAC; 3 amps at 250 VAC (UL/CSA). Operating Temperature: -30°C to 85°C. Case and Bushing: Glass filled nylon. Actuator: Nylon, black with internal O-ring seal. End Contacts: Coin silver, silver plated. Center Contact and Terminals: Brass, silver plated. Terminal Seal: Epoxy. Included Hardware: Nuts, screws, lockwashers, and standoffs.

**Rocker**

Stock No.	Mfr.'s Type	Fig.	Description	Switch Function*	EACH		
					1-99	100-499	500-999
676-1000	E101J12QE2	D	SPDT	On-None-On	5.64	5.01	4.25
676-1005	E103J12QE2	D	SPDT	On-Off-On	6.51	5.91	5.01


**Lever Handle**

Stock No.	Mfr.'s Type	Fig.	Description	Switch Function*	EACH		
					1-99	100-499	500-999
676-1045	E105J22QE2	E	SPDT	Mom.-Off-Mom.	7.20	6.53	5.55
676-1060	E205J22QE2	E	DPDT	Mom.-Off-Mom.	7.95	7.21	6.12

\*Mom. = Momentary.


DF Series Snap-In Power Rocker Switches

Contact Rating: 16 amps at 125 VAC or 250 VAC 1/4 HP at 125 VAC 1/2 HP at 250 VAC, UL/CSA; 16 (2) at 250 VAC, T100, VDE. Actuator: Nylon, black with on/off markings. Housing: Nylon, black. Movable Contacts: Fine silver, silver plated. Stationary Contacts and Terminals: Copper, silver plated. Mounting Hole: 1.029" (25.14) x 0.483" (12.27) for 0.073" (1.85) thick panel. Switches are DPST circuitry with black actuator.



Stock No.	Mfr.'s Type	Fig.	Description	Switch Function	EACH		
					1-99	100-499	500-999
676-5500	DF62J12S215PDF	F	DPST	Off-On	4.53	4.04	3.69
676-9144	DF62J12S215PQA	F	DPST	Off-On	3.58	3.19	2.92
676-9145	DF62J12S2ADA	G	DPST	Off-On	3.87	3.45	3.15
676-5501	DF62J12S2APDF	G	DPST	Off-On	5.25	4.65	4.26
676-9146	DF62J12S215PQA	F	DPST	Off-On	4.73	4.22	3.86

C Series Power Rocker Switches




Contact Rating: 15 amps at 125 VAC; 10 amps at 250 VAC. Housing and Actuator: Nylon, black. Movable Contact: Copper, silver plated. Contacts and Terminals: Copper, silver plated (15 amp models, copper). Electrical Life: 10,000 make-and-break cycles at full load. Dielectric Strength: 2500 Vrms min. at sea level. All models UL, CSA.

Stock No.	Mfr.'s Type	Fig.	Description	Switch Function	EACH		
					1-99	100-499	500-999
676-9147	C121J12S205QA	H	SPDT	On-On	2.62	2.31	2.14
676-9148	C121J12S205QF	H	SPDT	On-On	2.87	2.53	2.34
676-5100	C122J12S205PDF*	H	SPST	On-Off	3.48	3.09	2.83
676-5101	C221J12S205QA†	I	DPDT	On-On	3.54	3.16	2.86
676-5102	C222J12S205QA†	I	DPST	On-Off	3.42	3.03	2.77
676-9149	C222J12S205QF	I	DPST	On-Off	3.50	3.09	2.86
676-5103	C222J12S205PDF*	I	DPST	On-Off	4.45	3.94	3.61

\*VDE, SEV, SEMKO. †Terminals: Copper, copper.

7000 Series Snap-In Rocker and Lever Handle Switches

Contact Rating: 5 amps at 120 VAC or 28 VDC; 2 amps at 250 VAC. Operating Temperature: -30° to 85°C. Rocker and Lever Handles: Black nylon. Bushings: Brass, nickel plated. End Contact: Coin silver, silver plated. Center Contact and Terminals: Brass, silver plated. Mounting Bracket: Stainless steel. Case: Red diallyl phthalate. Panel Cutout: 0.500 x 0.600".



Small Rocker with Bezel


Stock No.	Mfr.'s Type	Fig.	Description	Switch Function*	EACH		
					1-99	100-499	500-999
676-0150	7101J512QE22	J	SPDT	On-None-On	6.07	5.41	4.94
676-0155	7103J512QE22	J	SPDT	On-Off-On	6.54	5.93	5.43
676-0160	7105J512QE22	J	SPDT	Mom.-Off-Mom.	6.81	6.18	5.65
676-0165	7107J512QE22	J	SPDT	On-Off-Mom.	6.81	6.18	5.65
676-0170	7108J512QE22	J	SPDT	On-None-Mom.	5.81	5.27	4.82
676-0175	7201J512QE22	J	DPDT	On-None-On	7.99	7.24	6.62
676-0180	7203J512QE22	J	DPDT	On-Off-On	8.95	8.12	7.42
676-0185	7205J512QE22	J	DPDT	Mom.-Off-Mom.	8.95	8.12	7.42

Small Lever Handle with Bezel

Stock No.	Mfr.'s Type	Fig.	Description	Switch Function*	EACH		
					1-99	100-499	500-999
676-0200	7101J612QE22	K	SPDT	On-None-On	6.07	5.41	4.94
676-0210	7105J612QE22	K	SPDT	Mom.-Off-Mom.	6.81	6.18	5.65
676-9600	7107J612QE22	K	SPDT	On-Off-Mom.	6.81	6.18	5.65
676-0220	7108J612QE22	K	SPDT	On-None-Mom.	5.81	5.27	4.82
676-0225	7201J612QE22	K	DPDT	On-None-On	7.99	7.24	6.62
676-0230	7203J612QE22	K	DPDT	On-Off-On	8.94	8.12	7.42
676-0235	7205J612QE22	K	DPDT	Mom.-Off-Mom.	8.95	8.12	7.42
676-9150	7207J612QE22	K	DPDT	On-Off-On	9.14	8.29	7.59

\*Mom. = Momentary.

7000 Series Panel-Mounted Rocker and Lever Handle Switches



Contact Rating: 5 amps at 120 VAC or 28 VDC; 2 amps at 250 VAC. Operating Temperature: -30° to 85°C. Rocker and Lever Handles: Black nylon. Bushings: Brass, nickel plated. End Contact: Coin silver, silver plated. Center Contact and Terminals: Brass, silver plated. Mounting Bracket: Stainless steel. Case: Red diallyl phthalate. Included Hardware: Nuts, screws, lockwashers, and standoffs.

Small Rocker

Mounting Hole Centers: 0.937".

Stock No.	Mfr.'s Type	Fig.	Description	Switch Function*	EACH		
					1-99	100-499	500-999
676-9151	7101J1ABE2	L	SPDT	On-None-On	5.23	4.66	4.27
676-9152	7101J1AOE2	L	SPDT	On-None-On	5.23	4.66	4.27
676-0005	7101J12QE2	M	SPDT	On-None-On	5.49	4.90	4.47
676-9153	7103J1ABE2	L	SPDT	On-Off-On	4.50	4.01	3.67
676-0015	7105J12QE2	M	SPDT	Mom.-Off-Mom.	6.32	5.63	5.15
676-0025	7201J12QE2	M	DPDT	On-None-On	7.38	6.70	6.12
676-0035	7205J12QE2	M	DPDT	Mom.-Off-Mom.	7.08	6.42	5.87
676-9154	7301J1AV2QE2	N	3PDT	On-None-On	12.07	10.75	9.84

Small Lever Handle

Mounting Hole Centers: 0.937".

Stock No.	Mfr.'s Type	Fig.	Description	Switch Function*	EACH		
					1-99	100-499	500-999
676-0055	7105J22QE2	O	SPDT	Mom.-Off-Mom.	5.81	5.27	4.82
676-9155	7301J22QE2	P	3PDT	On-None-On	11.24	10.01	9.16
676-9156	7401J22QE2	P	4PDT	On-None-On	15.05	13.41	12.27

Large Rocker

Mounting Hole Centers: 1.375".

676-0085	7105J32QE2	Q	SPDT	Mom.-Off-Mom.	6.81	6.17	5.65
676-0105	7205J32QE2	Q	DPDT	Mom.-Off-Mom.	8.95	8.12	7.42

Large Lever Handle

Mounting Hole Centers: 1.375".

676-0125	7105J42QE2	R	SPDT	Mom.-Off-Mom.	7.55	6.85	6.26
----------	------------	---	------	---------------	------	------	------

\*Mom. = Momentary.