

Bussmann Information Fax 314-527-1450

Bussmann product information at your convenience. Available 24 hours a day — 7 days a week. Please have your fax number ready when you call.

To speak with a Customer Satisfaction Representative please call 314-527-3877 (Monday-Friday, 8 am-5 pm central).

GDA Fast-Acting High Breaking Capacity Fuses

Designed to meet IEC specification 127-2, Standard Sheet 1. UL recognized. (5 mm × 20 mm.) Ceramic.

Stock No.	Amps	Volts	EACH		
			1-49	50-249	250-Up
740-5158	100.00 mA	250	3.08	2.45	2.12
740-5159	125.00 mA	250	1.82	1.68	1.57
740-5160	160.00 mA	250	2.81	2.23	1.52
740-5161	200.00 mA	250	2.96	2.29	1.58
740-5162	250.00 mA	250	2.97	2.35	1.61
740-5163	315.00 mA	250	3.08	2.44	2.12
740-5164	400.00 mA	250	2.82	2.23	1.52
740-5165	500.00 mA	250	2.63	2.09	1.42
740-5166	630.00 mA	250	2.68	2.09	1.42
740-5167	800.00 mA	250	2.76	2.18	1.50
740-5168	1.00	250	2.79	2.17	1.48
740-5169	1.25	250	2.63	2.09	1.42
740-5170	1.60	250	2.63	2.09	1.44
740-5171	2.00	250	2.76	2.18	1.50
740-5172	2.50	250	2.87	2.27	1.80
740-5174	4.00	250	2.63	2.09	1.42
740-5175	5.00	250	2.68	2.09	1.42
740-9566	6.30	250	2.73	2.12	1.46

GDB Fast-Acting Low Breaking Capacity Fuses

Designed to meet IEC 127-2, Standard Sheet 2. (5 mm × 20 mm.) Glass.

Stock No.	Amps	Volts	EACH		
			1-49	50-249	250-Up
740-5176	50.00 mA	250	3.42	2.71	1.85
740-5179	100.00 mA	250	3.42	2.72	1.85
740-5180	125.00 mA	250	2.53	1.98	1.35
740-5181	160.00 mA	250	2.53	1.98	1.35
740-5182	200.00 mA	250	2.67	2.07	1.40
740-5183	250.00 mA	250	2.53	1.98	1.35
740-5185	400.00 mA	250	1.79	1.64	1.31
740-5186	500.00 mA	250	2.12	1.65	1.11
740-5187	630.00 mA	250	2.23	1.74	1.17
740-5188	800.00 mA	250	2.12	1.65	1.11
740-5189	1.00	250	2.23	1.74	1.17
740-5191	1.60	250	2.12	1.65	1.11
740-5192	2.00	250	2.23	1.74	1.17
740-5193	2.50	250	2.12	1.65	1.11
740-5194	3.15	250	2.12	1.65	1.11
740-5195	4.00	250	2.23	1.74	1.17
740-5196	5.00	250	2.23	1.74	1.17
740-5197	6.30	250	2.06	1.60	1.08
740-9570	8.00	250	2.12	1.65	1.11
740-9575	10.00	250	2.23	1.75	1.18

GDC Time-Delay Fuses (Low Breaking Capacity)

Designed to meet IEC 127-2, Standard Sheet 3. (5 mm × 20 mm.) Glass.

Stock No.	Amps	Volts	EACH		
			1-49	50-249	250-Up
740-5198	32.00 mA	250	4.66	3.57	2.42
740-5200	50.00 mA	250	4.65	3.56	2.42
740-5201	63.00 mA	250	4.43	3.38	2.31
740-5203	100.00 mA	250	4.04	3.21	2.18
740-5204	125.00 mA	250	4.43	3.38	2.31
740-5205	160.00 mA	250	4.09	3.25	2.21
740-5207	250.00 mA	250	4.30	3.42	2.33
740-5208	315.00 mA	250	4.09	3.25	2.21
740-5210	500.00 mA	250	2.31	1.89	1.50
740-5211	630.00 mA	250	2.63	2.09	1.42
740-5212	800.00 mA	250	2.81	2.18	1.50
740-5213	1.00	250	2.76	2.18	1.50
740-5214	1.25	250	2.61	2.03	1.38
740-5215	1.60	250	3.32	2.64	1.79
740-5216	2.00	250	2.68	2.09	1.42
740-5217	2.50	250	2.76	2.18	1.50
740-5218	3.15	250	2.76	2.18	1.50
740-5219	4.00	250	2.76	2.18	1.50
740-5220	5.00	250	.78	.62	.54
740-5221	6.30	250	.98	.74	.59

Emergency Fuse Kit with Fusepuller FP-A3

Works with Models: Peugeot, Renault, Volvo — 1985 or later; Audi, BMW, Fiat, Saab — 1984 or later; Plymouth, Datsun, Honda, Mazda, Subaru, Nissan, Volkswagen — 1982 or later; Toyota — 1981 or later; Chevrolet, Buick, Pontiac — 1980 or later; Ford, Lincoln, Mercury, Dodge, Chrysler, Cadillac — 1979 or later; Oldsmobile — 1978 or later.

740-0007. AT-7. Includes Blade-Type Fuses ATC-5, 10, 15, 20, 25, 30, and FP-A3 Fusepuller EACH 3.65

264 ▲ ALLIED

GMA Fast Acting Fuses For Foreign Equipment

Compact 5 mm × 20 mm fuse. UL listed, CSA Certified through 6 amps. UL Recognized through 15 amps.



Dimensions (mm)
(inches)

End View: 2.69 ± 0.15 (0.106 ± 0.006) mm (in)

Top View: 2.69 ± 0.15 (0.106 ± 0.006) mm (in)

Side View: 2.69 ± 0.15 (0.106 ± 0.006) mm (in)

Land Pattern: 3.60 (0.138) mm (in)

Width: 2.60 (0.102) mm (in)

Height: 3.00 (0.118) mm (in)

Thickness: 4.00 (0.157) mm (in)

► Time Delay Surface Mount Fuse Capable of Replacing Glass Tube Fuses in Certain Applications

► Environmentally Rugged, Satisfies EIA-IS-722 Standard

► Solder Immersion Compatible

► Targeted for Consumer Electronics

► UL Recognition Guide and File Number: JDYX2 and E19180

► Voltage Rating: 125 VAC/60 VDC — 50 A

► Interrupting Rating*: 125 VAC — 50 A; 60 VDC — 50 A

The time delay 6125TD fuse has a ceramic body with wire-in-air design. 6125 Brick™ fuses are the solution for engineers needing overcurrent protection of systems up to 125 VAC in a surface mount package.

*AC interrupting rating (measured at designated voltage, 100% power factor); DC interrupting Rating (measured at designated voltage, rise time of less than 50 microseconds, battery source).

Stock No.	Mfr.'s Type	EACH		
		1-99	100-499	500-999
740-5800	6125TD500MA	.94	.77	.70
740-5801	6125TD750MA	.94	.77	.65
740-5802	6125TD1A	.84	.69	.63
740-5803	6125TD1.5A	.84	.69	.58
740-5804	6125TD2A	.84	.69	.63
740-5805	6125TD2.5A	.84	.69	.58
740-5806	6125TD3A	.84	.69	.63
740-5807</				