



Note: These connectors meet or exceed military specification, but aren't on the RPL and are intended for commercial use only. Military specification numbers, where shown, are for reference only.

RFX™ Commercial Coaxial Connectors

BNC 3-Piece Crimp-Type Plugs

Miniature bayonet-lock units. Materials: Body — brass or diecast brass. Plating: Nickel. Contacts: Male — brass, gold plated; Female — phosphor bronze, gold plated. Insulator: Delrin or Teflon (where noted). Frequency: 50 Ω — 0-4GHz, 750 Ω — 0-1 GHz.

8

Stock No.	Mfr.'s Type	Fig.	RG/U Cable	Cable Attachment		Imp.	EACH		
				Outer	Inner		1-24	25-99	100-249
713-9000	31-5558-RFX	1	6 (0.314" O.D.)	Crimp	Crimp	50 ohm	3.01	2.28	1.83
713-9004	31-71000-RFX	1	6	Crimp	Crimp	75 ohm	2.49	1.98	1.68
713-9005	31-320-RFX	1	58, 141	Crimp	Crimp	50 ohm	1.54	1.22	1.04
713-9007	36650-3RFX	1	Plenum 58	Crimp	Crimp	50 ohm	1.30	1.09	.93
713-9010	31-321-RFX	1	59, 62	Crimp	Crimp	50 ohm	1.48	1.17	1.00
713-9008	31-71008-RFX	1	59 (20 AWG ctr. cond.)	Crimp	Crimp	75 ohm	1.40	1.11	.95
713-9003	31-71008-1RFX	1	59 (20 AWG ctr. cond.)	Crimp	Crimp	75 ohm	1.49	1.18	1.01
713-9011	68175-5RFX	1	Plenum 59	Crimp	Crimp	50 ohm	1.49	1.17	1.00
713-9012	68175-1RFX	1	179, 187	Crimp	Crimp	50 ohm	1.72	1.36	1.17
713-9009	31-71013-RFX	1	179, 187	Crimp	Crimp	50 ohm	2.10	1.63	1.37
713-9015	31-315-RFX	1	174, 188, 316	Crimp	Crimp	50 ohm	1.80	1.43	1.22
713-9025	31-321-10RFX	1	Belden 8281	Crimp	Crimp	50 ohm	1.87	1.48	1.26

*20 AWG Center Cond.

BNC 2-Piece Single Crimp Plugs

713-9030	31-5557-RFX	2	58, 141, 142	Crimp	Press fit	50 ohm	1.96	1.56	1.33
713-9040	31-5556-RFX	2	59, 62	Crimp	Press fit	50 ohm	2.05	1.63	1.38
713-9045	31-5560-RFX	2	Plenum 59, 62	Crimp	Press fit	50 ohm	2.05	1.56	1.31

BNC SureTwist® Plugs

713-9050	31-5137-RFX	3	58	SureTwist®	SureTwist®	—	50 ohm	1.80	1.43	1.22
713-9055	31-5136-RFX	3	59	—	—	50 ohm	1.80	1.43	1.22	

BNC Clamp-Type Plugs

713-9060	31-2-RFX	4	58, 141, 142	Clamp	Solder	50 ohm	2.00	1.58	1.35
713-9065	31-212-RFX	4	59, 62	Clamp	Solder	50 ohm	1.99	1.57	1.34

BNC Quicktrim® Plug

713-9002	31-4541-RFX	5	59, 62	—	Quicktrim®	50 ohm	3.99	3.23	2.75
----------	-------------	---	--------	---	------------	--------	------	------	------

Right Angle Crimp Plugs — Diecast Body

713-9034	31-335-RFX	6	58, 141	—	—	50 ohm	3.76	3.13	2.57
713-9032	31-336-RFX	6	59, 62	—	—	50 ohm	4.41	3.57	3.04
713-9031	31-316-RFX	6	174, 188, 316	—	—	50 ohm	5.65	4.71	4.04

BNC 3-Piece Crimp Jack

713-9068	36800-RFX	7	58, 141	Crimp	Crimp	50 ohm	1.56	1.24	1.05
713-9032	31-327-RFX*	7	58, 141	—	—	50 ohm	1.76	1.39	1.19
713-9033	31-328-RFX*	7	59, 62	—	—	50 ohm	1.76	1.39	1.19
713-9069	31-71014-RFX	7	179, 187	Crimp	Crimp	75 ohm	2.26	1.76	1.41

*Captive contact, teflon insulation.

Twinaxial Connectors

Keyed 90° Twinax Connectors

Plug, Twin Male Contacts

Stock No.	Mfr.'s Type	Fig.	RG/U Cable	Cable Attachment		IBM Ref. No.	EACH		
				Outer	Inner		1-24	25-99	100-249
713-9130	82-5589-RFX	19	Belden 8227, 9207, IBM 7362211	Clamp	Solder or Crimp	736229	4.68	3.79	3.22

Coaxial Connectors

BNC Bulkhead Jacks — Non-Captive Contacts

BNC Panel Receptacle

Stock No.	Mfr.'s Type	Fig.	Description	Terminal Type	Imp.	EACH			
						Outer	Inner	1-24	
713-9037	31-342-RFX	8	58, 141	—	—	50 ohm	2.56	2.14	1.83
713-9009	31-71011-RFX	8	59, 62	—	—	75 ohm	2.52	2.12	1.80
713-9070	31-318-RFX	8	174, 188, 316	Crimp	—	50 ohm	3.31	2.68	2.28
713-9075	31-245-RFX	8	179, 187	Crimp	—	50 ohm	3.36	2.58	2.19
713-9043	31-71016-RFX	8	179, 187	Crimp	—	75 ohm	3.17	2.57	2.18

Stock No.	Mfr.'s Type	Fig.	Description	Terminal Type	Imp.	EACH		
Outer	Inner	1-24	25-99	100-249				

<tbl_r cells="7" ix="1" maxcspan