

Visit Murata's website at www.murata.com

GRM Series Tip and Ring Capacitors

- Ideal for Leaded Film Capacitor Replacement to Save Space
Designed for Tip and Ring Circuit of FAX/Modem, Cable Modem, ISDN Modem
Max. Thickness: 0.08" (2 mm) That Fits in PCMCIA Card
D.F.: 2.5% Max. (±0.1 KHz @ 1 ± 0.2 Vrms
L.R.: 100 Gohm or 1 Gohm mF (Whichever is Less)
Dielectric Strength: 120% of Rated Voltage for 5 Sec. (50 mA Max. Charge Current)
See Section at Left for Art and Dimensions

Table with columns: Stock No., Mfr.'s Type, EIA Size, Cap. (pF), WVDC, Tol. (%), EACH\*. Rows include 231-1400, 231-1405, 231-1415, 231-1420.

\*Sold in multiples of 100 only.

GRM Series Monolithic Ceramic High Capacitors

- Applications: Decoupling and Bypassing
Features: Low ESR, Non Polarity, High Reliability and Base Metal Inner Electrode
Market: Cellular, Computer, AV, etc.
See Section at Left for Art and Dimensions

Table with columns: Stock No., Mfr.'s Type, EIA Size, Cap. (pF), WVDC, Tol. (%). Rows include 231-6000, 231-6002, 231-6008, 231-6012, 231-6014, 231-6016.

\*Sold in multiples of 100 only.

KH Type Safety Ceramic Capacitors

Used for across the line or line by-pass applications. Available in ammo pack for automatic insertion as custom order. Call for price and delivery. Temperature Range: -25°C to +125°C.




Table with columns: Stock No., Mfr.'s Type, Cap. (pF), VAC, Tol. (%), Dim. (in.) [Dia., L.S.], 1-99, 100-499. Rows include 711-1416, 711-1418, 711-1420, 711-1422, 711-1423, 711-1424, 711-1425, 711-1426.

Chip Ceramic Capacitors

These kits are specifically designed to aid the design engineer in prototyping applications. Each kit contains a wide selection of commonly used values and sizes that meet a variety of circuit design requirements.

Capacitors


Table with columns: Stock No., Mfr.'s Type, Description, Pieces Each, Values Per Kit, Temp. Coefficient, Volts. Rows include 711-2000, 711-2002, 711-2004, 711-2006, 711-2008, 711-2009, 711-2010.

Safety Capacitor Kits

Safety Standard Capacitors
711-2029. Kit-Safety-KHXK. 15 pieces each of 20 values ..... EACH 215.05

Chip Safety Standard Capacitors
711-2030. Kit-Safety-GHM3000. 11 values ..... EACH 236.15

GRM Series Chip Capacitors



Dimensions — mm

Table with columns: Type, Length L, Width W, Thickness T, e Min. Termination. Rows include GRM36, GRM40, GRM42-6, GRM42-2.

Non-polarized and miniature size chip capacitors have uniform dimensions and configuration. Flow and reflow solderable. Nickel barrier termination is highly resistant to metal migration. They have minimum series inductance.

Table with columns: Stock No., Mfr.'s Type, EIA Size, Cap. (pF), WVDC, Tol. (%). Rows include 231-1354, 231-1356, 231-1358, 231-1360.

\*Sold in multiples of 100 only.

Table with columns: Stock No., Mfr.'s Type, EIA Size, Cap. (pF), WVDC, Tol. (%). Rows include 231-1362, 231-1364, 231-1366, 231-1368, 231-1370, 231-1372, 231-1374, 231-1376, 231-1378, 231-1382, 231-1384, 231-1386, 231-1390, 231-1392, 231-1200, 231-0100, 231-0102, 231-0104, 231-0106, 231-0108, 231-0110, 231-0112, 231-0114, 231-0116, 231-0118, 231-0120, 231-0122, 231-0124, 231-0126, 231-0128, 231-0130, 231-0132, 231-0134, 231-0136, 231-0138, 231-0140, 231-0142.

\*Sold in multiples of 100 only.

Table with columns: Stock No., Mfr.'s Type, EIA Size, Cap. (pF), WVDC, Tol. (%). Rows include 231-0144, 231-0146, 231-0148, 231-0150, 231-0152, 231-0154, 231-0156, 231-0158, 231-0160, 231-0162, 231-0164, 231-0166, 231-0172, 231-0174, 231-0176, 231-0178, 231-0180, 231-0182, 231-0184, 231-0186, 231-0188, 231-0190, 231-0192, 231-0194, 231-0196, 231-0198, 231-0200, 231-0202, 231-0204, 231-0206, 231-0208, 231-0210, 231-0212, 231-0214, 231-0216, 231-0218, 231-0220.

\*Sold in multiples of 100 only.