


beispielhafte Darstellung UNI IRIS Dicht Verschraubung für EMV Pg29
exemplary drawings universal IRIS cable protection for EMC Pg29

C	09 62 000 5023	Pg11	4-6,5	2,5-6,5	20
	09 62 000 5024	Pg11	6,5-9,5	3,5-8,5	20
	09 62 000 5003	Pg13,5	6,5-9,5	2,5-6,5	22
	09 62 000 5004	Pg13,5	9-13	6,5-10,5	22
	09 62 000 5005	Pg16	6,5-9,5	3,5-8	24
	09 62 000 5006	Pg16	9-13	4,5-8	24
	09 62 000 5007	Pg21	11,5-15,5	9,5-13,5	30
	09 62 000 5008	Pg21	14-18	10,5-14,5	30
	09 62 000 5009	Pg29	17-20,5	15-20	40
D	09 62 000 5010	Pg29	20-25	15-20	40
	09 62 000 5011	Pg36	24-28	18-25,5	50
	09 62 000 5012	Pg36	27-32	24-31	50
	Bestell Nr <i>Part No</i>	Gewinde <i>thread</i>	Kabel/ <i>cab</i> le min.- max.	Schirm/ <i>sh</i> ield min.- max.	SW



All Dimensions in mm
Original Size DIN A 4

Techn. Character.		Maßstab/Scale 2:1
	Dat. Name	
Detail.	24.10.08 Bor	
Insp.	Be	
Stand.		

Nicht tolerierte Maße/Free size tolerances
UNI IRIS Dicht Verschraubung für EMV
universal IRIS cable protection for EMC

B	02.03.11	Ho
A		
Mod.	Dat.	Name

HARTING Electric GmbH & Co. KG
D-32339 Espelkamp



TB 09 62 000 50..
Sub. TB 09 62 000 50.. v. 23.10.96

Blatt/ page