

Material:

- Cable: USB2.0 Shielded E189529 UL2725 28#/1P+24#/2C+AEB
  - OD 4.7MM
  - Beige (IV-29#)
- P1 Connector: USB2.0 A Male Shell
  - Pin G/F
  - 4PCS Type
  - Insulator color: white
  - Shell Plate Nickel
- P2 Connector: USB2.0 B Male Shell
  - Pin G/F
  - 3PCS Type
  - Insulator color: white
  - -Shell Plate Nickel
- Outer Jacket: Beige (IV-29#) PVC-40P
- 80°C 30V VW-1

Electrical:

- 100% short, open, miswire test
- Conduct resistance: 2Ω Max.
- Insulation resistance: 5MΩ Min.
- Dielectric test: 300V DC

PIN Assignment:





1PC / PE Bag

RoHS Complaint

Scale	1:1						Name	Item No. AK672/2-2-R
TOLERANCE					Drawn	01.04.12	Chappell	
X.X	±0.40				Approved			Title USB 2.0 Cable - A Male <=> B Male, Beige, 2 Meters
X.XX	±0.25							Drawing No. rev00
X.XXX	±0.15							
Angle	±3°							Replace / Sheet
			Modification	Date	Name			

ASSMANN WSW components