



Part Number  .  .  .

**EPL.00.250.NTN**

Size/Series 00 / 00

Demande d'offres

MECHANICAL DETAILS

- Shell Style/Model** EPL\*: Elbow receptacle for printed circuit
- Keying** Circular (can rotate)
- Housing Material** Brass (nickel plated) shell, collet nut, latch sleeve and mid pieces
- Cable Fixing** ∅ : 0 - 0 mm
- Variant** :

	A	H	L	Weight
mm.	7	10	17.5	4.3
in.	0.28	0.39	0.69	0.17

MECHANICAL DETAILS

- Insert Configuration** 0.25 : 1 Coax (50 Ohm)
- Insulator** T: PTFE
- Specifications**
- Contact Type:** Coaxial 50 Ohm (Printed Circuit Board)
- Max. Matings:** 5000
- Contact Dia.:** 0.7 mm (0.028in)
- R (max):** 6.1 mOhm
- Vtest:** 2100 V (AC), 3000 V (DC)
- Rated Current:** 4 A (AC/DC)
- Impedance:** 50 Ohm
- VSWR:** 1.09 + 0.11 \* f/GHz

MECHANICAL DETAILS

- Endurance (Shell)** 3839 matir
- F ret (min):** 100 N
- IP Rating** 50
- Catalog**



[Download 3D draw](#)

