



DETAIL A
OPTIONAL CONSTRUCTIONS

- 1 MATES WITH APPROPRIATE UNIVERSAL MATE-N-LOK™ CAP OR HEADER.
- 2 SMALL NICKS ARE PERMITTED ON THE CIRCUIT TOWERS WHICH COULD INCREASE THE INITIAL HOUSING MATING FORCE BY UP TO 4.4 NEWTONS (1.0 LBS). NO INDIVIDUAL NICKED TOWER SHALL INCREASE THIS FORCE BY OVER 2.2 NEWTONS (.5 LBS).
- 3 DIMENSION INDICATED IS AS MOLDED. ADDITIONAL GROWTH DUE TO SUBSEQUENT MOISTURE ABSORPTION MAY OCCUR.
- 4 FOUR RIBS EQUALLY SPACED, NO SPECIFIC ORIENTATION. NO RIBS OR SIX RIBS EQUALLY SPACED, NO SPECIFIC ORIENTATION, OPTIONAL.
- 5 UNDERWRITES RECOGNIZED COMPONENT LOGO AND CSA CERTIFICATION LOGO TO BE LOCATED ONCE EACH SIDE OF HOUSING.
- 6 150° C TEMPERATURE RATING FOR THIS HOUSING IS FOR SHORT TERM DURATION MAX OPERATING TEMPERATURE REMAINS 125° C.
- 7 SPECIAL PACKAGING.
- 8 PHOSPHOR BRONZE CONTACTS SHOULD ALWAYS BE USED WITH THIS HOUSING.
- 9 SHOWN FOR CONVENIENCE, LOGO MAY BE ON ANY EXTERNAL SURFACE.

27.43	1.080
14.73	.580
13.97	.550
11.68	.460
7.62	.300
0.38	.015
0.13	.005
MM	IN

CONVERSION TABLE

BLACK	8-794814-1
BLACK	794814-1
COLOR	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN K. WHITAKER 15MAY01	TE Connectivity	
DIMENSIONS: mm		CHK S. RIDGILL 15MAY01		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APPV S. RIDGILL 15MAY01	NAME	
0. PLC ± -			PLUG, 2 CIRCUIT, UNIVERSAL MATE-N-LOK™	
1. PLC ± -			APPLICATION SPEC	
2. PLC ± 0.13			SIZE	
3. PLC ± -			CAGE CODE	
4. PLC ± -			DRAWING NO	
ANGLES ± 0° 30'			RESTRICTED TO	
MATERIAL NYLON, UL 94V-2, HIGH TEMP	FINISH -	WEIGHT -	A1 00779 C=794814	
CUSTOMER DRAWING		SCALE 4:1		SHEET 1 OF 1