



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
  2. GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
  3. TERM. NOS. FOR REFERENCE ONLY.
  4. RATING: 4A @125VAC, 2A @250VAC
  5. CONTACT RESISTANCE: 10mILLI-OHMS
  6. DIELECTRIC STRENGTH: 1500 VAC-1Minute
  7. INSULATION RESISTANCE: 200 Mega-OHMS
  8. MATERIALS:  
HOUSING: ZINC ALLOY DIE CAST  
CYLINDER: ZINC ALLOY W/CHROME PLATE  
CONTACTS: SILVER PLATE  
CRISS CROSS TUMBLERS. (11 BLADE)  
DOUBLE BITTED KEYS (2) STAMPED 2007  
9. KEYLOCK, KEYS, AND HEX NUT TO BE PACKED TOGETHER IN INDIVIDUAL BAGS.

LEGEND  
 ● = INDICATE NO KEY PULL  
 ⊙ = INDICATES KEY PULL POSSIBLE

REV.	ECN NO.	DESCRIPTION	DATE	CHKD
C	18008	ADD NOTE 9	3/12/08	RC
B	12872	REMOVE TERM /NOTE 8	3/4/03	CJB
A	11402	RELEASED FOR PRODUCTION	4/10/01	RJC

TITLE		SCALE	DATE	DR	DWG	REV
E-SWITCH®		1.5:1	4/10/01	RJC	K200201	C
K0128A-2007						

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED