


NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
3. TERM. NOS. FOR REFERENCE ONLY.
4. RATING: 4A @125VAC, 2A @250VAC
5. CONTACT RESISTANCE: 10mILLI-OHMS
6. DIELECTRIC STRENGTH: 1500 VAC-1Minute
7. INSULATION RESISTANCE: 200 Mega-OHMS
8. MATERIALS:

HOUSING: ZINC ALLOY DIE CAST
 CYLINDER: ZINC ALLOY W/CHROME PLATE
 CONTACTS: SILVER PLATE
 CRISS CROSS TUMBLERS. (11 BLADE)
 DOUBLE BITTED KEYS (2) STAMPED 2007



CIRCUIT: SPST
CONTACT CONFIGURATION

| SWITCH FUNCTION | |
|-----------------|-------|
| POS 1 | POS 2 |
| ↑ | → |
| OFF | (ON) |

() = MOMMENTARY

LEGEND

- = INDICATE NO KEY PULL
- ⊙ = INDICATES KEY PULL POSSIBLE

RECOMMENDED PANEL CUTOUT

| | | | | |
|------|---------|-------------------------|----------|------|
| C | 13991 | OVERALL LENGTH | 5/6/04 | AR |
| B | 12872 | REMOVE TERM /NOTE 8 | 3/4/03 | CJB |
| A | 11754 | RELEASED FOR PRODUCTION | 10/17/01 | CJB |
| REV. | ECN No. | DESCRIPTION | DATE | CHKD |

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

| | | | | |
|------------------|----------|-----|---------|-----|
| E-SWITCH® | | | | |
| TITLE | | | | |
| K0128E-2007 | | | | |
| SCALE | DATE | DR | DWG | REV |
| 1.5:1 | 10/17/01 | CJB | K200205 | C |