



CIRCUIT: SP (90° INDEXING)  
CONTACT CONFIGURATION

SWITCH FUNCTION	
CONNECTED TERMINAL #	POS. #
1-3	1-3
8-1	1-3

RECOMMENDED PANEL LAYOUT

LEGEND  
 • =Detent Positions (45° or 90°)  
 ⊙ =Key pull possible in these positions

- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
  2. GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
  3. TERM. NOS. FOR REF. ONLY
  4. CONTACT RATING: 4A @125VAC/28VDC, 2A @250VAC
  5. DIELECTRIC STRENGTH: 1KV RMS min. at sea level
  6. ELECTRICAL LIFE: 10,000 make-and-break cycles at full load.
  7. MATERIALS:  
 CONTACTS: Silver Plated CU (Q Contact material)  
 TERMINALS: GOLD Plated Cu (Q Contact material)  
 MOUNTING NUT: Nickel Plated zinc alloy  
 CONTACT SPRING: Piano Wire  
 KEYS (2): Brass with code no. A126  
 LOCK: Bright Ni plated zinc alloy with Ni facing  
 TUMBLER Mechanism: 4-disc tumbler cylinder.

REV. B	ECN NO. 11722	REVISION	10/11/01	CHKD CJB
DESCRIPTION		DATE	CHKD	

TITLE		SCALE	DATE	DR	DWG	REV
K0130R-A126		1:1	10/11/01	CJB	K200227	B



THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSMITTED