



Part Number & Date Code Printing

PC card drilling dimensions (thickness 1.60mm)

D3W3P36AGV08**
 LF FOR LEAD FREE

REQUIREMENTS

Technical characteristics:

- Shell: steel tin plated
- Insulators: self-extinguishing thermoplastic, ULclass94V0
- Contacts: brass, 0.76» Au +2» Ni mini on mating end and 2» SnPb +1.27 Ni mini on termination end
- Grounding brackets: brass, tin plated
- Female screwlock: brass, tin plated
- Harpoon: brass, tin plated

Electrical characteristics:

- max. current rating: 30A per contact
- Test voltage: 1000V
- Rated voltage: 300V
- Contact resistance: ?5m?
- Shell resistance: ?5m?
- Insulation resistance: ?5000M?
- Climatic characteristics:
 Operating temperature range: -55?c +125?c
- Dimensions:
 in accordance with MIL-C-24308

FOR ROHS DETAILS REFER DWG.NO: C01-8646-0000

mat'l. code	ISO 1302	tolerance	ISO 406 ISO 1101	projection	product family
lit	ecn no	dr	date	ISO 1302	ISO 406 ISO 1101
E	106-0124	JS	2005-07-27	tolerances unless otherwise specified	
F	106-0074	SK	2006-06-08	linear	0.xx±0.1
				angles	0.xx±0.1
				0.x°±1'	0.xxx±0.1
				dr	JOHN SLIEBA 1994-07-06
				enjr	GEORGE VJ 1994-07-06
				chr	GEORGE VJ 2005-07-27
				appd	KVSD 2005-07-27
sheet index	revision	sheet	F	1	



product family: D-SUB
 title: SUB DELTA D 3W3 WITH POWER CONTACTS
 right angle - UNC4-40 harpoon
 dwg no: C01-8646-0246
 sheet 1 of 1
 size: A3
 type: Product Customer Drawing