

### ESMR, SMR, CELLULAR, GSM, CONVENTIONAL YAGI ANTENNAS

For 800 MHz ESMR and SMR or conventional applications, choose 4 element PC804N, 6 element PC806N, or ten element PC8010N. The Laird Technologies PC804N, PC826N, and PC8210N are also available in the 900 MHz GSM frequency band.

#### FEATURES

- All-welded unit construction
- No adjustments ever needed
- Waterproof design
- Stainless steel hardware
- Pigtail mounted N-female connector

#### COMMON SPECIFICATIONS


- Power handling – 200 Watts
- Elements – 1/4 in (.63 cm) 6061T6 aluminum rod;
- Boom – 3/4 in (1.9 cm) 6061T6 aluminum channel
- Mounting style – U-bolt; maximum mast diameter – 2-1/8 in (5.4 cm) pigtail – 19 in (48.3 cm)

#### MARKETS


- WiMAX

MODEL	FREQ. MHz	GAIN dBd	NO. ELEM	F TO B dB	-3 dB BEAMWIDTH		CONN. TYPE (FEMALE)	W/SURF. AREA ft² (m²)	W/SURV. mph (kph)	W/ 1/2 in ICE	LENGTH in (cm)	WT. LB. (KG)
					E-PLANE	H-PLANE						
PC9013N	902-928	13	13	20	35°	40°	N	0.46 (0.043)	125 (200)	100 (161)	53-1/2 (135.9)	3.12 (1.40)
PC9010N	928-960	12	10	20	40°	45°	N	0.38 (0.035)	125 (200)	100 (161)	41-7/16 (105.2)	2.31 (1.04)
PC926N	928-960	8.5	6	18	55°	65°	N	0.26 (0.024)	125 (200)	100 (161)	24-3/4 (62.9)	1.61 (.72)
PC904N	896-980	6	4	15	70°	100°	N	0.11 (0.01)	125 (200)	100 (161)	13 (33)	1.12 (.50)
PC906N	896-940	8.5	6	18	55°	65°	N	0.26 (0.024)	125 (200)	100 (161)	24-3/4 (62.9)	1.62 (.73)
PC8910N	896-940	11	10	20	40°	45°	N	0.38 (0.035)	125 (200)	100 (161)	41-7/16 (105.2)	2.31 (1.04)
PC886N	880-960	8.5	6	18	55°	65°	N	0.26 (0.024)	125 (200)	100 (161)	24-3/4 (62.9)	1.69 (.76)
PC884N	880-960	6	4	15	70°	90°	N	0.11 (0.01)	125 (200)	100 (161)	13 (33)	1.12 (.50)
PC8210N	824-896	11	10	20	40°	45°	N	0.38 (0.035)	125 (200)	100 (161)	46 (116.8)	2.37 (1.07)
PC8010N	806-869	11	10	20	40°	45°	N	0.38 (0.035)	125 (200)	100 (161)	46 (116.8)	2.44 (1.10)
PC804N	806-902	6	4	15	70°	90°	N	0.11 (0.01)	125 (200)	100 (161)	13 (33)	1.12 (.50)
PC806N	806-866	8.5	6	18	55°	65°	N	0.26 (0.024)	125 (200)	100 (161)	24-3/4 (62.9)	1.69 (.76)
PC826N	824-896	8.5	6	18	55°	65°	N	0.26 (0.024)	125 (200)	100 (161)	24-3/4 (62.9)	1.67 (.75)

Typical 4 Element



Typical 6 Element



global solutions: local support™

Americas: +1.847.839.6907  
IAS-AmericasEastSales@lairdtech.com

Europe: +1.32.80.7866.12  
IAS-EUSales@lairdtech.com

Asia: +1.65.6.243.8022  
IAS-AsiaSales@lairdtech.com

www.lairdtech.com

ANT-DS-800-900-YAGI 0611

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2011 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trademarks or registered trademarks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.